



Certification Exhibit

FCC ID: 2A3QA-001

FCC Rule Part: 47 CFR Part 2.1093

Project Number: 72154975

Manufacturer: Cue Health, Inc.
Model: C0201

RF Exposure

General Information:

Applicant: Cue Health, Inc.
Environment: General Population/Uncontrolled Exposure
Exposure Conditions: Portable

Technical Information:

Minimum Test Separation Distance: 5 mm
Highest Operating Frequency: 2480 MHz
Antenna Type: Ceramic Chip antenna
Antenna Gain: 0.5 dBi
Maximum Transmitter Conducted Power: 2.5 dBm, 1.778 mW
Maximum Transmitter EIRP: 3.0 dBm, 1.995 mW

Justification for SAR Test Exclusion:**Standalone SAR Test Exclusion:**

Per KDB 447498 D01 General RF Exposure Guidance v05r02, the standalone 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \left[\sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

$$= (1.775 / 5) \cdot (\sqrt{2.48}) = 0.6$$

0.6 < 3.0

Standalone SAR test exclusion is applied.