

承认书项目表

NO.	内 容 (Contents)	页 数 (Number of Page)	页 码 (Page Code)
1	承认书封面 (Spec Cover)	1	1
2	承认书项目表 (Spec Item)	1	2
3	工程成品图 (Drawing)	1	3
4	电性测试报告 (Test Reports)	1	4
5	S参数测试 (S Parameter)	1	5
6	增益测试 (Gain Test)	1	6
7			
8			
9			
10	-	-	-
11	-	-	-
12	-	-	-


电 性 测 试 报 告

Test Reports

Electrical Properties	
Frequency	2.4GHz
Impedance	50 Ohm Nominal
V.S.W.R	1.92 : 1 Max
Return Loss	-10 dB Max
Radiation	Omni-directional
Gain (Peak)	3dBi
Cable Loss	3.2 dB / m Max @ 2450 MHz
Polarization	Linear, Vertical
Admitted Power	1 W
Connector	ipex
Physical Properties	
Antenna Material	FPCB
Cable Type	O.D. 1.13mm // 220 mm
Operating Temp.	-40 ~ +85 °C
Storage Temp.	-40 ~ +85 °C
Cable Color	Black

add: 东莞市长厦岗夏联路1号Tel:0769-89158063 Fax:0769-85309196

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			



3	NB030B	FPC	42*12mm	1
2	R-CB-113B	Coaxial Cable	SHOWA-O.D. 1.13mm Black	1
1	Cl-113	Connector	Mini Connector	1
No.	Part Number	Name	Material	Q'ty

東莞皓諾電子有限公司

TITLE: 2.4GHz Antenna

PART NO.: NB030-13B-IX130

DWG NAME: NB030-13B-IX130.DWG

APPROVED BY

CHECKED BY

DESIGNED BY

UNITS: mm

SCALE: 1/1

REVISION: A

Tolerance

jeff

leon

YD

SCALE: 1/1

REVISION: A



X.X ±0.20
X.XX ±0.10
X° ±3°

Tel:86-0769-89158063
Fax:86-0769-85309196

S 参数测试

S Parameter Test

Agilent E5071C



增益测试

Gain Test

*Antenna
Radiation
Pattern
VS
Gain*

