TEST REPORT

Applicant	:	Shenzhen Qixin Technology Co., Ltd.
Address	:	Room 2508, Baoshan Times Tower, Minqiang Community, Minzhi Street, Longhua District, Shenzhen, Guangdong Province, China
Manufacturer	:	Shenzhen Qixin Technology Co., Ltd.
Address	:	Room 2508, Baoshan Times Tower, Minqiang Community, Minzhi Street, Longhua District, Shenzhen, Guangdong Province, China
Product Name	:	DFirst Scanner
Model Number	:	DFirst Slink WiFi
Trademark	:	N/A
FCC ID	:	2A3SM-WIFI
Test Date	:	Aug. 11, 2026 to Sep. 23, 2026
Date of Report	:	Sep. 23, 2026
Test Result	:	This device described above has been tested by BKC, and the test results show that the equipment under test (EUT) is in compliance with the Standard requirements. And it is applicable only to the tested sample identified in the report.

Test Procedure Used:

Standards	:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

Prepared by(Test Engineer):
Cindy Qin

Reviewer(Supervisor):
Ken Wu

Approved(Manager):
Abel Yu

Shenzhen NTT Testing Technology Co., Ltd. Special Seal for Inspection and Testing

TABLE OF CONTENT

1. General Information 5
1.1. Description of Device (EUT) 5
1.2. Channel List 5
1.3. Test configuration 5
1.4. Summary of test result 6
1.5. Special Accessories and Auxiliary Equipment 6
1.6. Test mode 6
1.7. Block Diagram 7
1.8. Test Conditions 7
1.9. Measurement Uncertainty (95% confidence levels, k=2) 7
1.10. Test Facility 8
1.11. Test Equipment 8
2. Conducted emission at the mains terminals test 10
2.1. Limit 10
2.2. Test Setup 10
2.3. Test Procedure 10
2.4. Test Result 11
3. Radiated Spurious Emissions 12
3.1. Limit 12
3.2. Test Setup 13
3.3. Test Procedure 15
3.4. Test Result 16
4. Duty cycle 23
4.1. Limit 23
4.2. Test Setup 23
4.3. Test Procedure 23
4.4. Test Result 23
5. Conducted Spurious Emissions 25
5.1. Limit 25
5.2. Test Setup 25
5.3. Test Procedure 25
5.4. Test Result 26
6. Band Edge Measurement 29
6.1. Limit 29
6.2. Test setup 29
6.3. Test Procedure 29
6.4. Test Result 30
7. -6 dB Bandwidth 32
7.1. Limit 32
7.2. Test Setup 32
7.3. Test Procedure 32
7.4. Test Result 33
8. Maximum Output Power 37
8.1. Limit 37
8.2. Test Setup 37
8.3. Test Procedure 37
8.4. Test Result 37
9. Power Spectral density 38
9.1. Limit 38
9.2. Test Setup 38

9.3. Test Procedure 38
9.4. Test Result 39
10. Antenna Requirement 43
11. TEST SETUP & EUT PHOTOGRAPH 44

Revision History of This Test Report		
Report Number	Description	Issued Date
SZNTT26038304E1-2	Initial Issue	Sep. 23, 2026

1. General Information

1.1.Description of Device (EUT)

EUT Name	:	DFirst Scanner
Model No.	:	DFirst Slink WiFi
Model Difference	:	N/A
Power supply	:	DC 12V power supply
Operation frequency	:	2412-2462MHz for 802.11b/g/n20
Modulation	:	802.11b:(DQPSK, DBPSK, CCK) DSSS 802.11g/n:(64-QAM,16-QAM, QPSK, BPSK) OFDM
Antenna Type	:	Chip antenna, Maximum Gain is 2.12dBi
Intend use environment	:	Residential, commercial and light industrial environment

1.2.Channel List

Frequency and Channel list for 802.11 b/g/n(HT20):

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	2	2417	3	2422	4	2427
5	2432	6	2437	7	2442	8	2447
9	2452	10	2457	11	2462		

Test Frequency and Channel for 802.11 b/g/n(HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2412	6	2437	11	2462
3	2422	6	2437	9	2452

1.3.Test configuration

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	EspRFTestTool
Power level setup	Default

1.4.Summary of test result

RF PART		
Test Items	**Test Requirement**	**Result**
Antenna requirement	FCC part 15.203/15.247 (b)	PASS
Duty cycle	/	PASS
AC Power Line Conducted Emission	FCC part 15.207	N/A
Conducted Peak Output Power	FCC part 15.247 (b)(3)	PASS
Channel Bandwidth	FCC part 15.247 (a)(2)	PASS
Power Spectral Density	FCC part 15.247 (e)	PASS
Band Edge	FCC part 15.247(d)	PASS
Spurious Emission	FCC part 15.205/15.209	PASS
Remark: N/A is an abbreviation for Not Applicable. Measurement Uncertainty is not taken into account for conformity statement		

1.5.Special Accessories and Auxiliary Equipment

Description	Manufacturer	Model No.	Hardware Version	Software Version
Adapter	JIYIN	JY-05100C	/	/
Laptop	DELL	Vostro 5490	/	/
Cable	/	/	/	/

1.6.Test mode

The special RF test software was used to control EUT work in Continuous WIFI TX mode, and select test channel, wireless mode.

Test mode	Low channel	Middle channel	High channel
802.11b	2412MHz	2437MHz	2462MHz
802.11g	2412MHz	2437MHz	2462MHz
802.11n20	2412MHz	2437MHz	2462MHz
Note：All modes have been tested., Only the worst Data Record in the report			

1.7.Block Diagram

Radiated Emission



Conducted Spurious

RF Conducted Test



1.8.Test Conditions

Category	Normal Conditions	Extreme Conditions
Temperature range	15-35℃	N/A
Humidity range	20-75%	N/A
Pressure range	86-106kPa	N/A
Note: N/A is an abbreviation for Not Applicable.		

1.9.Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for radio frequency	±7×10-8	
Conducted Emissions (150kHz~30MHz)	±3.64dB	
Radiated Emission(9KHz~30MHz)	±4.51dB	
Radiated Emission(30MHz~1GHz)	±5.03dB	
Radiated Emission(1GHz~6GHz)	±3.92dB	
Radiated Emission(6GHz~18GHz)	±4.33dB	
Radiated Emission(18GHz~40GHz)	±3.38dB	
Uncertainty for conducted RF Power	±0.20dB	
Conducted spurious emissions	±0.24dB	
Uncertainty for temperature	0.6℃	
Uncertainty for humidity	1%	
Bandwidth	± 1.5 x 10-6	
Time	±2%	
Duty Cycle	±2%	
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%		

1.10.Test Facility

Site Description		
Name of Firm	:	Shenzhen NTT Testing Technology Co.,Ltd.
Site Location	:	1B, Building 2, Factory Building & 103, Building 3, Factory Building, Dayang Industrial Park No.4, Industrial Avenue, Tangwei Community, Fuhai Sub-district, Bao 'an District, Shenzhen City, China
FCC Designation Number	:	CN3446
FCC Test Firm Registration Number	:	129414

1.11.Test Equipment

Radiated Test Site(Below 1G and Above 1G)&RF Test Site

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
966 Shielded Room	966 Room	/	EMToni	2025/07/24	2028/07/23
EMI Test Receiver	ESPI	101018	ROHDE&SCHWARZ	2025/09/08 2026/09/04	2026/09/07 2027/09/03
Amplifi（30MHz-1GHz）	BBV 9745	00431	SCHWARZBECK	2025/09/08 2026/09/09	2026/09/07 2027/09/08
Bilog Antenna（30MHz-1GHz）	VULB9168	1858	SCHWARZBECK	2025/09/09 2026/09/05	2026/09/08 2027/09/04
Horn antenna（1GHz-18GHz）	BBHA 9120 D	02622	SCHWARZBECK	2025/09/09 2026/09/05	2026/09/08 2027/09/04
Pream plifier（1GHz-18GHz）	BBV 9718D	0024	SCHWARZBECK	2025/09/08 2026/09/04	2026/09/07 2027/09/03
Spectrum Analyze（10Hz-40GHz）	FSV 40	100952	ROHDE&SCHWARZ	2025/09/08 2026/09/04	2026/09/07 2027/09/03
Pream plifier（18GHz-40GHz）	BBV 9721	0056	SCHWARZBECK	2025/09/08 2026/09/04	2026/09/07 2027/09/03
Double Ridge Guide Horn Antenna（18GHz-40GHz）	SAS-574	588	A.H.System	2025/09/09 2026/09/05	2026/09/08 2027/09/04
Loop Antenna (9KHz-30MHz)	FMZB 1513-60	00115	SCHWARZBECK	2025/09/08 2026/09/04	2026/09/07 2027/09/03
MXG Signal Analyzer	N9020A	MY49100730	Agilent	2025/09/08 2026/09/04	2026/09/07 2027/09/03
MXG Vector Signal Generator	N5182A	MY50144920	Agilent	2025/09/08 2026/09/04	2026/09/07 2027/09/03
WIDEBAND RADIO COMMUNICATION TESTER	CMW500	/	ROHDE&SCHWARZ	2025/09/08 2026/09/07	2026/09/07 2027/09/06
Power Sensor	MW100-RFCB-2	MW260105NTT-64	MWRFtest	2025/09/08 2026/09/04	2026/09/07 2027/09/03

RF Swith	MW100-RFCB-1	MW260105NTT-64	MWRFtest	2025/09/08 2026/09/04	2026/09/07 2027/09/03
Cable	RG223-3M	/	DA	2025/09/08 2026/09/04	2026/09/07 2027/09/03
Cable	RG223-12M	/	DA	2025/09/08 2026/09/04	2026/09/07 2027/09/03
Cable	SFT205-NMNMSW-2.5M	/	DA	2025/09/08 2026/09/04	2026/09/07 2027/09/03
Cable	SFT205-NMNM-12M	/	DA	2025/09/08 2026/09/04	2026/09/07 2027/09/03
Cable	UCA500-NJWSM-1.5M	017	MWRFtest	2025/09/08 2026/09/04	2026/09/07 2027/09/03

Test software

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	FALA	EZ-EMC	Ver.EMC-CON 3A1.1+
2	EMC radiation test system	FALA	EZ-EMC	Ver.FA-03A2 RE+
3	RF test system	TACHOY	RFTest	V1.0.0
4	RF communication test system	TACHOY	RFTest	V1.0.0

2. Conducted emission at the mains terminals test

2.1.Limit

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

Frequency MHz	Limits dB(μV)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66 ~ 56*	56 ~ 46*
0.50 ~ 5.00	56	46
5.00 ~ 30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

2.2.Test Setup



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

2.3.Test Procedure

1. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
2. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
3. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
4. LISN at least 80 cm from nearest part of EUT chassis.
5.For the actual test configuration, please refer to the related Item – EUT Test Photos.

2.4.Test Result

N/A

The EUT DC 12V DC power supply is not applicable to this item.

3. Radiated Spurious Emissions

3.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.209 & 15.247

Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019; ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

Test Result: PASS

Measurement Distance: 3m

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120KHz	360KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log(2400/F(kHz)) + 80
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log(24000/F(kHz)) + 40
1.705 ~ 30	30	30	100 * 30	20log(30) + 40
30 ~ 88	100	3	100	20log(100)
88 ~ 216	150	3	150	20log(150)
216 ~ 960	200	3	200	20log(200)
Above 960	500	3	500	20log(500)

3.2.Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10.

The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.





3.3.Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.

2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.

3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.

4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.

5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

6. Repeat above procedures until the measurements for all frequencies are complete.

7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in Z axis,so the worst data were shown as follow.

8. A 2.4GHz high - pass filter is used druing radiated emissions above 1GHz measurement.

3.4.Test Result

Test Frequency: 9KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 1GHz

Radiation Emission Test Data			
Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Horizontal
Test Voltage :	DC 12V	Test Mode :	802.11b(2462.00MHz)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		37.0248	26.19	-6.24	19.95	40.00	-20.05	QP
2		67.2021	28.36	-5.11	23.25	40.00	-16.75	QP
3	*	150.5377	38.73	-4.53	34.20	43.50	-9.30	QP
4		300.8942	37.77	-3.29	34.48	46.00	-11.52	QP
5		401.8383	35.62	-1.81	33.81	46.00	-12.19	QP
6		892.2907	28.13	8.13	36.26	46.00	-9.74	QP

Note:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor
Margin=Emission Level-Limit
2. All the modes have tested and recorded the worst mode(802.11b) in the report

Radiation Emission Test Data			
Temperature:	25.1℃	Relative Humidity:	56%
Pressure:	1008hPa	Phase :	Vertical
Test Voltage :	DC 12V	Test Mode :	802.11b(2462.00MHz)

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		56.3947	29.78	-4.83	24.95	40.00	-15.05	QP
2		150.5377	31.54	-4.53	27.01	43.50	-16.49	QP
3		233.3486	34.64	-6.79	27.85	46.00	-18.15	QP
4		401.8383	35.70	-1.81	33.89	46.00	-12.11	QP
5		650.7997	28.64	4.75	33.39	46.00	-12.61	QP
6	*	948.7608	28.90	8.80	37.70	46.00	-8.30	QP

Note:
1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor
Margin=Emission Level-Limit
2. All the modes have tested and recorded the worst mode(802.11b) in the report

Test Frequency 1GHz-25GHz

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824	53.57	34.12	5.03	32.39	56.87	74	-17.13	Pk
V	4824	40.79	34.12	5.03	32.39	44.09	54	-9.91	AV
V	7236	50.44	32.54	6.29	35.86	60.05	74	-13.95	Pk
V	7236	35.12	32.54	6.29	35.86	44.73	54	-9.27	AV
V	9648	48.11	32.98	7.55	38.4	61.08	74	-12.92	Pk
V	9648	34.25	32.98	7.55	38.4	47.22	54	-6.78	AV
V	12060	44.10	32.09	8.93	39	59.94	74	-14.06	Pk
V	12060	27.79	32.09	8.93	39	43.63	54	-10.37	AV
H	4824	48.84	34.12	5.03	32.39	52.14	74	-21.86	Pk
H	4824	39.90	34.12	5.03	32.39	43.20	54	-10.80	AV
H	7236	48.60	32.54	6.29	35.86	58.21	74	-15.79	Pk
H	7236	32.81	32.54	6.29	35.86	42.42	54	-11.58	AV
H	9648	47.53	32.98	7.55	38.4	60.50	74	-13.50	Pk
H	9648	30.78	32.98	7.55	38.4	43.75	54	-10.25	AV
H	12060	39.61	32.09	8.93	39	55.45	74	-18.55	Pk
H	12060	26.48	32.09	8.93	39	42.32	54	-11.68	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874	49.57	34.07	5.09	32.59	53.18	74	-20.82	Pk
V	4874	38.47	34.07	5.09	32.59	42.08	54	-11.92	AV
V	7311	46.27	32.63	6.34	35.96	55.94	74	-18.06	Pk
V	7311	36.01	32.63	6.34	35.96	45.68	54	-8.32	AV
V	9748	42.89	32.92	7.59	38.4	55.96	74	-18.04	Pk
V	9748	31.35	32.92	7.59	38.4	44.42	54	-9.58	AV
V	12815	41.02	31.96	8.88	39.04	56.98	74	-17.02	Pk
V	12815	30.18	31.96	8.88	39.04	46.14	54	-7.86	AV
H	4874	49.10	34.07	5.09	32.59	52.71	74	-21.29	Pk
H	4874	39.19	34.07	5.09	32.59	42.80	54	-11.20	AV
H	7311	47.44	32.63	6.34	35.96	57.11	74	-16.89	Pk
H	7311	33.92	32.63	6.34	35.96	43.59	54	-10.41	AV
H	9748	43.26	32.92	7.59	38.4	56.33	74	-17.67	Pk
H	9748	29.90	32.92	7.59	38.4	42.97	54	-11.03	AV
H	12815	40.35	31.96	8.88	39.04	56.31	74	-17.69	Pk
H	12815	29.99	31.96	8.88	39.04	45.95	54	-8.05	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2462MHz									
V	4924	48.59	34.02	5.15	32.8	52.52	74	-21.48	Pk
V	4924	35.57	34.02	5.15	32.8	39.50	54	-14.50	AV
V	7386	44.87	32.71	6.4	36.05	54.61	74	-19.39	Pk
V	7386	36.18	32.71	6.4	36.05	45.92	54	-8.08	AV
V	9848	41.34	32.86	7.62	38.4	54.50	74	-19.50	Pk
V	9848	29.80	32.86	7.62	38.4	42.96	54	-11.04	AV
V	12310	37.74	31.82	8.84	39.08	53.84	74	-20.16	Pk
V	12310	28.08	31.82	8.84	39.08	44.18	54	-9.82	AV
H	4924	47.91	34.02	5.15	32.8	51.84	74	-22.16	Pk
H	4924	38.16	34.02	5.15	32.8	42.09	54	-11.91	AV
H	7386	45.79	32.71	6.4	36.05	55.53	74	-18.47	Pk
H	7386	32.67	32.71	6.4	36.05	42.41	54	-11.59	AV
H	9848	40.19	32.86	7.62	38.4	53.35	74	-20.65	Pk
H	9848	27.51	32.86	7.62	38.4	40.67	54	-13.33	AV
H	12310	39.94	31.82	8.84	39.08	56.04	74	-17.96	Pk
H	12310	30.53	31.82	8.84	39.08	46.63	54	-7.37	AV

Note: 1. The testing has been conformed to 10*2462MHz=24620MHz.
2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Reading + Factor
Margin=Emission Level-Limit

All the modes have tested and recorded the worst mode(802.11b) in the report.

The 1-25GHz range has been tested, and the report only records the worst performance of the 1-18G range.

Radiated Band Emission Measurement:

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
802.11b	Low Channel: 2412MHz									
	H	2390	58.09	35.17	3.48	27.49	53.89	74	-20.11	PK
	H	2390	49.37	35.17	3.48	27.49	45.17	54	-8.83	AV
	H	2400	60.18	35.16	3.49	27.52	56.03	74	-17.97	PK
	H	2400	49.95	35.16	3.49	27.52	45.80	54	-8.20	AV
	V	2390	58.67	35.17	3.48	27.49	54.47	74	-19.53	PK
	V	2390	51.60	35.17	3.48	27.49	47.40	54	-6.60	AV
	V	2400	61.78	35.16	3.49	27.52	57.63	74	-16.37	PK
	V	2400	51.12	35.16	3.49	27.52	46.97	54	-7.03	AV
	High Channel: 2462MHz									
	H	2483.5	58.38	35.11	3.56	27.75	54.58	74	-19.42	PK
	H	2483.5	50.62	35.11	3.56	27.75	46.82	54	-7.18	AV
	H	2500	60.05	35.1	3.57	27.8	56.32	74	-17.68	PK
	H	2500	49.39	35.1	3.57	27.8	45.66	54	-8.34	AV
	V	2483.5	57.80	35.11	3.56	27.75	54.00	74	-20.00	PK
	V	2483.5	50.46	35.11	3.56	27.75	46.66	54	-7.34	AV
	V	2500	58.77	35.1	3.57	27.8	55.04	74	-18.96	PK
	V	2500	50.74	35.1	3.57	27.8	47.01	54	-6.99	AV
802.11g	Low Channel: 2412MHz									
	H	2390	59.88	35.17	3.48	27.49	55.68	74	-18.32	PK
	H	2390	49.63	35.17	3.48	27.49	45.43	54	-8.57	AV
	H	2400	61.79	35.16	3.49	27.52	57.64	74	-16.36	PK
	H	2400	51.52	35.16	3.49	27.52	47.37	54	-6.63	AV
	V	2390	58.11	35.17	3.48	27.49	53.91	74	-20.09	PK
	V	2390	51.05	35.17	3.48	27.49	46.85	54	-7.15	AV
	V	2400	59.07	35.16	3.49	27.52	54.92	74	-19.08	PK
	V	2400	49.40	35.16	3.49	27.52	45.25	54	-8.75	AV
	High Channel: 2462MHz									
	H	2483.5	58.92	35.11	3.56	27.75	55.12	74	-18.88	PK
	H	2483.5	50.63	35.11	3.56	27.75	46.83	54	-7.17	AV
	H	2500	59.08	35.1	3.57	27.8	55.35	74	-18.65	PK
	H	2500	49.79	35.1	3.57	27.8	46.06	54	-7.94	AV
	V	2483.5	57.67	35.11	3.56	27.75	53.87	74	-20.13	PK
	V	2483.5	49.68	35.11	3.56	27.75	45.88	54	-8.12	AV
	V	2500	60.37	35.1	3.57	27.8	56.64	74	-17.36	PK
	V	2500	49.40	35.1	3.57	27.8	45.67	54	-8.33	AV
802.11 n20	Low Channel: 2412MHz									
	H	2390	59.09	35.17	3.48	27.49	54.89	74	-19.11	PK
	H	2390	51.56	35.17	3.48	27.49	47.36	54	-6.64	AV
	H	2400	58.85	35.16	3.49	27.52	54.70	74	-19.30	PK
	H	2400	49.07	35.16	3.49	27.52	44.92	54	-9.08	AV
	V	2390	57.82	35.17	3.48	27.49	53.62	74	-20.38	PK
	V	2390	51.32	35.17	3.48	27.49	47.12	54	-6.88	AV
	V	2400	61.66	35.16	3.49	27.52	57.51	74	-16.49	PK
	V	2400	49.55	35.16	3.49	27.52	45.40	54	-8.60	AV

	High Channel: 2462MHz									
	H	2483.5	57.05	35.11	3.56	27.75	53.25	74	-20.75	PK
	H	2483.5	50.26	35.11	3.56	27.75	46.46	54	-7.54	AV
	H	2500	60.12	35.1	3.57	27.8	56.39	74	-17.61	PK
	H	2500	49.63	35.1	3.57	27.8	45.90	54	-8.10	AV
	V	2483.5	58.70	35.11	3.56	27.75	54.90	74	-19.10	PK
	V	2483.5	51.13	35.11	3.56	27.75	47.33	54	-6.67	AV
	V	2500	57.88	35.1	3.57	27.8	54.15	74	-19.85	PK
	V	2500	51.38	35.1	3.57	27.8	47.65	54	-6.35	AV
802.11 n40	Low Channel 2422MHz									
	H	2390	59.40	35.17	3.48	27.49	55.20	74	-18.80	PK
	H	2390	50.84	35.17	3.48	27.49	46.64	54	-7.36	AV
	H	2400	58.99	35.16	3.49	27.52	54.84	74	-19.16	PK
	H	2400	51.46	35.16	3.49	27.52	47.31	54	-6.69	AV
	V	2390	59.20	35.17	3.48	27.49	55.00	74	-19.00	PK
	V	2390	52.02	35.17	3.48	27.49	47.82	54	-6.18	AV
	V	2400	59.91	35.16	3.49	27.52	55.76	74	-18.24	PK
	V	2400	50.74	35.16	3.49	27.52	46.59	54	-7.41	AV
	High Channel 2452MHz									
	H	2483.5	59.32	35.11	3.56	27.75	55.52	74	-18.48	PK
	H	2483.5	48.19	35.11	3.56	27.75	44.39	54	-9.61	AV
	H	2500	59.79	35.1	3.57	27.8	56.06	74	-17.94	PK
	H	2500	49.71	35.1	3.57	27.8	45.98	54	-8.02	AV
	V	2483.5	59.29	35.11	3.56	27.75	55.49	74	-18.51	PK
	V	2483.5	51.56	35.11	3.56	27.75	47.76	54	-6.24	AV
	V	2500	58.87	35.1	3.57	27.8	55.14	74	-18.86	PK
	V	2500	51.73	35.1	3.57	27.8	48.00	54	-6.00	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss － Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

4. Duty cycle

4.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019; ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Result: PASS

4.2.Test Setup

4.3.Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
a) Set the center frequency of the instrument to the center frequency of the transmission.
b) Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value.
c) Set VBW ≥ RBW. Detector = peak or average.
d) Sweep time = auto couple.
e) Trace mode = max hold.
f) Allow trace to fully stabilize.

4.4.Test Result

Duty Cycle

Mode	Channel.	Duty Cycle(%)	Correction Factor (dB)
802.11b	LCH	100	0
802.11g	LCH	100	0
802.11n(HT20)	LCH	100	0

Test Graph:

Graphs		
802.11b/LCH		
802.11g/LCH		
802.11n(HT20)/LCH		

5. Conducted Spurious Emissions

5.1.Limit

Test Requirement:	FCC CFR47 Part 15 Section 15.247
Test Method:	KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019; ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Result:	PASS

Limit:
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.2.Test Setup

5.3.Test Procedure

a) Set instrument center frequency to DTS channel center frequency.
b) Set the span to ≥ 1.5 times the DTS bandwidth.
c) Set the RBW = 100 kHz.
d) Set the VBW ≥ [3 × RBW].
e) Detector = peak.
f) Sweep time = No faster than coupled (auto) time.
g) Trace mode = max-hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum PSD level.
Note that the channel found to contain the maximum PSD level can be used to establish the reference level
Establish an emission level by using the following procedure:
a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.
NOTE—the number of points can also be increased for large spans to retain frequency resolution
b) Set the RBW = 100 kHz.
c) Set the VBW ≥ [3 × RBW].
d) Detector = peak.
e) Sweep time = No faster than coupled (auto) time.
f) Trace mode = max-hold.
g) Allow trace to fully stabilize.
h) Use the peak marker function to determine the maximum amplitude level.

5.4.Test Result

RF Conducted Spurious Emissions Graphs		
802.11b/LCH		
802.11b/MCH		
802.11b/HCH		

RF Conducted Spurious Emissions Graphs			
802.11g/LCH			
802.11g/MCH			
802.11g/HCH			

RF Conducted Spurious Emissions Graphs		
802.11n(HT20)/LCH		
802.11n(HT20)/MCH		
802.11n(HT20)/HCH		

6. Band Edge Measurement

6.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019;
ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Limit: Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
Test Mode: Transmitting

6.2.Test setup



6.3.Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer:
3. Establish a reference level by using the following procedure
a) Set instrument center frequency to DTS channel center frequency.
b) Set the span to _ 1.5 times the DTS bandwidth.
c) Set the RBW = 100 kHz.
d) Set the VBW _ [3 × RBW].
e) Detector = peak.
f) Sweep time = No faster than coupled (auto) time.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum PSD level.
Note that the channel found to contain the maximum PSD level can be used to establish the reference level.
4. Establish an emission level by using the following procedure:
a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.
NOTE—the number of points can also be increased for large spans to retain frequency resolution
b) Set the RBW = 100 kHz.
c) Set the VBW ≥ [3 × RBW].
d) Detector = peak.
e) Sweep time = No faster than coupled (auto) time.
f) Trace mode = max-hold.
g) Allow trace to fully stabilize.
h) Use the peak marker function to determine the maximum amplitude level.

6.4.Test Result

BAND EDGE Graphs		
802.11b/LCH		
802.11b/HCH		

BAND EDGE Graphs		
802.11g/LCH		

802.11g/HCH			
802.11n(HT20)/LCH			
802.11n(HT20)/HCH			

7. -6 dB Bandwidth

7.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019; ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.2.Test Setup

7.3.Test Procedure

DTS Bandwidth
a)Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
b) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
c) Set the VBW ≥ [3 × RBW].
d) Detector = peak.
e) Trace mode = max-hold.
f) Sweep = No faster than coupled (auto) time.
g) Allow the trace to stabilize.
99% Bandwidth
a) The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be at least three times the RBW, unless otherwise specified by the applicable requirement
c) Detector = peak.
d) Trace mode = max-hold.
e) Sweep = No faster than coupled (auto) time.
f) Allow the trace to stabilize.

7.4.Test Result

Test Mode	Frequency	6dB Bandwidth (MHz)	Limit(kHz)	Result
802.11b	LCH	9.464	500	PASS
	MCH	9.192	500	PASS
	HCH	8.601	500	PASS
802.11g	LCH	16.507	500	PASS
	MCH	16.61	500	PASS
	HCH	16.552	500	PASS
802.11n(HT20)	LCH	17.456	500	PASS
	MCH	17.511	500	PASS
	HCH	17.469	500	PASS

Test Graph:
6dB Bandwidth

Graphs		
802.11b /LCH		
802.11b /MCH		
802.11b/HCH		

802.11g/LCH			
802.11g/MCH			
802.11g/HCH			

802.11n(HT20)/LCH			
802.11n(HT20)/MCH			
802.11n(HT20)/HCH			

8. Maximum Output Power

8.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019;ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2.Test Setup



8.3.Test Procedure

1. The EUT was directly connected to the Power meter

8.4.Test Result

Mode	Channel.	Maximum Peak Output Power [dBm]	Limit [dBm]	Verdict
802.11b	LCH	7.879	30	PASS
	MCH	7.375	30	PASS
	HCH	7.96	30	PASS
802.11g	LCH	7.315	30	PASS
	MCH	7.031	30	PASS
	HCH	7.563	30	PASS
802.11n(HT20)	LCH	8.075	30	PASS
	MCH	7.611	30	PASS
	HCH	7.257	30	PASS

9. Power Spectral density

9.1.Limit

Test Requirement: FCC CFR47 Part 15 Section 15.247
Test Method: KDB 558074 D01 15.247 Meas Guidance v05r02April 2,2019; ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

9.2.Test Setup



9.3.Test Procedure

KDB 558074 D01 15.247 Meas Guidance v05r02;
1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set instrument center frequency to DTS channel center frequency
3. Set span to > 1.5 times the OBW.
4. Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz
5. Set VBW ≥ [3 x RBW]
6. Detector = power averaging (rms) or sample detector (when rms not available).
7. Ensure that the number of measurement points in the sweep ≥ [2 x span /RBW].
8. Sweep time = auto couple.
9. Employ trace averaging (rms) mode over a minimum of 100 traces.
10. Use the peak marker function to determine the maximum amplitude level.
11. If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat(note that this might require zooming in on the emission of interest and reducing the span to meetthe minimum measurement point requirement as the RBW is reduced).
12. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

9.4.Test Result

Mode	Channel.	Power Spectral Density [dBm /3kHz]	Limit(8 dBm (in any 3kHz))	Verdict
802.11b	LCH	-21.035	8	PASS
	MCH	-23.4	8	PASS
	HCH	-21.38	8	PASS
802.11g	LCH	-25.482	8	PASS
	MCH	-26.441	8	PASS
	HCH	-25.776	8	PASS
802.11n(HT20)	LCH	-25.284	8	PASS
	MCH	-25.109	8	PASS
	HCH	-25.324	8	PASS

Test Graph

Graphs			
802.11b/LCH			
802.11b/MCH			
802.11b/HCH			

802.11g/LCH			
802.11g/MCH			
802.11g/HCH			

802.11n(HT20)/LCH			
802.11n(HT20)/MCH			
802.11n(HT20)/HCH			

10. Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. This product has an integrated antenna fulfill the requirement of this section.

This product has an Chip antenna, and the maximum antenna gain is 2.12dBi, fulfill the requirement of this section.

11. TEST SETUP & EUT PHOTOGRAPH

Please see the attachment for details.

---------- End of Report ----------