



SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghengleng New Industrial Zone, Shanghengleng Community,
Dalang Street, Longhua District, Shenzhen, Guangdong,
People's Republic of China, 518000
Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V06
Report Template Revision Date: 2026-1-30

TEST REPORT

Report No.: CQASZ20260300565E-02
Applicant: DREO PTE. LTD.
Address of Applicant: 112 ROBINSON ROAD, #03-01, ROBINSON 112, SINGAPORE 068902
Equipment Under Test (EUT):
Product: Humidifier
Model No.: DR-HHM006S, DWHM06S, DR-HHM008S, DWHM08S, DR-HHM019S, DWHM19S
Test Model No.: DR-HHM008S
Brand Name: DREO, DREO HOME
FCC ID: 2A3SYHHM006
Standards: 47 CFR Part 15, Subpart C
Date of Receipt: 2026-03-18
Date of Test: 2024-07-29 to 2024-08-07
2026-03-18 to 2026-06-03
Date of Issue: 2026-6-3
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20240701520E-02	Rev.01	Initial report	2024-09-02
CQASZ20260300565E-02	Rev.02	Update report	2026-6-3

Note:

This test report (Ref. No.: CQASZ20260300565E-02)

All test data comes from source test reports (Ref. No.: CQASZ20240701520E-02).

Add the model number based on the original report, Add a trademark, Add factory information, Due to the changes in the product's casing and power board, the tests for conducted emission and radiated emission have been added.

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15.203	N/A	N/A
AC Power Line Conducted Emission	47 CFR Part 15.207	ANSI C63.10:2020	PASS
Conducted Peak & Average Output Power	47 CFR Part 15.247	ANSI C63.10:2020	PASS
6dB Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10:2020	N/A
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10:2020	N/A
Band-edge for RF Conducted Emissions	47 CFR Part 15.247	ANSI C63.10:2020	N/A
RF Conducted Spurious Emissions	47 CFR Part 15.247	ANSI C63.10:2020	N/A
Radiated Spurious Emissions	47 CFR Part 15.209	ANSI C63.10:2020	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15.205/15.209	ANSI C63.10:2020	N/A

Remark:

The tested sample(s) and the sample information are provided by the client.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 CLIENT INFORMATION	5
4.2 GENERAL DESCRIPTION OF EUT	5
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	5
4.4 TEST ENVIRONMENT AND MODE	8
4.5 TEST LOCATION	9
4.6 TEST FACILITY	9
4.7 STATEMENT OF THE MEASUREMENT UNCERTAINTY	10
4.8 DEVIATION FROM STANDARDS	10
4.9 ABNORMALITIES FROM STANDARD CONDITIONS	10
4.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER	10
4.11 EQUIPMENT LIST	11
5 TEST RESULTS AND MEASUREMENT DATA	13
5.1 ANTENNA REQUIREMENT	13
5.2 CONDUCTED EMISSIONS	14
5.3 RADIATED SPURIOUS EMISSIONS	24
5.3.1 Radiated emission below 1GHz	27
6 PHOTOGRAPHS - EUT TEST SETUP	29
6.1 RADIATED SPURIOUS EMISSION	29
6.2 CONDUCTED EMISSION	30
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	31

4 General Information

4.1 Client Information

Applicant:	DREO PTE. LTD.
Address of Applicant:	112 ROBINSON ROAD, #03-01, ROBINSON 112, SINGAPORE 068902
Manufacturer:	DREO PTE. LTD.
Address of Manufacturer:	112 ROBINSON ROAD, #03-01, ROBINSON 112, SINGAPORE 068902
Factory:	Huizhou Huimo Technology Co., Ltd
Address of Factory:	Office building Tower four, Tower Five, Tower Six of Shuangjie Industrial Co., Ltd., Yinshan Industrial Zone, Beilian Village, Liangjing Town, Huiyang District, HUIZHOU CITY, Guangdong Province
Factory 2:	QUNYOU (CAMBODIA) ELECTRIC APPLIANCE CO.,LTD.
Address of Factory 2:	Giga SEZ, St. National Road No. 1, Daeum Pou Village., Kandeing Reay Commune., Svay Teab District., SVAY RIENG PROVINCE, CAMBODIA

4.2 General Description of EUT

Product Name:	Humidifier
Model No.:	DR-HHM006S, DWHM06S, DR-HHM008S, DWHM08S, DR-HHM019S, DWHM19S
Test Model No.:	DR-HHM008S
Trade Mark:	DREO, DREO HOME
Software Version:	V1.0
Hardware Version:	PAI-053 V1.1 20220119
Power Supply:	Power supply AC120V
EUT Supports Radios application:	BLE: 2402-2480MHz 2.4GHz: Wi-Fi: 802.11b/g/n(HT20): 2412MHz~2462MHz;
Simultaneous Transmission	☐ Simultaneous TX is supported and evaluated in this report. ☒ Simultaneous TX is not supported.

4.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps
Product Type:	☒ Mobile ☐ Portable
Test Software of EUT:	Beken WIFI Test Tool V1.7.2

Antenna Type:	FPC antenna
Antenna Gain:	-1.61dBi

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz


Note:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.4 Test Environment and Mode

Operating Environment:	
Radiated Emissions:	
Temperature:	25.3 °C
Humidity:	55 % RH
Atmospheric Pressure:	1009 mbar
Conducted Emissions:	
Temperature:	25.6 °C
Humidity:	60 % RH
Atmospheric Pressure:	1009 mbar
Radio conducted item test (RF Conducted test room):	
Temperature:	25.5 °C
Humidity:	52 % RH
Atmospheric Pressure:	1009 mbar
Test mode:	
Transmitting mode:	EUT is set in RF test mode in all supported modulation types, bandwidth and data rate, etc.

Run Software:



Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.5 Test Location

All tests were performed at:

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community,
Dalang Street, Longhua District, Shenzhen, Guangdong,
People's Republic of China, 518000

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 4742.01)**

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.7 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.8 Deviation from Standards

None.

4.9 Abnormalities from Standard Conditions

None.

4.10 Other Information Requested by the Customer

None.

4.11 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Spectrum analyzer	R&S	FSU26	CQA-038	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Spectrum analyzer	R&S	FSU40	CQA-075	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Preamplifier	EMCI	EMC184055SE	CQA-089	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2021/09/16 2023/9/8	2024/09/15 2026/9/7
Bilog Antenna	R&S	HL562	CQA-011	2021/09/16 2023/11/01	2024/09/15 2026/10/31
Horn Antenna	R&S	HF906	CQA-012	2021/09/16 2023/11/01	2024/09/15 2026/10/31
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/09/16 2023/11/01	2024/09/15 2026/10/31
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2023/09/08 2025/9/1	2024/09/07 2026/8/31
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Antenna Connector	CQA	RFC-01	CQA-080	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Power Sensor	KEYSIGHT	U2021XA	CQA-30	2023/09/08 2025/9/1	2024/09/07 2026/8/31
N1918A Power Analysis Manager Power Panel	Agilent	N1918A	CQA-074	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Power meter	R&S	NRVD	CQA-029	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2023/09/08 2025/9/1	2024/09/07 2026/8/31
EMI Test Receiver	R&S	ESR7	CQA-005	2023/09/08 2025/9/1	2024/09/07 2026/8/31
LISN	R&S	ENV216	CQA-003	2023/09/08 2025/9/1	2024/09/07 2026/8/31
Coaxial cable	CQA	N/A	CQA-C009	2023/09/08 2025/9/1	2024/09/07 2026/8/31
DC power	KEYSIGHT	E3631A	CQA-028	2023/09/08 2025/9/1	2024/09/07 2026/8/31


Test software:

	Manufacturer	Software brand
Radiated Emissions test software	Tonscend	JS1120-3

Conducted Emissions test software	Audix	e3
RF Conducted test software	Audix	e3

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is FPC antenna. The connection/connection type between the antenna to the EUT's antenna port is: unique coupling. This is either permanently attachment or a unique coupling that satisfies the requirement.	


5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10:2020		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2020 on conducted measurement.		
Test Setup:	Shielding Room AC Mains LISN1 EUT AE LISN2 AC Mains Test Receiver 80cm 80cm 80cm Ground Reference Plane		

Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC120V/60Hz
Test Results:	Pass

Measurement Data

Live Line:




		Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	AV	0.150	31.78	9.70	41.48	56.00	-14.52	Average	Line
2	PP	0.150	46.75	9.70	56.45	66.00	-9.55	QP	Line
3		0.160	28.32	9.68	38.00	55.46	-17.46	Average	Line
4		0.160	43.99	9.68	53.67	65.46	-11.79	QP	Line
5		0.205	25.30	9.61	34.91	53.41	-18.50	Average	Line
6		0.205	39.63	9.61	49.24	63.41	-14.17	QP	Line
7		0.215	24.80	9.59	34.39	53.01	-18.62	Average	Line
8		0.215	38.45	9.59	48.04	63.01	-14.97	QP	Line
9		0.225	24.69	9.58	34.27	52.63	-18.36	Average	Line
10		0.225	39.42	9.58	49.00	62.63	-13.63	QP	Line
11		2.455	18.99	11.21	30.20	46.00	-15.80	Average	Line
12		2.455	31.44	11.21	42.65	56.00	-13.35	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.150	31.24	9.70	40.94	56.00	-15.06	Average	Neutral
2 PP	0.150	46.07	9.70	55.77	66.00	-10.23	QP	Neutral
3	0.165	25.74	9.67	35.41	55.21	-19.80	Average	Neutral
4	0.165	41.42	9.67	51.09	65.21	-14.12	QP	Neutral
5	0.210	24.56	9.59	34.15	53.21	-19.06	Average	Neutral
6	0.210	37.99	9.59	47.58	63.21	-15.63	QP	Neutral
7	0.230	22.32	9.56	31.88	52.45	-20.57	Average	Neutral
8	0.230	35.07	9.56	44.63	62.45	-17.82	QP	Neutral
9 AV	0.660	23.36	9.86	33.22	46.00	-12.78	Average	Neutral
10	0.660	30.20	9.86	40.06	56.00	-15.94	QP	Neutral
11	2.455	22.23	9.75	31.98	46.00	-14.02	Average	Neutral
12	2.455	33.68	9.75	43.43	56.00	-12.57	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak & Average Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10: 2013
Test Setup:	<i>Setup for Power meter measurement method</i>  <i>Setup for Spectrum analyser measurement method</i> 
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass


Test Result


Test Mode	Frequency[MHz]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	10.05	≤30.00	PASS
	2437	9.95	≤30.00	PASS
	2462	9.56	≤30.00	PASS
11G	2412	11.10	≤30.00	PASS
	2437	11.38	≤30.00	PASS
	2462	10.38	≤30.00	PASS
11N20SISO	2412	11.40	≤30.00	PASS
	2437	10.56	≤30.00	PASS
	2462	10.66	≤30.00	PASS

Note:

When Duty cycle >98%, D.C.F is not required.


Test Graphs






Date: 3 JUN 2026 12:21:07

11G_Ant1_2412




Date: 3 JUN 2026 12:26:43

11G_Ant1_2437




Date: 3 JUN 2026 12:27:39

11G_Ant1_2462




Date: 3 JUN 2026 12:29:21

11N20SISO_Ant1_2412




Date: 3 JUN 2026 12:34:12

11N20SISO_Ant1_2437



Date: 3 JUN 2026 12:38:05

11N20SISO_Ant1_2462



Date: 3 JUN 2026 12:38:00

5.4 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2020				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:


- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case . i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

5.4.1 Radiated emission below 1GHz

30MHz~1GHz

Vertical



		Read		Limit	Over			APos	TPos
	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase	
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			cm deg
1	pp	39.85	22.68	10.60	33.28	40.00	-6.72 Peak	VERTICAL	100 80
2		85.60	19.87	9.13	29.00	40.00	-11.00 Peak	VERTICAL	100 166
3		92.14	18.36	10.56	28.92	43.50	-14.58 Peak	VERTICAL	100 189
4		102.36	15.08	11.88	26.96	43.50	-16.54 Peak	VERTICAL	100 202
5		501.18	14.14	20.94	35.08	46.00	-10.92 Peak	VERTICAL	100 241
6		872.18	10.01	28.84	38.85	46.00	-7.15 Peak	VERTICAL	100 296

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Horizontal



	Read		Limit	Over				APos	TPos
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase		
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB			cm	deg
1	37.15	15.10	9.67	24.77	40.00	-15.23 Peak	HORIZONTAL	100	50
2	42.30	13.57	11.29	24.86	40.00	-15.14 Peak	HORIZONTAL	100	69
3	102.72	15.02	11.87	26.89	43.50	-16.61 Peak	HORIZONTAL	100	111
4	251.18	16.44	15.74	32.18	46.00	-13.82 Peak	HORIZONTAL	100	190
5	289.00	18.57	16.62	35.19	46.00	-10.81 Peak	HORIZONTAL	100	213
6 pp	881.41	10.01	28.99	39.00	46.00	-7.00 Peak	HORIZONTAL	100	341

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission

9kHz~30MHz:



30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emission



7 Photographs - EUT Constructional Details

Refer to PHOTOGRAPHS OF EUT for CQASZ20260300565E-01.

*** END OF REPORT ***