

MPE Calculation

RF feature(Mode)	Frequency range (MHz)			Max Target Power (dBm)	ANT Gain (dBi)	Maximum EIRP (dBm)	Maximum EIRP (mW)	Maximum power density (mW/cm ²)	Requirement (mW/cm ²)
WALN(802.11b)	2 412.00	~	2 462.00	13.50	3.01	16.51	44.772	0.009 0	1.000 0
WALN(802.11g)	2 412.00	~	2 462.00	9.00	3.01	12.01	15.886	0.003 2	1.000 0
WLAN(802.11n-HT20)	2 412.00	~	2 462.00	9.50	3.01	12.51	17.824	0.003 6	1.000 0
WLAN(802.11n-HT40)	2 422.00	~	2 452.00	9.50	3.01	12.51	17.824	0.003 6	1.000 0
		~							
		~							
		~							
		~							

Note: Please refer to the operation description for Max tune-up power.

The EUT will only be used with a separation of 20 centimeters or greater between the antenna and the body of the user.

The MPE sample calculation for this exposure is shown below.

$$\begin{aligned}
 S &= \text{EIRP} / (4 R^2 \pi) \\
 &= 44.772 / (4 \times 20^2 \times \pi) \\
 &= 0.009 \text{ mW/cm}^2
 \end{aligned}$$

- Note

S= Maximum power density(mW/cm²)

EIRP= Equivalent Isotropic Radiated Power(mW)

R= Distance to the center of the radiation of the antenna(20)

▪ Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)			Electric Field strength (V/m)	Magnetic field strength (A/m)	Power Density (mW/cm ²)	Averaging time (minutes)
0.3	~	1.34	614	1.63	*100	30
1.34	~	30	824/f	2.19 / f	*180 / f ²	30
30	~	300	27.5	0.073	0.2	30
300	~	1,500			f / 1500	30
1,500	~	100,000			1.0	30

Conclusion : The exposure condition of this device is compliant with FCC