

RF Exposure Evaluation

According to KDB447498D01 General RF Exposure Guidance v06 4.3.1. Standalone SAR test exclusion considerations Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$ Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Result of RF Exposure Evaluation

Antenna Gain: 3dBi, MIMO Gain: 6.01 dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

The Max Conducted Peak Output Power data refer to report Report No.: ZKT-211130L6558-01 & ZKT-211130L6558-02

2.4GWIFI:

worst mode and channel						
Test channel	Antenna Output Power (dBm)			Tune up tolerance (dBm)		
	ANT1	ANT2	SUM	ANT1	ANT2	SUM
802.11b						
CH01	11.53	11.624	/	12±1	12±1	/
CH06	11.65	11.678	/	12±1	12±1	/
CH11	11.88	11.271	/	12±1	12±1	/
802.11g						
CH01	10.29	10.459	/	11±1	11±1	/
CH06	10.53	10.703	/	11±1	11±1	/
CH11	11.24	11.362	/	11±1	11±1	/
802.11n20						
CH01	10.87	10.365	13.64	11±1	11±1	14±1
CH06	10.86	10.733	13.81	11±1	11±1	14±1
CH11	11.01	11.258	14.15	11±1	11±1	14±1
802.11n40						
CH01	9.30	9.411	12.37	10±1	10±1	12±1
CH06	9.55	10.454	13.04	10±1	10±1	12±1
CH11	9.06	9.144	12.11	10±1	10±1	12±1

Test worst case

Maximum tune-up Power (dBm)			Maximum tune-up Power (mW)			Calculated value (mW/cm2)	Limit (mW/cm2)
ANT1	ANT2	SUM	ANT1	ANT2	SUM	/	/
12	12	15	15.85	15.85	31.623	0.0251	1.0

Remark:

- 1) $P_d = (P_{out} * G) / (4 * \pi * R^2) = (31.623 * 6.01) / (4 * 3.1415 * 20 * 20) = 0.0251$; $G = 10^{gain/10} = 3.99$
- 2) EUT is more than 20cm away from the human body.