

FCC TEST REPORT

FCC ID:2A3WC-S230

Applicant Name..... : ShenZhen Homan Technology Co.,LTD

Address..... : Room 502, Huixin Complex Building, Baomin 2nd Road, Xixiang
Sub-district, Baoan District, Shenzhen, China

Manufacturer Name..... : ShenZhen Homan Technology Co.,LTD

Address..... : Room 502, Huixin Complex Building, Baomin 2nd Road, Xixiang
Sub-district, Baoan District, Shenzhen, China

Product..... : Smart Projector

Model(s)..... : S230

Additional Model(s)..... : Inspire 2000, A1200

Trademark..... : /

Model Difference..... : S230 is the test model, while the other models are derivative models.
These models have the same circuitry, but differ in the model name.
Therefore, the test data of S230 can represent all the other models.

Prepared by..... : Guangdong Zhonghan Testing Technology Co., Ltd.

Address..... : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai
Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Date of Receipt..... : July 7, 2026

Date of Test(s)..... : July 7, 2026 to Aug. 11, 2026

Date of Issue..... : Sept. 23, 2026

Test Requested..... : Select test(s) as requested by the client.

Test Standard(s)..... : FCC Part 15 Subpart E 15.407
KDB789033 D02 General U-NII Test Procedures New Rules v02r01

Test procedure..... : ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to
C63.10a-2024

In the configuration tested, the EUT complied with the standards specified above.

Prepared by:

Kimi Lu

Kimi Lu/ Engineer

Reviewed by:

Baret Wu

Baret Wu/ Director

Approved by:

Levi Lee

Levi Lee/ Manager

Note: The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report shall not be reproduced except in full, without prior written approval of ZHT. This document may be altered or revised by ZHT, personnel only, and shall be noted in the revision of the document.

Table of Contents

Page

1.SUMMARY OF TEST RESULTS	4
2. GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	8
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	8
3. TEST FACILITY AND TEST INSTRUMENT USED	9
3.1 TEST FACILITY	9
3.2 EQUIPMENTS LIST FOR ALL TEST ITEMS	9
3.3 TESTING SOFTWARE	10
3.4 MEASUREMENT UNCERTAINTY	11
4.EMC EMISSION TEST	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 POWER LINE CONDUCTED EMISSION Limits	12
4.1.2 TEST PROCEDURE	12
4.1.3 DEVIATION FROM TEST STANDARD	12
4.1.4 TEST SETUP	13
4.1.5 EUT OPERATING CONDITIONS	13
4.1.6 TEST RESULTS	14
4.2 RADIATED EMISSION MEASUREMENT	16
4.2.1 APPLICABLE STANDARD	16
4.2.2 CONFORMANCE LIMIT	16
4.2.3 MEASURING INSTRUMENTS	17
4.2.4 TEST CONFIGURATION	18
4.2.5 TEST PROCEDURE	19
5.POWER SPECTRAL DENSITY TEST	70
5.1 APPLIED PROCEDURES / LIMIT	70
5.2 TEST PROCEDURE	71
5.3 DEVIATION FROM STANDARD	71
5.4 TEST SETUP	71
5.5 EUT OPERATION CONDITIONS	71
5.6 TEST RESULTS	72
6. 26DB & 6DB &99% EMISSION BANDWIDTH	73
6.1 APPLIED PROCEDURES / LIMIT	73
6.2 TEST PROCEDURE	73
6.3 EUT OPERATION CONDITIONS	74
6.4 TEST RESULTS	74

Table of Contents	Page
7.MAXIMUM CONDUCTED OUTPUT POWER	75
7.1 PLIED PROCEDURES / LIMIT	75
7.2 TEST PROCEDURE	76
7.3 DEVIATION FROM STANDARD	76
7.4 TEST SETUP	76
7.5 EUT OPERATION CONDITIONS	76
7.6 TEST RESULTS	76
8.OUT OF BAND EMISSIONS	77
8.1 APPLICABLE STANDARD	77
8.2 TEST PROCEDURE	78
8.3 DEVIATION FROM STANDARD	78
8.4 TEST SETUP	78
8.5 EUT OPERATION CONDITIONS	78
8.6 TEST RESULTS	78
9.SPURIOUS RF CONDUCTED EMISSIONS	79
9.1 CONFORMANCE LIMIT	79
9.3 TEST SETUP	79
9.4 TEST PROCEDURE	79
9.5 TEST RESULTS	80
10.FREQUENCY STABILITY MEASUREMENT	81
10.1 LIMIT	81
10.2 TEST PROCEDURES	81
10.3 TEST SETUP LAYOUT	81
10.4 EUT OPERATION DURING TEST	82
10.5 TEST RESULTS	82
11.ANTENNA REQUIREMENT	83
12. TEST SETUP PHOTO	84
13. EUT CONSTRUCTIONAL DETAILS	84

**1.SUMMARY OF TEST RESULTS**

Test procedures according to the technical standards:

FCC Part15 (15.407) , Subpart E			
Standard Section	Test Item	Judgment	Remark
15.207(a)	AC Power Line Conducted Emission	PASS	
15.205(a)/§15.209(a) 15.407(b)(1) 15.407(b)(4) 15.407(b)(8)	Radiated Emissions and Band Edge	PASS	
15.407 (e) 789033 D02 General U-NII	26dB Emission Bandwidth and 6dB Occupied Bandwidth	PASS	
15.407(a)(1) 15.407 (a)(3) i	Power Spectral Density	PASS	
15.407(a)(1) 15.407 (a)(3) i 15.407(a)(12)	Maximum Conducted Output Power	PASS	
15.407(b)(1) 15.407(b)(4) 15.407(b)(8)	Conducted Band Edge	PASS	
15.407(g)	Frequency Stability	PASS	
789033 D02 General U-NII	Duty Cycle	PASS	
15.203	Antenna Requirement	PASS	
15.407(h)(2)(iii)	Channel Move Time, Channel Closing Transmission Time	N/A	
15.407(h)(2)(iv)	Non-Occupancy Period Test	N/A	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



2.1 GENERAL DESCRIPTION OF EUT

Product Name:	Smart Projector	
Test Model No.:	S230	
Product Description	IEEE 802.11 WLAN Mode Supported	☒ 802.11a/n/ac (20MHz channel bandwidth) ☒ 802.11n/ac (40MHz channel bandwidth) ☐ 802.11ac(80MHz channel bandwidth)
	Data Rate	802.11a: 6,9,12,18,24,36,48,54Mbps; 802.11n/ac(HT20/HT40):MCS0-MCS7;
	Modulation	OFDM with BPSK/QPSK/16QAM/64QAM/256QAM for 802.11a/n/ac;
	Operating Frequency Range	☒ 5180-5240MHz for 802.11a/n(HT20)/ac20; 5190-5230MHz for 802.11n(HT40)/ac40; ☐ 5260-5320MHz for 802.11a/n(HT20)/ac20; 5270-5310MHz for 802.11n(HT40)/ac40; ☐ 5500-5700MHz for 802.11a/n(HT20)/ac20; 5510-5670MHz for 802.11n(HT40)/ac40; ☒ 5745-5825 MHz for802.11a/n(HT20)/ac20; 5755-5795 MHz for 802.11a/n(HT40)/ac40;
	Number of Channels	☒ 4 channels for 802.11a/n20/ac20 in the 5180-5240MHz band ; 2 channels for 802.11 n40/ac40 in the 5190-5230 MHz band ; ☐ 4 channels for 802.11a/n20/ac20 in the 5260-5320MHz band ; 2 channels for 802.11 n40/ac40 in the 5270-5310 MHz band ; ☐ 11 channels for 802.11a/n20/ac20 in the 5500-5700MHz band ; 5 channels for 802.11 n40/ac40 in the 5510-5670 MHz band ; ☒ 5 channels for 802.11a/n20/ac20 in the 5745-5825MHz band ; 2 channels for 802.11 n40/ac40 in the 5755-5795 MHz band ;
TPC:	☐ Supported ☒ Unspported	
Channel Puncturing Function:	☒ Supported ☐ Unspported	
Antenna Type and Antenna gain:	FPC Antenna, 5.2GWi-Fi: 0.98dBi, 5.8GWi-Fi:1.43dBi	
Power supply:	Input: 12 V $\pm$ 3 A or DC 7.4V Rechargeable Li-ion battery	
Channel List	Please refer to the Note 2.	
AC Adapter:	MODEL:FJ-GN236CN Input: 100-240 V~, 50/60 Hz,1.2 A Max USB-C Output: 5.0 V $\pm$ 3.0 A, 9.0 V $\pm$ 3.0 A, 12.0 V $\pm$ 3.0 A. 15.0 V $\pm$ 2.4 A, 20.0 V $\pm$ 1.8 A, 36.0 W MAX Manufacturer: HUIZHOUFUJIA APPLIANCE TECH.CO.,LTD.	
Remote Control:	DC 3 V	

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

802.11a/n/ac(20MHz) Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	40	5200	48	5240
149	5745	153	5765	157	5785	161	5805
165	5825						

802.11n(40MHz) Frequency Channel							
802.11n /ac(40MHz)Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	46	5230	151	5755	159	5795

2.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Pretest Mode	Description
Mode 1	802.11a / n20/ac 20/ CH36/ CH40/ CH48/ CH149 / CH157 / CH165
Mode 2	802.11n 40/ac40 CH38/ CH46/ CH151/ CH159
Mode 3	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11a / n20/ac 20/ CH36/ CH40/ CH48/ CH149 / CH157 / CH165
Mode 2	802.11n 40/ac40 CH38/ CH46/ CH151/ CH159
Mode 3	Link Mode

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.



2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emissions




Radiated Emission(30MHz-1GHz)



Radiated Emission(above 1GHz)



RF Conducted Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Laptop	Lenovo (Beijing) Co., Ltd	ThinkPad E480	N/A	AE
E-2	USB serial port board	/	/	/	AE

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) The test software is the adb.exe which can set the EUT into the individual test modes.TX Power:default.

3. TEST FACILITY AND TEST INSTRUMENT USED

3.1 TEST FACILITY

Guangdong Zhonghan Testing Technology Co., Ltd.
Add. : Room 104/201, Building 1, Yibaolai Industrial Park, Qiaotou, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

FCC Registration Number:255941
Designation Number: CN0325
IC Registered No.: 29832
CAB identifier: CN0143

3.2 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Equipment No.	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	100874	ZH-E005	Apr. 24, 2026	Apr. 23, 2027
2	Loop Antenna	TESEQ	HLA6121	58357	ZH-E036	Sept. 8, 2025	Sept. 7, 2026
3	Amplifier	Schwarzbeck	BBV 9743 B	00378	ZH-E019	Apr. 24, 2026	Apr. 23, 2027
4	Amplifier	Schwarzbeck	BBV 9718 B	00040	ZH-E021	May 8, 2026	May 7, 2027
5	Bilog Antenna	Schwarzbeck	VULB9162	00498	ZH-E017	Apr. 25, 2026	Apr. 24, 2027
6	Horn Antenna	Schwarzbeck	BBHA9120D	02623	ZH-E020	Apr. 25, 2026	Apr. 24, 2027
7	Horn Antenna	A.H.SYSTEMS	SAS574	588	ZH-E062	Oct. 20, 2025	Oct. 19, 2026
8	Amplifier	AEROFLEX	100KHz-40GHz	097	ZH-E063	Oct. 20, 2025	Oct. 19, 2026
9	Spectrum Analyzer	R&S	FSV40	101413	ZH-E064	Apr. 24, 2026	Apr. 23, 2027
10	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	ZH-E032	Apr. 24, 2026	Apr. 23, 2027
11	WIDBAND RADIO COMMUNICATION TESTER	R&S	CMW500	109863	ZH-E033	Apr. 24, 2026	Apr. 23, 2027
12	Single Generator	Agilent	N5182A	MY48180575	ZH-E034	Apr. 24, 2026	Apr. 23, 2027
13	Power Sensor	MWRFtest	MW100-RFCB	/	ZH-E066	Apr. 24, 2026	Apr. 23, 2027
14	CABLE	EMToni	DA800-NM-NM-11000MM	/	ZH-E018	Apr. 24, 2026	Apr. 23, 2027



Item	Equipment	Manufacturer	Model	Serial No.	Equipment No.	Last Cal.	Next Cal.
1	Receiver	R&S	ESCI	100874	ZH-E005	Apr. 24, 2026	Apr. 23, 2027
2	LISN	R&S	ENV216	102794	ZH-E006	Aug. 22, 2025	Aug. 21, 2026
3	ISN CAT 6	Schwarzbeck	NTFM 8158	00318	ZH-E012	Apr. 24, 2026	Apr. 23, 2027
4	ISN CAT 5	Schwarzbeck	CAT5 8158	00343	ZH-E013	Apr. 24, 2026	Apr. 23, 2027
5	Capacitive Voltage Probe	Schwarzbeck	CVP 9222C	00101	ZH-E014	May 8, 2026	May 7, 2027
6	Current Transformer Clamp	Schwarzbeck	SW 9605	SW9605 #209	ZH-E015	May 8, 2026	May 7, 2027
7	CABLE	EMToni	RG223-NM-BNCM-2000MM	/	ZH-E007	Apr. 24, 2026	Apr. 23, 2027

Conducted Test equipment

Item	Equipment	Manufacturer	Model	Serial No.	Equipment No.	Last Cal.	Next Cal.
1	Spectrum Analyzer	R&S	FSV40	101413	ZH-E064	Apr. 24, 2026	Apr. 23, 2027
2	Spectrum Analyzer	KEYSIGHT	N9020A	MY53420208	ZH-E032	Apr. 24, 2026	Apr. 23, 2027
3	Power Sensor	MWRFTest	MW100-RFCB	/	ZH-E066	Apr. 24, 2026	Apr. 23, 2027
4	Constant Temperature and Humidity Test Chamber	OJN	OJN-9606	/	ZH-B008	Apr. 15, 2026	Apr. 14, 2027
5	DC power supply	R&S	SMB100A	259098	ZH-SA135	Apr. 15, 2026	Apr. 14, 2027

3.3 TESTING SOFTWARE

Project	Software name	Edition
RF Conducted	MTS 8310	2.0.0.0
Conducted Emission	EZ-EMC	EMC-CON 3A1.1+
Radiated Emission	EZ-EMC	FA-03A2 RE+

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	0.92dB
2	RF conducted power	0.16dB
3	Conducted spurious emissions	0.21dB
4	All radiated emissions (9k-30MHz)	4.68dB
5	All radiated emissions (30-1GHz)	5.1dB
6	All radiated emissions (1-6GHz)	3.9dB
7	All radiated emissions (6GHz-18GHz)	4.3dB
8	All radiated emissions (18-40GHz)	4.65dB
9	Temperature	0.5°C
10	Humidity	2%
11	Occupied Bandwidth	4.96%
12	RF Power Density	0.77dB

Decision Rule

- ☒ Uncertainty is not included
☐ Uncertainty is included

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207, RSS-Gen 8.8
Test Method:	ANSI C63.10-2020 + Cor.1-2023 + C63.10a-2024 + Errata to C63.10a-2024
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



4.1.6 TEST RESULTS

Temperature:	24.6℃	Relative Humidity :	54.3%
Pressure:	101.4kPa	Phase :	L
Test Voltage:	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1768	17.67	9.90	27.57	64.63	-37.06	QP	P	
2	0.1768	3.23	9.90	13.13	54.63	-41.50	AVG	P	
3	0.2940	16.86	9.95	26.81	60.41	-33.60	QP	P	
4	0.2940	5.17	9.95	15.12	50.41	-35.29	AVG	P	
5	0.3634	18.32	9.97	28.29	58.65	-30.36	QP	P	
6	0.3634	9.96	9.97	19.93	48.65	-28.72	AVG	P	
7	0.4468	14.27	10.00	24.27	56.93	-32.66	QP	P	
8	0.4468	3.27	10.00	13.27	46.93	-33.66	AVG	P	
9	0.4711	17.98	10.01	27.99	56.49	-28.50	QP	P	
10	0.4711	3.44	10.01	13.45	46.49	-33.04	AVG	P	
11	0.5128	15.61	10.02	25.63	56.00	-30.37	QP	P	
12 *	0.5128	7.71	10.02	17.73	46.00	-28.27	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case 802.11n(HT40) 5755MHz.



Temperature:	24.6°C	Relative Humidity :	54.3%
Pressure:	101.4kPa	Phase :	N
Test Voltage:	AC 120V/60Hz		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1635	28.10	9.90	38.00	65.28	-27.28	peak	P	
2	0.1635	3.59	9.90	13.49	55.28	-41.79	AVG	P	
3	0.2040	25.09	9.91	35.00	63.45	-28.45	peak	P	
4	0.2040	4.71	9.91	14.62	53.45	-38.83	AVG	P	
5	0.2490	25.40	9.93	35.33	61.79	-26.46	peak	P	
6	0.2490	4.16	9.93	14.09	51.79	-37.70	AVG	P	
7	0.3345	21.82	9.96	31.78	59.34	-27.56	peak	P	
8	0.3345	4.75	9.96	14.71	49.34	-34.63	AVG	P	
9	0.4811	19.95	10.01	29.96	56.32	-26.36	peak	P	
10	0.4811	3.86	10.01	13.87	46.32	-32.45	AVG	P	
11	7.8855	21.97	10.10	32.07	60.00	-27.93	peak	P	
12 *	7.8855	15.82	10.10	25.92	50.00	-24.08	AVG	P	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor
4. The test data shows only the worst case 802.11n(HT40) 5755MHz.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 APPLICABLE STANDARD

According to FCC Part 15.407(d) and 15.209, RSS-247 6.2.1.2, RSS-Gen

4.2.2 CONFORMANCE LIMIT

According to FCC Part 15.407(b)(7): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

RSS-Gen 8.10 Restricted frequency bands

MHz	MHz	MHz	GHz
0.090 - 0.110	13.36 - 13.41	960 - 1427	9.0 - 9.2
0.495 - 0.505	16.42 - 16.423	1435 - 1626.5	9.3 - 9.5
2.1735 - 2.1905	16.69475 - 16.69525	1645.5 - 1646.5	10.6 - 12.7
3.020 - 3.026	16.80425 - 16.80475	1660 - 1710	13.25 - 13.4
4.125 - 4.128	25.5 - 25.67	1718.8 - 1722.2	14.47 - 14.5
4.17725 - 4.17775	37.5 - 38.25	2200 - 2300	15.35 - 16.2
4.20725 - 4.20775	73 - 74.6	2310 - 2390	17.7 - 21.4
5.677 - 5.683	74.8 - 75.2	2483.5 - 2500	22.01 - 23.12
6.215 - 6.218	108 - 138	2655 - 2900	23.6 - 24.0
6.26775 - 6.26825	149.9 - 150.05	3260 - 3267	31.2 - 31.8
6.31175 - 6.31225	156.52475-156.52525	3332 - 3339	36.43 - 36.5
8.291 - 8.294	156.7 - 156.9	3345.8 - 3358	Above 38.6
8.362 - 8.366	162.0125 - 167.17	3500 - 4400	
8.37625 - 8.38675	167.72 - 173.2	4500 - 5150	
8.41425 - 8.41475	240 - 285	5350 - 5460	
12.29 - 12.293	322 - 335.4	7250 - 7750	
12.51975 - 12.52025	399.9 - 410	8025 - 8500	
12.57675 - 12.57725	608 - 614		

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

Limits of unwanted emission out of the restricted bands

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBuV/m)
5150~5250	-27	68.2
5250~5350	-27	68.2
5470~5725	-27	68.2
5725~5850	-27(Note 2)	68.2
	10(Note 2)	105.2
	15.6(Note 2)	110.8
	27(Note 2)	122.2

NOTE:

1, The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \text{ uV/m, where P is the eirp (Watts)}$$

2, According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

According to RSS-Gen§8.9: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field

strength limits specified in RSS-Gen Issue 5 is not required.

In case the emission fall within the restricted band specified on RSS-Gen Issue 5, then the RSS-Gen Issue 5 limit in the table below has to be followed.


Frequency (MHz)	Distance (Meters)	Radiated (dBuV/m)	Radiated (uV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

4.2.3 MEASURING INSTRUMENTS


The Measuring equipment is listed in the section 6.3 of this test report.

4.2.4 TEST CONFIGURATION


1. For radiated emissions below 30MHz



2. For radiated emissions from 30MHz to 1000MHz



3. Radiated Emission Test-Up Frequency Above 1GHz





4.2.5 TEST PROCEDURE

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2020+Cor 1-2023. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020+Cor 1-2023 and CAN/CSA-CEI/IEC CISPR 22. This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$, the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.


4.2.6 TEST RESULT(Between 9KHz – 30MHz)

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.




Between 30MHz – 1GHz

Temperature:	24.2℃	Relative Humidity:	52.3%
Pressure:	101.4kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		





Temperature:	24.2℃	Relative Humidity:	52.3%
Pressure:	101.4kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F
1 *	601.4265	42.18	-1.64	40.54	46.00	-5.46	QP	-	-	P
2	833.3170	35.32	1.76	37.08	46.00	-8.92	QP	-	-	P
3	872.1832	30.84	2.51	33.35	46.00	-12.65	QP	-	-	P
4	900.1473	31.24	3.05	34.29	46.00	-11.71	QP	-	-	P
5	932.2714	31.02	3.35	34.37	46.00	-11.63	QP	-	-	P
6	1000.0000	37.66	3.99	41.65	54.00	-12.35	QP	-	-	P

Remarks:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. All mode have been tested, The worst mode is 802.11n(HT40) 5755MHz is recorded.



Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n(HT40)-5755MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	16096.0000	34.82	18.51	53.33	74.00	-20.67	peak
2	16096.0000	23.71	18.51	42.22	54.00	-11.78	AVG
3	16742.0000	36.17	20.06	56.23	74.00	-17.77	peak
4	16742.0000	24.65	20.06	44.71	54.00	-9.29	AVG
5	17779.0000	35.22	22.13	57.35	74.00	-16.65	peak
6 *	17779.0000	24.19	22.13	46.32	54.00	-7.68	AVG




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36370.0000	56.38	0.59	56.97	74.00	-17.03	peak
2	36370.0000	44.58	0.59	45.17	54.00	-8.83	AVG
3	38064.0000	58.55	-1.02	57.53	74.00	-16.47	peak
4 *	38064.0000	46.83	-1.02	45.81	54.00	-8.19	AVG
5	39736.0000	55.85	1.31	57.16	74.00	-16.84	peak
6	39736.0000	44.20	1.31	45.51	54.00	-8.49	AVG



Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n(HT40)-5755MHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	15688.0000	38.00	15.91	53.91	74.00	-20.09	peak
2	15688.0000	26.21	15.91	42.12	54.00	-11.88	AVG
3	16334.0000	39.30	16.21	55.51	74.00	-18.49	peak
4	16334.0000	26.78	16.21	42.99	54.00	-11.01	AVG
5	17915.0000	35.13	22.28	57.41	74.00	-16.59	peak
6 *	17915.0000	23.76	22.28	46.04	54.00	-7.96	AVG



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36766.0000	56.88	0.54	57.42	74.00	-16.58	peak
2	36766.0000	44.67	0.54	45.21	54.00	-8.79	AVG
3	38064.0000	58.47	-1.02	57.45	74.00	-16.55	peak
4 *	38064.0000	46.96	-1.02	45.94	54.00	-8.06	AVG
5	39340.0000	57.58	0.59	58.17	74.00	-15.83	peak
6	39340.0000	45.01	0.59	45.60	54.00	-8.40	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n(HT40)-5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	15722.0000	35.04	17.77	52.81	74.00	-21.19	peak
2	15722.0000	23.58	17.77	41.35	54.00	-12.65	AVG
3	16878.0000	35.77	20.39	56.16	74.00	-17.84	peak
4	16878.0000	23.40	20.39	43.79	54.00	-10.21	AVG
5	17779.0000	35.43	22.13	57.56	74.00	-16.44	peak
6 *	17779.0000	23.96	22.13	46.09	54.00	-7.91	AVG




100 dBuV/m




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36700.0000	55.68	0.55	56.23	74.00	-17.77	peak
2	36700.0000	44.24	0.55	44.79	54.00	-9.21	AVG
3	38042.0000	59.34	-1.03	58.31	74.00	-15.69	peak
4	38042.0000	46.70	-1.03	45.67	54.00	-8.33	AVG
5	39802.0000	55.75	1.45	57.20	74.00	-16.80	peak
6 *	39802.0000	44.78	1.45	46.23	54.00	-7.77	AVG



Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n(HT40)-5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	15637.0000	37.55	16.04	53.59	74.00	-20.41	peak
2	15637.0000	25.00	16.04	41.04	54.00	-12.96	AVG
3	16708.0000	38.30	17.87	56.17	74.00	-17.83	peak
4	16708.0000	26.28	17.87	44.15	54.00	-9.85	AVG
5	17830.0000	34.68	21.67	56.35	74.00	-17.65	peak
6 *	17830.0000	24.07	21.67	45.74	54.00	-8.26	AVG



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36744.0000	56.53	0.54	57.07	74.00	-16.93	peak
2	36744.0000	44.57	0.54	45.11	54.00	-8.89	AVG
3	38064.0000	58.55	-1.02	57.53	74.00	-16.47	peak
4	38064.0000	46.78	-1.02	45.76	54.00	-8.24	AVG
5	39428.0000	57.52	0.77	58.29	74.00	-15.71	peak
6 *	39428.0000	45.61	0.77	46.38	54.00	-7.62	AVG


Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
4. All the modes have been tested and recorded worst 802.11n(HT40) 5755MHz mode in the report.



RADIATED Band EMISSION MEASUREMENT


Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11a-5180MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5043.5600	32.46	5.21	37.67	74.00	-36.33	peak
2	5043.5600	19.63	5.21	24.84	54.00	-29.16	AVG
3	5150.0000	30.95	5.39	36.34	74.00	-37.66	peak
4 *	5150.0000	19.84	5.39	25.23	54.00	-28.77	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11a-5180MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5046.2599	32.86	5.45	38.31	74.00	-35.69	peak
2	5046.2599	19.26	5.45	24.71	54.00	-29.29	AVG
3	5150.0000	30.55	5.54	36.09	74.00	-37.91	peak
4 *	5150.0000	19.85	5.54	25.39	54.00	-28.61	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11a-5240MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	31.78	5.72	37.50	74.00	-36.50	peak
2	5350.0000	21.56	5.72	27.28	54.00	-26.72	AVG
3	5402.9800	34.05	5.80	39.85	74.00	-34.15	peak
4 *	5402.9800	21.57	5.80	27.37	54.00	-26.63	AVG


Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11a-5240MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	32.93	5.12	38.05	74.00	-35.95	peak
2	5350.0000	22.26	5.12	27.38	54.00	-26.62	AVG
3	5419.2599	34.74	5.24	39.98	74.00	-34.02	peak
4 *	5419.2599	22.27	5.24	27.51	54.00	-26.49	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n20-5180MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5133.0200	32.53	5.36	37.89	74.00	-36.11	peak
2 *	5133.0200	20.19	5.36	25.55	54.00	-28.45	AVG
3	5150.0000	30.53	5.39	35.92	74.00	-38.08	peak
4	5150.0000	19.96	5.39	25.35	54.00	-28.65	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n20-5180MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5133.5600	32.85	5.43	38.28	74.00	-35.72	peak
2	5133.5600	19.99	5.43	25.42	54.00	-28.58	AVG
3	5150.0000	31.97	5.54	37.51	74.00	-36.49	peak
4 *	5150.0000	20.03	5.54	25.57	54.00	-28.43	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n20-5240MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	32.16	5.72	37.88	74.00	-36.12	peak
2	5350.0000	21.62	5.72	27.34	54.00	-26.66	AVG
3	5389.6600	34.49	5.78	40.27	74.00	-33.73	peak
4 *	5389.6600	21.93	5.78	27.71	54.00	-26.29	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n20-5240MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	33.04	5.12	38.16	74.00	-35.84	peak
2	5350.0000	22.37	5.12	27.49	54.00	-26.51	AVG
3	5356.1750	35.14	5.10	40.24	74.00	-33.76	peak
4 *	5356.1750	22.42	5.10	27.52	54.00	-26.48	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11ac20-5180MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5121.6800	32.72	5.34	38.06	74.00	-35.94	peak
2	5121.6800	19.96	5.34	25.30	54.00	-28.70	AVG
3	5150.0000	31.01	5.39	36.40	74.00	-37.60	peak
4 *	5150.0000	20.30	5.39	25.69	54.00	-28.31	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11ac20-5180MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5123.8400	32.46	5.36	37.82	74.00	-36.18	peak
2	5123.8400	19.96	5.36	25.32	54.00	-28.68	AVG
3	5150.0000	30.61	5.54	36.15	74.00	-37.85	peak
4 *	5150.0000	20.21	5.54	25.75	54.00	-28.25	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11ac20-5240MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	32.29	5.72	38.01	74.00	-35.99	peak
2 *	5350.0000	21.82	5.72	27.54	54.00	-26.46	AVG
3	5380.7799	34.64	5.76	40.40	74.00	-33.60	peak
4	5380.7799	21.78	5.76	27.54	54.00	-26.46	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11ac20-5240MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	33.20	5.12	38.32	74.00	-35.68	peak
2 *	5350.0000	22.65	5.12	27.77	54.00	-26.23	AVG
3	5360.8000	35.96	5.09	41.05	74.00	-32.95	peak
4	5360.8000	22.50	5.09	27.59	54.00	-26.41	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n40-5190MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5088.4800	32.40	5.28	37.68	74.00	-36.32	peak
2	5088.4800	19.62	5.28	24.90	54.00	-29.10	AVG
3	5150.0000	31.16	5.39	36.55	74.00	-37.45	peak
4 *	5150.0000	20.02	5.39	25.41	54.00	-28.59	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n40-5190MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5129.4500	38.24	5.40	43.64	74.00	-30.36	peak
2	5129.4500	20.63	5.40	26.03	54.00	-27.97	AVG
3	5150.0000	34.44	5.54	39.98	74.00	-34.02	peak
4 *	5150.0000	20.59	5.54	26.13	54.00	-27.87	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n40-5230MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	33.18	5.72	38.90	74.00	-35.10	peak
2	5350.0000	21.60	5.72	27.32	54.00	-26.68	AVG
3	5380.1400	35.27	5.76	41.03	74.00	-32.97	peak
4 *	5380.1400	21.99	5.76	27.75	54.00	-26.25	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n40-5230MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	32.83	5.12	37.95	74.00	-36.05	peak
2	5350.0000	22.40	5.12	27.52	54.00	-26.48	AVG
3	5382.8600	35.74	5.03	40.77	74.00	-33.23	peak
4 *	5382.8600	22.66	5.03	27.69	54.00	-26.31	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11ac40-5190MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5091.2000	31.91	5.29	37.20	74.00	-36.80	peak
2	5091.2000	19.59	5.29	24.88	54.00	-29.12	AVG
3	5150.0000	30.62	5.39	36.01	74.00	-37.99	peak
4 *	5150.0000	19.95	5.39	25.34	54.00	-28.66	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11ac40-5190MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5142.0299	35.86	5.48	41.34	74.00	-32.66	peak
2 *	5142.0299	20.44	5.48	25.92	54.00	-28.08	AVG
3	5150.0000	32.76	5.54	38.30	74.00	-35.70	peak
4	5150.0000	20.32	5.54	25.86	54.00	-28.14	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11ac40-5230MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	33.43	5.72	39.15	74.00	-34.85	peak
2	5350.0000	21.80	5.72	27.52	54.00	-26.48	AVG
3	5362.2900	35.25	5.73	40.98	74.00	-33.02	peak
4 *	5362.2900	22.00	5.73	27.73	54.00	-26.27	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11ac40-5230MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5350.0000	33.34	5.12	38.46	74.00	-35.54	peak
2 *	5350.0000	22.41	5.12	27.53	54.00	-26.47	AVG
3	5372.8300	35.02	5.06	40.08	74.00	-33.92	peak
4	5372.8300	22.40	5.06	27.46	54.00	-26.54	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11a-5745MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5695.9800	33.52	6.33	39.85	74.00	-34.15	peak
2	5695.9800	20.19	6.33	26.52	54.00	-27.48	AVG
3	5725.0000	35.52	6.37	41.89	74.00	-32.11	peak
4 *	5725.0000	21.77	6.37	28.14	54.00	-25.86	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11a-5745MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5708.5600	39.02	6.09	45.11	74.00	-28.89	peak
2	5708.5600	21.47	6.09	27.56	54.00	-26.44	AVG
3	5725.0000	44.97	6.30	51.27	74.00	-22.73	peak
4 *	5725.0000	25.83	6.30	32.13	54.00	-21.87	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11a-5825MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5825.0000	60.86	6.56	67.42	74.00	-6.58	peak
2 *	5825.0000	52.30	6.56	58.86	54.00	4.86	AVG
3	5842.9400	39.02	6.59	45.61	74.00	-28.39	peak
4	5842.9400	22.15	6.59	28.74	54.00	-25.26	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11a-5825MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 X	5825.0000	67.53	6.62	74.15	74.00	0.15	peak
2 *	5825.0000	58.74	6.62	65.36	54.00	11.36	AVG
3	5842.9400	42.27	6.67	48.94	74.00	-25.06	peak
4	5842.9400	22.83	6.67	29.50	54.00	-24.50	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n20-5745MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5701.5299	34.39	6.33	40.72	74.00	-33.28	peak
2	5701.5299	20.63	6.33	26.96	54.00	-27.04	AVG
3	5725.0000	38.86	6.37	45.23	74.00	-28.77	peak
4 *	5725.0000	22.04	6.37	28.41	54.00	-25.59	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n20-5745MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5714.2950	42.03	6.17	48.20	74.00	-25.80	peak
2	5714.2950	22.07	6.17	28.24	54.00	-25.76	AVG
3	5725.0000	46.84	6.30	53.14	74.00	-20.86	peak
4 *	5725.0000	26.98	6.30	33.28	54.00	-20.72	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n20-5825MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5825.0000	61.29	6.56	67.85	74.00	-6.15	peak
2 *	5825.0000	52.74	6.56	59.30	54.00	5.30	AVG
3	5840.5350	42.60	6.59	49.19	74.00	-24.81	peak
4	5840.5350	23.61	6.59	30.20	54.00	-23.80	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n20-5825MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5825.0000	67.25	6.62	73.87	74.00	-0.13	peak
2 *	5825.0000	58.73	6.62	65.35	54.00	11.35	AVG
3	5842.3849	45.69	6.66	52.35	74.00	-21.65	peak
4	5842.3849	23.59	6.66	30.25	54.00	-23.75	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11ac20-5745MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5720.5850	35.59	6.36	41.95	74.00	-32.05	peak
2	5720.5850	20.93	6.36	27.29	54.00	-26.71	AVG
3	5725.0000	34.87	6.37	41.24	74.00	-32.76	peak
4 *	5725.0000	21.30	6.37	27.67	54.00	-26.33	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11ac20-5745MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5720.5850	43.15	6.25	49.40	74.00	-24.60	peak
2	5720.5850	23.46	6.25	29.71	54.00	-24.29	AVG
3 *	5725.0000	48.25	6.30	54.55	74.00	-19.45	peak
4	5725.0000	27.03	6.30	33.33	54.00	-20.67	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11ac20-5825MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5825.0000	61.04	6.56	67.60	74.00	-6.40	peak
2 *	5825.0000	52.60	6.56	59.16	54.00	5.16	AVG
3	5844.4200	39.73	6.59	46.32	74.00	-27.68	peak
4	5844.4200	21.86	6.59	28.45	54.00	-25.55	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11ac20-5825MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 X	5825.0000	67.78	6.62	74.40	74.00	0.40	peak
2 *	5825.0000	58.57	6.62	65.19	54.00	11.19	AVG
3	5845.1600	40.06	6.67	46.73	74.00	-27.27	peak
4	5845.1600	21.91	6.67	28.58	54.00	-25.42	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n40-5755MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5715.9450	37.71	6.36	44.07	74.00	-29.93	peak
2 *	5715.9450	21.28	6.36	27.64	54.00	-26.36	AVG
3	5725.0000	38.19	6.37	44.56	74.00	-29.44	peak
4	5725.0000	21.25	6.37	27.62	54.00	-26.38	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n40-5755MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	5720.5650	47.75	6.25	54.00	74.00	-20.00	peak
2	5720.5650	25.60	6.25	31.85	54.00	-22.15	AVG
3	5725.0000	46.16	6.30	52.46	74.00	-21.54	peak
4	5725.0000	27.12	6.30	33.42	54.00	-20.58	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11n40-5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5825.0000	31.81	6.56	38.37	74.00	-35.63	peak
2	5825.0000	20.90	6.56	27.46	54.00	-26.54	AVG
3	5831.4100	37.30	6.58	43.88	74.00	-30.12	peak
4 *	5831.4100	21.17	6.58	27.75	54.00	-26.25	AVG




Temperature:	24.8℃	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11n40-5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5825.0000	35.92	6.62	42.54	74.00	-31.46	peak
2 *	5825.0000	21.96	6.62	28.58	54.00	-25.42	AVG
3	5829.7700	38.63	6.64	45.27	74.00	-28.73	peak
4	5829.7700	21.45	6.64	28.09	54.00	-25.91	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11ac40-5755MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5711.8200	35.53	6.35	41.88	74.00	-32.12	peak
2	5711.8200	20.69	6.35	27.04	54.00	-26.96	AVG
3	5725.0000	35.26	6.37	41.63	74.00	-32.37	peak
4 *	5725.0000	21.29	6.37	27.66	54.00	-26.34	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11ac40-5755MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	5721.8849	48.21	6.26	54.47	74.00	-19.53	peak
2	5721.8849	25.83	6.26	32.09	54.00	-21.91	AVG
3	5725.0000	44.86	6.30	51.16	74.00	-22.84	peak
4	5725.0000	26.76	6.30	33.06	54.00	-20.94	AVG




Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Horizontal
Test Voltage:	DC 7.4V	Test mode:	802.11ac40-5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5825.0000	32.26	6.56	38.82	74.00	-35.18	peak
2 *	5825.0000	21.19	6.56	27.75	54.00	-26.25	AVG
3	5832.0250	35.56	6.58	42.14	74.00	-31.86	peak
4	5832.0250	21.07	6.58	27.65	54.00	-26.35	AVG



Temperature:	24.8°C	Relative Humidity:	61.2%
Pressure:	1014kPa	Polarization:	Vertical
Test Voltage:	DC 7.4V	Test mode:	802.11ac40-5795MHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5825.0000	35.13	6.62	41.75	74.00	-32.25	peak
2 *	5825.0000	21.81	6.62	28.43	54.00	-25.57	AVG
3	5848.8350	35.67	6.68	42.35	74.00	-31.65	peak
4	5848.8350	21.16	6.68	27.84	54.00	-26.16	AVG



5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

According to FCC §15.407(a)

Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.2 TEST PROCEDURE

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or <500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHZ is available on nearly all spectrum analyzers.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



5.6 TEST RESULTS

Temperature :	24.0℃	Relative Humidity:	53.3%
Pressure :	101.4kPa	Test Voltage :	DC 7.4 V
Test Mode :	TX		
5.2G(5180-5240MHz):	Please refer to the Appendix A.5 for 5G WIFI RF Test Data.		
5.8G(5745-5825 MHz):	Please refer to the Appendix B.5 for 5G WIFI RF Test Data.		



6. 26DB & 6DB & 99% EMISSION BANDWIDTH

6.1 APPLIED PROCEDURES / LIMIT

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band, the minimum bandwidth 6 dB bandwidth of U-NII devices shall be at least 500KHz. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

6.2 TEST PROCEDURE

- a) Set RBW = 1 % to 5 % of the OBW .
- b) Set the VBW = 3 · RBW
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by -26 dB relative to the maximum level measured in the fundamental emission.

The following procedure shall be used for measuring (99 %) power bandwidth:

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.


Emission bandwidth for the band 5.725 GHz to 5.85 GHz.

The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.



- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



6.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.4 TEST RESULTS

Temperature :		24.0℃	Relative Humidity:	53.3%
Pressure :		101.4kPa	Test Voltage :	DC 7.4 V
Test Mode :		TX		
-26dB Bandwidth	5.2G(5180-5240MHz):	Please refer to the Appendix A.3 for 5G WIFI RF Test Data.		
-6dB Bandwidth	5.8G(5745-5825 MHz):	Please refer to the Appendix B.3 for 5G WIFI RF Test Data.		
99% Bandwidth	5.2G(5180-5240MHz):	Please refer to the Appendix A.4 for 5G WIFI RF Test Data.		
	5.8G(5745-5825 MHz):	Please refer to the Appendix B.4 for 5G WIFI RF Test Data.		



7. MAXIMUM CONDUCTED OUTPUT POWER

7.1 PLIED PROCEDURES / LIMIT

According to FCC §15.407,
The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	250mW
5725~5850	1W

For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power.

For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.

If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.850 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

7.2 TEST PROCEDURE

According 789033 D02 General UNII Test Procedures New Rules v02r01.

EUT Measurement using a Power Meter (PM)

a) Method PM (Measurement using an RF average power meter):

(i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:

- The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
- At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
- The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.

(ii) If the transmitter does not transmit continuously, measure the duty cycle, x , of the transmitter output signal as described in II.B.

(iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

(iv) Adjust the measurement in dBm by adding $10 \log (1/x)$ where x is the duty cycle (e.g., $10 \log (1/0.25)$ if the duty cycle is 25%).

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.6 TEST RESULTS

Temperature :	24.0℃	Relative Humidity:	53.3%
Pressure :	101.4kPa	Test Voltage :	DC 7.4 V
Test Mode :	TX		
5.2G (5180-5240MHz):	Please refer to the Appendix A.7 for 5G WIFI RF Test Data.		
5.8G(5745-5825 MHz):	Please refer to the Appendix B.7 for 5G WIFI RF Test Data.		



8.OUT OF BAND EMISSIONS

8.1 APPLICABLE STANDARD

According to FCC §15.407(b), RSS-247 6.2.1.2, RSS-247 6.2.4.2

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:
 - (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 - (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in § 15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.

According to RSS-247 section 6.2.1.2: For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250- 5350 MHz band.



1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULTS

Temperature :	24.0℃	Relative Humidity:	53.3%
Pressure :	101.4kPa	Test Voltage :	DC 7.4 V
Test Mode :	TX		
5.2G (5180-5240MHz):	Please refer to the Appendix A.6 for 5G WIFI RF Test Data.		
5.8G(5745-5825 MHz):	Please refer to the Appendix B.6 for 5G WIFI RF Test Data.		



9.SPURIOUS RF CONDUCTED EMISSIONS

9.1 CONFORMANCE LIMIT

Refer to 15.407(b):

Except as shown in paragraph 15.407(b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

Refer to RSS-247/6.2.1.2:

For transmitters with operating frequencies in the band 5150-5250 MHz, all emissions outside the band 5150-5350 MHz shall not exceed -27 dBm/MHz e.i.r.p. Any unwanted emissions that fall into the band 5250-5350 MHz shall be attenuated below the channel power by at least 26 dB, when measured using a resolution bandwidth between 1 and 5% of the occupied bandwidth (i.e. 99% bandwidth), above 5250 MHz. The 26 dB bandwidth may fall into the 5250-5350 MHz band; however, if the occupied bandwidth also falls within the 5250-5350 MHz band, the transmission is considered as intentional and the devices shall comply with all requirements in the band 5250-5350 MHz including implementing dynamic frequency selection (DFS) and TPC, on the portion of the emission that resides in the 5250-5350 MHz band.

Devices operating in the band 5725-5850 MHz shall have e.i.r.p. of unwanted emissions comply with the following:

- a) 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges;
- b) 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges;
- c) 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and
- d) -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.

9.2 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

9.3 TEST SETUP



9.4 TEST PROCEDURE

The Spurious RF conducted emissions compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10-2020+Cor 1-2023 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW=100kHz and VBW= 300kHz to measure the peak field strength, and measure frequency range from 30MHz to 1GHz. Set RBW=1MHz and VBW= 3MHz to measure the peak field strength, and measure frequency range from 1GHz to 40GHz.



Temperature :	24.0℃	Relative Humidity:	53.3%
Pressure :	101.4kPa	Test Voltage :	DC 7.4 V
Test Mode :	TX		
5.2G (5180-5240MHz):	Please refer to the Appendix A.8 for 5G WIFI RF Test Data.		
5.8G(5745-5825 MHz):	Please refer to the Appendix B.8 for 5G WIFI RF Test Data.		

Remark1: The measurement frequency range is from 30MHz to the 10th harmonic or 40G of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandedge measurement data.

Remark2: From 26.5GHz to 40GHz, the amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



10.FREQUENCY STABILITY MEASUREMENT

10.1 LIMIT


Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

According to RSS-247 "Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual." According to RSS-Gen "The frequency stability shall be measured with variation of ambient temperature as follows:" (1) From -30° to $+50^{\circ}$ centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section. (2) From -20° to $+50^{\circ}$ centigrade for equipment to be licensed for use in the Maritime Services under part 80 of this chapter, except for Class A, B, and S Emergency Position Indicating Radiobeacons (EPIRBS), and equipment to be licensed for use above 952 MHz at operational fixed stations in all services, stations in the Local Television Transmission Service and Point-to-Point Microwave Radio Service under part 21 of this chapter, equipment licensed for use aboard aircraft in the Aviation Services under part 87 of this chapter, and equipment authorized for use in the Family Radio Service under part 95 of this chapter. (3) From 0° to $+50^{\circ}$ centigrade for equipment to be licensed for use in the Radio Broadcast Services under part 73 of this chapter.

10.2 TEST PROCEDURES

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 30 kHz with peak detector and maxhold settings.
5. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
6. Extreme temperature is $-30^{\circ}\text{C}\sim 50^{\circ}\text{C}$.

10.3 TEST SETUP LAYOUT



10.4 EUT OPERATION DURING TEST

The EUT was programmed to be in continuously un-modulation transmitting mode.

10.5 TEST RESULTS

Temperature :	24.0℃	Relative Humidity:	53.3%
Pressure :	101.4kPa	Test Voltage :	DC 7.4 V
Test Mode :	TX		
5.2G (5180-5240MHz):	Please refer to the Appendix A.7 for 5G WIFI RF Test Data.		
5.8G(5745-5825 MHz):	Please refer to the Appendix B.7 for 5G WIFI RF Test Data.		



Standard requirement:	FCC Part15 C Section 15.203, RSS-247 6.8
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the licence-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. Licence-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (EIRP) limits specified in the applicable standard (RSS) for the licence-exempt apparatus. Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.⁹ When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.	
EUT Antenna: The antenna is FPC Antenna, the best case gain of the antenna is 5.2GWi-Fi: 0.98dBi, 5.8GWi-Fi: 1.43dBi, reference to the appendix II for details.	



ZHONGHAN

12. TEST SETUP PHOTO

Reference to the appendix I for details.

13. EUT CONSTRUCTIONAL DETAILS

Reference to the appendix II for details.

***** **END OF REPORT** *****