

Product Name: Wireless Access Point	Report No: FCC022022-5921RF14
Product Model: AP 6WB	Security Classification: Open
Version: V1.0	Total Page: 7

TIRT Testing Report



Prepared By:	Checked By:	Approved By:	A circular blue stamp with the text "TIRT Technology Service Co., Ltd." around the perimeter and "TIRT Shenzhen" in the center.
Stone Tang	Randy Lv	Daniel Chen	
Stone Tang	Randy Lv	Daniel chen	

FCC RF EXPOSURE REPORT

FCC ID: 2A3WK-AP6WB

Project No. : 22022-05921
Equipment : Wireless Access Point
Brand Name : Nomadix
Test Model : AP 6WB
Series Model : NA
Applicant : Nomadix, Inc.
Address : 21600 Oxnard Street - 19th floor, Woodland Hills, California, United States
Manufacturer : Nomadix, Inc.
Address : 21600 Oxnard Street - 19th floor, Woodland Hills, California, United States
Factory : Nomadix, Inc.
Address : 21600 Oxnard Street - 19th floor, Woodland Hills, California, United States
Date of Receipt : Dec. 12, 2022
Date of Test : Dec. 12, 2022~Dec. 13, 2022
Issued Date : Dec. 21, 2022
Report Version : V1.0
Test Sample : 20221103020001
Standard(s) : FCC CFR Title 47, Part 15, Subpart C
FCC KDB 558074 D01 15.247 Meas Guidance v05r02
FCC KDB 662911 D01 Multiple Transmitter Output v02r01
ANSI C63.10-2013

- The test result referred exclusively to the presented test model /sample.
- Without written approval of TIRT Inc. the test report shall not reproduced except in full.

Lab: Beijing TIRT Technology Service Co.,Ltd Shenzhen

Add: 101, 3 # Factory Building, Gongjin Electronics Shatin Community, Kengzi Street, Pingshan

District, Shenzhen, China

TEL: +86-0755-27087573

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
FCC022022-5921RF14	V1.0	Original Report	Dec. 21, 2022	Valid

1. TEST FACILITY

Company:	Beijing TIRT Technology Service Co.,Ltd Shenzhen
Address:	101, 3 # Factory Building, Gongjin Electronics Shatin Community, Kengzi Street, Pingshan District, Shenzhen, China
CNAS Registration Number:	CNAS L14158
A2LA Registration Number:	6049.01
FCC Accredited Lab. Designation Number:	CN1309
FCC Test Firm Registration Number:	825524
Telephone:	+86-0755-27087573

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

For BLE:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Wanshih	TW2WFI0035A	PIFA	N/A	2.5

Note: The antenna gain is provided by the manufacturer.

For WIFI 2.4GHz:

Antenna Specification:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Wanshih	TW2WFI0036A	PIFA	MHF	3.7
2	Wanshih	TW2WFI0037A	PIFA	MHF	5.6

Note:

- 1) This EUT supports MIMO 2X2, any transmit signals are correlated with each other, so Directional gain=10log[(10^{G1/20}+10^{G2/20})/N]dBi, that is Directional gain=10log[(10^{3.7/20}+10^{5.6/20})/2]dBi =7.71.
- 2) The antenna gain and beamforming gain are provided by the manufacturer.

Table for Antenna Configuration:

Operating Mode	TX Mode	2TX
IEEE 802.11b		V(Ant. 1 + Ant. 2)
IEEE 802.11g		V(Ant. 1 + Ant. 2)
IEEE 802.11n(HT20)		V(Ant. 1 + Ant. 2)
IEEE 802.11n(HT40)		V(Ant. 1 + Ant. 2)
IEEE 802.11ax(HE20)		V(Ant. 1 + Ant. 2)
IEEE 802.11ax(HE40)		V(Ant. 1 + Ant. 2)

For WIFI 5GHz:

Antenna Specification:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Wanshih	TW2WFI0036A	PIFA	MHF	4.6
2	Wanshih	TW2WFI0037A	PIFA	MHF	5.5

Note:

- 1) This EUT supports MIMO 2X2, any transmit signals are correlated with each other, so Directional gain= $10\log[(10^{G1/20} + 10^{G2/20})^2 / N]$ dBi, that is Directional gain= $10\log[(10^{4.6/20} + 10^{5.5/20})^2 / 2]$ dBi =8.07.
- 2) The antenna gain and beamforming gain are provided by the manufacturer.

Table for Antenna Configuration:

Operating Mode	TX Mode	2TX
IEEE 802.11a		V (Ant. 1 + Ant. 2)
IEEE 802.11n(HT20)		V (Ant. 1 + Ant. 2)
IEEE 802.11n(HT40)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT20)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT40)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT80)		V (Ant. 1 + Ant. 2)
IEEE 802.11ac(VHT160)		V (Ant. 1 + Ant. 2)
IEEE 802.11ax(HE20)		V (Ant. 1 + Ant. 2)
IEEE 802.11ax(HE40)		V (Ant. 1 + Ant. 2)
IEEE 802.11ax(HE80)		V (Ant. 1 + Ant. 2)
IEEE 802.11ax(HE160)		V (Ant. 1 + Ant. 2)

3. TEST RESULTS

For BT (BLE):

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Tune up Power (dBm)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
2.50	1.7783	5.20	6.00	0.0014	1	Complies

For 2.4GHz:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Tune up Power (dBm)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
7.71	5.9020	25.73	26.00	0.4675	1	Complies

For 5GHz:

Directional Gain (dBi)	Directional Gain (numeric)	Max. Output Power (dBm)	Max. Tune up Power (dBm)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
8.07	6.4121	21.18	22.00	0.2022	1	Complies

For the max simultaneous transmission MPE:

Ratio			Total	Limit of Ratio	Test Result
BLE	2.4GHz	5GHz			
0.0014	0.4675	0.2022	0.6711	1	Complies

Note: 1. The calculated distance is 20 cm.
2. Max. Tune up Power is declared by the manufacturer.
3. WIFI 2.4GHz and 5GHz can be simultaneously transmitted.

End of Test Report