

TEST REPORT



DT&C Co., Ltd.

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2201-0013(1)

2. Customer

- Name (FCC) : HANYANG ELECTRONICS IND CO., LTD.
- Address (FCC) : #49, Seongsui-ro 20-gil, Seongdong-gu, Seoul, South Korea

3. Use of Report : FCC Original Grant

4. Product Name / Model Name : Wireless conference system Main Controller / KMC-200
FCC ID : 2A3WO-KMC-200

5. FCC Regulation(s): Part 15.247
Test Method used: KDB558074 D01v05r02, ANSI C63.10-2013


6. Date of Test : 2021.09.16 ~ 2022.01.07

7. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing

8. Testing Environment : See appended test report.

9. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Reviewed by
	Name : SeungMin Gil 	Name : JaeJin Lee 

2022 . 01 . 25 .

DT&C Co., Ltd.

If this report is required to confirmation of authenticity, please contact to report@dtnc.net

Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2201-0013	Jan. 13, 2022	Initial issue	SeungMin Gil	JaeJin Lee
DRTFCC2201-0013(1)	Jan. 25, 2022	Revised the section 8	SeungMin Gil	JaeJin Lee

Table of Contents

1. General Information.....	4
1.1. Description of EUT	4
1.2. Declaration by the applicant / manufacturer	4
1.3. Testing Laboratory	5
1.4. Testing Environment	5
1.5. Measurement Uncertainty	5
1.6. Conclusion of worst-case and operation mode	6
1.8. Test Equipment List.....	7
2. Antenna Requirement.....	8
3. Summary of Test Results	9
4. Maximum Peak Conducted Output Power	10
4.1. Test Setup	10
4.2. Limit.....	10
4.3. Test Procedure.....	10
4.4. Test Results	11
5. 20 dB BW	14
5.1. Test Setup	14
5.2. Limit.....	14
5.3. Test Procedure.....	14
5.4. Test Results	14
6. Carrier Frequency Separation	17
6.1. Test Setup	17
6.2. Limit.....	17
6.3. Test Procedure.....	17
6.4. Test Results	17
7. Number of Hopping Channels	19
7.1. Test Setup	19
7.2. Limit.....	19
7.3. Test Procedure.....	19
7.4. Test Results	19
8. Time of Occupancy.....	21
8.1. Test Setup	21
8.2. Limit.....	21
8.3. Test Procedure.....	21
8.4. Test Results	21
9. Unwanted Emissions.....	22
9.1. Test Setup	22
9.2. Limit.....	22
9.3. Test Procedures.....	24
9.3.1. Test Procedures for Unwanted Emissions(Radiated)	24
9.3.2. Test Procedures for Unwanted Emissions(Conducted).....	25
9.4. Test Results	26
9.4.1. Unwanted Emissions(Radiated).....	26
9.4.2. Unwanted Emissions(Conducted)	28
10. AC Power-Line Conducted Emissions.....	36
10.1. Test Setup	36
10.2. Limit.....	36
10.3. Test Procedure.....	36
10.4. Test Results	37
APPENDIX I.....	39
APPENDIX II.....	40

1. General Information

1.1. Description of EUT

Equipment Class	Part 15 Spread Spectrum Transmitter (DSS)
Product Name	Wireless conference system Main Controller
Model Name	KMC-200
Add Model Name	KMC-220, MCU-200, MCU-220
Firmware Version Identification Number	V 1.0
EUT Serial Number	No Specified
Power Supply	DC 5 V
Frequency Range	2 402 MHz ~ 2 476 MHz
Max. RF Output Power	14.67 dBm (0.029 W)
Modulation Technique	FSK (2Mbps)
Number of hopping Channels	16
Antenna Specification	Antenna Type: Dipole Antenna Gain: 2.72 dBi (PK)

1.2. Declaration by the applicant / manufacturer

- NA

1.3. Testing Laboratory

DT&C Co., Ltd.		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042.		
The test site complies with the requirements of Part 2.948 according to ANSI C63.4-2014.		
- FCC & IC MRA Designation No. : KR0034		
- ISED#: 5740A		
www.dtnc.net		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

1.4. Testing Environment

Ambient Condition	
▪ Temperature	+20 °C ~ +24 °C
▪ Relative Humidity	34 % ~ 46 %

1.5. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.4-2014 and ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
Antenna-port conducted emission	1.0 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (1 GHz Below)	4.9 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (1 GHz ~ 18 GHz)	5.0 dB (The confidence level is about 95 %, $k = 2$)
Radiated emission (18 GHz Above)	5.3 dB (The confidence level is about 95 %, $k = 2$)

1.6. Conclusion of worst-case and operation mode

Tested frequency information,

- Hopping Function : Enable

	Tested Frequency (MHz)
Hopping Band	2 402 ~ 2 476

- Hopping Function : Disable

	Tested Frequency (MHz)
Lowest Channel	2 402
Middle Channel	2 440
Highest Channel	2 476

1.8. Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	21/08/30	22/08/30	MY46471622
Spectrum Analyzer	Agilent Technologies	N9020A	20/12/16 21/12/16	21/12/16 22/12/16	MY48011700
Spectrum Analyzer	Agilent Technologies	N9020A	21/06/24	22/06/24	US47360812
Multimeter	FLUKE	17B+	20/12/16 21/12/16	21/12/16 22/12/16	36390701WS
Signal Generator	Rohde Schwarz	SMBV100A	20/12/16 21/12/16	21/12/16 22/12/16	255571
Signal Generator	ANRITSU	MG3695C	20/12/16 21/12/16	21/12/16 22/12/16	173501
Thermohygrometer	BODYCOM	BJ5478	20/12/16 21/12/16	21/12/16 22/12/16	120612-1
Thermohygrometer	BODYCOM	BJ5478	20/12/16 21/12/16	21/12/16 22/12/16	120612-2
Thermohygrometer	BODYCOM	BJ5478	21/06/24	22/06/24	N/A
Loop Antenna	ETS-Lindgren	6502	21/01/28	23/01/28	00226186
BILOG ANTENNA	Schwarzbeck	VULB 9160	20/12/16 21/12/16	21/12/16 22/12/16	3362
Horn Antenna	ETS-Lindgren	3117	21/06/24	22/06/24	00143278
Horn Antenna	A.H.Systems Inc.	SAS-574	21/06/24	22/06/24	155
PreAmplifier	tsj	MLA-0118-B01-40	20/12/16 21/12/16	21/12/16 22/12/16	1852267
PreAmplifier	tsj	MLA-1840-J02-45	21/06/24	22/06/24	16966-10728
PreAmplifier	H.P	8447D	20/12/16 21/12/16	21/12/16 22/12/16	2944A07774
High Pass Filter	Wainwright Instruments	WHKX12-935- 1000-15000-40SS	21/06/24	22/06/24	8
High Pass Filter	Wainwright Instruments	WHKX10-2838- 3300-18000-60SS	21/06/24	22/06/24	1
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5- 6SS	21/06/24	22/06/24	3
Attenuator	Hefei Shunze	SS5T2.92-10-40	21/06/24	22/06/24	16012202
Attenuator	Aeroflex/Weinschel	56-3	21/06/24	22/06/24	Y2370
Attenuator	SMAJK	SMAJK-2-3	21/06/24	22/06/24	3
Attenuator	SMAJK	SMAJK-2-3	21/06/24	22/06/24	2
Attenuator	Aeroflex/Weinschel	86-10-11	21/06/24	22/06/24	408
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2495A MA2490A	21/06/24	22/06/24	1306007 1249001
Cable	DT&C	Cable	21/01/08	22/01/08	G-1
Cable	DT&C	Cable	21/01/08	22/01/08	G-2
Cable	HUBER+SUHNER	SUCOFLEX 100	21/01/08	22/01/08	G-3
Cable	DT&C	Cable	21/01/08	22/01/08	G-4
Cable	Junkosha	MWX241	21/01/08	22/01/08	mmW-1
Cable	Junkosha	MWX241	21/01/08	22/01/08	mmW-4
Cable	HUBER+SUHNER	SUCOFLEX100	21/01/08	22/01/08	M-01
Cable	HUBER+SUHNER	SUCOFLEX100	21/01/08	22/01/08	M-02
Cable	JUNFLON	MWX241	21/01/08	22/01/08	M-03
Cable	JUNFLON	J12J101757-00	21/01/08	22/01/08	M-07
Cable	HUBER+SUHNER	SUCOFLEX106	21/01/08	22/01/08	M-09
Cable	DT&C	Cable	21/01/05 22/01/04	22/01/05 23/01/04	RFC-69
Test Software	tsj	Noise Terminal Measurement	NA	NA	Version 2.00.0170
Test Software	tsj	Radiated Emission Measurement	NA	NA	Version 2.00.0177

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017

Note2: The cable is not a regular calibration item, so it has been calibrated by DT & C itself.

2. Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions.

Conclusion: Comply

This device is professionally installed.

3. Summary of Test Results

FCC part section(s)	Test Description	Limit (Using in 2400~ 2483.5 MHz)	Test Condition	Status Note 1
15.247(a) 15.247(b)	Maximum Peak Conducted Output Power	=< 0.125 W(conducted)	Conducted	C
15.247(a)	20 dB Bandwidth	NA		C
	Carrier Frequency Separation	>= 25 kHz or >= the 20 dB BW, whichever is greater.		C
	Number of Hopping Channels	>= 15 hops		C
	Time of Occupancy	=< 0.4 seconds		C
15.247(d)	Unwanted Emissions (Conducted)	The radiated emission to any 100 kHz of out-band shall be at least 20 dB below the highest in-band spectral density.		C
15.247(d) 15.205 15.209	Unwanted Emissions (Radiated)	Part 15.209 Limits (Refer to section 9)	Radiated	C ^{Note3}
15.207	AC Power-Line Conducted Emissions	Part 15.207 Limits (Refer to section 10)	AC Line Conducted	C
15.203	Antenna Requirement	Part 15.203 (Refer to section 2)	-	C
Note 1: C = Comply NC = Not Comply NT = Not Tested NA = Not Applicable Note 2: For radiated emission tests below 30 MHz were performed on semi-anechoic chamber which is correlated with OATS. Note 3: This test item was performed in three orthogonal EUT positions and the worst case data was reported.				

4. Maximum Peak Conducted Output Power

4.1. Test Setup

Refer to the APPENDIX I.

4.2. Limit

■ FCC Requirements

The maximum peak output power of the intentional radiator shall not exceed the following :

1. §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. **Alternatively, frequency hopping systems operating in the 2 400 MHz - 2 483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.**
2. §15.247(b)(1), For frequency hopping systems operating in the 2 400 – 2 483.5 MHz employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5 725 MHz – 5 805 MHz band : 1 Watt. **For all other frequency hopping systems in the 2 400 MHz – 2 483.5 MHz band: 0.125 watts.**

4.3. Test Procedure

1. The RF output power was measured with a spectrum analyzer connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency, A spectrum analyzer was used to record the shape of the transmit signal.
2. The peak output power of the fundamental frequency was measured with the spectrum analyzer using ;
Span = approximately 5 times of the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ 20 dB BW
VBW $\geq$ RBW
Sweep = auto
Detector function = peak
Trace = max hold

4.4. Test Results


Modulation	Tested Channel	Burst Average Output Power		Peak Output Power	
		dBm	mW	dBm	mW
<u>FSK</u>	Lowest	11.55	14.29	11.71	14.83
	Middle	13.98	25.00	14.08	25.59
	Highest	14.53	28.38	14.67	29.31

Note 1: The average output power was tested using an average power meter for reference only.

Note 2: See next pages for actual measured spectrum plots.


Peak Output Power

Lowest Channel & Modulation : FSK




Peak Output Power

Middle Channel & Modulation : FSK



Peak Output Power

Highest Channel & Modulation : FSK



5. 20 dB BW

5.1. Test Setup

Refer to the APPENDIX I.

5.2. Limit

Limit : Not Applicable

5.3. Test Procedure

1. The 20 dB bandwidth was measured with a spectrum analyzer connected to RF antenna Connector (conducted measurement) while EUT was operating in transmit mode. The analyzer center frequency was set to the EUT carrier frequency, using the analyzer.

2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using below setting:

RBW = 1 % to 5 % of the 20 dB BW

VBW $\geq 3 \times$ RBW

Span = between two times and five times the 20 dB bandwidth

Sweep = auto

Detector function = peak

Trace = max hold

5.4. Test Results

Modulation	Tested Channel	20 dB BW (MHz)
<u>FSK</u>	Lowest	2.408
	Middle	2.409
	Highest	2.416


20 dB BW

Lowest Channel & Modulation : FSK



20 dB BW

Middle Channel & Modulation : FSK



20 dB BW

Highest Channel & Modulation : FSK



6. Carrier Frequency Separation

6.1. Test Setup

Refer to the APPENDIX I.

6.2. Limit

Limit : ≥ 25 kHz or $\geq$ the 20 dB BW whichever is greater.

6.3. Test Procedure

The carrier frequency separation was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

After the trace being stable, the reading value between the peaks of the adjacent channels using the marker-delta function was recorded as the measurement results.

The spectrum analyzer is set to :

Span = wide enough to capture the peaks of two adjacent channels

RBW = Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak


Trace = max hold

6.4. Test Results

Hopping Mode	Modulation	Peak of reference channel(MHz)	Peak of adjacent Channel(MHz)	Test Result (MHz)
Enable	FSK	2 437.472	2 439.472	2.000

Note 1 : See next pages for actual measured spectrum plots.

Carrier Frequency Separation (FH) *Hopping mode : Enable & FSK*



7. Number of Hopping Channels

7.1. Test Setup

Refer to the APPENDIX I.

7.2. Limit

Limit : ≥ 15 hops

7.3. Test Procedure

The number of hopping frequencies was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :

Start Frequency = 2 400 MHz, Stop Frequency = 2 483.5 MHz

RBW = To identify clearly the individual channels, set the RBW to less than 30 % of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


7.4. Test Results

Hopping mode	Modulation	Test Result (Total Hops)
Enable	FSK	16

Note 1 : See next pages for actual measured spectrum plots.

Number of Hopping Channels (FH)

Hopping mode : Enable & FSK



8. Time of Occupancy

8.1. Test Setup

Refer to the APPENDIX I.

8.2. Limit

The maximum permissible time of occupancy is 400 ms within a period of 400 ms multiplied by the number of hopping channels employed.

8.3. Test Procedure

The dwell time was measured with a spectrum analyzer connected to the antenna terminal, while EUT had its hopping function enabled.

The spectrum analyzer is set to :

Center frequency = 2 440 MHz

Span = zero

RBW = 1 MHz (RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected dwell time per channel)

VBW $\geq$ RBW


Detector function = peak

Trace = max hold

8.4. Test Results

Hopping mode	Length of transmission time(ms)	Number of Hopping in 100 ms	Period (400ms x number of hopping channels)	Total number of in 6.4 s	Time of occupancy in 6.4 s (ms)	Limit (ms)
Enable	0.810	3	6.4 s	192	155.52	400

Note: Time of occupancy(worst case) = (0.81 ms x 192) = 155.52 ms



9. Unwanted Emissions

9.1. Test Setup

Refer to the APPENDIX I.

9.2. Limit

Part 15.247(d), Part 15.205, Part 15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of Part 15.247 the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

- Part 15.209: General requirement

Frequency (MHz)	FCC Limit (uV/m)	Measurement Distance (m)
0.009 – 0.490	2 400 / F (kHz)	300
0.490 – 1.705	2 4000 / F (kHz)	30
1.705 – 30.0	30	30

Frequency (MHz)	FCC Limit (uV/m)	Measurement Distance (m)
30 ~ 88	100 **	3
88 ~ 216	150 **	3
216 ~ 960	200 **	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §15.231 and 15.241.

- Part 15.205(a): Restricted band of operation

MHz	MHz	MHz	MHz	GHz	GHz
0.009 ~ 0.110	8.414 25 ~ 8.414 75	108 ~ 121.94	1 300 ~ 1 427	4.5 ~ 5.15	14.47 ~ 14.5
0.495 ~ 0.505	12.29 ~ 12.293	123 ~ 138	1 435 ~ 1 626.5	5.35 ~ 5.46	15.35 ~ 16.2
2.173 5 ~ 2.190 5	12.519 75 ~ 12.520 25	149.9 ~ 150.05	1 645.5 ~ 1 646.5	7.25 ~ 7.75	17.7 ~ 21.4
4.125 ~ 4.128	12.576 75 ~ 12.577 25	156.524 75 ~ 156.525 25	1 660 ~ 1 710	8.025 ~ 8.5	22.01 ~ 23.12
4.177 25 ~ 4.177 75	13.36 ~ 13.41	156.7 ~ 156.9	1 718.8 ~ 1 722.2	9.0 ~ 9.2	23.6 ~ 24.0
4.207 25 ~ 4.207 75	16.42 ~ 16.423	162.012 5 ~ 167.17	2 200 ~ 2 300	9.3 ~ 9.5	31.2 ~ 31.8
6.215 ~ 6.218	16.694 75 ~ 16.695 25	167.72 ~ 173.2	2 310 ~ 2 390	10.6 ~ 12.7	36.43 ~ 36.5
6.267 75 ~ 6.268 25	16.804 25 ~ 16.804 75	240 ~ 285	2 483.5 ~ 2 500	13.25 ~ 13.4	Above 38.6
6.311 75 ~ 6.312 25	25.5 ~ 25.67	322 ~ 335.4	2 655 ~ 2 900		
8.291 ~ 8.294	37.5 ~ 38.25	399.90 ~ 410	3 260 ~ 3 267		
8.362 ~ 8.366	73 ~ 74.6	608 ~ 614	3 332 ~ 3 339		
8.376 25 ~ 8.386 75	74.8 ~ 75.2	960 ~ 1 240	3 345.8 ~ 3 358		
			3 600 ~ 4 400		

9.3. Test Procedures

9.3.1. Test Procedures for Unwanted Emissions(Radiated)

1. The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 1 or 3 meter away from the interference-receiving antenna.
3. For measurements above 1 GHz absorbers are placed on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1 GHz, the absorbers are removed.
4. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
6. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Measurement Instrument Setting

- Frequencies less than or equal to 1 000 MHz
RBW = As specified in table, VBW $\geq 3 \times$ RBW, Sweep = Auto, Detector = Peak^{Note1} or Quasi Peak, Trace mode = Max Hold until the trace stabilize

Frequency	RBW
9 kHz - 150 kHz	200 Hz - 300 Hz
0.15 MHz - 30 MHz	9 kHz -10 kHz
30 MHz – 1 000 MHz	100 kHz - 120 kHz

Note1: Measurements were performed using the peak detector.

The data measured using the peak detector of a spectrum analyzer will represent the worst-case results.

- Frequencies above 1 000 MHz
Peak Measurement
RBW = 1 MHz, VBW = 3 MHz, Detector = Peak, Sweep time = Auto, Trace mode = Max Hold until the trace stabilizes
Average Measurement > 1GHz
RBW = 1MHz, VBW = Reduce the video bandwidth until no significant variations in the displayed signal are observed in subsequent traces, provided the video bandwidth is no less than 1 Hz.
(Actual VBW setting: 30Hz)
Detector = Peak, Sweep Time = Auto, Trace Mode = Max Hold until the trace stabilizes

9.3.2. Test Procedures for Unwanted Emissions(Conducted)

1. The transmitter output was connected to the spectrum analyzer.
2. The **reference level** of the fundamental frequency was measured with the spectrum analyzer using RBW = 100 kHz, VBW = 300 kHz.
3. The conducted spurious emission was tested each ranges were set as below.

Frequency range : 9 kHz ~ 30 MHz

RBW = 100 kHz, VBW = 300 kHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40 001

Frequency range : 30 MHz ~ 10 GHz, 10 GHz ~ 25 GHz

RBW = 1 MHz, VBW = 3 MHz, SWEEP TIME = AUTO, DETECTOR = PEAK, TRACE = MAX HOLD, SWEEP POINT : 40 001

LIMIT LINE = 20 dB below of the reference level of above measurement procedure Step 2. (RBW = 100 kHz, VBW = 300 kHz)

If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2 001 to get accurate emission level within 100 kHz BW.

Also the path loss for conducted measurement setup was used as described on the Appendix I of this test report.

9.4. Test Results

9.4.1. Unwanted Emissions(Radiated)

▪ Test Notes.

- The radiated emissions were investigated 9 kHz to 1 GHz and the worst case data was reported.(FSK & Lowest Channel)
- Information of Distance Correction Factor
For finding emissions, measurements may be performed at a distance closer than that specified in the regulations.
In this case, the distance correction factor is applied to the result.
- Calculation of distance factor
At frequencies below 30 MHz = $40 \log(\text{tested distance} / \text{specified distance})$
At frequencies at or above 30 MHz = $20 \log(\text{tested distance} / \text{specified distance})$
When distance factor is "N/A", the measurements were performed at the specified distance and distance factor is not applied.
- Sample Calculation.
 $\text{Margin} = \text{Limit} - \text{Result} \quad / \quad \text{Result} = \text{Reading} + \text{TF} + \text{DCCF} + \text{DCF} \quad / \quad \text{TF} = \text{AF} + \text{CL} + \text{HL} + \text{AL} - \text{AG}$
Where, TF = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain, HL = High pass filter Loss, AL = Attenuator Loss, DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor


9 kHz ~ 1 GHz Data (Modulation : FSK)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
53.54	H	Z	PK	44.03	-8.50	N/A	N/A	35.53	40.00	4.47

FSK & Lowest & X & Hor

Detector Mode : PK



▪ Test Notes.

- The radiated emissions were investigated 1 GHz to 25 GHz. No other spurious and harmonic emissions were found below listed frequencies.
- Information of Distance Correction Factor
For finding emissions, measurements may be performed at a distance closer than that specified in the regulations.
In this case, the distance correction factor is applied to the result.
- Calculation of distance factor
At frequencies below 30 MHz = $40 \log(\text{tested distance} / \text{specified distance})$
At frequencies at or above 30 MHz = $20 \log(\text{tested distance} / \text{specified distance})$
When distance factor is "N/A", the measurements were performed at the specified distance and distance factor is not applied.
- Sample Calculation.
Margin = Limit – Result / Result = Reading + TF+ DCCF + DCF / TF = AF + CL + HL + AL – AG
Where, TF = Total Factor, AF = Antenna Factor, CL = Cable Loss, AG = Amplifier Gain, HL = High pass filter Loss,
AL = Attenuator Loss, DCCF = Duty Cycle Correction Factor, DCF = Distance Correction Factor
- * = Peak PSD in 100 kHz bandwidth.
- Please refer to the appendix II for the worst case test plots.

1 GHz ~ 25 GHz Data (Modulation : FSK)

▪ Lowest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
*2 402.00	H	Z	PK	110.28	4.52	N/A	N/A	114.80	-	-
2 165.96	H	Z	PK	80.21	4.53	N/A	N/A	84.74	94.80	10.06
2 385.76	H	Z	PK	61.15	4.45	N/A	N/A	65.60	74.00	8.40
2 385.85	H	Z	AV	41.81	4.45	N/A	N/A	46.26	54.00	7.74
2 637.07	H	Z	PK	70.57	6.19	N/A	N/A	76.76	94.80	18.04
4 803.58	H	Z	PK	50.00	2.40	N/A	N/A	52.40	74.00	21.60
4 803.90	H	Z	AV	38.08	2.40	N/A	N/A	40.48	54.00	13.52

▪ Middle Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
*2 440.00	H	Z	PK	109.44	4.90	N/A	N/A	114.34	-	-
2 174.82	H	Z	PK	80.61	4.50	N/A	N/A	85.11	94.34	9.23
2 704.75	H	Z	PK	66.22	6.12	N/A	N/A	72.34	74.00	1.66
2 704.00	H	Z	AV	40.12	6.13	N/A	N/A	46.25	54.00	7.75
4 877.66	H	Z	PK	49.60	2.26	N/A	N/A	51.86	74.00	22.14
4 877.88	H	Z	AV	37.96	2.27	N/A	N/A	40.23	54.00	13.77

▪ Highest Channel

Frequency (MHz)	ANT Pol	EUT Position (Axis)	Detector Mode	Reading (dBuV)	TF (dB/m)	DCCF (dB)	DCF (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)
*2 476.00	H	Z	PK	109.83	5.31	N/A	N/A	115.14	-	-
2 167.81	H	Z	PK	68.58	4.52	N/A	N/A	73.10	95.14	22.04
2 483.83	H	Z	PK	67.65	5.40	N/A	N/A	73.05	74.00	0.95
2 483.50	H	Z	AV	45.72	5.40	N/A	N/A	51.12	54.00	2.88
4 949.94	H	Z	PK	49.72	2.46	N/A	N/A	52.18	74.00	21.82
4 949.59	H	Z	AV	38.07	2.46	N/A	N/A	40.53	54.00	13.47

9.4.2. Unwanted Emissions(Conducted)

Low Band-edge

Lowest Channel & Modulation : FSK





Low Band-edge

Hopping mode & Modulation : FSK




Conducted Spurious Emissions

Lowest Channel & Modulation : FSK



Conducted Spurious Emissions

Lowest Channel & Modulation : FSK




Reference for limit

Middle Channel & Modulation : FSK





Conducted Spurious Emissions

Middle Channel & Modulation : FSK



Conducted Spurious Emissions

Middle Channel & Modulation : FSK




High Band-edge

Highest Channel & Modulation : FSK





High Band-edge

Hopping mode & Modulation : FSK



Conducted Spurious Emissions Highest Channel & Modulation : FSK



Conducted Spurious Emissions *Highest Channel & Modulation : FSK*



10. AC Power-Line Conducted Emissions

10.1. Test Setup

See test photographs for the actual connections between EUT and support equipment.

10.2. Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network (LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15 ~ 0.50	66 to 56 *	56 to 46 *
0.5 ~ 5.0	56	46
5 ~ 30	60	50

* Decreases with the logarithm of the frequency

10.3. Test Procedure

Conducted emissions from the EUT were measured according to the ANSI C63.10.

1. The test procedure is performed in a 6.5 m × 3.5 m × 3.5 m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m (W) × 1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.
4. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

10.4. Test Results

Results of Conducted Emission

DTNC


Date 2022-01-07

Order No.
Model No. KMC-200
Serial No.
Test Condition 2.4G

Reference No.
Power Supply
Temp/Humi. 23 'C / 48 %
Operator S.M.Gil

Memo

LIMIT : FCC P15.207 QP
FCC P15.207 AV



Results of Conducted Emission

DTNC

Date 2022-01-07

Order No.
Model No. KMC-200
Serial No.
Test Condition 2.4G

Reference No.
Power Supply
Temp/Humi. 23 °C / 46 %
Operator S.M.Gil

Memo


LIMIT : FCC P15.207 QP
FCC P15.207 AV

NO	FREQ [MHz]	READING		C. FACTOR [dB]	RESULT		LIMIT		MARGIN		PHASE
		QP [dBuV]	CAV [dBuV]		QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	QP [dBuV]	CAV [dBuV]	
1	0.16128	25.38	12.32	9.90	35.28	22.22	65.40	55.40	30.12	33.18	N
2	0.29773	36.97	27.39	9.90	46.87	37.29	60.31	50.31	13.44	13.02	N
3	0.55020	23.45	13.92	9.91	33.36	23.83	56.00	46.00	22.64	22.17	N
4	8.28253	16.44	7.09	10.26	26.70	17.35	60.00	50.00	33.30	32.65	N
5	18.88097	24.98	13.48	10.36	35.34	23.84	60.00	50.00	24.66	26.16	N
6	0.16069	26.35	14.29	9.90	36.25	24.19	65.43	55.43	29.18	31.24	L
7	0.29801	37.85	28.20	9.90	47.75	38.10	60.30	50.30	12.55	12.20	L
8	0.55087	23.59	14.03	9.91	33.50	23.94	56.00	46.00	22.50	22.06	L
9	8.31064	16.86	7.16	10.22	27.08	17.38	60.00	50.00	32.92	32.62	L
10	18.88386	27.15	15.34	10.36	37.51	25.70	60.00	50.00	22.49	24.30	L


APPENDIX I

Test set up diagrams

▪ Radiated Measurement



▪ Conducted Measurement



Path loss information

Frequency (GHz)	Path Loss (dB)	Frequency (GHz)	Path Loss (dB)
0.03	9.86	15	10.44
1	9.91	20	10.56
2.402 & 2.440 & 2.476	10.00	25	10.98
5	10.04	-	-
10	10.07	-	-


Note 1 : The path loss from EUT to Spectrum analyzer was measured and used for test.
 Path loss (S/A's correction factor) = Cable A + Attenuator

APPENDIX II

Unwanted Emissions (Radiated) Test Plot


FSK & Lowest & Z & Hor

Detector Mode : PK




FSK & Lowest & Z & Hor

Detector Mode : AV




FSK & Highest & Z & Hor

Detector Mode : PK



FSK & Highest & Z & Hor

Detector Mode : AV



FSK & Middle & Z & Hor

Detector Mode : PK

