



KSIGN Testing Co., Ltd.

Building 5, No. 316, Jianghong South Road Binjiang District, Hangzhou 310052, China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

RF Exposure Evaluation

FCC ID: 2A3ZM-ECT105W

REQUIREMENT

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

TEST RESULT

☒ **Passed**

☐ **Not Applicable**

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up tolerance Power (dBm)	Max. Tune up tolerance Power (mW)	Calculating data	Limit	Results
GFSK	2402	-1.32	-2±1	0.79	0.2462	3.00	Pass
	2440	-1.5	-2±1	0.79	0.2482		
	2480	-2.11	-2±1	0.79	0.2502		

Note:

-The exposure safety distance is less than 5mm.

--THE END--