



Report No.: PTC22021805801E-FC03

FCC TEST REPORT

FCC ID: 2A43H-SJB01

Product	:	Smart Light Panels
Model Name	:	QT-SJB01
Brand	:	N/A
Report No.	:	PTC22021805801E-FC03
Prepared for		
TOLEZ LTD		
Building 308, Hesheng cultural and creative park, Longhua District, Shenzhen, Guangdong		
Prepared by		
Precise Testing & Certification Co., Ltd		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China		



Report No.: PTC22021805801E-FC03

TEST RESULT CERTIFICATION

Applicant's name : TOLEZ LTD
Address : Building 308, Hesheng cultural and creative park, Longhua District, Shenzhen, Guangdong
Manufacture's name : TOLEZ LTD
Address : Building 308, Hesheng cultural and creative park, Longhua District, Shenzhen, Guangdong
Product name : Smart Light Panels
Model name : QT-SJB01
Test procedure : KDB 447498 D01 General RF Exposure Guidance v06
Test Date : Mar. 02, 2022 to Mar. 09, 2022
Date of Issue : Mar. 09, 2022
Test Result : Pass

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Abel Yu'.

Abel Yu / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Wu Weimin'.

Wu Weimin / Manager



Contents

	Page
2 TEST SUMMARY.....	4
3 GENERAL INFORMATION.....	5
3.1 GENERAL DESCRIPTION OF E.U.T.....	5
4 RF EXPOSURE.....	6
4.1 REQUIREMENTS.....	6
4.2 THE PROCEDURES / LIMIT.....	6
4.3 MPE CALCULATION METHOD.....	7
4.4 TEST RESULT.....	7



2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS
Remark:		
N/A: Not Applicable		



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Smart Light Panels
Model Name	:	QT-SJB01
Additional model	:	N/A
Specification	:	802.11b/g/n HT20 BT 4.2 BLE
Operation Frequency	:	2412-2462MHz for 802.11b/g; n(HT20) 2402-2480MHz for BT
Number of Channel	:	11 channels for 802.11b/g; n(HT20) 40 channels for BT
Type of Modulation	:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n; GFSK For BT
Antenna installation	:	PCB antenna
Antenna Gain	:	2.5 dBi
Power supply	:	Adapter model: JYH36-2401500BX Input : AC100-240V 50/60HZ 1.2A, Output: DC 24V 1.5A 36W
Hardware Version	:	N/A
Software Version	:	N/A



4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : FCC Part 2.1091

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density



4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

4.4 Test Result

Item	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Result
WIFI	1.78	15.931	39.183	0.0139	1	Pass
BLE	1.78	3.210	2.094	0.00074	1	Pass

*****THE END REPORT*****