

FCC RF Exposure

EUT Description: Bluetooth Speaker

Model No.: BT525, BT525 FM, BT525-FMJ, BT525 II, BT525-III, BT525-IV, BT525-V, BT525-VI, BT525 V, BT525 VI, BT525 VII, BT525VIII, BT525 IX, BT525 X, BT526, BT526 FM, BT526 II, BT526 III, BT708, BT709

FCC ID: 2A430-BT525

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1 - g and 10 - g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
[(max power of channel, including tune - up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1 - g SAR and ≤ 7.5 for 10 - g extremity SAR,

Where:

Result= $P/D \cdot \sqrt{F}$

F= the RF channel transmit frequency in GHz

P=Maximum turn - up power in mw

D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

Frequency (MHz)	Output power (dBm)	Tune Up Power (dBm)	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm ²)	SAR Test Exclusion
2441	-0.11	-1 $\pm$ 1	0/1.00	5	0.312	3.0	Pass
Note: PK Output power= conducted power. Conducted power see the test report HK2202240696-E , antenna gain=0dBi							

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.312 which is ≤ 3 , RF Exposure testing is not required.

Note: Exclusion Thresholds Results=[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(\text{GHz})}]$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Distance=5mm