



FCC PART 15.247 TEST REPORT

For

Austar Hearing Science and Technology (Xiamen) Co., Ltd.

B8, Biomedical Industrial Park, No.2064 Wengjiao West Road, Haicang Dist. Xiamen, Fujian, China

FCC ID: 2A445FAIP916-DW


Report Type: Original Report	Product Name: Digital Rechargeable BTE Hearing Aids
Report Number:	2607S35862E-RF-02
Report Date:	2026-08-05
Reviewed By:	Ash Lin 
Approves By:	Miles Chen 
Prepared By:	Bay Area Compliance Laboratories Corp. (Xiamen) Unit 102, No. 902 Meifeng South Road, Binhai West Avenue Science and Technology Innovation Park, Torch High Tech Zone Xiamen, People's Republic of China Tel: +86-592-3200111 www.baclcorp.com.cn

TABLE OF CONTENTS

REPORT REVISION HISTORY.....	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
TEST FACILITY	6
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION.....	7
TEST MODE AND VOLTAGE.....	7
DESCRIPTION OF TEST CONFIGURATION	7
★EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES.....	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	8
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §15.203 – ANTENNA REQUIREMENT	12
APPLICABLE STANDARD	12
ANTENNA CONNECTOR CONSTRUCTION	12
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	13
APPLICABLE STANDARD	13
TEST SYSTEM SETUP	13
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	15
FINAL MEASUREMENT FOR EMISSION IDENTIFIED DURING THE PRE-SCAN:	15
TEST PROCEDURE	15
RESULT & MARGIN CALCULATION.....	16
TEST DATA	17
FCC §15.247(a) (1) –CHANNEL SEPARATION TEST.....	74
APPLICABLE STANDARD	74
EUT SETUP	74
TEST PROCEDURE	74
TEST DATA	75
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	77
APPLICABLE STANDARD	77
EUT SETUP	77
TEST PROCEDURE	77
TEST DATA	78
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	84
APPLICABLE STANDARD	84
EUT SETUP	84
TEST PROCEDURE	84
TEST DATA	85
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	87
APPLICABLE STANDARD	87
EUT SETUP	87

TEST PROCEDURE	87
TEST DATA	88
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	92
APPLICABLE STANDARD	92
EUT SETUP	92
TEST PROCEDURE	92
TEST DATA	93
FCC §15.247(d) - BAND EDGES TESTING	98
APPLICABLE STANDARD	98
EUT SETUP	98
TEST PROCEDURE	98
TEST DATA	99
EUT PHOTOGRAPHS.....	106
TEST SETUP PHOTOGRAPHS	107

REPORT REVISION HISTORY

Number of Revisions	Report No.	Version	Issue Date	Description
0	2607S35862E-RF-02	R1V1	2026-08-05	Initial Release

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:		Austar Hearing Science and Technology (Xiamen) Co., Ltd.	
Product Name:		Digital Rechargeable BTE Hearing Aids	
Tested Model:		FAIP916-DW	
Multiple Model(s):		N/A	
Trade Mark:		AUSTAR [®]	
Power Supply:		Charging case: DC 5V from adapter or DC 3.7V from battery Hearing aid: DC 3.6V from battery or DC 5V from Charging case	
Adapter information	Model:	LX050100	
	Input:	AC 100-240V, 50/60Hz, 0.35A	
	Output:	DC 5V, 1A	
Maximum Peak Output Power:		0.05 dBm	
RF Function:		Classic BT	
Operating Band/Frequency:		2402-2480 MHz	
Channel Number:		79	
Channel Separation:		1 MHz	
Modulation Type:		GFSK, $\pi/4$ -DQPSK, 8DPSK	
Antenna Type:		Monopole Antenna	
★Maximum Antenna Gain:		0.96 dBi	
EUT Received Status:		Good	
Note:			
1. The Maximum Antenna Gain was declared by manufacturer.			
2. The device includes left and right unit, and the two units were electrically identical. Please refer to the declaration letter for more detail, which was provided by manufacturer. Only the left unit was tested.			
3. All measurement and test data in this report was gathered from production sample serial number:			
3L5E-10 (RF conducted), 3L5E-12 (Radiated Spurious Emission) (Assigned by the BACL(Xiamen). The EUT supplied by the applicant was received on 2026-04-29)			

Objective

This test report is prepared for *Austar Hearing Science and Technology (Xiamen) Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and KDB 558074 D01 15.247 Meas Guidance v05r02.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Xiamen) to collect test data is located on the Unit 102, No. 902 Meifeng South Road, Binhai West Avenue Science and Technology Innovation Park, Torch High Tech Zone Xiamen, People's Republic of China.

Bay Area Compliance Laboratories Corp. (Xiamen) Lab is accredited to ISO/IEC 17025 by A2LA (Certificate Number: 7134.01) and the lab has been recognized as the FCC accredited lab under the KDB 974614 D01, the FCC Designation No. : CN1384.

Measurement Uncertainty

Item		U_{lab}
Radiated Spurious Emission	9kHz-150kHz	2.82dB
	150kHz-30MHz	2.74dB
	30MHz~1GHz	4.68dB
	1GHz~18GHz	5.00dB
	18GHz~26.5GHz	4.90dB
Occupied Channel Bandwidth		1.69%
Transmitter Conducted Power(Conducted RF power)		0.43dB
Conducted Spurious Emission		2.92dB
Duty Cycle		1%
Temperature		1°C
Humidity		5%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

SYSTEM TEST CONFIGURATION

Test Mode and Voltage

The system was configured for testing in a typical mode (as normally used by a typical user).	
Test mode:	Test Mode: Transmitting
Test voltage:	DC 3.6V from battery
Remark:	During all emission tests, the EUT was configured to measure its highest possible emission level and the worst case's test data was presented in this test report.

Description of Test Configuration

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

★EUT Exercise Software

BT test in the engineer mode.

RF Test Tool: Airoha.Tool.Kit.exe

Test Modes	Power Level Setting		
	Lowest Channel	Middle Channel	Highest Channel
BDR(GFSK)	45	45	45
EDR($\pi/4$ -DQPSK)	45	45	45
EDR(8DPSK)	45	45	45

Note: The power level was declared by the applicant.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Lenovo	Laptop	T480	PF1P5K4F
Unknown	Debug board	Unknown	Unknown


External I/O Cable

Cable Description	Length (m)	From Port	To
Jumper Wire	0.2	Debug board	EUT
USB Cable	10	Debug board	Laptop
RF Cable	0.1	EUT antenna port	Spectrum Analyzer


Block Diagram of Test Setup

Radiated Spurious Emission:

Below 1GHz:



Above 1GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Not applicable (See Note 1)
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions & Antenna-port conducted emission	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

Note:

1. The EUT is powered by Battery.

TEST EQUIPMENT LIST

Test Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emissions Below 1GHz					
EMI Test Receiver	Rohde & Schwarz	ESR3	103103	2026/1/21	2027/1/20
Loop Antenna	Rohde & Schwarz	HFH2-Z2	830749/001	2026/5/12	2029/5/11
Antenna	Sunol Sciences	JB6	A122022-5	2026/5/12	2029/5/11
Amplifier	Sonoma	310B	120903	2026/1/22	2027/1/21
Coaxial Cable	XINHANGWEIBO	XH400T-N-4M	CC002	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH460B-N-2M	CC006	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH460B-N-12M	CC007	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	HFH2-CC	335.3609	2026/5/12	2027/5/11
Test Software	Audix	E3	18621a	N/A	N/A
Radiated Emissions Above 1 GHz					
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102051	2026/1/21	2027/1/20
Spectrum Analyzer	Rohde & Schwarz	FSU	100405	2026/1/21	2027/1/20
Filter Switch Unit	Decentest	DT7220FSU	DS79904	2026/1/21	2027/1/20
Multiplex Switch Test Control Set	Decentest	DT7220SCU	DS79901	2026/1/20	2027/1/19
Horn Antenna	EMCO	3115	9002-3355	2024/11/19	2027/11/18
Preamplifier	GLOBAL	1313-A100M18G	4121301	2026/1/14	2027/1/13
Coaxial Cable	XINHANGWEIBO	XH800A-N-6M	CC003	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH800A-N-1M	CC005	2026/1/20	2027/1/19
Horn Antenna	EMCO	3116	9407-2232	2026/5/12	2029/5/11
Preamplifier	A.H.Systems	PAM-1840	200	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH360A-2.92-3M	CC008	2026/1/20	2027/1/19
Coaxial Cable	XINHANGWEIBO	XH360A-2.92-1M	CC009	2026/1/20	2027/1/19
Test Software	Audix	E3	18621a	N/A	N/A
RF Conducted Test					
Spectrum Analyzer	Rohde & Schwarz	FSU	100405	2026/1/21	2027/1/20
Test Software	JD	JDAutoTestSystem	1.0.0.3813	N/A	N/A

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Xiamen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction


The EUT has one Monopole antenna for Bluetooth, which was permanently attached and the Max. antenna gain is 0.96 dBi, fulfill the requirement of this section. Please refer to the EUT photos.



Result: Compliance

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test System Setup**9 kHz-30MHz**

Below 1 GHz:**Above 1GHz:**

The radiated emission tests using the setup accordance with the ANSI C63.10-2020. The specification used was the FCC 15.209, and FCC 15.247 limits.


NOTE: d is testing distance;

For Radiated Emission test (1GHz-18GHz) and Bandedge Emission test, which was performed at 3 m distance.

For Radiated Emission test (18GHz-25GHz), which was performed at 1.5 m distance, according to ANSI C63.10-2020, the test result shall be extrapolated to the specified distance using an extrapolation Factor of 20dB/decade from 3m to 1.5m.

Distance extrapolation Factor = $20 \log (\text{specific distance [3m]}/\text{test distance [1.5m]})$ dB = 6 dB

Antenna-port conducted emission:



Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

TDF = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & spectrum analyzer setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
9 kHz – 150 kHz	300Hz	1 kHz	200Hz	QP
150 kHz – 30 MHz	10 kHz	30 kHz	9 kHz	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	/	PK
	/	/	120kHz	QP

1GHz~25GHz:

Pre-scan:

Measurement	RBW	Video B/W	Detector
PK	1MHz	3MHz	PK
AV	1MHz	5kHz	PK

Final measurement for emission identified during the pre-scan:

Measurement	RBW	Video B/W	Detector
PK	1MHz	3MHz	PK
AV	1MHz	10Hz	PK

Test Procedure

Radiated Emissions:

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

For each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable. The report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground parallel) unless the margin is greater than 20 dB, then the following statement shall be made: “all emissions were greater than 20 dB below the limit.”

Below 1GHz, if the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is at least 6 dB below the QP emission limit, there's no need to record the measured QP level of the emissions in the report.

Above 1GHz, if the measured peak level of the emissions that the measuring receiver reading level plus corrected factor is below the AV emission limit, there's no need to record the measured AV level of the emissions in the report.

Antenna-port conducted emission:

Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The frequency range of testing shall span 30 MHz to 10 times the operating frequency and this may be done in a single sweep or, to aid resolution, across a number of sweeps. The resolution bandwidth shall be 100 kHz, video bandwidth 300 kHz, and a coupled sweep time with a peak detector.

The limit is based on the highest in-band level across all channels measured using the same instrument settings (resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector). To help clearly demonstrate compliance a display line may be set at the required offset (typically 20 dB) below the highest in-band level. Where the highest in-band level is not clearly identified in the out-of-band measurements a separate spectral plot showing the in-band level shall be provided.

When conducted measurements cannot be made (for example a device with integrated, non-removable antenna) radiated measurements shall be used. The reference level for determining the limit shall be established by maximizing the field strength from the highest power channel and measuring using the resolution and video bandwidth settings and peak detector as described above. The field strength limit for spurious emissions outside of restricted-bands shall then be set at the required offset (typically 20 dB) below the highest in-band level. Radiated measurements will follow the standards measurement procedures described in Clause 6 with the exception that the resolution bandwidth shall be 100 kHz, video bandwidth 300 kHz, and a coupled sweep time with a peak detector. Note that use of wider measurement bandwidths are acceptable for measuring the spurious emissions provided that the peak detector is used and that the measured value of spurious emissions are compared to the highest in-band level measured with the 100 kHz / 300 kHz bandwidth settings to determine compliance.

Result & Margin Calculation

The Result is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

For 9 kHz to 18GHz Radiated emission test and Bandedge emissions test

$$\text{Factor (dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

For 18GHz to 25GHz Radiated emission test

$$\text{Factor (dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)} - \text{Extrapolation factor (dB)}$$

$$\text{Extrapolation factor} = 6\text{dB (distance} = 1.5\text{m)}$$

$$\text{Result (dB}\mu\text{V/m)} = \text{Reading (dB}\mu\text{V)} + \text{Factor (dB/m)}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Result (dB}\mu\text{V/m)}$$

Test Data

Please refer to the below table and plots.


Frequency Range:	Below 1 GHz	Above 1 GHz	Antenna-port conducted emission
Temperature:	23.0°C	23.0°C	22.9°C
Relative Humidity:	60%	60%	41%
ATM Pressure:	100.1kPa	100.1kPa	100.1kPa
Test Date:	2026-07-24	2026-07-24	2026-07-16
Test Engineer:	Wlif Wu	Wlif Wu	Yuki

Note: Pre-scan in the X, Y and Z axes of orientation, the worst case Z-axis of orientation was recorded.

X-axis forward: From the Sound tube/earhook to the battery compartment.

Y-axis forward: From the top (with buttons) to the other side.

Z-axis forward: Vertical to the X and Y axes.



1) 9 kHz ~30MHz

Pre-scan in parallel, ground-parallel and perpendicular of orientation of loop antenna, parallel is worst case.

Note: The maximum output power mode: EDR (8DPSK) low channel was tested.

Project No.: 2607S35862E-RF

Temp/Humi/ATM: 23.0°C/60%/100.1kPa


Test Mode: EDR 3DH5 2402MHz

Tested by: Wlif Wu

EUT Model: FAIP916-DW

Power Source: DC 3.6V

Test distance: 3m




Condition: PK RBW:300Hz VBW:1kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
0.035	6.08	20.01	26.09	116.81	90.72	Peak
0.057	6.14	19.91	26.05	112.54	86.49	Peak
0.069	4.83	19.82	24.65	110.86	86.21	Peak
0.081	7.21	19.72	26.93	109.44	82.51	Peak
0.092	5.03	19.79	24.82	108.34	83.52	Peak
0.128	5.22	19.76	24.98	105.45	80.47	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V

Date: 2026-07-24



Condition: PK RBW:10kHz VBW:30kHz SWT:auto


Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Remark
0.457	16.47	19.79	36.26	94.40	58.14	Peak
3.210	14.02	19.83	33.85	69.54	35.69	Peak
11.893	14.28	19.76	34.04	69.54	35.50	Peak
15.030	14.01	19.86	33.87	69.54	35.67	Peak
22.687	13.68	20.22	33.90	69.54	35.64	Peak
26.394	12.82	20.22	33.04	69.54	36.50	Peak

2) 30MHz-1GHz

Note: The maximum output power mode: EDR (8DPSK) low channel was tested.

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
30.58	26.83	-5.47	21.36	40.00	18.64	Horizontal	Peak
119.92	26.87	-10.08	16.79	43.50	26.71	Horizontal	Peak
601.72	27.13	-1.88	25.25	46.00	20.75	Horizontal	Peak
698.52	27.25	-0.05	27.20	46.00	18.80	Horizontal	Peak
797.37	26.76	1.72	28.48	46.00	17.52	Horizontal	Peak
916.87	26.63	2.93	29.56	46.00	16.44	Horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:100kHz VBW:300kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
35.72	27.60	-8.43	19.17	40.00	20.83	Vertical	Peak
127.68	26.52	-9.73	16.79	43.50	26.71	Vertical	Peak
493.08	27.68	-3.20	24.48	46.00	21.52	Vertical	Peak
666.32	27.05	-0.42	26.63	46.00	19.37	Vertical	Peak
806.97	27.29	1.53	28.82	46.00	17.18	Vertical	Peak
907.17	27.55	2.91	30.46	46.00	15.54	Vertical	Peak

3) 1 GHz-3 GHz

Project No.: 2607S35862E-RF
Test Mode: BDR DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2689.00	47.76	-10.07	37.69	74.00	36.31	horizontal	Peak
2914.00	46.17	-9.53	36.64	74.00	37.36	horizontal	Peak
2988.00	47.08	-9.06	38.02	74.00	35.98	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: BDR DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2671.20	46.94	-10.15	36.79	74.00	37.21	vertical	Peak
2823.60	46.84	-9.71	37.13	74.00	36.87	vertical	Peak
2949.60	46.62	-9.27	37.35	74.00	36.65	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: BDR DH5 2441MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V



Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2642.40	47.57	-10.25	37.32	74.00	36.68	horizontal	Peak
2771.60	46.78	-9.87	36.91	74.00	37.09	horizontal	Peak
2942.80	46.50	-9.32	37.18	74.00	36.82	horizontal	Peak

Project No.: 2607S35862E-RF

Test Mode: BDR DH5 2441MHz


EUT Model: FAIP916-DW

Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa

Tested by: Wlif Wu

Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2598.20	46.79	-10.43	36.36	74.00	37.64	vertical	Peak
2765.20	47.05	-9.89	37.16	74.00	36.84	vertical	Peak
2917.40	47.47	-9.51	37.96	74.00	36.04	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2554.80	46.55	-10.60	35.95	74.00	38.05	horizontal	Peak
2740.80	47.09	-9.97	37.12	74.00	36.88	horizontal	Peak
2935.80	46.40	-9.38	37.02	74.00	36.98	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2600.00	46.85	-10.42	36.43	74.00	37.57	vertical	Peak
2724.40	46.71	-9.99	36.72	74.00	37.28	vertical	Peak
2877.60	47.20	-9.64	37.56	74.00	36.44	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2604.60	46.42	-10.40	36.02	74.00	37.98	horizontal	Peak
2708.40	46.62	-10.01	36.61	74.00	37.39	horizontal	Peak
2841.20	47.55	-9.67	37.88	74.00	36.12	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2619.00	47.26	-10.34	36.92	74.00	37.08	vertical	Peak
2709.00	46.99	-10.01	36.98	74.00	37.02	vertical	Peak
2887.40	47.01	-9.65	37.36	74.00	36.64	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2441MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2601.60	47.51	-10.41	37.10	74.00	36.90	horizontal	Peak
2810.60	46.87	-9.75	37.12	74.00	36.88	horizontal	Peak
2939.20	47.66	-9.34	38.32	74.00	35.68	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2441MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V

Date: 2026-07-24




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2605.40	47.28	-10.40	36.88	74.00	37.12	vertical	Peak
2778.80	46.83	-9.84	36.99	74.00	37.01	vertical	Peak
2925.20	47.14	-9.45	37.69	74.00	36.31	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2691.40	47.30	-10.06	37.24	74.00	36.76	horizontal	Peak
2819.20	47.31	-9.72	37.59	74.00	36.41	horizontal	Peak
2981.20	46.65	-9.10	37.55	74.00	36.45	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2611.60	46.78	-10.36	36.42	74.00	37.58	vertical	Peak
2728.20	46.72	-9.98	36.74	74.00	37.26	vertical	Peak
2848.00	47.53	-9.66	37.87	74.00	36.13	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2569.00	46.58	-10.54	36.04	74.00	37.96	horizontal	Peak
2668.60	47.09	-10.16	36.93	74.00	37.07	horizontal	Peak
2839.40	47.05	-9.67	37.38	74.00	36.62	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2671.00	47.09	-10.15	36.94	74.00	37.06	vertical	Peak
2813.40	47.06	-9.74	37.32	74.00	36.68	vertical	Peak
2922.60	46.77	-9.46	37.31	74.00	36.69	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2441MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2532.80	46.71	-10.67	36.04	74.00	37.96	horizontal	Peak
2718.80	47.40	-10.00	37.40	74.00	36.60	horizontal	Peak
2901.80	46.69	-9.62	37.07	74.00	36.93	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2441MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2602.20	46.54	-10.41	36.13	74.00	37.87	vertical	Peak
2646.40	46.46	-10.23	36.23	74.00	37.77	vertical	Peak
2849.80	46.73	-9.65	37.08	74.00	36.92	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2532.00	46.91	-10.68	36.23	74.00	37.77	horizontal	Peak
2673.20	47.30	-10.14	37.16	74.00	36.84	horizontal	Peak
2837.00	46.77	-9.68	37.09	74.00	36.91	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2622.20	47.52	-10.33	37.19	74.00	36.81	vertical	Peak
2769.60	47.52	-9.87	37.65	74.00	36.35	vertical	Peak
2955.00	46.12	-9.24	36.88	74.00	37.12	vertical	Peak

4) 3 GHz-18 GHz

Project No.: 2607S35862E-RF
Test Mode: BDR DHS 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.00	44.45	-5.26	39.19	74.00	34.81	horizontal	Peak
7206.00	53.02	-2.53	50.49	74.00	23.51	horizontal	Peak
14544.00	46.50	5.11	51.61	74.00	22.39	horizontal	Peak
17995.50	35.65	6.84	42.49	54.00	11.51	horizontal	Average
17995.50	45.39	6.84	52.23	74.00	21.77	horizontal	Peak

Project No.: 2607S35862E-RF

Test Mode: BDR DH5 2402MHz


EUT Model: FAIP916-DW

Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa

Tested by: Wlif Wu

Power Source: DC 3.6V



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.50	44.89	-5.27	39.62	74.00	34.38	vertical	Peak
7206.00	46.30	-2.53	43.77	74.00	30.23	vertical	Peak
14544.00	45.86	5.11	50.97	74.00	23.03	vertical	Peak
17983.50	35.29	6.83	42.12	54.00	11.88	vertical	Average
17983.50	45.50	6.83	52.33	74.00	21.67	vertical	Peak

Project No.: 2607S35862E-RF

Test Mode: BDR DH5 2441MHz

EUT Model: FAIP916-DW


Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa

Tested by: Wlif Wu

Power Source: DC 3.6V

Date: 2026-07-24



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.00	44.97	-5.25	39.72	74.00	34.28	horizontal	Peak
7323.00	51.39	-2.27	49.12	74.00	24.88	horizontal	Peak
14479.50	45.95	5.19	51.14	74.00	22.86	horizontal	Peak
17923.50	34.78	6.79	41.57	54.00	12.43	horizontal	Average
17923.50	46.45	6.79	53.24	74.00	20.76	horizontal	Peak

Project No.: 2607S35862E-RF

Test Mode: BDR DH5 2441MHz


EUT Model: FAIP916-DW

Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa

Tested by: Wlif Wu

Power Source: DC 3.6V



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.00	44.34	-5.25	39.09	74.00	34.91	vertical	Peak
7323.00	46.70	-2.27	44.43	74.00	29.57	vertical	Peak
14025.00	45.97	5.17	51.14	74.00	22.86	vertical	Peak
17988.00	35.53	6.83	42.36	54.00	11.64	vertical	Average
17988.00	46.64	6.83	53.47	74.00	20.53	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.50	49.00	-5.09	43.91	74.00	30.09	horizontal	Peak
7440.00	52.30	-2.12	50.18	74.00	23.82	horizontal	Peak
14491.50	46.42	5.17	51.59	74.00	22.41	horizontal	Peak
17991.00	36.08	6.83	42.91	54.00	11.09	horizontal	Average
17991.00	45.94	6.83	52.77	74.00	21.23	horizontal	Peak

Project No.: 2607S35862E-RF

Test Mode: BDR DH5 2480MHz


EUT Model: FAIP916-DW

Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa

Tested by: Wlif Wu

Power Source: DC 3.6V



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.00	47.05	-5.09	41.96	74.00	32.04	vertical	Peak
7440.00	50.40	-2.12	48.28	74.00	25.72	vertical	Peak
14485.50	45.68	5.17	50.85	74.00	23.15	vertical	Peak
17976.00	34.80	6.83	41.63	54.00	12.37	vertical	Average
17976.00	46.17	6.83	53.00	74.00	21.00	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.00	43.56	-5.26	38.30	74.00	35.70	horizontal	Peak
7206.00	48.36	-2.53	45.83	74.00	28.17	horizontal	Peak
14511.00	46.28	5.14	51.42	74.00	22.58	horizontal	Peak
17994.00	35.46	6.83	42.29	54.00	11.71	horizontal	Average
17994.00	45.45	6.83	52.28	74.00	21.72	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.50	44.32	-5.27	39.05	74.00	34.95	vertical	Peak
7206.00	45.52	-2.53	42.99	74.00	31.01	vertical	Peak
14523.00	46.62	5.13	51.75	74.00	22.25	vertical	Peak
17989.50	35.24	6.83	42.07	54.00	11.93	vertical	Average
17989.50	45.59	6.83	52.42	74.00	21.58	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2441MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.00	45.82	-5.25	40.57	74.00	33.43	horizontal	Peak
7323.00	50.64	-2.27	48.37	74.00	25.63	horizontal	Peak
14502.00	46.17	5.16	51.33	74.00	22.67	horizontal	Peak
17983.50	35.19	6.83	42.02	54.00	11.98	horizontal	Average
17983.50	45.96	6.83	52.79	74.00	21.21	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2441MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.50	44.21	-5.24	38.97	74.00	35.03	vertical	Peak
7323.00	47.50	-2.27	45.23	74.00	28.77	vertical	Peak
14560.50	46.37	5.09	51.46	74.00	22.54	vertical	Peak
17919.00	34.81	6.79	41.60	54.00	12.40	vertical	Average
17919.00	45.88	6.79	52.67	74.00	21.33	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.00	46.49	-5.09	41.40	74.00	32.60	horizontal	Peak
7440.00	51.69	-2.12	49.57	74.00	24.43	horizontal	Peak
14019.00	46.44	5.17	51.61	74.00	22.39	horizontal	Peak
17991.00	35.31	6.83	42.14	54.00	11.86	horizontal	Average
17991.00	46.63	6.83	53.46	74.00	20.54	horizontal	Peak

Project No.: 2607S35862E-RF

Test Mode: EDR 2DH5 2480MHz


EUT Model: FAIP916-DW

Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa

Tested by: Wlif Wu

Power Source: DC 3.6V



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.50	45.38	-5.09	40.29	74.00	33.71	vertical	Peak
7440.00	50.37	-2.12	48.25	74.00	25.75	vertical	Peak
14521.50	45.84	5.13	50.97	74.00	23.03	vertical	Peak
17983.50	35.19	6.83	42.02	54.00	11.98	vertical	Average
17983.50	46.09	6.83	52.92	74.00	21.08	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.00	47.06	-5.26	41.80	74.00	32.20	horizontal	Peak
7206.00	52.97	-2.53	50.44	74.00	23.56	horizontal	Peak
14518.50	46.09	5.14	51.23	74.00	22.77	horizontal	Peak
17929.50	34.81	6.80	41.61	54.00	12.39	horizontal	Average
17929.50	46.23	6.80	53.03	74.00	20.97	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4804.00	44.38	-5.26	39.12	74.00	34.88	vertical	Peak
7206.00	45.29	-2.53	42.76	74.00	31.24	vertical	Peak
14523.00	46.46	5.13	51.59	74.00	22.41	vertical	Peak
17995.50	35.41	6.84	42.25	54.00	11.75	vertical	Average
17995.50	46.23	6.84	53.07	74.00	20.93	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2441MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.00	45.39	-5.25	40.14	74.00	33.86	horizontal	Peak
7323.00	50.48	-2.27	48.21	74.00	25.79	horizontal	Peak
14530.50	45.89	5.12	51.01	74.00	22.99	horizontal	Peak
17991.00	35.57	6.83	42.40	54.00	11.60	horizontal	Average
17991.00	46.27	6.83	53.10	74.00	20.90	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2441MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4882.50	44.58	-5.24	39.34	74.00	34.66	vertical	Peak
7323.00	46.47	-2.27	44.20	74.00	29.80	vertical	Peak
14542.50	46.48	5.11	51.59	74.00	22.41	vertical	Peak
17953.50	34.33	6.81	41.14	54.00	12.86	vertical	Average
17953.50	45.85	6.81	52.66	74.00	21.34	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.00	45.41	-5.09	40.32	74.00	33.68	horizontal	Peak
7440.00	52.36	-2.12	50.24	74.00	23.76	horizontal	Peak
14487.00	46.00	5.17	51.17	74.00	22.83	horizontal	Peak
17992.50	35.56	6.83	42.39	54.00	11.61	horizontal	Average
17992.50	46.46	6.83	53.29	74.00	20.71	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V



Trace: 1

Condition: PK RBW:1MHz VBW:3MHz SWT:auto
AV RBW:1MHz VBW:5kHz SWT:auto


Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
4960.50	45.66	-5.09	40.57	74.00	33.43	vertical	Peak
7440.00	50.51	-2.12	48.39	74.00	25.61	vertical	Peak
14542.50	45.80	5.11	50.91	74.00	23.09	vertical	Peak
17961.00	34.37	6.81	41.18	54.00	12.82	vertical	Average
17961.00	46.17	6.81	52.98	74.00	21.02	vertical	Peak

5) 18 GHz-25 GHz

Note: The maximum output power mode: EDR (8DPSK) low channel was tested.

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 1.5m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto

AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
21859.80	37.88	5.10	42.98	54.00	11.02	horizontal	Average
21859.80	51.45	5.10	56.55	74.00	17.45	horizontal	Peak
22878.30	36.08	5.01	41.09	54.00	12.91	horizontal	Average
22878.30	50.82	5.01	55.83	74.00	18.17	horizontal	Peak
24376.30	35.60	6.07	41.67	54.00	12.33	horizontal	Average
24376.30	49.86	6.07	55.93	74.00	18.07	horizontal	Peak

Project No.: 2607S35862E-RF
 Test Mode: EDR 3DH5 2402MHz
 EUT Model: FAIP916-DW
 Test distance: 1.5m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
 Tested by: Wlif Wu
 Power Source: DC 3.6V



Trace: 1


Condition: PK RBW:1MHz VBW:3MHz SWT:auto
 AV RBW:1MHz VBW:5kHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
21882.20	38.18	5.27	43.45	54.00	10.55	vertical	Average
21882.20	51.80	5.27	57.07	74.00	16.93	vertical	Peak
23861.10	37.33	5.30	42.63	54.00	11.37	vertical	Average
23861.10	51.03	5.30	56.33	74.00	17.67	vertical	Peak
24363.00	36.19	6.05	42.24	54.00	11.76	vertical	Average
24363.00	49.79	6.05	55.84	74.00	18.16	vertical	Peak

Restricted Bands Emissions:

Project No.: 2607S35862E-RF
Test Mode: BDR DHS 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V



Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2379.12	47.17	-1.31	45.86	74.00	28.14	horizontal	Peak
2390.00	44.89	-1.26	43.63	74.00	30.37	horizontal	Peak

Project No.: 2607S35862E-RF

Test Mode: BDR DH5 2402MHz


EUT Model: FAIP916-DW

Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa

Tested by: Wlif Wu

Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2389.13	47.97	-1.26	46.71	74.00	27.29	vertical	Peak
2390.00	44.68	-1.26	43.42	74.00	30.58	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	44.13	-0.82	43.31	74.00	30.69	horizontal	Peak
2489.10	47.57	-0.79	46.78	74.00	27.22	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: BDR DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	44.18	-0.82	43.36	74.00	30.64	vertical	Peak
2485.12	47.14	-0.81	46.33	74.00	27.67	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2374.07	46.70	-1.33	45.37	74.00	28.63	horizontal	Peak
2390.00	45.31	-1.26	44.05	74.00	29.95	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2389.53	47.43	-1.26	46.17	74.00	27.83	vertical	Peak
2390.00	44.32	-1.26	43.06	74.00	30.94	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	43.48	-0.82	42.66	74.00	31.34	horizontal	Peak
2490.01	47.57	-0.79	46.78	74.00	27.22	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 2DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	43.51	-0.82	42.69	74.00	31.31	vertical	Peak
2488.54	47.06	-0.80	46.26	74.00	27.74	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2375.15	47.20	-1.33	45.87	74.00	28.13	horizontal	Peak
2390.00	43.95	-1.26	42.69	74.00	31.31	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2402MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2370.34	47.66	-1.35	46.31	74.00	27.69	vertical	Peak
2390.00	43.52	-1.26	42.26	74.00	31.74	vertical	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	44.50	-0.82	43.68	74.00	30.32	horizontal	Peak
2489.74	46.82	-0.79	46.03	74.00	27.97	horizontal	Peak

Project No.: 2607S35862E-RF
Test Mode: EDR 3DH5 2480MHz
EUT Model: FAIP916-DW
Test distance: 3m

Temp/Humi/ATM: 23.0°C/60%/100.1kPa
Tested by: Wlif Wu
Power Source: DC 3.6V




Condition: PK RBW:1MHz VBW:3MHz SWT:auto

Freq MHz	Reading dBuV	Factor dB/m	Result dBuV/m	Limit dBuV/m	Margin dB	Polarity	Remark
2483.50	44.68	-0.82	43.86	74.00	30.14	vertical	Peak
2487.90	47.56	-0.80	46.76	74.00	27.24	vertical	Peak


Antenna-port conducted emission:

DH5_Low




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 13:15:22

DH5_Middle




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 13:22:44

DH5_High




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 13:33:04

2DH5_Low




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 13:44:03

2DH5_Middle




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 13:52:47


2DH5_High




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 13:58:19



ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 14:08:53



ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 14:14:48




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 14:22:38

FCC §15.247(a) (1) –CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

EUT Setup

Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 7.8.2

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A plot of the data shall be included in the test report.


Where the device shares the same channel plan (carrier frequencies and number of channels) across multiple data rates or modulation schemes then the carrier separation need only be measured for one of those modulation schemes or data rates.

Test Data

Test Mode:		Transmitting	Test Engineer:	Yuki	
Test Date:		2026-07-16	Environment:	Temp.: 22.9°C Humi.: 41% Atm.: 100.1kPa	
Mode	Channel	Channel Separation (MHz)	Limit (MHz)	Result	
BDR (GFSK)	2402	1.002	0.849	Pass	
	2441	1.002	0.851	Pass	
	2480	1.005	0.849	Pass	


Note:

1. Limit = 20 dB bandwidth*2/3

2. Only BDR (GFSK) mode result is reported since EDR ($\pi/4$ -DQPSK), EDR (8DPSK) has the same channel plan.**BDR (GFSK): Low Channel**


ProjectNo.:2607S35862E-RF Tester:Yuki
 Date: 16.JUL.2026 14:51:12

BDR (GFSK): Middle Channel



ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 14:54:39

BDR (GFSK): High Channel




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 14:57:50

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

EUT Setup

Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 6.9.2

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be at least three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in 4.1.6.2
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “–xx dB down” requirement; that is, if the requirement calls for measuring the –20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max-hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “–xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.

i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).

j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.


k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Test Data

Test Mode:	Transmitting	Test Engineer:	Yuki
Test Date:	2026-07-16	Environment:	Temp.: 22.9°C Humi.: 41% Atm.: 100.1kPa
Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.962
	Middle	2441	0.96
	High	2480	0.962
EDR ($\pi/4$-DQPSK)	Low	2402	1.243
	Middle	2441	1.243
	High	2480	1.243
EDR (8DPSK)	Low	2402	1.274
	Middle	2441	1.277
	High	2480	1.274


Please refer to below plots:

BDR (GFSK): Low Channel




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 10:55:34


BDR (GFSK): Middle Channel



ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 10:57:30


BDR (GFSK): High Channel

ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:01:43

EDR ($\pi/4$ -DQPSK): Low Channel


ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:04:58

EDR ($\pi/4$ -DQPSK): Middle Channel




ProjectNo.:2607S35862E-RF Tester:Yuki
 Date: 16.JUL.2026 11:09:03

EDR ($\pi/4$ -DQPSK): High Channel




ProjectNo.:2607S35862E-RF Tester:Yuki
 Date: 16.JUL.2026 11:10:54

EDR (8DPSK): Low Channel




ProjectNo.:2607S35862E-RF Tester:Yuki
 Date: 16.JUL.2026 11:13:11

EDR (8DPSK): Middle Channel



ProjectNo.:2607S35862E-RF Tester:Yuki
 Date: 16.JUL.2026 11:14:47

EDR (8DPSK): High Channel




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:18:29

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

EUT Setup

Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 7.8.3

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:


- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.


Where the device shares the same channel plan (carrier frequencies and number of channels) across multiple data rates or modulation schemes then the number of channels need only be measured for one of those modulation schemes or data rates.

Test Data


Test Mode:	Transmitting	Test Engineer:	Yuki
Test Date:	2026-07-16	Environment:	Temp.: 22.9°C Humi.: 41% Atm.: 100.1kPa
Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥15
EDR (π/4-DQPSK)	2400-2483.5	79	≥15
EDR (8DPSK)	2400-2483.5	79	≥15

BDR (GFSK): Number of Hopping Channels

ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:56:37

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels

ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 16:00:04


EDR (8DPSK): Number of Hopping Channels

ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 16:03:33

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

EUT Setup

Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 7.8.4

Use the following spectrum analyzer settings to determine the dwell time per hop:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected transmission time per hop.
- c) Sweep time: Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = $1/\text{hopping rate}$) should achieve this.
- d) Use a video trigger, where possible with a trigger delay, so that the start of the transmission is clearly observed. The trigger level might need adjustment to reduce the chance of triggering when the system hops on an adjacent channel.
- e) Detector function: Peak.
- f) Trace: Clear-write, single sweep.
- g) Place markers at the start of the first transmission on the channel and at the end of the last transmission. The dwell time per hop is the time between these two markers.

To determine the number of hops on a channel in the regulatory observation period repeat the measurement using a longer sweep time. When the device uses a single hopping sequence the period of measurement should be sufficient to capture at least 2 hops. When the device uses a dynamic hopping sequence, or the sequence varies, the period of measurement may need to capture multiple hops to better determine the average time of occupancy. Count the number of hops on the channel across the sweep time.


The average number of hops on the same channel within the regulatory observation period is calculated from the number of hops on the channel divided by the spectrum analyzer sweep time multiplied by the regulatory observation period. For example, if three hops are counted with an analyzer sweep time of 500 ms and the regulatory observation period is 10 s, then the number of hops in that ten seconds is $3 / 0.5 \times 10$, or 60 hops.

The average time of occupancy is calculated by multiplying the dwell time per hop by the number of hops in the observation period.

Test Data


Test Mode:		Transmitting		Test Engineer:		Yuki
Test Date:		2026-07-16		Environment:		Temp.: 22.9°C Humi.: 41% Atm.: 100.1kPa
Mode	Packet Type	Test Frequency (MHz)	BurstWidth (ms)	TotalHops (Num)	Result (s)	Limit (s)
BDR (GFSK)	DH1	2441	0.382	319	0.122	0.400
	DH3	2441	1.642	160	0.263	0.400
	DH5	2441	2.896	106	0.307	0.400
EDR ($\pi/4$ -DQPSK)	2DH1	2441	0.386	320	0.124	0.400
	2DH3	2441	1.644	159	0.261	0.400
	2DH5	2441	2.896	107	0.310	0.400
EDR (8DPSK)	3DH1	2441	0.386	320	0.124	0.400
	3DH3	2441	1.642	160	0.263	0.400
	3DH5	2441	2.900	107	0.310	0.400
Note: Note 1: A period time = $0.4 \times 79 = 31.6(S)$, Result = BurstWidth * Totalhops Note 2: Totalhops = Hopping Number in 31.6s Note 3: Hopping Number in 31.6s = Total of highest signals in 31.6s(Second high signals were other channel)						

DH1_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:27:28

DH1_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:31:07

DH3_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:32:05

DH3_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:32:53

DH5_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:33:45

DH5_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:34:42

2DH1_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:35:43

2DH1_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:36:30

2DH3_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:37:22

2DH3_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:38:17

2DH5_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:51:52

2DH5_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:52:43

3DH1_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:41:23

3DH1_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:42:21

3DH3_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:43:10

3DH3_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:43:56

3DH5_Hopping



ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:44:44

3DH5_Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 15:45:46

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

EUT Setup

Note: A short RF cable with low cable loss connected to the EUT antenna port. The insert loss of this RF cable was offset into the setting of test equipment:

Offset = Insert loss of RF cable

★ The Insert loss was declared by manufacturer.

Test Procedure

According to ANSI C63.10-2020 Section 7.8.5


This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. Frequency hopping shall be disabled for this test. Use the following spectrum analyzer setting:

- a) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- b) RBW > 20 dB bandwidth of the emission being measured.
- c) VBW $\geq$ RBW.
- d) Sweep: No faster than coupled (auto) time.
- e) Detector function: Peak.
- f) Trace: Max-hold.
- g) Allow trace to stabilize.
- h) Use the marker-to-peak function to set the marker to the peak of the emission.
- i) The indicated level is the peak output power, after any corrections for external attenuators and cables.
- j) A plot of the test results and setup description shall be included in the test report.

Test Data


Test Mode:	Transmitting	Test Engineer:	Yuki
Test Date:	2026-07-16	Environment:	Temp.: 22.9°C Humi.: 41% Atm.: 100.1kPa
Mode	Frequency (MHz)	Peak Conducted Output Power (dBm)	Limit (dBm)
BDR (GFSK)	2402	-0.91	21
	2441	-1.05	21
	2480	-1.33	21
EDR ($\pi/4$-DQPSK)	2402	0.02	21
	2441	-0.15	21
	2480	-0.43	21
EDR (8DPSK)	2402	0.05	21
	2441	-0.13	21
	2480	-0.42	21

Please refer to below plots:

BDR (GFSK): 2402MHz


ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:26:55

BDR (GFSK): 2441MHz




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:28:02

BDR (GFSK): 2480MHz




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:29:35

EDR ($\pi/4$ -DQPSK): 2402MHz




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:30:54

EDR ($\pi/4$ -DQPSK): 2441MHz




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:32:00

EDR ($\pi/4$ -DQPSK): 2480MHz




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:33:37

EDR (8DPSK): 2402MHz




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:41:52

EDR (8DPSK): 2441MHz



ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:43:06

EDR (8DPSK): 2480MHz




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 11:44:34

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

EUT Setup**Test Procedure**

According to ANSI C63.10-2020 Section 7.8.7.2 & Claus 6.10

- 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products that fall outside of the authorized band of operation.
- 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.6.2.
- 3) Attenuation: Auto (at least 10 dB preferred).
- 4) Sweep time: No faster than coupled (auto) time.
- 5) Resolution bandwidth: 100 kHz.
- 6) Video bandwidth: 300 kHz.
- 7) Detector: Peak.
- 8) Trace: Max-hold.


Test Data

Test Mode:	Transmitting	Test Engineer:	Yuki
Test Date:	2026-07-16	Environment:	Temp.: 22.9°C Humi.: 41% Atm.: 100.1kPa

Please refer to the below plots:


Band Edge

BDR (GFSK): Left Side




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 16:34:39

BDR (GFSK): Right Side




ProjectNo.:2607S35862E-RF Tester:Yuki
 Date: 16.JUL.2026 16:39:27

BDR (GFSK): Left Side - Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
 Date: 16.JUL.2026 16:43:03

BDR (GFSK): Right Side - Hopping




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 16:45:59


EDR ($\pi/4$ -DQPSK): Left Side



ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 16:50:55

EDR ($\pi/4$ -DQPSK): Right Side


ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 16:53:43

EDR ($\pi/4$ -DQPSK): Left Side - Hopping

ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 16:56:47


[illegible]

EDR (8DPSK): Left Side




Page 103 of 108

EDR (8DPSK): Right Side




ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 17:09:23

EDR (8DPSK): Left Side - Hopping



ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 17:12:47

EDR (8DPSK): Right Side - Hopping



ProjectNo.:2607S35862E-RF Tester:Yuki
Date: 16.JUL.2026 17:16:18

EUT PHOTOGRAPHS

Please refer to the attachment 2607S35862E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2607S35862E-RF-INP EUT INTERNAL PHOTOGRAPHS.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2607S35862E-RF-TSP SETUP PHOTOGRAPHS.

Declarations

1. Bay Area Compliance Laboratories Corp. (Xiamen) is not responsible for authenticity of any information provided by the applicant. Information from the applicant that may affect test results are marked with an asterisk “★”.
2. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
3. Unless required by the rule provided by the applicant or product regulations, then decision rule in this report did not consider the uncertainty.
4. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor $k=2$ with the 95% confidence interval.
5. This report cannot be reproduced except in full, without prior written approval of Bay Area Compliance Laboratories Corp. (Xiamen).
6. This report is valid only with a valid digital signature. The digital signature may be available only under the adobe software above version 7.0.

******* END OF REPORT *******