


## Label and label position



### PORTABLE POWER STATION

Model: J300

Rated Power: 300W

Rated Capacity: 14.8V, 20.8Ah, 307.84Wh

Battery Capacity: 3.7V/83200mAh

DC Input: 12V~24V=5A, 60W Max.

PV Input: 18V~23V=5A, 60W Max.

DC 5525 Output: 12V~16.8V=8A

Cigarette Lighter Output: 12V~16.8V=8A

USB Output\*2: 5V=3A, 9V=2A, 12V=1.5A, 18W

Type-C Output 1: 5V=3A, 9V=2A, 12V=1.67A, 20W Max.

Type-C Output 2: 5V=3A, 9V=3A, 12V=3A, 15V=3A,  
20V=3A, 60W Max.

AC Output: 110V±10%/60Hz 300W

Wireless Charge: 5V=1A, 7.5V=1A, 9V=1.12A,

9V=1.66A, 15W



Made in China

### ⚠ WARNINGS!

- ⊘ Do not put the product in water.
  - ⊘ Do not heat the product or get close to the fire source! Do not disassemble or transform the product without authorization! Do not hit the product hard.
  - ⊘ It is forbidden to use or place the battery under high temperature (hot sunshine or very hot car), otherwise it may cause overheating, fire, function failure and short service life of the battery.
  - ⊘ Do not disassemble the battery.
  - ⊘ Do not short circuit the battery.
  - ⊘ Do not use a non dedicated charger to charge the battery, which will cause danger.
  - ⊘ Do not directly touch the leaking battery. The leaking electrolyte will cause skin discomfort. In case the electrolyte enters the eyes, rinse it with clean water as soon as possible, do not rub the eyes, and send it to the hospital for treatment quickly.
  - ⊘ If the battery has been stored for more than three months, the customer is requested to charge and discharge the product once with a charger within the specified parameter range.
- FCC ID: 2A44J-J300

Label: 119.4mm\*59.4mm