


Operation Manual




2


- 7" 9" inch digital TFT Touch Screen
- With TF (optional) card Slot, With USB 2.0 port.
- 1080P Video Format
- Support the Audio playback format of MP3/M4A/WMA/WAV/FLAC/VOGG
- Support the Video playback format of RM/RMVB/DVD/VOB/VCODAT/MP4/MPEG4/M4V/MP4/H263/H264/AVI/3GP/SWF/AVI/ASF/MPEG etc.
- MOSFET amplifier: 45Watts X 4 max power output.
- FM Range: 87.5MHz~ 108 MHz/Hz
- With Remote Control
- Power-off with Auto-memory store function under radio or TF/USB mode TF (optional)
- Clock Function
- Mute Function
- BT Function
- Bass & Treble/LBR channel stabilizer
- Aux in Function(option)
- Reverbrance carmen Function
- Video Input Function




3



4




5



6



7




8

Before using Carplay, you need to prepare an original USB cable, and the iOS system is also recommended to upgrade to version 9.0 and above. Connect the data cable to the USB port of the car. At this time, you will be prompted to open the Siri in the phone, and the car will automatically start Carplay. If the carplay does not appear on the main interface of the car, click the Carplay icon on the phone to start the system.




9



10

pls do not playback video or mobile phone while driving
it only support 4.4-9.0 android phone , and iphone .if you don't
know how to do, pls contact seller for the video.




13

Use the Original ISO Cable connect the radio and iphone, it will show "Trust This Computer" choose "Trust".
Enter into your touch code.Finally the radio will show the phone picture on the Radio, and you only can use your iphone operation.
If you dont know how to do, pls contact seller for the video.



12



1

1. This product is only applicable to automobile installation with 12V power supply. If it is installed directly on the 24V vehicle or the 24V vehicle without lowering voltage, the machine will be burn out.
2. Before install to the car, wrap the unnecessary wire, don't expose the copper wire outside, avoid touching the power supply or ground wire, burn out the machine and make it unable to open, no sound etc

3. The connection must be made according to the wiring diagram. Failure to connect properly may cause machine failure or damage to the vehicle's electrical system.
4. The horn (+, -) lead must be connected to the speaker (+, -) terminal. Do not connect the car body or interconnect the speakers.
5. Please do not plug the vent or heat dissipation plate to avoid the instability of machine performance caused by internal overheating.
6. In order to drive safely, it is recommended to set "Turn On the brake control" as "ON" in the output control of the system, then the image will be displayed only when the brake is applied, while the sound will only be output without the image, and the screen will prompt "handbrake".

1-

Please turn off the car when you are connected, and wire connection according to the above method, after the connection is made, wrap joint with insulating tape. The blue line, the orange line, the pink line if you don't use it. Please wrap the wire end with insulating tape before installation. (blue line, orange line touch power will burn machine; Pink touch power will be blue screen!). Check with the meter: A/C (Red line) , B+ (Yellow line) If there is 10V~16V voltage, the machine cannot be used normally if it is lower or higher than this voltage range.

Simple troubleshooting:

Don't turn on

Check whether the B+ power line, ACC ignition line, and GND ground line have connection or no voltage.

Check whether the fuse on the power seat is burned during install and if so, replace the fuse of the same model.

Blue screen

Check whether the reversing line is connected to the power

Check whether the reversing line is connected to other functional lines.

No sound

Check whether the speaker line is properly connected

Check to see if only voices are recorded, or if both speakers are negatively connected.

It is normal to press reset to reset, or to restore factory Settings.

The steering wheel with auto buttons should not be set in the square control Settings, if set clear reset.

19

No reception
Check whether the radio antenna is in place. The radio antenna is
whether the core wire is broken
Do not read the USB
Please format USB before copying video or music.
Please copy this machine support video, music, figure format
try to change the USB is normal
Don't read the TF card

- Please copy this machine support video, music, figure format when trying to change TF is normal
- There's no reverse video
 - When checking the reverse side, the machine is turned to the reverse side interface. If the machine is not turned to the reverse side interface, the control line of the reverse side is not connected properly or correctly.
- Check whether the camera power supply, video line and components are normal
- The reversing is disruptive
- Camera flooring needs to be ground or iron bound
- Some of the rear vehicle interference needs to be added relay after the filter
- Touch the partial
- Re-calibration again in Settings.
 - The system did not start properly
 - Please contact after-sales or customer service staff to update the software.

16

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Warning: changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment

Radiation Exposure Statement

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.