

RF EXPOSURE EVALUATION

EUT Specification

EUT	waterproof led controller
Model Number	WIFI-SL2022
FCC ID	2A47V-WIFI-SL2022
Antenna gain (Max)	1.3dBi
Operation Frequency	BT:2.402-2.480GHz WLAN: 2.412GHz ~ 2.462GHz
Input Rating	DC 5V from Adpater 120V/50Hz
Max. output power	BT:1.97dBm WLAN: 802.11b: 15.58dBm 802.11g: 12.89dBm 802.11n(HT20): 11.57dBm 802.11n(HT40): 10.12dBm

Test Requirement:

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF)

Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

11.1 Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

$P_i = 3.1416$

R= distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1 mW/cm^2 . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

11.2 Measurement Result

Antenna gain: 1.3 dBi

BT:

Mode	Channel Freq. (MHz)	Measured power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain (Numeric)	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
GFSK	2402	1.97	2±1	3	1.349	0.000535	1
GFSK	2440	1.75	2±1	3	1.349	0.000535	1
GFSK	2480	0.87	1±1	2	1.349	0.000425	1

WIFI:

Operating Mode	Test Channel	Tune up tolerance (dBm)	Max tune up conducted power (dBm)	Output Peak power (mW)	Ant. Gain (dBi)	Ant. Gain (numeric)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
802.11b	1	15±1	16	39.811	1.3	1.349	0.010684	1
	6	15±1	16	39.811	1.3	1.349	0.010684	1
	11	15±1	16	39.811	1.3	1.349	0.010684	1
802.11g	1	13±1	14	25.119	1.3	1.349	0.006741	1
	6	12±1	13	19.953	1.3	1.349	0.005355	1
	11	12±1	13	19.953	1.3	1.349	0.005355	1
802.11n (HT20)	1	12±1	13	19.953	1.3	1.349	0.005355	1
	6	11±1	12	15.849	1.3	1.349	0.004253	1
	11	11±1	12	15.849	1.3	1.349	0.004253	1
802.11n (HT40)	3	10±1	11	12.589	1.3	1.349	0.003379	1
	6	10±1	11	12.589	1.3	1.349	0.003379	1
	9	9±1	10	10.000	1.3	1.349	0.002684	1

Signature:

A handwritten signature in black ink that reads "Alan He". The signature is fluid and cursive, with the first name "Alan" and the last name "He" clearly distinguishable.

Alan He

Date: 2022-03-17