

TEST REPORT

FCC ID.....:	2A48S-A20	
Test Report No.....:	TCT260128E031	
Date of issue.....:	Feb. 04, 2026	
Testing laboratory	SHENZHEN TONGCE TESTING LAB	
Testing location/ address:	2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China	
Applicant's name.....:	Shenzhenshi weiduli Technology Co., Ltd	
Address.....:	4h Floor, Building 4, Dejin industrial Zone, No. 40, Fuyuan 1st Road, HepingCommunity, Fuhai Street, Bao'an District Shenzhen, China	
Manufacturer's name ...:	Shenzhenshi weiduli Technology Co., Ltd	
Address.....:	4h Floor, Building 4, Dejin industrial Zone, No. 40, Fuyuan 1st Road, HepingCommunity, Fuhai Street, Bao'an District Shenzhen, China	
Standard(s)	FCC CFR Title 47 Part 1.1310 KDB 680106 D01 RF Exposure Wireless Charging App v04	
Product Name.....:	Power Bank	
Trade Mark	WEIDULI	
Model/Type reference.....:	A20-B, A20-A, A20, X2, PB-57, PB-58	
Rating(s).....:	Refer to EUT description of page 3	
Date of receipt of test item	Jan. 19, 2026	
Date (s) of performance of test.....:	Jan. 19, 2026 ~ Feb. 04, 2026	
Tested by (+signature) ...:	Yannie ZHONG	
Check by (+signature)....:	Beryl ZHAO	
Approved by (+signature):	Tomsin	

General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. General Product Information	3
1.1. EUT description	3
1.2. Model(s) list.....	3
2. General Information.....	4
2.1. Test environment and mode.....	4
2.2. Description of Support Units.....	4
3. Facilities and Accreditations	5
3.1. Facilities	5
3.2. Location	5
4. Measurement Uncertainty	5
5. Technical Requirements Specification	6
5.1. Requirements.....	6
5.2. Test Setup	7
5.3. Test Procedure	8
5.4. Test Instruments List	8
5.5. Test Result	9
5.6. Test Set-up Photo.....	11

1. General Product Information

1.1. EUT description

Product Name	Power Bank
Model/Type reference	A20-B
Sample Number.....	TCT260128E030-0101
Operation Frequency.....	111kHz~205kHz for 5W~15W 360kHz for 25W
Output power.....	5W/7.5W/10W/15W/MPP 25W
Modulation Technology	Load modulation
Antenna Type	Inductive loop coil Antenna
Rating(s)	Battery Energy: 38.5 Wh / 3.85 V Rated Capacity: 5800 mAh (DC 5 V, 3 A) Type-C Input: DC 5 V, 3 A/ DC 9 V, 2.22 A Type-C Output: DC 5 V, 3 A/ DC 9 V, 3 A/ DC 12 V, 2.92 A/ DC 15 V, 2.33 A/ DC 20 V, 1.75 A Wireless Charger Output: 5 W/ 7.5 W/ 10 W/15 W/ MPP 25 W

1.2. Model(s) list

No.	Model No.	Tested with
1	A20-B	☒
Other models	A20-A, A20, X2, PB-57, PB-58	☐

Note: A20-B is tested model, other models are derivative models. The models are identical in circuit and PCB layout, schematics, and BOM lists. The different are the model names and enclosure colour for commercial purpose. So the test data of A20-B can represent the remaining models.

2. General Information

2.1. Test environment and mode

Operating Environment:		
Temperature:	25 °C	
Humidity:	55 % RH	
Atmospheric Pressure:	1010 mbar	
Test Mode:		
DC Mode	TM1	wireless charging(5W)
	TM2	wireless charging(15W)
	TM3	wireless charging(25W)

2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Mobile Phone	MYW23CH/A	HYR59DVQWV	/	iPhone 16 PM

3. Facilities and Accreditations

3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

Designation Number: CN1205

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- A2LA-No.: 4320.01

SHENZHEN TONGCE TESTING LAB

The testing lab has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories.

3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339

4. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Magnetic field	1.6 dB
2	Electric field	1.6 dB

5. Technical Requirements Specification

5.1. Requirements

According to the item 5 of KDB 680106 D01 RF Exposure Wireless Charging App v04:

- 1) Power transfer frequency is below 1 MHz.
Wireless power transfer operation frequency is 111kHz ~ 205kHz and 360kHz
- 2) Output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.
The output power is 25W
- 3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)
The EUT is in physical contact with the client device.
- 4) Only § 2.1091-Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions)
Mobile exposure
- 5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1.
Yes, E-field and H-field strengths meet the requirements
- 6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested.
Yes, All the modes were tested


Limits For Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30


F=frequency in MHz
 *=Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

5.2. Test Setup


A:



B:




C:




Note: Length × Width × Height= 101.8*68.5*17 ± 0.3 mm

5.3. Test Procedure

- 1) The RF exposure test was performed in an echoic chamber;
- 2) The measurement probe was placed at test distance(15 cm from edges, 20 cm and 15cm from top) Which is between the edge of the charger and the geometric center of probe, for test setup A;
- 3) In addition to what is described in KDB 680106 D01, please measure and provide magnetic and electrical field strength at a distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 0cm, 2cm, 4cm, 20cm. Which is between the edge of the charger and the edge of of probe, for test setup B;
- 4) The highest emission leve laws recorded and compared with limit as soon as measurement of each points (A, B, C, D, E)were completed;
- 5) According to the requirements if KDB 680106 D01 v04, If the center of the probe sensing element is located more than 5 mm (The sensitive elements are located approximately 8 mm below the external surface specified in user manual of EHP-200A) from the probe outer surface, the field strengths need to be estimated through modeling for those positions that are not reachable;
- 6) Use **Biot-Savart Law**, the value of 0 cm can be estimated through the results of 2 cm, according to the formula:



$$B = \frac{\mu_0 * I * N * R^2}{2 * (R^2 + x^2)^{3/2}}$$



$$B = \frac{\mu_0 * I * N}{2 * x}$$

Remark:

B: H-field(Unit:T)

μ_0 : Space permeability= $4 * \pi * 10^{-7}$

I (Unit: A): The current element passing through a radiated coil.

R: Radius of radiated coil, according to the coil specification: R=0.02m

X: The distance from the sensing elements of the probe to the edge of the radiated coil (the dimensions of EUT and load are take into account) (Unit: m)

N: Turns of the radiated coil, according to the coil specification: N=20.

5.4. Test Instruments List

Equipment	Manufacturer	Model No.	Serial No.	Date of Cal.	Due Date
Electric and Magnetic Field Analyzer	Narda	EHP-200A	180ZX20511	Jul. 01, 2025	Jun. 30, 2026

5.5. Test Result

Test Result for Test setup A:

DC mode(15W)

5W, 10W, 15W load all have been tested, only worse case Max load (15W) is reported.

H-Filed Strength at (distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 20cm, 18cm, 16cm, 0cm, Which is between the edge of the charger and the edge of of probe,) surrounding the EUT (A/m)

Test distance (cm)	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)	Test Position F(A/m)	Limits (A/m)
2	0.5642	0.5302	0.4365	0.4601	0.2157	0.2228	1.63
4	0.2208	0.1924	0.2028	0.2045	0.0927	0.1231	1.63
6	0.1806	0.1761	0.1422	0.1836	0.2107	0.1528	1.63
8	0.1428	0.1262	0.1143	0.1442	0.1629	0.1205	1.63
10	0.1282	0.1035	0.0935	0.1281	0.1415	0.1007	1.63
12	0.0934	0.0716	0.0613	0.0965	0.1012	0.0784	1.63
14	0.0597	0.0598	0.0587	0.0598	0.0589	0.0591	1.63
16	0.0582	0.0584	0.0585	0.0587	0.0585	0.0587	1.63
18	0.0577	0.0581	0.0574	0.0584	0.0577	0.0582	1.63
20	0.0572	0.0567	0.0566	0.0572	0.0568	0.0575	1.63

Use the Biot-Savart Law to estimated the results of 2cm through 4 cm.

Test position	Measure Value(A/m)	Estimated Value (A/m)	Agreement Ratio	Limits
A	0.5642	0.4713	-16.47%	30%
B	0.5302	0.4111	-22.46%	30%
C	0.4365	0.3503	-19.75%	30%
D	0.4601	0.3532	-23.23%	30%
E	0.2157	0.1716	-20.45%	30%
F	0.2228	0.1733	-22.20%	30%

As the model is sufficient, the value of 0cm can be estimated through the results of 2 cm

Test position	Estimated Value (A/m)	Limits(A/m)
A	0.8086	1.63
B	0.7891	
C	1.2844	
D	1.2952	
E	1.1521	
F	0.2929	

DC mode(25W)

H-Filed Strength at (distance 0cm to 20cm at 2cm iteration, i.e. at a distance of 20cm, 18cm, 16cm, 0cm, Which is between the edge of the charger and the edge of of probe,) surrounding the EUT (A/m)

Test distance (cm)	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)	Test Position F(A/m)	Limits (A/m)
2	0.6405	0.5328	0.5171	0.5314	0.2436	0.2201	1.63
4	0.2601	0.2163	0.2317	0.2409	0.1032	0.1214	1.63
6	0.2044	0.2047	0.2048	0.2045	0.0965	0.1062	1.63
8	0.1542	0.1445	0.1446	0.1444	0.0862	0.0864	1.63
10	0.1248	0.1042	0.1044	0.1041	0.0661	0.0657	1.63
12	0.0945	0.0837	0.0845	0.0846	0.0585	0.0587	1.63
14	0.0597	0.0589	0.0591	0.0588	0.0582	0.0585	1.63
16	0.0589	0.0584	0.0586	0.0585	0.0577	0.0580	1.63
18	0.0585	0.0583	0.0577	0.0579	0.0571	0.0575	1.63
20	0.0571	0.0575	0.0570	0.0574	0.0568	0.0571	1.63

Use the Biot-Savart Law to estimated the results of 2cm through 4 cm.

Test position	Measure Value(A/m)	Estimated Value (A/m)	Agreement Ratio	Limits
A	0.6405	0.5552	-13.32%	30%
B	0.5328	0.4622	-13.25%	30%
C	0.5171	0.4002	-22.61%	30%
D	0.5314	0.4161	-21.70%	30%
E	0.2436	0.1910	-21.58%	30%
F	0.2201	0.1710	-22.33%	30%

As the model is sufficient, the value of 0cm can be estimated through the results of 2 cm

Test position	Estimated Value (A/m)	Limits(A/m)
A	0.9525	1.63
B	0.8871	
C	1.4674	
D	1.5257	
E	1.2826	
F	0.2888	

5.6. Test Set-up Photo

Please refer to document Appendix No.: TCT260128E030-A

*******END OF REPORT*******