

RF EXPOSURE REPORT

FOR

Applicant	:	SHENZHEN STARFIRE Technology Company CO., LTD
Address	:	9th Floor, Block B, Tsinghua Information Port, No. 1, Songpingshan Xindong Road, Xili Street, Nanshan District, Shenzhen, Guangdong, 518000, China
Equipment under Test	:	WiFi Smart Video Lock
Model No.	:	WV01
Trade Mark	:	Revol
FCC ID	:	2A4AC-WV01
Manufacturer	:	Shenzhen Kaadas Intelligent Technology co., Ltd.
Address	:	Floor 9, Building B, Tsinghua Hi-Tech Park, Nanshan District, Shenzhen, Guangdong, 518000, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

	Test report declares.....	3
1.	General Information	5
1.1.	Description of equipment	5
1.2.	Assess laboratory.....	5
2.	RF Exposure Evaluation	6
2.1.	Requirement.....	6
2.2.	Calculation method	6
2.3.	Estimation result.....	7

Test Report Declare

Applicant	:	SHENZHEN STARFIRE Technology Company CO., LTD
Address	:	9th Floor, Block B, Tsinghua Information Port, No. 1, Songpingshan Xindong Road, Xili Street, Nanshan District, Shenzhen, Guangdong, 518000, China
Equipment under Test	:	WiFi Smart Video Lock
Model No.	:	WV01
Trade mark	:	Revolvo
Manufacturer	:	Shenzhen Kaadas Intelligent Technology co., Ltd.
Address	:	Floor 9, Building B, Tsinghua Hi-Tech Park, Nanshan District, Shenzhen, Guangdong, 518000, China

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No.:	DDT-R21122113-2E03		
Date of Receipt:	Jan. 04, 2022	Date of Test:	Jan. 04, 2022 ~ Jan. 19, 2022

Prepared By:

Sam Li
Sam Li/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Jan. 19, 2022	

1. General Information

1.1. Description of equipment

EUT* Name	: WiFi Smart Video Lock
Model Number	: WfV01
EUT function description	: Please reference user manual of this device
Power Supply	: DC powered by a built-in 7.2V lithium battery or an external adapter for emergency.
Radio Specification	: Bluetooth V5.0, IEEE 802.11b/g/n
Operation Frequency	Bluetooth: 2402 MHz - 2480 MHz 2.4G WIFI: IEEE 802.11b: 2412 MHz - 2462 MHz IEEE 802.11g: 2412 MHz - 2462 MHz IEEE 802.11n HT20: 2412 MHz - 2462 MHz
Modulation	Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK 2.4G WIFI: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK, BPSK)
Data rate	Bluetooth: 1 Mbps, 2 Mbps, 3 Mbps 2.4G WIFI: IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps IEEE 802.11n HT20: 6.5, 13, 19.5, 26, 39, 52, 58.5, 65 Mbps
Antenna Gain	: 2 dBi
Maximum tune-up tolerance	: 1 dB
Sample Type	: Series production
Sample Number	: W023221310038

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,

Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2. RF Exposure Evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, d= 0.2 m, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation result

Mode	Maximum tune-up power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
BLE Max power	3.32	2.15	2	1.58	0.00068	1
2.4G WIFI Max power	17.41	55.08	2	1.58	0.01731	1

Note: The estimation distance is 20 cm

Conclusion: The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

END OF REPORT