

Give birth to Article Dividers Square Book



Specificat	20250603001
Effective	June /3

Customer's name	Ai Xiaodian
Product type	Three-in-one wireless charging coil
Top intelligence material number	TX-DZ43.5008005-K6.9-L47 (Open double slot)
Customer material number	A36-01303-47

[☒ Release of the new version, ☐ Version revision] [This specification includes a total of contents 3 Page] [RoHS Compliant Parts]

Weave	Check	Ratify
Li Pinghui	/	Ma Xiangping

Guangdong Dingzhi Electronic Technology Co., Ltd.

Address: 1st Floor, No. 1231 Yingbin Avenue, Longmen County, Huizhou City, Guangdong Province

TEL: 13147097490

This acknowledgement is received by the customer. 30 Within the day, please be sure to sign and return it. If it is overdue, it will be deemed to be implemented according to the standards of this letter of recognition at the time of production.

[Customer approval]

Date :

Recognition status: ☐ Fully admit ☐ Conditional recognition ☐ Refuse to admit

Ratify	Check	Re-examination	Examine

Explain:

Give birth to Article Dividers

Square Book

Customer's name	Ai Xiaodian	Customer material number	A36-01303-47
Top intelligence material number	TX-DZ43.5008005-K6.9-L47 (Open double slot)	Specification number	20250603001
Circulate/Revision record			
Edition	Effective date	Change the content/Reason	Examine and approve
01	June 3, 2025	Release of new specifications	Ma Xiangping

Weave	Check	Ratify	
Li Pinghui	/	Ma Xiangping	

Give birth to Article Dividers
Square Book

Customer's name	Ai Xiaodian	Customer material number	A36-01303-47		
Top intelligence material number	TX-DZ43.5008005-K6.9-L47 (Open double slot)	Specification number	20250603001	Edition	01
◆, external size			(Unit:Mm)		
			A	8.0 ± 0.5	
			B	13.8 ±1.Zero	
			Centigrade	38.5 ±1.0	
			Dimension	43.5 ±0.5	
			E	43.5 ±1.0	
			Fahrenheit	47.0 ±3.0	
			Generation	3.0 ± 1.0	
			H	1.4 ±0.3	
			I	0.50 ±0.2(Thickness of magnetic sheet)	
			One (1)Wire diameter: 0.08*24P*2Enamel-insulated wire		
			(2)Number of windings:12TS		
			(3)Does the starting and tail lines cross? : Yes		
			(Four)Coil bagSix millimetersWide high-temperature tape		
			(5)The coil and the magnetic sheet need to be pasted in the middle.		
			SixBlack film on the back of the magnetic sheet		

					(7)Coil surface sticker38Round large hole white glue			
◆, electrical characteristics :								
Parameter	Specifications		Test conditions	Test instrument				
L0	6.9 ± 10% μH		100KHz/1V	■TH1816B ■TH1816B ■CH-502BC				
Q	More than 30 minutes		100KHz/1V					
DCR.	Less than ninety-n mΩ		@25℃					
◆, temperature level :								
Operating temperature	-40℃~125℃							
◆, list of materials :								
Serial number	Classification	Material specifications	Supplier	Remarks				
1	Magnetic sheet	43.5*8*0.5T Open double slots	PC40Strong zinc					
2	Copper wire	0.08*24P*2		Enamel – insulated wire				
3	High-temperature tape	Six millimeters	Environmental protection tape					
Four	Glue	White glue	Environmentally friendly adhesive paper					
5	Stannum	107 hours	Qiandao Environmental Protection Tin					
6	Glue	Yellow glue	Environmentally friendly glue					

Weave	Check	Ratify
Li Pinghui	/	Ma Xiangping