



# Spot Check Evaluation

APPLICANT : Amazon.com Services LLC  
EQUIPMENT : Electronic Display Device  
MODEL NAME : PA2MA5  
FCC ID : 2A4DH-2425  
STANDARD : 47 CFR Part 15 Subpart C §15.247  
47 CFR Part 15 Subpart E §15.407  
TEST DATE(S) : Jul. 30, 2025 ~ Sep. 10, 2025

We, Sporton International Inc. (Shenzhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

*Fly Liang*

Approved by: Fly Liang



**Sporton International Inc. (ShenZhen)**

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055**  
**People's Republic of China**



## TABLE OF CONTENTS

|                                                  |    |
|--------------------------------------------------|----|
| REVISION HISTORY.....                            | 3  |
| 1 GENERAL DESCRIPTION.....                       | 4  |
| 1.1 Applicant.....                               | 4  |
| 1.2 Product Feature of Equipment Under Test..... | 4  |
| 1.3 Modification of EUT .....                    | 4  |
| 1.4 Testing Site.....                            | 4  |
| 1.5 Test Software.....                           | 5  |
| 1.6 Applicable Standards.....                    | 5  |
| 2 RE-USE OF MEASURED DATA.....                   | 6  |
| 2.1 Introduction Section.....                    | 6  |
| 2.2 Model Difference Information .....           | 6  |
| 2.3 Reference detail Section: .....              | 7  |
| 2.4 Spot Check Verification Data Section.....    | 7  |
| 3 LIST OF MEASURING EQUIPMENT.....               | 10 |
| 4 MEASUREMENT UNCERTAINTY .....                  | 11 |



## REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION                                                                                                                                        | ISSUED DATE   |
|------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
| 510202-02A | Rev. 01 | Initial issue of report                                                                                                                            | Aug. 14, 2025 |
| 510202-02A | Rev. 02 | Updated AC Conducted Emission test data for Bluetooth on Page 8<br>This report is an udated version, replacing the report issued on Aug. 14, 2025. | Sep. 11, 2025 |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |
|            |         |                                                                                                                                                    |               |

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



# 1 General Description

## 1.1 Applicant

Amazon.com Services LLC

410 Terry Avenue N Seattle, WA 98109-5210 United States

## 1.2 Product Feature of Equipment Under Test

| Product Feature |                                                                                                  |
|-----------------|--------------------------------------------------------------------------------------------------|
| Equipment       | Electronic Display Device                                                                        |
| Model Name      | PA2MA5                                                                                           |
| FCC ID          | 2A4DH-2425                                                                                       |
| SN Code         | Conducted/ Radiation: G0B4PH0352740071<br>DFS: P0B4FF01526600H3<br>Conduction: G0B4PFB045276007E |

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.3 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.4 Testing Site

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

|                    |                                                                                                                                                                                                                 |                     |                                |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|--------------------------------|
| Test Firm          | Sporton International Inc. (ShenZhen)                                                                                                                                                                           |                     |                                |
| Test Site Location | 101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China<br>TEL: +86-755-86066985 |                     |                                |
| Test Site No.      | Sporton Site No.                                                                                                                                                                                                | FCC Designation No. | FCC Test Firm Registration No. |
|                    | TH01-SZ<br>DFS01-SZ<br>03CH03-SZ<br>CO02-SZ                                                                                                                                                                     | CN1256              | 421272                         |

## 1.5 Test Software

| Item | Site      | Manufacturer | Name       | Version     |
|------|-----------|--------------|------------|-------------|
| 1.   | 03CH03-SZ | AUDIX        | E3         | 6.2009-8-24 |
| 2.   | DFS01-SZ  | Sporton      | Test Tools | 1.0         |
| 3.   | CO02-SZ   | AUDIX        | E3         | 6.120613b   |

## 1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB 484596 D01 Referencing Test Data v03
- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ 47 CFR Part 15 Subpart E §15.407
- ♦ ANSI C63.10-2013
- ♦ ANSI C63.26-2015



## **2 Re-use of Measured Data**

### **2.1 Introduction Section**

This application re-uses data collected on a similar device. The subject device of this application (Model: PA2MA5, FCC ID: 2A4DH-2425) is electrically identical to the reference device (Model: PA2MA4, FCC ID: 2A4DH-2424) for the portions of the circuitry corresponding to the data being re-used, following the FCC KDB 484596 D01 Referencing Test Data v03.

The criteria set in section 3 of KDB 484596 D01 v03 is followed to determine whether the data referencing is justified. For SAR, the higher between the referenced value and the spot check value is used to determine compliance in both standalone and simultaneous transmission conditions

The applicant takes full responsibility that the test data as referenced in this report represent compliance for this FCC ID: 2A4DH-2425 .

### **2.2 Model Difference Information**

The **main** difference between FCC ID: 2A4DH-2424 and FCC ID: 2A4DH-2425 is as below:

- Added color display.
- Changed to 4GB DRAM

Other differences and all the details of similarity and difference can be found in the confidential documents (2A4DH-2425 Operational Description of Product Equality Declaration).

## 2.3 Reference detail Section:

| Rule Part | Equipment Class | Frequency Band (MHz)   | Reference FCC ID (Parent) | Reference on test | Reference Title | FCC ID Filling (Variant) | Test on the variant | Data Referencing (Y/N) |
|-----------|-----------------|------------------------|---------------------------|-------------------|-----------------|--------------------------|---------------------|------------------------|
| 15C       | DSS (BR/EDR)    | 2400~2483.5            | 2A4DH-2424                | Full test         | FR510202-01A    | 2A4DH-2425               | Spot check          | Y,<br>All test items   |
|           | DTS (BLE)       | 2400~2483.5            | 2A4DH-2424                | Full test         | FR510202-01B    | 2A4DH-2425               | Spot check          | Y,<br>All test items   |
|           | DTS (WLAN)      | 2400~2483.5            | 2A4DH-2424                | Full test         | FR510202-01C    | 2A4DH-2425               | Spot check          | Y,<br>All test items   |
| 15E       | U-NII           | 5180~5240              | 2A4DH-2424                | Full test         | FR510202-01D    | 2A4DH-2425               | Spot check          | Y,<br>All test items   |
|           |                 | 5260~5320              | 2A4DH-2424                | Full test         | FR510202-01D    | 2A4DH-2425               | Spot check          | Y,<br>All test items   |
|           |                 | 5500~5720              | 2A4DH-2424                | Full test         | FR510202-01D    | 2A4DH-2425               | Spot check          | Y,<br>All test items   |
|           |                 | 5745~5825              | 2A4DH-2424                | Full test         | FR510202-01D    | 2A4DH-2425               | Spot check          | Y,<br>All test items   |
|           |                 | 5260~5320<br>5500~5720 | 2A4DH-2424                | Full test         | FZ510202-01     | 2A4DH-2425               | Spot check          | Y,<br>All test items   |

Y: Pointer to spot-check exhibit; N: Pointer to full test exhibit

## 2.4 Spot Check Verification Data Section

All test items test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model.

All test procedures follow the related section of parent report.

Spot-check measurements, while being always compliant with the applicable rule part(s) for the test under consideration, show a deviation  $d_{dB}$  from the reference data no larger than 3 dB:

$$d_{dB} = |V_{dB} - R_{dB}| \leq 3 \text{ dB} \quad (1)$$

$V_{dB}$ , the variant spot-check level

$R_{dB}$ , the corresponding measurement level for the reference model

An alternative to the limit of eq. (1) is available, and is based on considering how far the reference data  $R_{dB}$  is from the compliance threshold  $C_{dB}$  (also expressed in dB), for the particular test under consideration. In this case, if  $M_{dB} = |C_{dB} - R_{dB}|$  is the margin in dB from the compliance limit, a spot check may be considered acceptable when the deviation  $d_{dB}$  from the reference data satisfies the following condition:

$$d_{dB} = |V_{dB} - R_{dB}| \leq (3 + M_{dB} / 20) \text{ dB} , \text{ for } 0 \leq M_{dB} \leq 60 \text{ dB} \quad (2)$$

$$d_{dB} = |V_{dB} - R_{dB}| = 6 \text{ dB} , \text{ for } M_{dB} > 60 \text{ dB}$$

where “| |” is the absolute value of the measured quantity.

When using the option in eq. (2),  $d_{dB}$  increases linearly from 3 dB to 6 dB.



Summary for spot check for each rule entry and technology is listed as below:

| Mode                        | Test Item                                          | 2A4DH-2424<br>Parent<br>Worst mode<br>Test Result | 2A4DH-2425<br>Variant<br>Check Test<br>Result | Deviation<br>(dB) | Deviation<br>Limit<br>(dB) |
|-----------------------------|----------------------------------------------------|---------------------------------------------------|-----------------------------------------------|-------------------|----------------------------|
| BT 1Mbps (CH78)             | Number of Channels                                 | 79                                                | 79                                            | 0                 | 3                          |
|                             | Hopping Channel Separation                         | 1.003                                             | 0.990                                         | 0.013             | 3                          |
|                             | Dwell Time of Each Channel                         | 0.31                                              | 0.31                                          | 0                 | 3                          |
|                             | 20 Bandwidth                                       | 0.865                                             | 0.865                                         | 0                 | 3                          |
|                             | 99% Bandwidth                                      | 0.751                                             | 0.751                                         | 0                 | 3                          |
|                             | Conducted Band Edges                               | -55.38                                            | -56.67                                        | 1.29              | 3                          |
|                             | Conducted Spurious Emission                        | -37.78                                            | -37.16                                        | 0.62              | 3                          |
| BT 1Mbps (CH78)             | Radiated Band Edges and Radiated Spurious Emission | 48.24                                             | 47.64                                         | 0.6               | 3                          |
| BT                          | AC Conducted Emission                              | 19.53                                             | 19.82                                         | 0.29              | 3                          |
| BLE 1Mbps (CH39)            | 6 Bandwidth                                        | 0.656                                             | 0.656                                         | 0                 | 3                          |
|                             | 99% Bandwidth                                      | 1.013                                             | 1.015                                         | 0.002             | 3                          |
|                             | Power Spectral Density                             | -2.52                                             | -2.78                                         | 0.26              | 3                          |
|                             | Conducted Band Edges                               | -45.83                                            | -46.93                                        | 1                 | 3                          |
|                             | Conducted Spurious Emission                        | -37.8                                             | -37.52                                        | 0.28              | 3                          |
| BLE 1Mbps (CH19)            | Radiated Band Edges and Spurious Emission          | 46.16                                             | 45.92                                         | 0.2               | 3                          |
| BLE                         | AC Conducted Emission                              | 19.53                                             | 19.82                                         | 0.29              | 3                          |
| WIFI 2.4G<br>(802.11b CH01) | 6 Bandwidth                                        | 8.1                                               | 8.1                                           | 0                 | 3                          |
|                             | 99% Bandwidth                                      | 12.794                                            | 12.794                                        | 0                 | 3                          |
|                             | Power Spectral Density                             | -8.03                                             | -8.34                                         | 0.31              | 3                          |
|                             | Conducted Band Edges                               | -44.59                                            | -45.69                                        | 1.11              | 3                          |
|                             | Conducted Spurious Emission                        | -37.08                                            | -37.31                                        | 0.23              | 3                          |
| WIFI 2.4G<br>(802.11b CH06) | Radiated Band Edges and Spurious Emission          | 49.37                                             | 50.79                                         | 1.42              | 3                          |
| WIFI 5G<br>(802.11a CH149)  | 26 & 99% Bandwidth                                 | 20.4                                              | 20.34                                         | 0.06              | 3                          |
|                             | Power Spectral Density                             | -1.45                                             | -1.98                                         | 0.53              | 3                          |
|                             | DFS                                                | 0.026                                             | 0.0048                                        | 0.0212            | 3                          |
| WIFI 5G<br>(802.11ac CH58)  | Radiated Band Edges and Spurious Emission          | 50.73                                             | 49.89                                         | 0.84              | 3                          |
| WIFI 5G                     | AC Conducted Emission                              | 19.82                                             | 20.39                                         | 0.57              | 3                          |



| Test Item                   | Mode                        | 2A4DH-2424<br>Parent<br>Worst mode<br>Test Result | 2A4DH-2425<br>Variant<br>Check Test<br>Result | Deviation<br>(dB) | Deviation<br>Limit<br>(dB) |
|-----------------------------|-----------------------------|---------------------------------------------------|-----------------------------------------------|-------------------|----------------------------|
| Conducted<br>Power<br>(dBm) | BT BR/EDR_Ant1              | 7.58                                              | 7.08                                          | 0.5               | 3                          |
|                             | BLE 1M_Ant1                 | -1.6                                              | -2.5                                          | 0.9               | 3                          |
|                             | 2.4G 11b_Ant1               | 15.1                                              | 14.9                                          | 0.2               | 3                          |
|                             | 2.4G 11g_Ant1               | 15                                                | 14.8                                          | 0.1               | 3                          |
|                             | 2.4G 11n20_Ant1             | 15                                                | 14.8                                          | 0.2               | 3                          |
|                             | 5G 11a, UNII-2C_Ant1        | 14.44                                             | 14.32                                         | 0.12              | 3                          |
|                             | 5G 11n HT20, UNII-2C_Ant1   | 12.29                                             | 12.23                                         | 0.06              | 3                          |
|                             | 5G 11n HT40, UNII-2C_Ant1   | 12.34                                             | 12.31                                         | 0.03              | 3                          |
|                             | 5G 11ac VHT20, UNII-2C_Ant1 | 12.27                                             | 12.2                                          | 0.07              | 3                          |
|                             | 5G 11ac VHT40, UNII-2C_Ant1 | 12.31                                             | 12.3                                          | 0.01              | 3                          |
|                             | 5G 11ac VHT80, UNII-2C_Ant1 | 12.21                                             | 12.16                                         | 0.05              | 3                          |
|                             | 5G 11a, UNII-3_Ant1         | 14.93                                             | 14.9                                          | 0.03              | 3                          |
|                             | 5G 11n HT20, UNII-3_Ant1    | 12.59                                             | 12.49                                         | 0.1               | 3                          |
|                             | 5G 11n HT40, UNII-3_Ant1    | 12.64                                             | 12.62                                         | 0.02              | 3                          |
|                             | 5G 11ac VHT20, UNII-3_Ant1  | 12.55                                             | 12.5                                          | 0.05              | 3                          |
|                             | 5G 11ac VHT40, UNII-3_Ant1  | 12.59                                             | 12.55                                         | 0.04              | 3                          |
|                             | 5G 11ac VHT80, UNII-3_Ant1  | 12.36                                             | 12.3                                          | 0.06              | 3                          |
|                             | BT BR/EDR_Ant2              | 7.36                                              | 6.92                                          | 0.44              | 3                          |
|                             | BLE 1M_Ant2                 | -1.6                                              | -2.2                                          | 0.6               | 3                          |
|                             | 2.4G 11b_Ant2               | 15.1                                              | 14.9                                          | 0.2               | 3                          |
|                             | 2.4G 11g_Ant2               | 15                                                | 14.8                                          | 0.2               | 3                          |
|                             | 2.4G 11n20_Ant2             | 14.9                                              | 14.8                                          | 0.1               | 3                          |
|                             | 5G 11a, UNII-2C_Ant2        | 14.51                                             | 14.44                                         | 0.07              | 3                          |
|                             | 5G 11n HT20, UNII-2C_Ant2   | 12.21                                             | 12.19                                         | 0.02              | 3                          |
|                             | 5G 11n HT40, UNII-2C_Ant2   | 12.45                                             | 12.35                                         | 0.1               | 3                          |
|                             | 5G 11ac VHT20, UNII-2C_Ant2 | 12.18                                             | 12.12                                         | 0.06              | 3                          |
|                             | 5G 11ac VHT40, UNII-2C_Ant2 | 12.37                                             | 12.31                                         | 0.06              | 3                          |
|                             | 5G 11ac VHT80, UNII-2C_Ant2 | 12.29                                             | 12.22                                         | 0.07              | 3                          |
|                             | 5G 11a, UNII-3_Ant2         | 14.8                                              | 14.75                                         | 0.05              | 3                          |
|                             | 5G 11n HT20, UNII-3_Ant2    | 12.52                                             | 12.5                                          | 0.02              | 3                          |
|                             | 5G 11n HT40, UNII-3_Ant2    | 12.59                                             | 12.53                                         | 0.06              | 3                          |
|                             | 5G 11ac VHT20, UNII-3_Ant2  | 12.47                                             | 12.44                                         | 0.03              | 3                          |
|                             | 5G 11ac VHT40, UNII-3_Ant2  | 12.55                                             | 12.5                                          | 0.05              | 3                          |
|                             | 5G 11ac VHT80, UNII-3_Ant2  | 12.22                                             | 12.2                                          | 0.02              | 3                          |

**Conclusion:**

All test items test against the variant model based on the worst-case condition from the original model was performed in this filing to demonstrate the test data from original model remains representative for the variant model.

Based on the spot check test result, the test data from the original model is representative for the variant model. All spot check test data are shown within expected level compliant to limit line.

We are using power measurements from the original parent model reports to list on the grant.

We confirm that the test data referencing policy of FCC KDB 484596 D01 Referencing Test Data v03 has been followed and the test data as referenced from the parent model report represents compliance with new FCC ID.



### 3 List of Measuring Equipment

| Instrument                 | Manufacturer    | Model No.                | Serial No.   | Characteristics | Calibration Date | Test Date                   | Due Date      | Remark                |
|----------------------------|-----------------|--------------------------|--------------|-----------------|------------------|-----------------------------|---------------|-----------------------|
| Spectrum Analyzer          | R&S             | FSV40                    | 101078       | 10Hz~40GHz      | Apr. 02, 2025    | Aug. 05, 2025               | Apr. 01, 2026 | Conducted (TH01-SZ)   |
| Pulse Power Sensor         | Anritsu         | MA2411B                  | 1339473      | 30MHz~40GHz     | Dec. 25, 2024    | Aug. 05, 2025               | Dec. 24, 2025 | Conducted (TH01-SZ)   |
| Power Meter                | Anritsu         | ML2495A                  | 1218010      | 50MHz Bandwidth | Oct.14, 2024     | Aug. 05, 2025               | Oct. 13, 2025 | Conducted (TH01-SZ)   |
| EMI Test Receiver&SA       | KEYSIGHT        | N9038A                   | MY54450083   | 20Hz~8.4GHz     | Apr. 02, 2025    | Jul. 30, 2025               | Apr. 01, 2026 | Radiation (03CH03-SZ) |
| EXA Signal Analyzer        | KEYSIGHT        | N9010B                   | MY59071191   | 10KHz~44GHz     | Apr. 02, 2025    | Jul. 30, 2025               | Apr. 01, 2026 | Radiation (03CH03-SZ) |
| Loop Antenna               | R&S             | HFH2-Z2E                 | 101141       | 9kHz~30MHz      | Dec. 28, 2024    | Jul. 30, 2025               | Dec. 27, 2025 | Radiation (03CH03-SZ) |
| Bilog Antenna              | TeseQ           | CBL6112D                 | 35408        | 30MHz~2GHz      | Aug. 20, 2023    | Jul. 30, 2025               | Aug. 19, 2025 | Radiation (03CH03-SZ) |
| Double Ridge Guide Antenna | ETS-Lindgren    | Burgeon-3117             | 00240107     | 1GHz~18GHz      | Jul. 13, 2025    | Jul. 30, 2025               | Jul. 12, 2026 | Radiation (03CH03-SZ) |
| HF Amplifier               | MITEQ           | TTA1840-35-HG            | 1871923      | 18GHz~40GHz     | Jul. 03, 2025    | Jul. 30, 2025               | Jul. 02, 2026 | Radiation (03CH03-SZ) |
| SHF-EHF Horn               | com-power       | AH-840                   | 101071       | 18GHz~40GHz     | Apr. 03, 2025    | Jul. 30, 2025               | Apr. 02, 2027 | Radiation (03CH03-SZ) |
| Amplifier                  | EM Electronics  | EM330                    | 060756       | 0.01Hz~3000MHz  | Apr. 02, 2025    | Jul. 30, 2025               | Apr. 01, 2026 | Radiation (03CH03-SZ) |
| HF Amplifier               | MITEQ           | AMF-7D-00101800-30-10P-R | 1943528      | 1GHz~18GHz      | Oct. 14, 2024    | Jul. 30, 2025               | Oct. 13, 2025 | Radiation (03CH03-SZ) |
| HF Amplifier               | Keysight        | 83017A                   | MY53270357   | 500MHz~26.5GHz  | Apr. 02, 2025    | Jul. 30, 2025               | Apr. 01, 2026 | Radiation (03CH03-SZ) |
| AC Power Source            | Chroma          | 61601                    | 616010002729 | N/A             | Oct. 18, 2024    | Jul. 30, 2025               | Oct. 17, 2025 | Radiation (03CH03-SZ) |
| Turn Table                 | EM              | EM1000                   | N/A          | 0~360 degree    | NCR              | Jul. 30, 2025               | NCR           | Radiation (03CH03-SZ) |
| Antenna Mast               | EM              | EM1000                   | N/A          | 1 m~4 m         | NCR              | Jul. 30, 2025               | NCR           | Radiation (03CH03-SZ) |
| Spectrum Analyzer          | Rohde & Schwarz | FSV 40                   | 101829       | 10Hz~40GHz      | Oct. 14, 2024    | Aug. 05, 2025               | Oct. 13, 2025 | Conducted (DFS01-SZ)  |
| Signal Generator           | Keysight        | N5182B                   | MY56200424   | 9KHz~6GHz       | Apr. 02, 2025    | Aug. 05, 2025               | Apr. 01, 2026 | Conducted (DFS01-SZ)  |
| Combiner                   | MTJ Cooperation | MTJ7112                  | N/A          | 0.4-6GHz        | NCR              | Aug. 05, 2025               | NCR           | Conducted (DFS01-SZ)  |
| EMI Receiver               | R&S             | ESR7                     | 102297       | 9kHz~7GHz;      | Jul. 02, 2025    | Aug. 11, 2025~Sep. 10, 2025 | Jul. 01, 2026 | Conduction (CO02-SZ)  |
| AC LISN                    | R&S             | ENV216                   | 101499       | 9kHz~30MHz      | Jul. 03, 2025    | Aug. 11, 2025~Sep. 10, 2025 | Jul. 02, 2026 | Conduction (CO02-SZ)  |
| AC Power Source            | CHROMA          | 61601                    | 616010002470 | 100Vac~250Vac   | Dec. 25, 2024    | Aug. 11, 2025~Sep. 10, 2025 | Dec. 24, 2025 | Conduction (CO02-SZ)  |

NCR: No Calibration Required.

## 4 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Measurement (BT/WIFI2.4G/5G)

| Test Item                              | Uncertainty |
|----------------------------------------|-------------|
| Conducted Spurious Emission & Bandedge | ±1.34 dB    |
| Occupied Channel Bandwidth             | ±0.012 MHz  |
| Conducted Power                        | ±1.34 dB    |
| Conducted Power Spectral Density       | ±1.32 dB    |
| Frequency                              | ±1.3 Hz     |

### Uncertainty of Conducted Measurement (DFS)

| Test Item                         | Uncertainty |
|-----------------------------------|-------------|
| Conducted Generated signal Levels | ±0.62 dB    |
| Conducted Time                    | 0.38%       |

### Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

|                                                                     |       |
|---------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 2.5dB |
|---------------------------------------------------------------------|-------|

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|                                                                     |       |
|---------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 5.0dB |
|---------------------------------------------------------------------|-------|

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

|                                                                     |       |
|---------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 4.9dB |
|---------------------------------------------------------------------|-------|

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

|                                                                     |       |
|---------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 5.0dB |
|---------------------------------------------------------------------|-------|

-THE END-