FCC RF Test Report

APPLICANT	:	Amazon.com Services LLC
EQUIPMENT	:	Wireless Remote
MODEL NAME	:	PA38CA
FCC ID	:	2A4DH-3832
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System
TEST DATE(S)	:	Oct. 24, 2023 ~ Nov. 01, 2023

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Product Feature of Equipment Under Test 5
1.3 Product Specification of Equipment Under Test 5
1.4 Modification of EUT 5
1.5 Testing Location 6
1.6 Test Software 6
1.7 Applicable Standards 6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **7**
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 EUT Operation Test Setup 9
2.5 Measurement Results Explanation Example 9
3 TEST RESULT **10**
3.1 6dB and 99% Bandwidth Measurement 10
3.2 Output Power Measurement 17
3.3 Power Spectral Density Measurement 18
3.4 Conducted Band Edges and Spurious Emission Measurement 25
3.5 Radiated Band Edges and Spurious Emission Measurement 34
3.6 Antenna Requirements 38
4 LIST OF MEASURING EQUIPMENT **39**
5 MEASUREMENT UNCERTAINTY **40**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. RADIATED SPURIOUS EMISSION
APPENDIX C. DUTY CYCLE PLOTS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR380109-01	Rev. 01	Initial issue of report	Dec. 21, 2023

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 6.70 dB at 4960.00 MHz
–	15.207	AC Conducted Emission	15.207(a)	Not Required	–
3.6	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-
Remark: Not required means after assessing, test items are not necessary to carry out.					

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Amazon.com Services LLC
410 Terry Avenue N Seattle, WA 98109-5210 United States

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Wireless Remote
Model Name	PA38CA
FCC ID	2A4DH-3832
SN Code	Conducted: 309000148845R1 Radiation: G0G3C1013424005P

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	BLE 1Mbps: 3.45 dBm (0.0022 W) BLE 2Mbps: 3.45 dBm (0.0022 W)
99% Occupied Bandwidth	BLE 1Mbps:1.03MHz BLE 2Mbps:2.07MHz
Antenna Type / Gain	PCB InV Antenna type with gain 3.63 dBi
Type of Modulation	Bluetooth LE : GFSK

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH05-KS TH01-KS	CN1257	314309

1.6 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	SPORTON	Test Tools	10.0
2.	03CH05-KS	AUDIX	E3	210616

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated:, radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps

2.3 Connection Diagram of Test System

< Radiated Emission >

EUT

This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

2.4 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss

Following shows an offset computation example with cable loss 5.80 dB.

Offset(dB) = RF cable loss(dB).

= 5.80 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

BLE 1Mbps

6 dB Bandwidth Plot on Channel 00



Date: 1.NOV.2023 14:52:29

6 dB Bandwidth Plot on Channel 19



Date: 1.NOV.2023 14:55:39

6 dB Bandwidth Plot on Channel 39



Date: 1.NOV.2023 14:57:14

BLE 2Mbps

6 dB Bandwidth Plot on Channel 00



Date: 1.NOV.2023 14:59:12

6 dB Bandwidth Plot on Channel 19



Date: 1.NOV.2023 15:01:46

6 dB Bandwidth Plot on Channel 39



Date: 1.NOV.2023 15:04:04

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

BLE 1Mbps

99% Occupied Bandwidth Plot on Channel 00



Date: 1.NOV.2023 14:53:16

99% Occupied Bandwidth Plot on Channel 19



Date: 1.NOV.2023 14:56:25

99% Occupied Bandwidth Plot on Channel 39



Date: 1.NOV.2023 14:58:01

BLE 2Mbps

99% Occupied Bandwidth Plot on Channel 00



Date: 1.NOV.2023 15:00:40

99% Occupied Bandwidth Plot on Channel 19



Date: 1.NOV.2023 15:02:44

99% Occupied Bandwidth Plot on Channel 39



Date: 1.NOV.2023 15:05:01

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)

BLE 1Mbps

PSD 100kHz Plot on Channel 00



Date: 1.NOV.2023 14:53:07

PSD 100kHz Plot on Channel 19



Date: 1.NOV.2023 14:56:16

PSD 100kHz Plot on Channel 39



Date: 1.NOV.2023 14:57:52

BLE 2Mbps

PSD 100kHz Plot on Channel 00



Date: 1.NOV.2023 14:59:50

PSD 100kHz Plot on Channel 19



Date: 1.NOV.2023 15:02:24

PSD 100kHz Plot on Channel 39



Date: 1.NOV.2023 15:04:42

3.3.7 Test Result of Power Spectral Density Plots (3kHz)

BLE 1Mbps

PSD 3kHz Plot on Channel 00



Date: 1.NOV.2023 14:52:48

PSD 3kHz Plot on Channel 19



Date: 1.NOV.2023 14:55:58

PSD 3kHz Plot on Channel 39



Date: 1.NOV.2023 14:57:33

BLE 2Mbps

PSD 3kHz Plot on Channel 00



Date: 1.NOV.2023 14:59:31

PSD 3kHz Plot on Channel 19



Date: 1.NOV.2023 15:02:05

PSD 3kHz Plot on Channel 39



Date: 1.NOV.2023 15:04:23

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

BLE 1Mbps

Low Band Edge Plot on Channel 00



Date: 1.NOV.2023 14:54:48

High Band Edge Plot on Channel 39



Date: 1.NOV.2023 14:58:15

BLE 2Mbps

Low Band Edge Plot on Channel 00



Date: 1.NOV.2023 15:00:51

High Band Edge Plot on Channel 39



Date: 1.NOV.2023 15:05:13

3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Date: 1.NOV.2023 14:55:00

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00



Date: 1.NOV.2023 14:55:11

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 19



Date: 1.NOV.2023 14:56:41

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 19



Date: 1.NOV.2023 14:56:52

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39



Date: 1.NOV.2023 14:58:30

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39



Date: 1.NOV.2023 14:58:40

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 00



Date: 1.NOV.2023 15:01:08

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 00



Date: 1.NOV.2023 15:01:18

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 19



Date: 1.NOV.2023 15:02:58

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 19



Date: 1.NOV.2023 15:03:08

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 39



Date: 1.NOV.2023 15:05:26

Conducted Spurious Emission Plot on Bluetooth LE 2Mbps

GFSK Channel 39



Date: 1.NOV.2023 15:05:37

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Nov. 01, 2023	Oct. 10, 2024	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 05, 2023	Nov. 01, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2023	Nov. 01, 2023	Jan. 04, 2024	Conducted (TH01-KS)
Attenuator	TOJOIN	SMA(JK)	EMC01	2W/DC-18G	Jan. 10, 2023	Nov. 01, 2023	Jan. 09, 2024	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 10, 2023	Oct. 24, 2023~ Oct. 26, 2023	Oct. 09, 2024	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Mar. 24, 2023	Oct. 24, 2023~ Oct. 26, 2023	Mar. 23, 2024	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Oct. 24, 2023~ Oct. 26, 2023	Oct. 09, 2024	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Apr. 09, 2023	Oct. 24, 2023~ Oct. 26, 2023	Apr. 08, 2024	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218642	1GHz~18GHz	Apr. 06, 2023	Oct. 24, 2023~ Oct. 26, 2023	Apr. 05, 2024	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 08, 2023	Oct. 24, 2023~ Oct. 26, 2023	Jan. 07, 2024	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	380826	9KHz-1GHz	Jul. 06, 2023	Oct. 24, 2023~ Oct. 26, 2023	Jul. 05, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Jan. 05, 2023	Oct. 24, 2023~ Oct. 26, 2023	Jan. 04, 2024	Radiation (03CH05-KS)
high gain Amplifier	EM	EM01G18GA	060839	1Ghz-18Ghz	Oct. 10, 2023	Oct. 24, 2023~ Oct. 26, 2023	Oct. 09, 2024	Radiation (03CH05-KS)
Amplifier	EM	EM01G18GA	060833	1Ghz-18Ghz	Jan. 05, 2023	Oct. 24, 2023~ Oct. 26, 2023	Jan. 04, 2024	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 24, 2023~ Oct. 26, 2023	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 24, 2023~ Oct. 26, 2023	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 24, 2023~ Oct. 26, 2023	NCR	Radiation (03CH05-KS)
Attenuator	TOJOIN	SMA(JK)	EMC01	2W/DC-18G	Jan. 10, 2023	Oct. 24, 2023~ Oct. 26, 2023	Jan. 09, 2024	Radiation (03CH05-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	**±2.26 dB**
Occupied Channel Bandwidth	**±0.1%**
Conducted Power	**±0.46 dB**
Conducted Power Spectral Density	**±0.88 dB**
Frequency	**±0.4 Hz**

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3 dB**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**6.28 dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.88 dB**

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.26 dB**

---------- THE END ----------

Appendix A. Conducted Test Results

Report Number : FR380109-01

Bluetooth Low Energy

Test Engineer:	Jiang Jun	Temperature:	20~26	°C
Test Date:	2023.11.1	Relative Humidity:	40~51	%

BLE1M-Ant1

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.03	0.66	0.50	Pass
BLE	1Mbps	1	19	2440	1.03	0.67	0.50	Pass
BLE	1Mbps	1	39	2480	1.03	0.66	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	3.44	30.00	3.63	7.07	36.00	Pass
BLE	1Mbps	1	19	2440	3.45	30.00	3.63	7.08	36.00	Pass
BLE	1Mbps	1	39	2480	3.29	30.00	3.63	6.92	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	0.65	3.27
BLE	1Mbps	1	19	2440	0.65	3.39
BLE	1Mbps	1	39	2480	0.65	3.21

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	2.75	-12.69	3.63	8.00	Pass
BLE	1Mbps	1	19	2440	2.64	-11.55	3.63	8.00	Pass
BLE	1Mbps	1	39	2480	2.51	-12.76	3.63	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Report Number : FR380109-01

Bluetooth Low Energy

BLE2M-Ant1

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.07	1.12	0.50	Pass
BLE	2Mbps	1	19	2440	2.05	1.13	0.50	Pass
BLE	2Mbps	1	39	2480	2.06	1.12	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	3.43	30.00	3.63	7.06	36.00	Pass
BLE	2Mbps	1	19	2440	3.45	30.00	3.63	7.08	36.00	Pass
BLE	2Mbps	1	39	2480	3.31	30.00	3.63	6.94	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	2Mbps	1	0	2402	2.34	3.38
BLE	2Mbps	1	19	2440	2.34	3.42
BLE	2Mbps	1	39	2480	2.34	3.23

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.83	-13.61	3.63	8.00	Pass
BLE	2Mbps	1	19	2440	2.72	-12.95	3.63	8.00	Pass
BLE	2Mbps	1	39	2480	2.61	-13.97	3.63	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Appendix B Radiated Spurious Emission Test Data

Test Engineer :	Carry Xu	Relative Humidity :	41 ~ 42 %
		Temperature :	22 ~ 23 ℃

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	Bluetooth-LE	00	2402	1Mbps	-	-
Mode 2	2400-2483.5	Bluetooth-LE	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	Bluetooth-LE	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	Bluetooth-LE	00	2402	2Mbps	-	-
Mode 5	2400-2483.5	Bluetooth-LE	19	2440	2Mbps	-	-
Mode 6	2400-2483.5	Bluetooth-LE	39	2480	2Mbps	-	-
Mode 7	2400-2483.5	Bluetooth-LE	39	2480	1Mbps		LF

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth-LE	00	2389.56	37.17	54.00	-16.83	V	AVERAGE	Pass	Band Edge
1	Bluetooth-LE	00	4804.00	46.44	54.00	-7.56	V	AVERAGE	Pass	Harmonic
2	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
2	Bluetooth-LE	19	4880.00	47.00	54.00	-7.00	V	AVERAGE	Pass	Harmonic
3	Bluetooth-LE	39	2483.50	38.26	54.00	-15.74	V	AVERAGE	Pass	Band Edge
3	Bluetooth-LE	39	4960.00	47.30	54.00	-6.70	V	AVERAGE	Pass	Harmonic
4	Bluetooth-LE	00	2387.22	37.36	54.00	-16.64	H	AVERAGE	Pass	Band Edge
4	Bluetooth-LE	00	4804.00	43.84	54.00	-10.16	V	AVERAGE	Pass	Harmonic
5	Bluetooth-LE	19	-	-	-	-	-	-	-	Band Edge
5	Bluetooth-LE	19	4880.00	44.96	54.00	-9.04	V	AVERAGE	Pass	Harmonic
6	Bluetooth-LE	39	2483.50	41.13	54.00	-12.87	V	AVERAGE	Pass	Band Edge
6	Bluetooth-LE	39	4960.00	43.92	54.00	-10.08	V	AVERAGE	Pass	Harmonic
7	Bluetooth-LE	39	30.00	30.00	40.00	-10.00	H	PEAK	Pass	LF

Mode	1	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2323.65 49.14 74.00 -24.86 41.07 31.87 7.00 36.80 6.00 100 50 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 92.32 ------ ------ 83.92 32.11 7.12 36.83 6.00 100 50 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2387.09 37.04 54.00 -16.96 28.71 32.06 7.10 36.83 6.00 100 50 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 91.31 ------ ------ 82.91 32.11 7.12 36.83 6.00 100 50 AVERAGE

Mode	1	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2317.02 48.63 74.00 -25.37 40.58 31.85 6.99 36.79 6.00 100 67 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 98.58 ------ ------ 90.18 32.11 7.12 36.83 6.00 100 67 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2389.56 37.17 54.00 -16.83 28.83 32.07 7.10 36.83 6.00 100 67 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 97.59 ------ ------ 89.19 32.11 7.12 36.83 6.00 100 67 AVERAGE

Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 42.70 74.00 -31.30 63.85 33.90 10.20 65.25 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 49.49 74.00 -24.51 70.64 33.90 10.20 65.25 0.00 109 151 PEAK 2 4804.00 46.44 54.00 -7.56 67.58 33.90 10.21 65.25 0.00 109 151 AVERAGE

Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH19_2440MHz	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 43.72 74.00 -30.28 64.80 33.90 10.30 65.28 0.00 -- -- PEAK 2 7320.00 42.58 74.00 -31.42 60.63 35.70 12.72 66.47 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 50.86 74.00 -23.14 71.94 33.90 10.30 65.28 0.00 100 152 PEAK 2 4880.00 47.00 54.00 -7.00 68.08 33.90 10.30 65.28 0.00 100 152 AVERAGE 3 7320.00 42.02 74.00 -31.98 60.07 35.70 12.72 66.47 0.00 -- -- PEAK

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2484.94 49.19 74.00 -24.81 40.39 32.52 7.26 36.98 6.00 100 52 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 93.13 ------ ------ 84.35 32.50 7.25 36.97 6.00 100 52 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.74 37.52 54.00 -16.48 28.72 32.52 7.26 36.98 6.00 100 52 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 92.16 ------ ------ 83.38 32.50 7.25 36.97 6.00 100 52 AVERAGE

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.80 52.52 74.00 -21.48 43.72 32.52 7.26 36.98 6.00 106 121 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 100.11 ------ ------ 91.33 32.50 7.25 36.97 6.00 106 121 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.50 38.26 54.00 -15.74 29.46 32.52 7.26 36.98 6.00 106 121 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 99.12 ------ ------ 90.34 32.50 7.25 36.97 6.00 106 121 AVERAGE

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 44.88 74.00 -29.12 65.77 34.02 10.40 65.31 0.00 -- -- PEAK 2 7440.00 41.42 74.00 -32.58 59.71 35.74 12.78 66.81 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 50.36 74.00 -23.64 71.25 34.02 10.40 65.31 0.00 272 101 PEAK 2 4960.00 47.30 54.00 -6.70 68.19 34.02 10.40 65.31 0.00 272 101 AVERAGE 3 7440.00 42.97 74.00 -31.03 61.26 35.74 12.78 66.81 0.00 -- -- PEAK

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
Peak Avg		

Note: Only the worst case has assessed 18G ~25GHz to test.

Mode	4	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2333.53 48.82 74.00 -25.18 40.72 31.90 7.02 36.82 6.00 122 48 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 91.45 ------ ------ 83.05 32.11 7.12 36.83 6.00 122 48 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2387.22 37.36 54.00 -16.64 29.03 32.06 7.10 36.83 6.00 122 48 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 89.07 ------ ------ 80.67 32.11 7.12 36.83 6.00 122 48 AVERAGE

Mode	4	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2364.21 49.33 74.00 -24.67 41.12 31.99 7.07 36.85 6.00 100 69 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 98.26 ------ ------ 89.86 32.11 7.12 36.83 6.00 100 69 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2369.54 37.35 54.00 -16.65 29.11 32.01 7.07 36.84 6.00 100 69 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 95.77 ------ ------ 87.37 32.11 7.12 36.83 6.00 100 69 AVERAGE

Mode	4	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH00_2402MHz	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 40.36 74.00 -33.64 61.51 33.90 10.20 65.25 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 49.03 74.00 -24.97 70.18 33.90 10.20 65.25 0.00 119 149 PEAK 2 4804.00 43.84 54.00 -10.16 64.98 33.90 10.21 65.25 0.00 119 149 AVERAGE

Mode	5	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH19_2440MHz	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 43.41 74.00 -30.59 64.49 33.90 10.30 65.28 0.00 -- -- PEAK 2 7320.00 41.90 74.00 -32.10 59.95 35.70 12.72 66.47 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 50.28 74.00 -23.72 71.36 33.90 10.30 65.28 0.00 105 151 PEAK 2 4880.00 44.96 54.00 -9.04 66.04 33.90 10.30 65.28 0.00 105 151 AVERAGE 3 7320.00 41.96 74.00 -32.04 60.01 35.70 12.72 66.47 0.00 -- -- PEAK

Mode	6	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.56 51.37 74.00 -22.63 42.57 32.52 7.26 36.98 6.00 100 51 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 93.04 ------ ------ 84.26 32.50 7.25 36.97 6.00 100 51 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.50 38.30 54.00 -15.70 29.50 32.52 7.26 36.98 6.00 100 51 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 90.68 ------ ------ 81.90 32.50 7.25 36.97 6.00 100 51 AVERAGE

Mode	6	
	Band Edge	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2484.28 54.11 74.00 -19.89 45.31 32.52 7.26 36.98 6.00 107 121 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 100.07 ------ ------ 91.29 32.50 7.25 36.97 6.00 107 121 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.50 41.13 54.00 -12.87 32.33 32.52 7.26 36.98 6.00 107 121 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 97.69 ------ ------ 88.91 32.50 7.25 36.97 6.00 107 121 AVERAGE

Mode	6	
	Harmonic	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 44.73 74.00 -29.27 65.62 34.02 10.40 65.31 0.00 -- -- PEAK 2 7440.00 41.46 74.00 -32.54 59.75 35.74 12.78 66.81 0.00 -- -- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 49.24 74.00 -24.76 70.13 34.02 10.40 65.31 0.00 123 145 PEAK 2 4960.00 43.92 54.00 -10.08 64.81 34.02 10.40 65.31 0.00 123 145 AVERAGE 3 7440.00 41.95 74.00 -32.05 60.24 35.74 12.78 66.81 0.00 -- -- PEAK

Mode	7	
	LF	
	2400-2483.5_Bluetooth-LE _CH39_2480MHz	
Pol.	Horizontal	Vertical
Peak QP	 	

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phas
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		
1	30.00	30.00	-10.00	40.00	37.74	24.57	0.71	33.02	---	---	Peak	HORIZONT
2	55.22	23.91	-16.09	40.00	42.28	13.45	1.10	32.92	---	---	Peak	HORIZONT
3	96.93	22.58	-20.92	43.50	37.48	16.49	1.48	32.87	---	---	Peak	HORIZONT
4	188.11	20.30	-23.20	43.50	35.41	15.65	2.08	32.84	---	---	Peak	HORIZONT
5	250.19	18.40	-27.60	46.00	30.33	18.42	2.42	32.77	---	---	Peak	HORIZONT
6	413.15	20.66	-25.34	46.00	28.55	21.90	3.10	32.89	---	---	Peak	HORIZONT

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark	Pol/Phas
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg		
1	34.85	28.97	-11.03	40.00	39.01	22.06	0.79	32.89	---	---	Peak	VERTICAL
2	56.19	27.01	-12.99	40.00	45.54	13.28	1.11	32.92	---	---	Peak	VERTICAL
3	104.69	28.24	-15.26	43.50	42.57	17.00	1.54	32.87	---	---	Peak	VERTICAL
4	185.20	23.63	-19.87	43.50	38.69	15.71	2.06	32.83	---	---	Peak	VERTICAL
5	471.35	24.58	-21.42	46.00	31.27	22.99	3.32	33.00	---	---	Peak	VERTICAL
6	642.07	26.23	-19.77	46.00	30.14	25.18	3.87	32.96	---	---	Peak	VERTICAL

Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE 1Mbps	86.09	2.152	0.465	0.47KHz
Bluetooth LE 2Mbps	58.30	1.094	0.914	1KHz

Bluetooth LE 1Mbps



Date: 24.OCT.2023 16:51:42

Bluetooth LE 2Mbps



Date: 24.OCT.2023 16:50:51