ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
FCC PART 15 SUBPART C REQUIREMENT

OF

Controller

Model No.: KZQ14A, KZQ16A, KZQ18A, KZQ20A, KZQ45W2, KZQCDD4, KZQCDD8, KZQFWD2, KZQPOD2, KZQPOD4, KZQCLQ4

Trademark: Nicoko

FCC ID: 2A4GGKZQ14A

Report No.: E01A22020046F00101

Issue Date: Feb. 24, 2022

Prepared for

Shenzhen Huacai Lijing Electronic Technology Co. Ltd

Building 1105 Room, BiXin Road Longyuanyinxiang garden, Longchengjiedao, Longgang district, Shenzhen, China

Prepared by

Dong Guan Anci Electronic Technology Co., Ltd.

1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr., China.

This report shall not be reproduced, except in full, without the written approval of Dong Guan Anci Electronic Technology Co., Ltd.

VERIFICATION OF COMPLIANCE

Applicant:	Shenzhen Huacai Lijing Electronic Technology Co. Ltd Building 1105 Room, BiXin Road Longyuanyinxiang garden, Longchengjiedao, Longgang district, Shenzhen, China
Manufacturer:	Shenzhen Huacai Lijing Electronic Technology Co. Ltd Building 1105 Room, BiXin Road Longyuanyinxiang garden, Longchengjiedao, Longgang district, Shenzhen, China
Product Description:	Controller
Trade Mark:	Nicoko
Model Number:	KZQ14A, KZQ16A, KZQ18A, KZQ20A, KZQ45W2, KZQCDD4, KZQCDD8, KZQFWD2, KZQPOD2, KZQPOD4, KZQCLQ4 (All models are the same except for different models, we choose KZQ14A for all tests)

We hereby certify that:

The above equipment was tested by Dong Guan Anci Electronic Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2021).

Date of Test : Feb. 14, 2022 to Feb. 23, 2022

Prepared by : Tomas Yang/Editor

Approved & Authorized Signer : Alan He/Manager

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	E01A22020046F00101

Table of Contents

1. GENERAL INFORMATION 6

1.1 PRODUCT DESCRIPTION 6
1.2 TEST METHODOLOGY 6

2. TEST FACILITY 7

3. DESCRIPTION OF TEST MODES 8

4. SUMMARY OF TEST RESULTS 10

5. TEST SYSTEM UNCERTAINTY 11

6. CONDUCTED EMISSIONS TEST 12

6.1MEASUREMENT PROCEDURE: 12
6.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 12
6.3MEASUREMENT EQUIPMENT USED: 12
6.4 CONDUCTED EMISSION LIMIT 12
6.5 MEASUREMENT RESULT: 13

7. RADIATED EMISSION TEST 14

7.1MEASUREMENT PROCEDURE 14
7.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 16
7.3MEASUREMENT EQUIPMENT USED: 17
7.4 RADIATED EMISSION LIMIT 18
7.5 MEASUREMENT RESULT 19
7.6 RADIATED MEASUREMENT PHOTOS: 25

8. 6DB BANDWIDTH MEASUREMENT 26

8.1MEASUREMENT PROCEDURE 26
8.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 26
8.3 MEASUREMENT EQUIPMENT USED: 26
8.4 LIMIT 26
8.5MEASUREMENT RESULTS: 26

9. MAXIMUM PEAK OUTPUT POWER TEST 29

9.1MEASUREMENT PROCEDURE 29
9.2TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 29
9.3 MEASUREMENT EQUIPMENT USED: 29
9.4 PEAK POWER OUTPUT LIMIT 29
9.5 MEASUREMENT RESULTS: 29
10.1MEASUREMENT PROCEDURE 32
10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 32
10.3 MEASUREMENT EQUIPMENT USED: 32
10.4 MEASUREMENT PROCEDURE 32

10.5 MEASUREMENT RESULTS:..... 33
11. BAND EDGE TEST..... 36
11.1 MEASUREMENT PROCEDURE..... 36
11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 37
11.3 MEASUREMENT EQUIPMENT USED:..... 37
11.4 MEASUREMENT RESULTS:..... 39
12 ANTENNA APPLICATION..... 45
12.1 ANTENNA REQUIREMENT..... 45
12.2 RESULT..... 45
13 PHOTOS OF EUT..... 46

1. GENERAL INFORMATION

1.1 Product Description

Characteristics	Description
Product Name	Controller
Model number	KZQ14A
Input Rating	DC12V-16V
Power Supply	Battery 12V
Kind of Device	Bluetooth Ver.5.0 BLE
Modulation	GFSK
Operating Frequency Range	2402-2480MHz
Number of Channels	40
Transmit Power Max(PK)	2.55dBm(0.0018W)
Antenna Type	PCB antenna
Antenna Gain	0 dBi

1.2 Test Methodology

All the test program has follow FCC new test procedure KDB 558074 D01 DTS Meas Guidance v05 and in accordance with the procedures given in ANSI C63.10-2013.

2. Test Facility

Site Description

EMC Lab.	:	Accredited by CNAS, 2017.06.26 The certificate is valid until 2022.10.28 The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L6214. Accredited by A2LA, 2018.03.15 The Certificate Number is 4422.01.
Name of Firm	:	Dong Guan Anci Electronic Technology Co., Ltd.
Site Location	:	1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan, Lake Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr., China.

3. Description of test modes

The EUT has been tested under its typical operating condition and fully-charged battery for EUT tested alone. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonics of the highest fundamental frequency or to 40 GHz, whichever is lower).

Configuration of Tested System

Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	Controller	Nicoko	KZQ14A	2A4GGKZQ14A	***EUT***
2.	Battery	JYHY	JYHY12550(12V55AH)	N/A	***Support EUT***
3.	LED Light	Nicoko	HMB300WC	N/A	***Support EUT***

The EUT has been tested under TX operating condition.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	**2402**	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	**19**	**2440**	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	**39**	**2480**
12	2426	26	2454		
13	2428	27	2456		

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.

4. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	N/A（see note 1）
§15.247(d),§15.209	Radiated Emission	Compliant
§15.247(a)(2)	6dB Bandwidth Measurement	Compliant
§15.247(b)	MAXIMUM PEAK OUTPUT POWER TEST	Compliant
§15.247(e)	Power Spectral Density Measurement	Compliant
§15.247(d)	Band EDGE test	Compliant
§15.203	Antenna Requirement	Compliant
Remark: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits. Note 1：The product is used in the car and can only be powered by a 12V battery.		

5. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0dB
Conducted Emissions Test	±2.0dB
Radiated Emission Test	±2.0dB
Power Density	±2.0dB
Occupied Bandwidth Test	±1.0dB
Band Edge Test	±3dB
All emission, radiated	±3dB
Antenna Port Emission	±3dB
Temperature	±0.5℃
Humidity	±3%

Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%

6. Conducted Emissions Test

6.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Calibrated until
L.I.S.N	SCHWARZBECK	NSLK 8127	8127-669	2022-05-22
10 db attenuator	JFW	50FP-010-H4	4360846-427-1	2022-05-22
RF Cable	N/A	N/A	2#	2022-05-22
EMI Test Receiver	ROHDE&SCHWARZ	ESCI	101358	2022-05-22

6.4 Conducted Emission Limit

(7) Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

6.5 Measurement Result:

N/A.

7. Radiated Emission Test

7.1 Measurement Procedure

1. The testing follows the guidelines in ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. The EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
5. For measurement below 1GHz, if the emission level of the EUT measured by the peak detector is 3dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
   1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
   2) Change the antenna polarization and repeat 1) with vertical polarization.
   3) Make a hardcopy of the spectrum.
   4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
   5) Change the analyser mode to Clear/ Write and found the cone of emission.
   6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
   7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
   8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

Use the following spectrum analyzer settings:

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Average
Trace	Max hold

For Average Measurement:

VBW=10Hz, when duty cycle is no less than 98 percent.

VBW≥1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(μs)	1/T(KHz)	Average Correction Factor	VBW Setting
2402-2480	100	-	-	0	10Hz

7.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



7.3 Measurement Equipment Used:

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1.	EMI Test Receiver	Rohde & Schwarz	ESPI	100502	2022-11-13
2.	Pre-Amplifier	HP	8447D	2727A06172	2022-05-22
3.	Bilog Antenna	Schwarzbeck	VULB9163	VULB9163-588	2022-05-22
4.	Loop Antenna	Schwarzbeck	FMZB 1516	1516-141	2022-11-13
5.	Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-13
6.	Low noise Amplifiers	A-INFO	LA1018N4009	J1013130524001	2022-05-22
7.	Horn antenna	A-INFO	LB-10180-SF	J2031090612123	2022-05-22
8.	Broadband RF Power Amplifier	AEROFLEX	AEROFLEX100KHz-40GHz	J1013130524001	2022-11-13
9.	DRG Horm Antenna	A.H.SYSTEMS	SAS-574	J2031090612123	2022-11-13
10.	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92J-2m	N/A	2022-11-13
11.	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92J-0.3m	N/A	2022-11-13
12.	RF Cable	N/A	N/A	6#	2022-05-22
13.	RF Cable	N/A	N/A	1-1#	2022-05-22
14.	RF Cable	N/A	N/A	1-2#	2022-05-22
15.	RF Cable	N/A	N/A	7#	2022-05-22
16.	3m Semi-anechoic Chamber	chengyu	9m*6m*6m	N/A	2022-05-22
17.	Test Software	Farad	EZ-EMC Ver:ANCI-3A1	N/A	N/A

7.4 Radiated emission limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

Remark : 1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of ξ 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

7.5 Measurement Result

Below 30MHz:

Operation Mode:	TX	Test Date :	2022-02-17
Frequency Range:	9KHz~30MHz	Temperature :	25℃
Test Result:	PASS	Humidity :	58 %
Measured Distance:	3m	Test By:	Best

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: The low frequency, which started from 9KHz-30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Below 1000MHz:

Pass.

The data of the mode (GFSK 2480MHz) are recorded in the following pages.



Site:	**843.3**	**Antenna::Horizontal**	**Temperature(C):26(C)**
Limit:	**FCC Part 15 C Conduction(QP)**		**Humidity(%):60%**
EUT:	**Controller**	**Test Time:**	**2022-02-17**
M/N.:	**KZQ14A**	**Power Rating:**	**Battery 12V**
Mode:	**TX2402**	**Test Engineer:**	**Bast**
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1 !	59.8588	53.47	-16.97	36.50	40.00	-3.50	QP	
2 !	73.6170	55.27	-19.47	35.80	40.00	-4.20	QP	
3 *	97.1148	57.03	-17.02	40.01	43.50	-3.49	QP	
4 !	119.0180	56.88	-17.20	39.68	43.50	-3.82	QP	
5 !	198.5879	55.54	-15.84	39.70	43.50	-3.80	QP	
6 !	209.3129	55.05	-15.55	39.50	43.50	-4.00	QP	

*:Maximum data x:Over limit !:over margin

Site:	**843.3**	**Antenna::Vertical**	**Temperature(C):26(C)**
Limit:	**FCC Part 15 C Conduction(QP)**		**Humidity(%):60%**
EUT:	**Controller**	**Test Time:**	**2022-02-17**
M/N.:	**KZQ14A**	**Power Rating:**	**Battery 12V**
Mode:	**TX2402**	**Test Engineer:**	**Bast**
Note:			

No.	Frequency (MHz)	Reading Level(dBuV)	Factor (dB)	Measure-ment(dBuV)	Limit (dBuV)	Over (dB)	Detector	Comment
1 !	31.3992	51.94	-17.71	34.23	40.00	-5.77	QP	
2 *	39.7146	53.09	-16.19	36.90	40.00	-3.10	QP	
3 !	59.6492	53.11	-16.91	36.20	40.00	-3.80	QP	
4 !	67.2022	54.75	-18.05	36.70	40.00	-3.30	QP	
5 !	120.6991	57.73	-17.53	40.20	43.50	-3.30	QP	
6 !	196.5098	56.33	-16.03	40.30	43.50	-3.20	QP	

*:Maximum data x:Over limit !:over margin

Above 1000MHz~10th Harmonics:

Operation Mode:	TX Mode (CH00: 2402MHz)	Test Date :	2022-02-17
Frequency Range:	1-25GHz	Temperature :	25℃
Test Result:	PASS	Humidity :	58 %
Measured Distance:	3m	Test By:	Best

Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4804	V	95.32	75.26	-32.3	63.02	42.96	74	54	-11	-11.04
7206	V	97.43	77.52	-37.2	60.23	40.32	74	54	-13.8	-13.68
9608	V	97.12	77.9	-39.8	57.32	38.1	74	54	-16.7	-15.9
12010	V	96.82	77.28	-40.5	56.32	36.78	74	54	-17.7	-17.22
14412	V	97.02	77.78	-41.7	55.32	36.08	74	54	-18.7	-17.92
16814	V	94.25	75.22	-40	54.25	35.22	74	54	-19.8	-18.78
4804	H	94.56	74.85	-31.6	62.96	43.25	74	54	-11	-10.75
7206	H	95.63	75.64	-35.5	60.13	40.14	74	54	-13.9	-13.86
9608	H	96.42	77.82	-38.3	58.12	39.52	74	54	-15.9	-14.48
12010	H	95.32	76.32	-39	56.32	37.32	74	54	-17.7	-16.68
14412	H	98.47	79.15	-42	56.47	37.15	74	54	-17.5	-16.85
16814	H	94.63	75.32	-39.3	55.33	36.02	74	54	-18.7	-17.98

Other harmonics emissions are lower than 20dB below the allowable limit.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) Measuring frequencies from 1GHz to 25GHz.

Operation Mode:	TX Mode (CH19: 2440MHz)	Test Date :	2022-02-17
Frequency Range:	1-25GHz	Temperature :	25℃
Test Result:	PASS	Humidity :	58 %
Measured Distance:	3m	Test By:	Best

Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4880	V	95.53	76.62	-32.3	63.23	44.32	74	54	-10.77	-9.68
7320	V	97.45	78.72	-37.2	60.25	41.52	74	54	-13.75	-12.48
9760	V	98.43	79.12	-39.8	58.63	39.32	74	54	-15.37	-14.68
12200	V	96.82	77.95	-40.5	56.32	37.45	74	54	-17.68	-16.55
14640	V	97.25	78.25	-41	56.25	37.25	74	54	-17.75	-16.75
17080	V	96.24	77.33	-41.1	55.14	36.23	74	54	-18.86	-17.77
4880	H	94.72	75.62	-31.6	63.12	44.02	74	54	-10.88	-9.98
7320	H	95.13	75.75	-35.5	59.63	40.25	74	54	-14.37	-13.75
9760	H	96.42	77.63	-38.3	58.12	39.33	74	54	-15.88	-14.67
12200	H	95.35	76.45	-39	56.35	37.45	74	54	-17.65	-16.55
14640	H	98.17	79.58	-42	56.17	37.58	74	54	-17.83	-16.42
17080	H	96.76	77.75	-41.5	55.26	36.25	74	54	-18.74	-17.75

Other harmonics emissions are lower than 20dB below the allowable limit.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) Measuring frequencies from 1GHz to 25GHz.

Operation Mode:	TX Mode (CH39: 2480MHz)	Test Date :	2022-02-17
Frequency Range:	1-25GHz	Temperature :	25℃
Test Result:	PASS	Humidity :	58 %
Measured Distance:	3m	Test By:	Best

Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4960	V	96.22	76.15	-32.3	63.92	43.85	74	54	-10.08	-10.15
7440	V	98.22	78.23	-37.2	61.02	41.03	74	54	-12.98	-12.97
9920	V	98.12	79.31	-39.8	58.32	39.51	74	54	-15.68	-14.49
12400	V	96.71	77.75	-40.5	56.21	37.25	74	54	-17.79	-16.75
14880	V	96.71	77.56	-41	55.71	36.56	74	54	-18.29	-17.44
17360	V	96.42	77.54	-41.1	55.32	36.44	74	54	-18.68	-17.56
4960	H	95.12	75.12	-31.6	63.52	43.52	74	54	-10.48	-10.48
7440	H	96.45	75.75	-35.5	60.95	40.25	74	54	-13.05	-13.75
9920	H	96.71	77.82	-38.3	58.41	39.52	74	54	-15.59	-14.48
12400	H	95.32	76.14	-39	56.32	37.14	74	54	-17.68	-16.86
14880	H	98.32	78.72	-42	56.32	36.72	74	54	-17.68	-17.28
17360	H	96.73	77.75	-41.5	55.23	36.25	74	54	-18.77	-17.75

Other harmonics emissions are lower than 20dB below the allowable limit.

Note: (1) All Readings are Peak Value and AV.
(2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
(3) The average measurement was not performed when the peak measured data under the limit of average detection.
(4) Measuring frequencies from 1GHz to 25GHz.

7.6 Radiated Measurement Photos:





8. 6dB Bandwidth Measurement

8.1 Measurement Procedure

The EUT was operating in Bluetooth mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-13
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-13
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-13

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

8.4 Limit

The minimum 6dB bandwidth shall be at least 500kHz.

8.5 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	2022-02-17
Test By:	Best	Temperature :	24 ℃
Test Result:	PASS	Humidity :	53 %

Channel number	Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)
00	2402	706	>500
19	2440	689	>500
39	2480	686	>500

6dBNVNT BLE 2402MHz Ant1



6dBNVNT BLE 2440MHz Ant1



6dBNVNT BLE 2480MHz Ant1



9. MAXIMUM PEAK OUTPUT POWER TEST

9.1 Measurement Procedure

a. The Transmitter output (antenna port) was connected to the spectrum Analyzer.
b. Turn on the EUT and then record the peak power value.
c. Repeat above procedures on all channels needed to be tested.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-13
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-13
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-13

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

9.4 Peak Power output limit

The maximum peak power shall be less 1Watt.

9.5 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	2022-02-17
Test By:	Best	Temperature :	24 ℃
Test Result:	PASS	Humidity :	53 %

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
0	2402	0.11	1.026	1000	PASS
19	2440	1.78	1.507	1000	PASS
39	2480	2.55	1.799	1000	PASS

Power NVNT BLE 2402MHz Ant1



Power NVNT BLE 2440MHz Ant1



Power NVNT BLE 2480MHz Ant1



10. Power Spectral Density Measurement

10.1Measurement Procedure

The EUT was operating in Bluetooth mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-13
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-13
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-13

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

10.4 Measurement Procedure

10.4.1 The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

10.4.2. Set to the maximum power setting and enable the EUT transmit continuously.

10.4.3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)

10.4.4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.

10.4.5. Measure and record the results in the test report.

10.4.6. The Measured power density (dBm)/ 100KHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

10.5 Measurement Results:

The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	3KHz
VB	10KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	2022-02-17
Test By:	Best	Temperature :	24 ℃
Test Result:	PASS	Humidity :	53 %

Channel number	Channel frequency (MHz)	Measurement level (dBm) PSD/3kHz	Required Limit (dBm/3kHz)	Pass/Fail
00	2402	-15.65	8	PASS
19	2440	-13.81	8	PASS
39	2480	-12.94	8	PASS

Note:
1. Measured power density(dBm) has offset with cable loss.
2. The measured power density(dBm)/100KHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.

PSD NVNT BLE 2402MHz Ant1



PSD NVNT BLE 2440MHz Ant1



PSD NVNT BLE 2480MHz Ant1



11. Band EDGE test

11.1 Measurement Procedure

For Conducted Test

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

For Radiated emission Test

The EUT was placed on a styrofoam table which is 1.5m above ground plane.

The measurement procedure at the ban edges was simplified by performing the measurement in just one plot. Both, the in-band-emission and the unwanted emission were be encompassed by the span. After trace stabilization, the maximum peak was be determined by a peak detector and the value was marked by an appropriate limit line. The second limit line, which is 20dB below the first, marks the limit for the emissions in the unrestricted band. A maximum-peak-detector marks the highest emission in the unrestricted band next to the band edge.

The measurements were performed at the lower end of the 2.4GHz band.

Use the following spectrum analyzer settings:

For Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

For Non-Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 100KHz, video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

11.2 Test SET-UP (Block Diagram of Configuration)

For Conducted Test



For Radiated emission Test



11.3 Measurement Equipment Used:

For Conducted Test

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	CALIBRATED UNTIL
Spectrum Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-13
Coaxial Cable	Gigalink Microwave	ZT40	19022092	2022-11-13
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	2022-11-13

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

For Radiated emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Signal Analyzer	Rohde & Schwarz	FSV40	US40240623	2022-11-13
2	Broadband RF Power Amplifier	AEROFLEX	AEROFLEX100KHz-40GHz	J1013130524001	2022-11-13
3	DRG Horm Antenna	A.H.SYSTEMS	SAS-574	J2031090612123	2022-11-13
4	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92J-2m	N/A	2022-05-22

5	RF Cable	Gigalink Microwave	ZT40-2.92J-2.92J-0.3m	N/A	2022-05-22

11.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	2022-02-17
Test By:	Best	Temperature :	24 ℃
Test Result:	PASS	Humidity :	53 %

1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2398.7	-0.18	-46.66	46.48	>20dBc
2484	2.44	-54.75	57.19	>20dBc


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 30 dB
SWT 5 ms
VBW 300 kHz
Mode Auto FFT
1Pk Max
D3[1]
M1[1]
M1
-46.44 dB
-3.3140 MHz
-0.18 dBm
2.4020120 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
D3
D2
CF 2.4 GHz
691 pts
Span 10.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.402012 GHz -0.18 dBm
D2 M1 1 -2.0116 MHz -44.48 dB
D3 M1 1 -3.314 MHz -46.44 dB
Measuring...


Spectrum
Ref Level 10.00 dBm
RBW 100 kHz
Att 30 dB
SWT 5 ms
VBW 300 kHz
Mode Auto FFT
1Pk Max
M1
D3[1]
M1[1]
-57.19 dB
3.9940 MHz
2.44 dBm
2.4799980 GHz
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
-80 dBm
D2
D3
CF 2.4835 GHz
691 pts
Span 10.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.479998 GHz 2.44 dBm
D2 M1 1 3.5022 MHz -54.43 dB
D3 M1 1 3.994 MHz -57.19 dB
Measuring...

2. Radiated emission Test



Site ANCI 843.3 Polarization: ***Horizontal*** Temperature: 26.5(C)

Limit: FCC Part 15 C 3m Above1G(Peak) Power: Battrery 12V Humidity: 60.6 %

Mode: TX2402

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1		2328.368	51.89	-5.23	46.66	74.00	-27.34	peak			
2		2390.000	51.24	-4.82	46.42	74.00	-27.58	peak			
3		2400.000	63.20	-4.75	58.45	74.00	-15.55	peak			
4	*	2400.000	48.15	-4.75	43.40	54.00	-10.60	AVG			

*:Maximum data x:Over limit !:over margin 〈Reference Only



Site ANCI 843.3 Polarization: *Vertical* Temperature: 26.5(C)

Limit: FCC Part 15 C 3m Above1G(Peak) Power: Battrery 12V Humidity: 60.6 %

Mode: TX2402

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
									Battery 3.7V		
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1		2352.998	52.49	-5.07	47.42	74.00	-26.58	peak			
2		2390.000	51.68	-4.82	46.86	74.00	-27.14	peak			
3		2400.000	68.00	-4.75	63.25	74.00	-10.75	peak			
4	*	2400.000	51.96	-4.75	47.21	54.00	-6.79	AVG			

*:Maximum data x:Over limit !:over margin 〈Reference Only



Site ANCI 843.3 Polarization: *Horizontal* Temperature: 26.5(C)

Limit: FCC Part 15 C 3m Above1G(Peak) Power: Battrery 12V Humidity: 60.6 %

Mode: TX2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1		2483.500	50.05	-4.19	45.86	74.00	-28.14	peak			
2	*	2485.883	51.66	-4.18	47.48	74.00	-26.52	peak			
3		2492.882	51.08	-4.14	46.94	74.00	-27.06	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Onl



Site ANCI 843.3 Polarization: *Vertical* Temperature: 26.5(C)

Limit: FCC Part 15 C 3m Above1G(Peak) Power: Battrery 12V Humidity: 60.6 %

Mode: TX2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector	cm	degree	Comment
1		2483.500	49.64	-4.19	45.45	74.00	-28.55	peak			
2	*	2487.631	52.35	-4.16	48.19	74.00	-25.81	peak			
3		2493.232	51.90	-4.14	47.76	74.00	-26.24	peak			

*:Maximum data x:Over limit !:over margin 〈Reference Only

12 Antenna Application

12.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:
Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

12.2 Result

The EUT'S antenna is an PCB antenna. The antenna's gain is 0dBi and meets the requirement.

13 Photos of EUT








T6. 3A 250V ac





----------The end of report----------