

FCC Test Report

Applicant : Shenzhen Yincheng Technology Co.,Ltd

Address : STE101, 201, 301, 401, Building 1,1st
Industrial Zone, Bitou Community, Songgang
Street, Bao'an District, Shenzhen, China

Product Name : Keyboard

Report Date : Aug. 15, 2023

Shenzhen Anbotek Compliance Laboratory Limited



Contents

1. General Information	6
1.1. Client Information	6
1.2. Description of Device (EUT)	6
1.3. Auxiliary Equipment Used During Test	7
1.4. Description of Test Configuration	7
1.5. Description Of Test Setup	8
1.6. Test Equipment List	9
1.7. Measurement Uncertainty	10
1.8. Description of Test Facility	10
2. Summary of Test Results	11
3. Conducted Emission Test	12
3.1. Test Standard and Limit	12
3.2. Test Setup	12
3.3. Test Procedure	12
3.4. Test Data	12
4. Radiation Spurious Emission and Band Edge	15
4.1. Test Standard and Limit	15
4.2. Test Setup	15
4.3. Test Procedure	16
4.4. Test Data	17
5. Maximum Peak Output Power Test	25
5.1. Test Standard and Limit	25
5.2. Test Setup	25
5.3. Test Procedure	25
5.4. Test Data	25
6. 6DB Occupy Bandwidth Test	26
6.1. Test Standard and Limit	26
6.2. Test Setup	26
6.3. Test Procedure	26
6.4. Test Data	26
7. Power Spectral Density Test	27
7.1. Test Standard and Limit	27
7.2. Test Setup	27
7.3. Test Procedure	27
7.4. Test Data	27
8. 100kHz Bandwidth of Frequency Band Edge Requirement	28
8.1. Test Standard and Limit	28
8.2. Test Setup	28



8.3. Test Procedure.....	28
8.4. Test Data	28
9. Antenna Requirement.....	29
9.1. Test Standard and Requirement.....	29
9.2. Antenna Connected Construction.....	29
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	30
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	30
APPENDIX III -- INTERNAL PHOTOGRAPH.....	30



TEST REPORT

Applicant : Shenzhen Yinchon Technology Co.,Ltd
Manufacturer : Shenzhen Yinchon Technology Co.,Ltd
Product Name : Keyboard
Model No. : MX108, MX104, MX98, MX87, MX84, MX82, MX68, MX61
Trade Mark : N/A
Rating(s) : Input: 5V $\pm$ 1A (with DC 3.7V, 300mAh battery inside)

Test Standard(s) : FCC Part15 Subpart C, Section 15.247

Test Method(s) : ANSI C63.10: 2020, KDB 558074 D01 15.247 Meas Guidance v05r02

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Receipt

Jul. 12, 2023

Date of Test

Jul. 12~ 21, 2023

Prepared By

Ella Liang

(Ella Liang)

Approved & Authorized Signer

Kingkong Jin

(Kingkong Jin)



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Aug. 15, 2023



1. General Information

1.1. Client Information

Applicant	:	Shenzhen Yinchun Technology Co.,Ltd
Address	:	STE101, 201, 301, 401, Building 1,1st Industrial Zone, Bitou Community, Songgang Street, Bao'an District, Shenzhen, China
Manufacturer	:	Shenzhen Yinchun Technology Co.,Ltd
Address	:	STE101, 201, 301, 401, Building 1,1st Industrial Zone, Bitou Community, Songgang Street, Bao'an District, Shenzhen, China
Factory	:	Shenzhen Yinchun Technology Co.,Ltd
Address	:	STE101, 201, 301, 401, Building 1,1st Industrial Zone, Bitou Community, Songgang Street, Bao'an District, Shenzhen, China

1.2. Description of Device (EUT)

Product Name	:	Keyboard
Model No.	:	MX108, MX104, MX98, MX87, MX84, MX82, MX68, MX61 (Note: All samples are the same except the model number, so we prepare "MX108" for test only.)
Trade Mark	:	N/A
Test Power Supply	:	DC 5V via PC input AC 120V,60Hz/ DC 3.7V battery inside
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Adapter	:	N/A

RF Specification

Operation Mode	:	☒ DSSS ☐ FHSS
Operation Frequency	:	2405~2470MHz
Number of Channel	:	16 Channels
Modulation Type	:	GFSK
Antenna Type	:	PCB antenna
Antenna Gain(Peak)	:	-1.52dBi (Provided by customer)

Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



1.3. Auxiliary Equipment Used During Test

Description	Rating(s)
acer	Model: N19W3 Input: 19V/3.42A;20V/3.25A CMIIT ID:2020AJ3862
Adapter	Model: PA-1650-58 Input: AC100-240~50/60Hz, 1.6A CMIIT KP06503020

1.4. Description of Test Configuration

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	2405	5	2422	9	2440	13	2460		
2	2409	6	2426	10	2445	14	2465		
3	2413	7	2430	11	2450	15	2467		
4	2417	8	2435	12	2455	16	2470		


Note:

1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.
2. EUT was tested with 2405MHz, 2440MHz and 2470MHz.




1.5. Description Of Test Setup

CE



RE



1.6. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 23, 2022	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040DT001	Jul. 05, 2023	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 13, 2022	1 Year
4.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 23, 2022	1 Year
5.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2022	1 Year
6.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Oct. 13, 2022	1 Year
7.	EMI Preamplifier	SKET Electronic	LNPA-0118G -45	SKET-PA-002	Oct. 13, 2022	1 Year
8.	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	Oct. 16, 2022	3 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	Oct. 23, 2022	3 Year
10.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Oct. 23, 2022	1 Year
11.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Oct. 23, 2022	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Oct. 23, 2022	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY53280032	Oct. 13, 2022	1 Year
15.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Oct. 13, 2022	1 Year
16.	Signal Generator	Agilent	E4421B	MY41000743	Oct. 13, 2022	1 Year
17.	DC Power Supply	IVYTECH	IV3605	1804D360510	Oct. 22, 2022	1 Year
18.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Oct. 19, 2022	1 Year
19.	Power Meter	Agilent	N1914A	MY50001102	Oct.26, 2022	1 Year



1.7. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.8dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.78dB; 6G-18GHz: 4.88dB 18G-40GHz: 5.68dB
This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.203/15.247(c)	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209	Spurious Emission	PASS
15.247(b)(3)	Conducted Peak Output Power	PASS
15.247(a)(2)	6dB Occupied Bandwidth	PASS
15.247(e)	Power Spectral Density	PASS
15.247(d)	Band Edge	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10: 2020 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

During the test, pre-scan all modes, only the worst case is recorded in the report.


AC conducted emission pre-test at both at AC 120V/60Hz and AC 240V/60Hz modes, recorded worst case AC 120V/60Hz.

Please to see the following pages.



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2470MHz
Test Specification: DC 5V via PC input AC 120V,60Hz
Comment: Live Line
Temp.(°C)/Hum.(%RH): 22.1°C/52%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1499	37.70	19.82	57.52	66.00	-8.48	QP	
2	0.1980	37.24	19.82	57.06	63.69	-6.63	QP	
3	0.1980	28.81	19.82	48.63	53.69	-5.06	AVG	
4	0.2987	32.98	19.84	52.82	60.28	-7.46	QP	
5	0.3820	17.42	19.81	37.23	48.23	-11.00	AVG	
6	0.4259	25.69	19.82	45.51	57.33	-11.82	QP	
7	0.4858	12.52	19.85	32.37	46.24	-13.87	AVG	
8	0.5420	23.78	19.86	43.64	56.00	-12.36	QP	
9	0.6219	11.81	19.87	31.68	46.00	-14.32	AVG	
10	1.1733	12.25	19.85	32.10	46.00	-13.90	AVG	
11	1.2740	22.87	19.86	42.73	56.00	-13.27	QP	
12	1.5420	12.25	19.85	32.10	46.00	-13.90	AVG	



Conducted Emission Test Data

Test Site: 1# Shielded Room
Operating Condition: 2470MHz
Test Specification: DC 5V via PC input AC 120V,60Hz
Comment: Neutral Line
Temp.(°C)/Hum.(%RH): 22.1°C/52%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1874	28.87	19.82	48.69	54.15	-5.46	AVG	
2	0.1912	38.12	19.82	57.94	63.98	-6.04	QP	
3	0.2508	35.07	19.83	54.90	61.73	-6.83	QP	
4	0.3578	29.44	19.82	49.26	58.78	-9.52	QP	
5	0.3659	17.22	19.82	37.04	48.59	-11.55	AVG	
6	0.6300	22.61	19.87	42.48	56.00	-13.52	QP	
7	0.7780	13.07	19.87	32.94	46.00	-13.06	AVG	
8	1.0100	21.89	19.86	41.75	56.00	-14.25	QP	
9	1.3850	11.56	19.86	31.42	46.00	-14.58	AVG	
10	1.5220	21.97	19.85	41.82	56.00	-14.18	QP	
11	1.8020	9.38	19.86	29.24	46.00	-16.76	AVG	
12	2.1459	6.50	19.85	26.35	46.00	-19.65	AVG	



4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1)The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup




Figure 1. Below 30MHz






Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.



For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep - auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep - auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector = Quasi-Peak, Trace mode = Max hold, Sweep - auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 3MHz, Detector = Peak, Trace mode = Max hold, Sweep - auto couple.

For average measurement:

–VBW = 3*RBW, Detector = RMS, When duty cycle is no less than 98 percent

–VBW = 3*RBW, Detector = RMS, When duty cycle is less than 98 percent and duty cycle is constant, average = peak level + correction factor (20log(duty cycle)).

–VBW ≥ 1/T, when duty cycle is less than 98 percent and duty cycle is not constant, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.4 duty cycle.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.


The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, pre-scan all the modes, only the worst case is recorded in the report.



Test Results (30~1000MHz)

Test Mode: 2470MHz
Power Source: DC 3.7V battery inside
Polarization: Horizontal
Temp.(°C)/Hum.(%RH): 22.5°C/50%RH




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	220.5205	42.89	-21.73	21.16	46.00	-24.84	QP	
2	224.4209	42.12	-21.66	20.46	46.00	-25.54	QP	
3	490.9598	46.05	-15.75	30.30	46.00	-15.70	QP	
4	524.3242	45.44	-15.16	30.28	46.00	-15.72	QP	
5	799.3300	38.79	-10.19	28.60	46.00	-17.40	QP	
6	842.4988	40.91	-9.60	31.31	46.00	-14.69	QP	



Test Results (30~1000MHz)

Test Mode: 2470MHz
Power Source: DC 3.7V battery inside
Polarization: Vertical
Temp.(°C)/Hum.(%RH): 22.5°C/50%RH



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Remark
1	46.6664	35.16	-21.48	13.68	40.00	-26.32	QP	
2	107.2747	34.77	-21.97	12.80	43.50	-30.70	QP	
3	148.1161	37.56	-24.93	12.63	43.50	-30.87	QP	
4	377.9211	36.90	-18.24	18.66	46.00	-27.34	QP	
5	555.5555	42.94	-14.50	28.44	46.00	-17.56	QP	
6	842.4988	39.70	-9.60	30.10	46.00	-15.90	QP	



Test Results (1GHz-25GHz)

Test channel: Lowest

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4810.00	27.50	15.27	42.77	74.00	-31.23	Vertical
7215.00	28.95	18.09	47.04	74.00	-26.96	Vertical
9620.00	29.76	23.76	53.52	74.00	-20.48	Vertical
12025.00	*			74.00		Vertical
14430.00	*			74.00		Vertical
4810.00	27.95	15.27	43.22	74.00	-30.78	Horizontal
7215.00	29.07	18.09	47.16	74.00	-26.84	Horizontal
9620.00	28.71	23.76	52.47	74.00	-21.53	Horizontal
12025.00	*			74.00		Horizontal
14430.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4810.00	16.88	15.27	32.15	54.00	-21.85	Vertical
7215.00	17.98	18.09	36.07	54.00	-17.93	Vertical
9620.00	18.78	23.76	42.54	54.00	-11.46	Vertical
12025.00	*			54.00		Vertical
14430.00	*			54.00		Vertical
4810.00	16.30	15.27	31.57	54.00	-22.43	Horizontal
7215.00	18.13	18.09	36.22	54.00	-17.78	Horizontal
9620.00	18.02	23.76	41.78	54.00	-12.22	Horizontal
12025.00	*			54.00		Horizontal
14430.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test channel: Middle

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	27.52	15.42	42.94	74.00	-31.06	Vertical
7320.00	28.80	18.02	46.82	74.00	-27.18	Vertical
9760.00	28.77	23.80	52.57	74.00	-21.43	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	27.65	15.42	43.07	74.00	-30.93	Horizontal
7320.00	29.06	18.02	47.08	74.00	-26.92	Horizontal
9760.00	28.41	23.80	52.21	74.00	-21.79	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	
4880.00	16.61	15.42	32.03	54.00	-21.97	polarization
7320.00	18.08	18.02	36.10	54.00	-17.90	Vertical
9760.00	18.64	23.80	42.44	54.00	-11.56	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	16.21	15.42	31.63	54.00	-22.37	Vertical
7320.00	17.69	18.02	35.71	54.00	-18.29	Horizontal
9760.00	18.53	23.80	42.33	54.00	-11.67	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal



Test Results (1GHz-25GHz)

Test channel: Highest

Peak value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4940.00	27.79	15.58	43.37	74.00	-30.63	Vertical
7410.00	28.81	17.93	46.74	74.00	-27.26	Vertical
9880.00	29.32	23.83	53.15	74.00	-20.85	Vertical
12350.00	*			74.00		Vertical
14820.00	*			74.00		Vertical
4940.00	27.72	15.58	43.30	74.00	-30.70	Horizontal
7410.00	29.09	17.93	47.02	74.00	-26.98	Horizontal
9880.00	29.09	23.83	52.92	74.00	-21.08	Horizontal
12350.00	*			74.00		Horizontal
14820.00	*			74.00		Horizontal

Average value:

Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4940.00	17.73	15.58	33.31	54.00	-20.69	Vertical
7410.00	19.09	17.93	37.02	54.00	-16.98	Vertical
9880.00	19.19	23.83	43.02	54.00	-10.98	Vertical
12350.00	*			54.00		Vertical
14820.00	*			54.00		Vertical
4940.00	17.65	15.58	33.23	54.00	-20.77	Horizontal
7410.00	19.06	17.93	36.99	54.00	-17.01	Horizontal
9880.00	18.43	23.83	42.26	54.00	-11.74	Horizontal
12350.00	*			54.00		Horizontal
14820.00	*			54.00		Horizontal

Remark:


1.Result =Reading + Factor

2. "*" means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.




Radiated Band Edge:

Test channel: Lowest



Test channel: Highest



Average:

Test Channel	Peak Value (dBuV/m)	Correction factor	Average Value (dBuV/m)	Limit (dBuV/m)	Polarization	Verdict
CH01	39.932	0.00	39.932	54.00	Vertical	Pass
	40.403	0.00	40.403	54.00	Horizontal	Pass
CH16	40.931	0.00	40.931	54.00	Vertical	Pass
	41.152	0.00	41.152	54.00	Horizontal	Pass

Remark:

1. Correction factor=20log(Duty Cycle)
2. Average Value=Peak Value+Correction factor




5. Maximum Peak Output Power Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (b)(3)
Test Limit	1W (30dBm)

5.2. Test Setup



5.3. Test Procedure

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

1. Set the RBW $\geq$ DTS bandwidth.
2. Set the VBW $\geq 3 \times$ RBW.
3. Set the span $\geq 3 \times$ RBW.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

5.4. Test Data

Pass

Please refer to Appendix C of the Appendix Test Data.

Additional test for duty cycle.

Please refer to Appendix G of the Appendix Test Data.




6. 6DB Occupy Bandwidth Test

6.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (a)(2)
Test Limit	≥500kHz

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
RBW = 100kHz, VBW≥3*RBW
Detector= Peak
Trace mode= Max hold.
Sweep- auto couple.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

6.4. Test Data

Pass

Please refer to Appendix A of the Appendix Test Data.




7. Power Spectral Density Test

7.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (e)
Test Limit	8dBm/3KHz

7.2. Test Setup



7.3. Test Procedure

1. Place the EUT on the table and set it in transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 30kHz, VBW $\geq 3 \times$ RBW, Span = 1.5xDTSS BW
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

7.4. Test Data

Pass

Please refer to Appendix D of the Appendix Test Data.




8. 100kHz Bandwidth of Frequency Band Edge Requirement

8.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.247 (d)
Test Limit	In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

8.2. Test Setup



8.3. Test Procedure

Using the following spectrum analyzer setting:

1. Set the RBW = 100KHz.
2. Set the VBW = 300KHz.
3. Sweep time = auto couple.
4. Detector function = peak.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.

8.4. Test Data

Pass

Please refer to Appendix E&F of the Appendix Test Data.



9. Antenna Requirement

9.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203 /247(c)
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 2) 15.247(c) (1)(i) requirement: Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

9.2. Antenna Connected Construction

The antenna is a PCB antenna which permanently attached, and the best case gain of the antenna is -1.52 dBi . It complies with the standard requirement.



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

