

# TEST REPORT

**Applicant:** Dongguan Antaina Vision Electronic Technology Co., Ltd.

**Address of Applicant:** Floor 12, Building 209,Xinhong Road, Lin Village, Tangxia Town, Dongguan City, Guangdong

**Manufacturer:** Dongguan Antaina Vision Electronic Technology Co., Ltd.

**Address of Manufacturer:** Floor 12, Building 209,Xinhong Road, Lin Village, Tangxia Town, Dongguan City, Guangdong

**Factory:** Dongguan Antaina Vision Electronic Technology Co., Ltd.

**Address of Factory:** Floor 12, Building 209,Xinhong Road, Lin Village, Tangxia Town, Dongguan City, Guangdong

**Equipment Under Test (EUT)**

Product Name: 2.4GHz Digital Camera

Model No.: RC-005WS

Add. Model No.: RM-7020, RM-7050WS, RM-7050TWS, RM-7051WS, LK5, R7, U13, Y31, K16, RC-006WS, RC-002WS, RC-019WS

Trade Mark: 

**FCC ID:** 2A4KR-7020ATN

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247

**Date of sample receipt:** 2022-03-01


**Date of Test:** 2022-03-02 to 2022-03-10

**Date of report issued:** 2022-03-15

**Test Result :** PASS \*

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Luo


Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

## 2 Version

| Version No. | Date       | Description |
|-------------|------------|-------------|
| 00          | 2022-03-15 | Original    |
|             |            |             |
|             |            |             |
|             |            |             |
|             |            |             |

Prepared By:




Date:

2022-03-15

Project Engineer

Check By:



Date:

2022-03-15

Reviewer

## 3 Contents

Page

|       |                                                  |    |
|-------|--------------------------------------------------|----|
| 1     | COVER PAGE .....                                 | 1  |
| 2     | VERSION .....                                    | 2  |
| 3     | CONTENTS .....                                   | 3  |
| 4     | TEST SUMMARY .....                               | 4  |
| 4.1   | MEASUREMENT UNCERTAINTY .....                    | 4  |
| 5     | GENERAL INFORMATION .....                        | 5  |
| 5.1   | GENERAL DESCRIPTION OF EUT .....                 | 5  |
| 5.2   | TEST MODE .....                                  | 7  |
| 5.3   | TEST FACILITY .....                              | 7  |
| 5.4   | TEST LOCATION .....                              | 7  |
| 5.5   | OTHER INFORMATION REQUESTED BY THE CUSTOMER..... | 7  |
| 5.6   | DESCRIPTION OF SUPPORT UNITS .....               | 7  |
| 5.7   | DEVIATION FROM STANDARDS .....                   | 7  |
| 5.8   | ABNORMALITIES FROM STANDARD CONDITIONS .....     | 7  |
| 5.9   | ADDITIONAL INSTRUCTIONS .....                    | 7  |
| 6     | TEST INSTRUMENTS LIST .....                      | 8  |
| 7     | TEST RESULTS AND MEASUREMENT DATA.....           | 10 |
| 7.1   | ANTENNA REQUIREMENT.....                         | 10 |
| 7.2   | CONDUCTED EMISSIONS .....                        | 11 |
| 7.3   | CONDUCTED PEAK OUTPUT POWER.....                 | 12 |
| 7.4   | 20dB EMISSION BANDWIDTH .....                    | 15 |
| 7.5   | CARRIER FREQUENCIES SEPARATION .....             | 18 |
| 7.6   | HOPPING CHANNEL NUMBER .....                     | 21 |
| 7.7   | DWELL TIME.....                                  | 24 |
| 7.8   | BAND EDGE .....                                  | 27 |
| 7.8.1 | Conducted Emission Method .....                  | 27 |
| 7.8.2 | Radiated Emission Method .....                   | 29 |
| 7.9   | SPURIOUS EMISSION.....                           | 34 |
| 7.9.1 | Conducted Emission Method .....                  | 34 |
| 7.9.2 | Radiated Emission Method .....                   | 37 |
| 8     | TEST SETUP PHOTO .....                           | 48 |
| 9     | EUT CONSTRUCTIONAL DETAILS .....                 | 48 |

## 4 Test Summary

| Test Item                        | Section            | Result |
|----------------------------------|--------------------|--------|
| Antenna Requirement              | 15.203/15.247 (c)  | Pass   |
| AC Power Line Conducted Emission | 15.207             | NA     |
| Conducted Peak Output Power      | 15.247 (b)(1)      | Pass   |
| 20dB Occupied Bandwidth          | 15.247 (a)(1)      | Pass   |
| Carrier Frequencies Separation   | 15.247 (a)(1)      | Pass   |
| Hopping Channel Number           | 15.247 (a)(1)(iii) | Pass   |
| Dwell Time                       | 15.247 (a)(1)(iii) | Pass   |
| Radiated Emission                | 15.205/15.209      | Pass   |
| Band Edge                        | 15.247(d)          | Pass   |

Pass: The EUT complies with the essential requirements in the standard.

Remark : Test according to ANSI C63.10:2013.

### 4.1 Measurement Uncertainty

| Test Item                        | Frequency Range | Measurement Uncertainty | Notes |
|----------------------------------|-----------------|-------------------------|-------|
| Radiated Emission                | 9kHz-30MHz      | 3.1dB                   | (1)   |
| Radiated Emission                | 30MHz-200MHz    | 3.8039dB                | (1)   |
| Radiated Emission                | 200MHz-1GHz     | 3.9679dB                | (1)   |
| Radiated Emission                | 1GHz-18GHz      | 4.29dB                  | (1)   |
| Radiated Emission                | 18GHz-40GHz     | 3.30dB                  | (1)   |
| AC Power Line Conducted Emission | 0.15MHz ~ 30MHz | 3.44dB                  | (1)   |

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

## 5 General Information

### 5.1 General Description of EUT

|                        |                                                                                                    |
|------------------------|----------------------------------------------------------------------------------------------------|
| Product Name:          | 2.4GHz Digital Camera                                                                              |
| Model No.:             | RC-005WS                                                                                           |
| Serial No.:            | RM-7020, RM-7050WS, RM-7050TWS,<br>RM-7051WS, LK5, R7, U13, Y31, K16, RC-006WS, RC-002WS, RC-019WS |
| Hardware Version:      | DV7209T(V1.4)                                                                                      |
| Software Version:      | DV7209T(V1.4)                                                                                      |
| Test sample(s) ID:     | GTSL202203000004-1                                                                                 |
| Sample(s) Status       | Engineer sample                                                                                    |
| Operation Frequency:   | 2408 ~ 2478MHz                                                                                     |
| Channel numbers:       | 19                                                                                                 |
| Modulation technology: | QPSK                                                                                               |
| Antenna Type:          | RP-SMA                                                                                             |
| Antenna gain:          | 3.0dBi                                                                                             |
| Power supply:          | Input: DC10V-32V                                                                                   |

| Operation Frequency each of channel |                 |         |                 |         |                 |         |                 |
|-------------------------------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel                             | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 0                                   | 2408            | 5       | 2425            | 10      | 2448            | 15      | 2468            |
| 1                                   | 2411            | 6       | 2428            | 11      | 2452            | 16      | 2472            |
| 2                                   | 2415            | 7       | 2432            | 12      | 2455            | 17      | 2475            |
| 3                                   | 2418            | 8       | 2442            | 13      | 2458            | 18      | 2478            |
| 4                                   | 2422            | 9       | 2445            | 14      | 2465            | 19      |                 |

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

| Channel             | Frequency |
|---------------------|-----------|
| The lowest channel  | 2408MHz   |
| The middle channel  | 2445MHz   |
| The Highest channel | 2478MHz   |

## 5.2 Test mode

|                   |                                    |
|-------------------|------------------------------------|
| Transmitting mode | Keep the EUT in transmitting mode. |
|-------------------|------------------------------------|

## 5.3 Test Facility

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> <li>• <b>FCC—Registration No.: 381383</b><br/>Designation Number: CN5029<br/>Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.</li> <li>• <b>IC —Registration No.: 9079A</b><br/>CAB identifier: CN0091<br/>The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing</li> <li>• <b>NVLAP (LAB CODE:600179-0)</b><br/>Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).</li> </ul> |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## 5.4 Test Location

|                                                                                                                                                                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| All other tests were performed at:                                                                                                                                                                                                                            |
| <p>Global United Technology Services Co., Ltd.<br/>Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102<br/>Tel: 0755-27798480<br/>Fax: 0755-27798960</p> |

## 5.5 Other Information Requested by the Customer

|       |
|-------|
| None. |
|-------|

## 5.6 Description of Support Units

|      |
|------|
| None |
|------|

## 5.7 Deviation from Standards

|       |
|-------|
| None. |
|-------|

## 5.8 Abnormalities from Standard Conditions

|       |
|-------|
| None. |
|-------|

## 5.9 Additional Instructions

|                   |                                               |
|-------------------|-----------------------------------------------|
| Test Software     | Special test command provided by manufacturer |
| Power level setup | Default                                       |

## 6 Test Instruments list

| Radiated Emission: |                                     |                                |                             |               |                     |                         |
|--------------------|-------------------------------------|--------------------------------|-----------------------------|---------------|---------------------|-------------------------|
| Item               | Test Equipment                      | Manufacturer                   | Model No.                   | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                  | 3m Semi- Anechoic Chamber           | ZhongYu Electron               | 9.2(L)*6.2(W)* 6.4(H)       | GTS250        | July. 02 2020       | July. 01 2025           |
| 2                  | Control Room                        | ZhongYu Electron               | 6.2(L)*2.5(W)* 2.4(H)       | GTS251        | N/A                 | N/A                     |
| 3                  | EMI Test Receiver                   | Rohde & Schwarz                | ESU26                       | GTS203        | June. 24 2021       | June. 23 2022           |
| 4                  | BiConiLog Antenna                   | SCHWARZBECK<br>MESS-ELEKTRONIK | VULB9163                    | GTS214        | June. 24 2021       | June. 23 2022           |
| 5                  | Double -ridged waveguide horn       | SCHWARZBECK<br>MESS-ELEKTRONIK | BBHA 9120 D                 | GTS208        | June. 24 2021       | June. 23 2022           |
| 6                  | Horn Antenna                        | ETS-LINDGREN                   | 3160                        | GTS217        | June. 24 2021       | June. 23 2022           |
| 7                  | EMI Test Software                   | AUDIX                          | E3                          | N/A           | N/A                 | N/A                     |
| 8                  | Coaxial Cable                       | GTS                            | N/A                         | GTS213        | June. 24 2021       | June. 23 2022           |
| 9                  | Coaxial Cable                       | GTS                            | N/A                         | GTS211        | June. 24 2021       | June. 23 2022           |
| 10                 | Coaxial cable                       | GTS                            | N/A                         | GTS210        | June. 24 2021       | June. 23 2022           |
| 11                 | Coaxial Cable                       | GTS                            | N/A                         | GTS212        | June. 24 2021       | June. 23 2022           |
| 12                 | Amplifier(100kHz-3GHz)              | HP                             | 8347A                       | GTS204        | June. 24 2021       | June. 23 2022           |
| 13                 | Amplifier(2GHz-20GHz)               | HP                             | 84722A                      | GTS206        | June. 24 2021       | June. 23 2022           |
| 14                 | Amplifier (18-26GHz)                | Rohde & Schwarz                | AFS33-18002<br>650-30-8P-44 | GTS218        | June. 24 2021       | June. 23 2022           |
| 15                 | Band filter                         | Amindeon                       | 82346                       | GTS219        | June. 24 2021       | June. 23 2022           |
| 16                 | Power Meter                         | Anritsu                        | ML2495A                     | GTS540        | June. 24 2021       | June. 23 2022           |
| 17                 | Power Sensor                        | Anritsu                        | MA2411B                     | GTS541        | June. 24 2021       | June. 23 2022           |
| 18                 | Wideband Radio Communication Tester | Rohde & Schwarz                | CMW500                      | GTS575        | June. 24 2021       | June. 23 2022           |
| 19                 | Splitter                            | Agilent                        | 11636B                      | GTS237        | June. 24 2021       | June. 23 2022           |
| 20                 | Loop Antenna                        | ZHINAN                         | ZN30900A                    | GTS534        | June. 24 2021       | June. 23 2022           |
| 21                 | Breitband hornantenne               | SCHWARZBECK                    | BBHA 9170                   | GTS579        | Oct. 17 2021        | Oct. 16 2022            |
| 22                 | Amplifier                           | TDK                            | PA-02-02                    | GTS574        | Oct. 17 2021        | Oct. 16 2022            |
| 23                 | Amplifier                           | TDK                            | PA-02-03                    | GTS576        | Oct. 17 2021        | Oct. 16 2022            |
| 24                 | PSA Series Spectrum Analyzer        | Rohde & Schwarz                | FSP                         | GTS578        | June. 24 2021       | June. 23 2022           |

| Conducted Emission |                           |                         |                      |               |                     |                         |
|--------------------|---------------------------|-------------------------|----------------------|---------------|---------------------|-------------------------|
| Item               | Test Equipment            | Manufacturer            | Model No.            | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                  | Shielding Room            | ZhongYu Electron        | 7.3(L)x3.1(W)x2.9(H) | GTS252        | May.15 2019         | May.14 2022             |
| 2                  | EMI Test Receiver         | R&S                     | ESCI 7               | GTS552        | June. 24 2021       | June. 23 2022           |
| 3                  | Coaxial Switch            | ANRITSU CORP            | MP59B                | GTS225        | June. 24 2021       | June. 23 2022           |
| 4                  | ENV216 2-L-V-NETZNACHB.DE | ROHDE&SCHWARZ           | ENV216               | GTS226        | June. 24 2021       | June. 23 2022           |
| 5                  | Coaxial Cable             | GTS                     | N/A                  | GTS227        | N/A                 | N/A                     |
| 6                  | EMI Test Software         | AUDIX                   | E3                   | N/A           | N/A                 | N/A                     |
| 7                  | Thermo meter              | KTJ                     | TA328                | GTS233        | June. 24 2021       | June. 23 2022           |
| 8                  | Absorbing clamp           | Elektronik-Feinmechanik | MDS21                | GTS229        | June. 24 2021       | June. 23 2022           |
| 9                  | ISN                       | SCHWARZBECK             | NTFM 8158            | GTS565        | June. 24 2021       | June. 23 2022           |
| 10                 | High voltage probe        | SCHWARZBECK             | TK9420               | GTS537        | July. 09 2021       | July. 08 2022           |

| RF Conducted Test: |                                                |              |                  |            |                     |                         |
|--------------------|------------------------------------------------|--------------|------------------|------------|---------------------|-------------------------|
| Item               | Test Equipment                                 | Manufacturer | Model No.        | Serial No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                  | MXA Signal Analyzer                            | Agilent      | N9020A           | GTS566     | June. 24 2021       | June. 23 2022           |
| 2                  | EMI Test Receiver                              | R&S          | ESCI 7           | GTS552     | June. 24 2021       | June. 23 2022           |
| 3                  | Spectrum Analyzer                              | Agilent      | E4440A           | GTS533     | June. 24 2021       | June. 23 2022           |
| 4                  | MXG vector Signal Generator                    | Agilent      | N5182A           | GTS567     | June. 24 2021       | June. 23 2022           |
| 5                  | ESG Analog Signal Generator                    | Agilent      | E4428C           | GTS568     | June. 24 2021       | June. 23 2022           |
| 6                  | USB RF Power Sensor                            | DARE         | RPR3006W         | GTS569     | June. 24 2021       | June. 23 2022           |
| 7                  | RF Switch Box                                  | Shongyi      | RFSW3003328      | GTS571     | June. 24 2021       | June. 23 2022           |
| 8                  | Programmable Constant Temp & Humi Test Chamber | WEWON        | WHTH-150L-40-880 | GTS572     | June. 24 2021       | June. 23 2022           |

| General used equipment: |                                 |              |           |               |                     |                         |
|-------------------------|---------------------------------|--------------|-----------|---------------|---------------------|-------------------------|
| Item                    | Test Equipment                  | Manufacturer | Model No. | Inventory No. | Cal.Date (mm-dd-yy) | Cal.Due date (mm-dd-yy) |
| 1                       | Humidity/ Temperature Indicator | KTJ          | TA328     | GTS243        | June. 24 2021       | June. 23 2022           |
| 2                       | Barometer                       | ChangChun    | DYM3      | GTS255        | June. 24 2021       | June. 23 2022           |

## 7 Test results and Measurement Data


### 7.1 Antenna requirement

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|
| <b>Standard requirement:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                     | FCC Part15 C Section 15.203 /247(c) |
| <b>15.203 requirement:</b><br>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. |                                     |
| <b>15.247(c) (1)(i) requirement:</b><br>(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.                                                                                |                                     |
| <b>EUT Antenna:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                     |
| <i>The antenna is RP-SMA, the best case gain of the antenna is 3.0dBi, reference to the appendix II for details</i>                                                                                                                                                                                                                                                                                                                                                              |                                     |

## 7.2 Conducted Emissions

|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       |              |     |           |          |
|--------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--------------|-----|-----------|----------|
| Test Requirement:                                | FCC Part15 C Section 15.207                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |       |              |     |           |          |
| Test Method:                                     | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |       |              |     |           |          |
| Test Frequency Range:                            | 150KHz to 30MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       |              |     |           |          |
| Receiver setup:                                  | RBW=9KHz, VBW=30KHz, Sweep time=auto                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       |              |     |           |          |
| Limit:                                           | Frequency range (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |       | Limit (dBuV) |     |           |          |
|                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       | Quasi-peak   |     | Average   |          |
|                                                  | 0.15-0.5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |       | 66 to 56*    |     | 56 to 46* |          |
|                                                  | 0.5-5                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |       | 56           |     | 46        |          |
|                                                  | 5-30                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       | 60           |     | 50        |          |
| * Decreases with the logarithm of the frequency. |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |       |              |     |           |          |
| Test setup:                                      | <div><p style="text-align: center;"><b>Reference Plane</b></p><p><i>Remark</i><br/>E.U.T: Equipment Under Test<br/>LISN: Line Impedance Stabilization Network<br/>Test table height=0.8m</p></div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |       |              |     |           |          |
| Test procedure:                                  | <div><div>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</div><div>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</div><div>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</div></div> |       |              |     |           |          |
| Test Instruments:                                | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |       |              |     |           |          |
| Test mode:                                       | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |       |              |     |           |          |
| Test environment:                                | Temp.:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 25 °C | Humid.:      | 52% | Press.:   | 1012mbar |
| Test voltage:                                    | NA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |       |              |     |           |          |
| Test results:                                    | NA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |       |              |     |           |          |

## 7.3 Conducted Peak Output Power


|                   |                                                                                    |
|-------------------|------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                 |
| Test Method:      | ANSI C63.10:2013                                                                   |
| Limit:            | 20.97dBm                                                                           |
| Test setup:       |  |
| Test Instruments: | Refer to section 6.0 for details                                                   |
| Test mode:        | Refer to section 5.2 for details                                                   |
| Test results:     | Pass                                                                               |

### Measurement Data


| Test channel | Peak Output Power (dBm) | Limit (dBm) | Result |
|--------------|-------------------------|-------------|--------|
| Lowest       | 16.39                   | 20.97       | Pass   |
| Middle       | 16.64                   |             |        |
| Highest      | 15.75                   |             |        |

Test plot as follows:


Lowest channel




Middle channel



## Highest channel



## 7.4 20dB Emission Bandwidth


|                   |                                                                                    |
|-------------------|------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                 |
| Test Method:      | ANSI C63.10:2013                                                                   |
| Limit:            | N/A                                                                                |
| Test setup:       |  |
| Test Instruments: | Refer to section 6.0 for details                                                   |
| Test mode:        | Refer to section 5.2 for details                                                   |
| Test results:     | Pass                                                                               |

### Measurement Data


| Test channel | 20dB Emission Bandwidth (MHz) | Result |
|--------------|-------------------------------|--------|
| Lowest       | 4.47                          | Pass   |
| Middle       | 4.48                          |        |
| Highest      | 4.48                          |        |

Test plot as follows:


Lowest channel




Middle channel



## Highest channel



## 7.5 Carrier Frequencies Separation

|                   |                                                                                     |
|-------------------|-------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)                                                  |
| Test Method:      | ANSI C63.10:2013                                                                    |
| Receiver setup:   | RBW=100KHz, VBW=300KHz, detector=Peak                                               |
| Limit:            | 0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)                        |
| Test setup:       |  |
| Test Instruments: | Refer to section 6.0 for details                                                    |
| Test mode:        | Refer to section 5.2 for details                                                    |
| Test results:     | Pass                                                                                |

### Measurement Data


| Test channel | Carrier Frequencies Separation (KHz) | Limit (KHz) | Result |
|--------------|--------------------------------------|-------------|--------|
| Lowest       | 2990                                 | 2981        | Pass   |
| Middle       | 2988                                 | 2981        | Pass   |
| Highest      | 3000                                 | 2981        | Pass   |

Note: According to section 7.4


| Mode | 20dB bandwidth (KHz)<br>(worse case) | Limit (KHz)<br>(Carrier Frequencies Separation) |
|------|--------------------------------------|-------------------------------------------------|
| QPSK | 4472                                 | 2981                                            |

Test plot as follows:


## Lowest channel




## Middle channel



## Highest channel




## 7.6 Hopping Channel Number

|                   |                                                                                    |
|-------------------|------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)(iii)                                            |
| Test Method:      | ANSI C63.10:2013                                                                   |
| Receiver setup:   | RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak           |
| Limit:            | 15 channels                                                                        |
| Test setup:       |  |
| Test Instruments: | Refer to section 6.0 for details                                                   |
| Test mode:        | Refer to section 5.2 for details                                                   |
| Test results:     | Pass                                                                               |


### Measurement Data:

| Hopping channel numbers | Limit | Result |
|-------------------------|-------|--------|
| CH0-CH18                | 19    | Pass   |


## CH0-CH06




## CH07-CH12



## CH08-CH18



## 7.7 Dwell Time

|                   |                                                                                                                                                                                                                                                                                                                                                                                               |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (a)(1)(iii)                                                                                                                                                                                                                                                                                                                                                       |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                              |
| Receiver setup:   | RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak                                                                                                                                                                                                                                                                                                                                                   |
| Limit:            | 0.4 Second                                                                                                                                                                                                                                                                                                                                                                                    |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. The E.U.T. is placed on a Non-Conducted Table, which is supported by a Ground Reference Plane. The Spectrum Analyzer is also connected to the Ground Reference Plane.</p> |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                              |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                              |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                          |

### Measurement Data

| Frequency | Ton (ms) | Dwell time(ms) | Limit(ms) | Result |
|-----------|----------|----------------|-----------|--------|
| 2408      | 7.40     | 281.20         | 400       | Pass   |
| 2445      | 7.40     | 281.20         | 400       | Pass   |
| 2478      | 7.40     | 281.20         | 400       | Pass   |

The formula as below:


2408MHz: Dwell time = Ton \* Ton times in 1s \* 0.4s \* channel numbers=7.40ms\*5\*0.4s\*19=281.2ms

2445MHz: Dwell time = Ton \* Ton times in 1s \* 0.4s \* channel numbers=7.40ms\*5\*0.4s\*19=281.2ms


2478MHz: Dwell time = Ton \* Ton times in 1s \* 0.4s \* channel numbers=7.40ms\*5\*0.4s\*19=281.2ms

Test plot as follows:


|            |         |
|------------|---------|
| Frequency: | 2408MHz |
|------------|---------|



|            |         |
|------------|---------|
| Frequency: | 2445MHz |
|------------|---------|




|            |         |
|------------|---------|
| Frequency: | 2478MHz |
|------------|---------|



## 7.8 Band Edge

### 7.8.1 Conducted Emission Method

|                   |                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                         |
| Test Method:      | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                        |
| Receiver setup:   | RBW=100kHz, VBW=300kHz, Detector=Peak                                                                                                                                                                                                                                                                                                                                                   |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p>                               |
| Test Instruments: | Refer to section6.0 for details                                                                                                                                                                                                                                                                                                                                                         |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                        |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                    |


## Test plot as follows:

Test channel:CH0

Lowest channel:2408MHz

No-hopping mode

Hopping mode




Test channel:CH18


Highest channel:2478MHz

No-hopping mode

Hopping mode



## 7.8.2 Radiated Emission Method


|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |          |                    |      |               |           |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|--------------------|------|---------------|-----------|
| Test Requirement:     | FCC Part15 C Section 15.209 and 15.205                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |          |                    |      |               |           |
| Test Method:          | ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |           |
| Test Frequency Range: | All restriction band have been tested, and 2.3GHz to 2.5GHz band is the worse case                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |                    |      |               |           |
| Test site:            | Measurement Distance: 3m                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |          |                    |      |               |           |
| Receiver setup:       | Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Detector | RBW                | VBW  | Remark        |           |
|                       | Above 1GHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Peak     | 1MHz               | 3MHz | Peak Value    |           |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Peak     | 1MHz               | 10Hz | Average Value |           |
| Limit:                | Frequency                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |          | Limit (dBuV/m @3m) |      | Remark        |           |
|                       | Above 1GHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |          | 54.00              |      | Average Value |           |
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |          | 74.00              |      | Peak Value    |           |
| Test setup:           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |          |                    |      |               |           |
| Test Procedure:       | <div>1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</div> <div>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</div> <div>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</div> <div>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</div> <div>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</div> <div>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</div> |          |                    |      |               |           |
| Test Instruments:     | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |           |
| Test mode:            | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |          |                    |      |               |           |
| Temp. / Hum.          | Temp.:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 25 °C    | Humid.:            | 52%  | Press.:       | 1 012mbar |
| Test results:         | Pass                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |          |                    |      |               |           |

## Measurement Data

Remark:


1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

|                   |                |               |          |
|-------------------|----------------|---------------|----------|
| Test channel: CH0 | Lowest-2408MHz | Polarization: | Vertical |
|-------------------|----------------|---------------|----------|




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2408.000        | 57.63          | 26.35       | 83.98        | 74.00        | 9.98        | peak     |
| 2   | 2408.000        | 6.23           | 26.35       | 32.58        | 54.00        | -21.42      | AVG      |

|                   |                |               |            |
|-------------------|----------------|---------------|------------|
| Test channel: CH0 | Lowest-2408MHz | Polarization: | Horizontal |
|-------------------|----------------|---------------|------------|




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2408.000        | 54.71          | 26.35       | 81.06        | 74.00        | 7.06        | peak     |
| 2   | 2408.000        | 12.23          | 26.35       | 38.58        | 54.00        | -15.42      | AVG      |

|                    |                 |               |          |
|--------------------|-----------------|---------------|----------|
| Test channel: CH18 | Highest-2478MHz | Polarization: | Vertical |
|--------------------|-----------------|---------------|----------|



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2478.000        | 58.12          | 26.46       | 84.58        | 74.00        | 10.58       | peak     |
| 2   | 2478.000        | 13.33          | 26.46       | 39.79        | 54.00        | -14.21      | AVG      |

|                    |                 |               |            |
|--------------------|-----------------|---------------|------------|
| Test channel: CH18 | Highest-2478MHz | Polarization: | Horizontal |
|--------------------|-----------------|---------------|------------|




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2478.000        | 52.58          | 26.46       | 79.04        | 74.00        | 5.04        | peak     |
| 2   | 2478.000        | 10.90          | 26.46       | 37.36        | 54.00        | -16.64      | AVG      |

**Remark:**


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 7.9 Spurious Emission

### 7.9.1 Conducted Emission Method


|                   |                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement: | FCC Part15 C Section 15.247 (d)                                                                                                                                                                                                                                                                                                                                                         |
| Test Method:      | ANSI C63.10:2013 and KDB558074 D01 Meas Guidance V04                                                                                                                                                                                                                                                                                                                                    |
| Limit:            | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. |
| Test setup:       |  <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.</p>                             |
| Test Instruments: | Refer to section 6.0 for details                                                                                                                                                                                                                                                                                                                                                        |
| Test mode:        | Refer to section 5.2 for details                                                                                                                                                                                                                                                                                                                                                        |
| Test results:     | Pass                                                                                                                                                                                                                                                                                                                                                                                    |

## Lowest channel




30MHz~25GHz

## Middle channel




30MHz~25GHz



## Highest channel



30MHz~25GHz

## 7.9.2 Radiated Emission Method

|                                |                                                                                      |              |         |                      |            |
|--------------------------------|--------------------------------------------------------------------------------------|--------------|---------|----------------------|------------|
| Test Requirement:              | FCC Part15 C Section 15.209                                                          |              |         |                      |            |
| Test Method:                   | ANSI C63.10:2013                                                                     |              |         |                      |            |
| Test Frequency Range:          | 9kHz to 25GHz                                                                        |              |         |                      |            |
| Test site:                     | Measurement Distance: 3m                                                             |              |         |                      |            |
| Receiver setup:                | Frequency                                                                            | Detector     | RBW     | VBW                  | Value      |
|                                | 9KHz-150KHz                                                                          | Quasi-peak   | 200Hz   | 600Hz                | Quasi-peak |
|                                | 150KHz-30MHz                                                                         | Quasi-peak   | 9KHz    | 30KHz                | Quasi-peak |
|                                | 30MHz-1GHz                                                                           | Quasi-peak   | 100KHz  | 300KHz               | Quasi-peak |
|                                | Above 1GHz                                                                           | Peak         | 1MHz    | 3MHz                 | Peak       |
|                                |                                                                                      | Peak         | 1MHz    | 10Hz                 | Average    |
| Limit:<br>(Spurious Emissions) | Frequency                                                                            | Limit (uV/m) | Value   | Measurement Distance |            |
|                                | 0.009MHz-0.490MHz                                                                    | 2400/F(KHz)  | QP      | 300m                 |            |
|                                | 0.490MHz-1.705MHz                                                                    | 24000/F(KHz) | QP      | 300m                 |            |
|                                | 1.705MHz-30MHz                                                                       | 30           | QP      | 30m                  |            |
|                                | 30MHz-88MHz                                                                          | 100          | QP      | 3m                   |            |
|                                | 88MHz-216MHz                                                                         | 150          | QP      |                      |            |
|                                | 216MHz-960MHz                                                                        | 200          | QP      |                      |            |
|                                | 960MHz-1GHz                                                                          | 500          | QP      |                      |            |
|                                | Above 1GHz                                                                           | 500          | Average |                      |            |
|                                |                                                                                      | 5000         | Peak    |                      |            |
| Test setup:                    | Below 30MHz                                                                          |              |         |                      |            |
|                                |  |              |         |                      |            |
|                                | Below 1GHz                                                                           |              |         |                      |            |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                          |  <p>Above 1GHz</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <p>Test Procedure:</p>   | <ol style="list-style-type: none"> <li>1. The EUT was placed on the top of a rotating table (0.8 meters for below 1GHz and 1.5meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol> |
| <p>Test Instruments:</p> | <p>Refer to section 5.8 for details</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <p>Test mode:</p>        | <p>Refer to section 5.2 for details</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

|               |        |       |         |     |         |           |
|---------------|--------|-------|---------|-----|---------|-----------|
| Temp. / Hum.  | Temp.: | 25 °C | Humid.: | 52% | Press.: | 1 012mbar |
| Test results: | Pass   |       |         |     |         |           |

**Remark:**


1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

**Measurement data:****■ Below 30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


## ■ 30MHz ~ 1GHz

Horizontal:



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 168.9970        | 32.47          | -6.61       | 25.86        | 43.50        | -17.64      | QP       |
| 2   | 205.7458        | 33.82          | -1.27       | 32.55        | 43.50        | -10.95      | QP       |
| 3   | 313.6482        | 43.35          | -4.44       | 38.91        | 46.00        | -7.09       | QP       |
| 4   | 360.9775        | 42.01          | -4.19       | 37.82        | 46.00        | -8.18       | QP       |
| 5   | 461.6313        | 39.09          | -2.20       | 36.89        | 46.00        | -9.11       | QP       |
| 6   | 516.5651        | 36.07          | -1.01       | 35.06        | 46.00        | -10.94      | QP       |


Vertical:



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 173.8146        | 43.70          | -6.33       | 37.37        | 43.50        | -6.13       | QP       |
| 2   | 205.7458        | 41.66          | -1.80       | 39.86        | 43.50        | -3.64       | QP       |
| 3   | 309.2710        | 37.88          | -4.49       | 33.39        | 46.00        | -12.61      | QP       |
| 4   | 360.9775        | 33.64          | -3.75       | 29.89        | 46.00        | -16.11      | QP       |
| 5   | 461.6313        | 37.32          | -2.20       | 35.12        | 46.00        | -10.88      | QP       |
| 6   | 875.0133        | 25.55          | 4.02        | 29.57        | 46.00        | -16.43      | QP       |


■ Above 1GHz

|                   |                |               |          |
|-------------------|----------------|---------------|----------|
| Test channel: CH0 | Lowest-2408MHz | Polarization: | Vertical |
|-------------------|----------------|---------------|----------|




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2408.000        | 57.63          | 26.35       | 83.98        | 74.00        | 9.98        | peak     |
| 2   | 2408.000        | 6.23           | 26.35       | 32.58        | 54.00        | -21.42      | AVG      |

|                   |                |               |            |
|-------------------|----------------|---------------|------------|
| Test channel: CH0 | Lowest-2408MHz | Polarization: | Horizontal |
|-------------------|----------------|---------------|------------|




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2408.000        | 54.71          | 26.35       | 81.06        | 74.00        | 7.06        | peak     |
| 2   | 2408.000        | 12.23          | 26.35       | 38.58        | 54.00        | -15.42      | AVG      |

|                    |                |               |          |
|--------------------|----------------|---------------|----------|
| Test channel: CH09 | Middle-2445MHz | Polarization: | Vertical |
|--------------------|----------------|---------------|----------|




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2445.000        | 57.00          | 26.41       | 83.41        | 74.00        | 9.41        | peak     |
| 2   | 2445.000        | 13.73          | 26.41       | 40.14        | 54.00        | -13.86      | AVG      |

|                    |                |               |            |
|--------------------|----------------|---------------|------------|
| Test channel: CH09 | Middle-2445MHz | Polarization: | Horizontal |
|--------------------|----------------|---------------|------------|




| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2445.000        | 57.02          | 26.41       | 83.43        | 74.00        | 9.43        | peak     |
| 2   | 2445.000        | 12.56          | 26.41       | 38.97        | 54.00        | -15.03      | AVG      |

|                    |                 |               |          |
|--------------------|-----------------|---------------|----------|
| Test channel: CH18 | Highest-2478MHz | Polarization: | Vertical |
|--------------------|-----------------|---------------|----------|



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2478.000        | 58.12          | 26.46       | 84.58        | 74.00        | 10.58       | peak     |
| 2   | 2478.000        | 13.33          | 26.46       | 39.79        | 54.00        | -14.21      | AVG      |

|                    |                 |               |            |
|--------------------|-----------------|---------------|------------|
| Test channel: CH18 | Highest-2478MHz | Polarization: | Horizontal |
|--------------------|-----------------|---------------|------------|



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|
| 1   | 2478.000        | 52.58          | 26.46       | 79.04        | 74.00        | 5.04        | peak     |
| 2   | 2478.000        | 10.90          | 26.46       | 37.36        | 54.00        | -16.64      | AVG      |

**Remark:**

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

## 8 Test Setup Photo

Reference to the **appendix I** for details.

## 9 EUT Constructional Details

Reference to the **appendix II** and **appendix III** for details.

---End---