



RADIO EXPOSURE TEST REPORT

FCC ID : 2A4M3-QV062201
Equipment : USB Type CO2 sensor
Brand Name : Telasia
Model Name : QV062201
Applicant : Reachtec Aire Ltd
6F., No. 252, Sec. 1, Wunhua 1st Rd., Linkou Dist.,
New Taipei City , Taiwan
Manufacturer : Telasia Symtonic Pte Ltd
18 Sin Ming Lane #07-02 Midview City Singapore
573960
Standard : 47 CFR Part 2.1093

The product was received on Apr. 07, 2022, and testing was started from Apr. 14, 2022 and completed on May 27, 2022. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1093 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result	4
1. General Description	5
1.1. EUT General Information	5
1.2. Antenna Information.....	5
1.3. Accessories	5
1.4. Applicable Standards	5
1.5. Testing Location.....	5
2. RF Exposure Evaluation	6
2.1. Applicable Standards	6
2.2. SAR evaluation.....	6
Photographs of EUT v01	



History of this test report

TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB-A2_1 Ver1.1

Page Number : 3 of 6
Issued Date : Jun. 28, 2022
Report Version : 01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Declaration of Conformity:

1. The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to report "Measurement Uncertainty".

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen

Report Producer: Wendy Pan



1. General Description

1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Bluetooth	2400-2483.5	2402-2480	LE: DSSS (GFSK)

1.2. Antenna Information

Ant.	Port	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	1	WCH	CH9143	PCB Antenna	N/A	2

Note: The above information was declared by manufacturer.

Only Port 1 can be used as transmitting/receiving antenna.

1.3. Accessories

N/A

1.4. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1093
- ♦ KDB447498 D01 General RF Exposure Guidance v06

1.5. Testing Location

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)
(TAF: 3787)	TEL: 886-3-656-9065 FAX: 886-3-656-9085
Test site Designation No. TW3787 with FCC.	
Conformity Assessment Body Identifier (CABID) TW3787 with ISED.	



2. RF Exposure Evaluation

2.1. Applicable Standards

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

1. Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Average Power	Tune-up Tolerance	Tune-up Average Power		Test Distance	Frequency	Exclusion Thresholds	Result
(dBm)	(dB)	(dBm)	(mW)	(mm)	(GHz)		
-13.22	0.50	-12.72	0.1	5	2.4620	0.02	PASS

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is $0.02 < 3$, RF exposure evaluation is not required.

————THE END————