

RADIO TEST REPORT

FCC ID: 2A4ND-E11A

Product: Active Noise Cancelling Headphones

Trade Mark: N/A

Model No.: E11 TV

Family Model: E11, E11-A, E11-B, E11-C, E11-D,
E11-E, E11-F, E11-S, E11-M, E11-N,
E11-MAX, E11-PRO, THL E11, E7TV,
E9TV, SE7TV

Report No.: N26020401518E

Issue Date: Jul. 25, 2026

Prepared for

JiangXi MeiDong Technology Co., Ltd

No.1, Food Avenue, Jingshan Comprehensive District, Shanggao
Prefecture Industrial Park, Yichun, Jiangxi, China

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street,
Baoan District, Shenzhen, Guangdong, People's Republic of China

Tel. 0755-23200050 Website: <http://www.ntek.org.cn>

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	SUMMARY OF TEST RESULTS.....	4
3	FACILITIES AND ACCREDITATIONS	5
3.1	FACILITIES.....	5
3.2	LABORATORY ACCREDITATIONS AND LISTINGS	5
3.3	MEASUREMENT UNCERTAINTY	5
4	GENERAL DESCRIPTION OF EUT	6
5	DESCRIPTION OF TEST MODES	8
6	SETUP OF EQUIPMENT UNDER TEST	9
6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM.....	9
6.2	SUPPORT EQUIPMENT.....	10
6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS.....	11
7	TEST REQUIREMENTS	13
7.1	CONDUCTED EMISSIONS TEST	13
7.2	RADIATED SPURIOUS EMISSION	16
7.3	NUMBER OF HOPPING CHANNEL	26
7.4	HOPPING CHANNEL SEPARATION MEASUREMENT	27
7.5	AVERAGE TIME OF OCCUPANCY (DWELL TIME)	28
7.6	20DB BANDWIDTH TEST	30
7.7	PEAK OUTPUT POWER.....	31
7.8	CONDUCTED BAND EDGE MEASUREMENT.....	32
7.9	SPURIOUS RF CONDUCTED EMISSION.....	34
7.10	ANTENNA APPLICATION	35
7.11	FREQUENCY HOPPING SYSTEM (FHSS) EQUIPMENT REQUIREMENTS	36
8	TEST RESULTS	37
8.1	CONDUCTED OUTPUT POWER	37
8.2	20dB BANDWIDTH.....	39
8.3	CARRIER FREQUENCIES SEPARATION	41
8.4	CONDUCTED SPURIOUS & BAND EDGE EMISSION	43
8.5	DWELL TIME	47
8.6	NUMBER OF HOPPING CHANNEL	50

1 TEST RESULT CERTIFICATION

Applicant's name	JiangXi MeiDong Technology Co., Ltd
Address.....	No.1, Food Avenue, Jingshan Comprehensive District, Shanggao Prefecture Industrial Park, Yichun, Jiangxi, China
Manufacturer's Name	JiangXi MeiDong Technology Co., Ltd
Address.....	No.1, Food Avenue, Jingshan Comprehensive District, Shanggao Prefecture Industrial Park, Yichun, Jiangxi, China
Product description	
Product name	Active Noise Cancelling Headphones
Model and/or type reference	E11 TV
Family Model	E11, E11-A, E11-B, E11-C, E11-D, E11-E, E11-F, E11-S, E11-M, E11-N, E11-MAX, E11-PRO, THL E11, E7TV, E9TV, SE7TV
Sample number	S2602060209-1#
Date of Test	Feb. 04, 2026 ~ Jul. 25, 2026


Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J FCC 47 CFR Part 15, Subpart C ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024	Complied

This device described above has been tested by Shenzhen NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of Shenzhen NTEK Testing Technology Co., Ltd., this document may be altered or revised by Shenzhen NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Prepared By : 
Mary Hu
(Project Engineer)

Reviewed By : 
Aaron Cheng
(Supervisor)

Approved By : 
Alex Li
(Manager)

2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C			
Standard Section	Test Item	Verdict	Remark
15.207	Conducted Emission	PASS	
15.209 (a) 15.205 (a)	Radiated Spurious Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.247 (d)	Band Edge Emission	PASS	
15.247 (d)	Spurious RF Conducted Emission	PASS	
15.203	Antenna Requirement	PASS	

Remark:

1. "N/A" denotes test is not applicable in this Test Report.
2. All test items were verified and recorded according to the standards and without any deviation during the test.

3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

CNAS-Lab. : The Certificate Registration Number is L5516.

IC-Registration : The Certificate Registration Number is 9270A.

CAB identifier:CN0074

FCC- Accredited : Test Firm Registration Number: 463705.

Designation Number: CN1184

A2LA-Lab. : The Certificate Registration Number is 4298.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025: 2017 General requirements for the competence of testing and calibration laboratories.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).

Name of Firm : Shenzhen NTEK Testing Technology Co., Ltd.

Site Location : No. 24 Xinfu East Road, Xiangshan Community, Xinqiao Street, Baoan District, Shenzhen, Guangdong, People's Republic of China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test(9-150kHz)	3.7dB
2	Conducted Emission Test(0.15-30MHz)	3.3dB
3	RF power, conducted	0.9dB
4	Power Spectral Density, conducted	0.9dB
5	Occupied bandwidth	1.2%
6	Spurious emissions, conducted	2.2dB
7	Radio Frequency	0.2ppm
8	All emissions, radiated(9kHz~30MHz)	4.5dB
9	All emissions, radiated(30MHz~1G)	4.9dB
10	All emissions, radiated(1G~18G)	5.1dB
11	All emissions, radiated(18G~40G)	5.0dB
12	Temperature	0.5°C
13	Humidity	2%

4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification	
Equipment	Active Noise Cancelling Headphones
Trade Mark	N/A
FCC ID	2A4ND-E11A
Model No.	E11 TV
Family Model	E11, E11-A, E11-B, E11-C, E11-D, E11-E, E11-F, E11-S, E11-M, E11-N, E11-MAX, E11-PRO, THL E11, E7TV, E9TV, SE7TV
Model Difference	All models have the same circuit and RF module, except for model names and colors.
Operating Frequency	BT: 2402MHz~2480MHz
Modulation	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Number of Channels	79 Channels
Antenna Type	PCB antenna
Antenna Gain	3.5dBi
Adapter	N/A
Battery	Battery1 :DC 3.7V, 430mAh, 1.59Wh Battery2 :DC 3.7V, 500mAh, 1.85Wh
Power supply	DC 5V from charge case or DC 3.7V from battery
HW Version	N/A
FW Version	N/A
SW Version	N/A

Note 1: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.

Note 2: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

Revision History

[illegible]

5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for GFSK modulation; 2Mbps for $\pi/4$ -DQPSK modulation; 3Mbps for 8-DPSK modulation) were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement -X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

Carrier Frequency and Channel list:

Channel	Frequency(MHz)
0	2402
1	2403
...	...
39	2441
40	2442
...	...
77	2479
78	2480

Note: $f_c = 2402\text{MHz} + k \times 1\text{MHz}$ $k=0$ to 78

The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission	
Final Test Mode	Description
Mode 1	normal link mode

Note: AC power line Conducted Emission was tested under maximum output power.

For Radiated Test Cases	
Final Test Mode	Description
Mode 1	normal link mode
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)

Note: For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

For Conducted Test Cases	
Final Test Mode	Description
Mode 2	CH00(2402MHz)
Mode 3	CH39(2441MHz)
Mode 4	CH78(2480MHz)
Mode 5	Hopping mode


Note: 1. The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.

- EUT built-in battery-powered, the battery is fully-charged.
- EUT contains two batteries have been tested, and only the worst data for battery 2 was recorded.


6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM


For AC Conducted Emission Mode



For Radiated Test Cases



For Conducted Test Cases



Note: 1. The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Model/Type No.	Series No.	Note
AE-1	Active Noise Cancelling Headphones	E11 TV	N/A	EUT
AE-2	Adapter	N/A	N/A	Peripherals

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	Power cable	NO	NO	80cm
C-2	RF Cable	YES	NO	10cm

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation& Conducted Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4440A	MY41000130	2025.04.24 2026.04.15	2026.04.23 2027.04.14	1 year
2	Spectrum Analyzer	Agilent	N9020A	MY49100060	2025.04.17 2026.04.08	2026.04.16 2027.04.07	1 year
3	Spectrum Analyzer	R&S	FSV40	101417	2025.04.17 2026.04.08	2026.04.16 2027.04.07	1 year
4	Test Receiver	R&S	ESPI7	101318	2025.04.17 2026.04.08	2026.04.16 2027.04.07	1 year
5	Bilog Antenna	TESEQ	CBL6111D	31216	2025.04.17 2026.04.08	2026.04.16 2027.04.07	1 year
6	50Ω Coaxial Switch	Anritsu	MP59B	6200983705	2024.04.26	2027.04.25	3 year
7	Horn Antenna	EM	EM-AH-10180	2011071402	2024.05.12	2027.05.11	3 year
8	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	803	2024.05.12	2027.05.11	3 year
9	Amplifier	EMC	EMC051835SE	980246	2025.04.17 2026.04.08	2026.04.16 2027.04.07	1 year
10	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	055	2024.05.17	2027.05.16	3 year
11	Power Meter	DARE	RPR3006W	15I00041SN084	2025.04.17 2026.04.08	2026.04.16 2027.04.07	1 year
12	Test Cable (9KHz-30MHz)	N/A	R-01	N/A	2024.05.06	2027.05.05	3 year
13	Test Cable (30MHz-1GHz)	N/A	R-02	N/A	2024.05.06	2027.05.05	3 year
14	High Test Cable(1G-40GHz)	N/A	R-03	N/A	2024.05.06	2027.05.05	3 year
15	Filter	TRILTHIC	2400MHz	29	2024.04.26	2027.04.25	3 year
16	temporary antenna connector (Note)	NTS	R001	N/A	N/A	N/A	N/A

Note:

We will use the temporary antenna connector (soldered on the PCB board) When conducted test
And this temporary antenna connector is listed within the instrument list

AC Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2025.04.17 2026.04.08	2026.04.16 2027.04.07	1 year
2	LISN	R&S	ENV216	101313	2025.04.17 2026.04.08	2026.04.16 2027.04.07	1 year
3	LISN	SCHWARZBECK	NNLK 8129	8129245	2025.04.17 2026.04.08	2026.04.16 2027.04.07	1 year
4	50Ω Coaxial Switch	ANRITSU CORP	MP59B	6200983704	2024.04.26	2027.04.25	3 year
5	Test Cable (9KHz-30MHz)	N/A	C01	N/A	2024.05.06	2027.05.05	3 year
6	Test Cable (9KHz-30MHz)	N/A	C02	N/A	2024.05.06	2027.05.05	3 year
7	Test Cable (9KHz-30MHz)	N/A	C03	N/A	2024.05.06	2027.05.05	3 year

Note: Each piece of equipment is scheduled for calibration once a year except the Aux Equipment & Test Cable which is scheduled for calibration every 2 or 3 years.

Measurement Software

Item	Manufacturer	Software Name	Software Version	Description
1	MWRFtest	MTS 8310 2.4GHz/5GHz	2.0	RF Conducted Test
2	Farad	EZ-EMC_RE	AIT-03A	RadiatedTest
3	Farad	EZ-EMC_CE	AIT-03A	AC Conducted Test

7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard


According to FCC Part 15.207(a)

7.1.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56*	56-46*
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. *Decreases with the logarithm of the frequency
2. The lower limit shall apply at the transition frequencies
3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Test Configuration



7.1.4 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
2. The EUT was placed on a table which is 0.8m above ground plane.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
6. LISN at least 80 cm from nearest part of EUT chassis.
7. The frequency range from 150KHz to 30MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
9. For the actual test configuration, please refer to the related Item –EUT Test Photos.

7.1.5 Test Results

Pass


7.1.6 Test Results

EUT:	Active Noise Cancelling Headphones	Model Name :	E11 TV
Temperature:	23.2℃	Relative Humidity:	51.4%
Pressure:	1010hPa	Phase :	L
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency (MHz)	Reading Level (dBμV)	Correct Factor (dB)	Measure-ment (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.2242	23.69	20.47	44.16	62.66	-18.50	QP
0.2242	13.05	20.47	33.52	52.66	-19.14	AVG
0.3260	21.16	20.50	41.66	59.55	-17.89	QP
0.3260	11.95	20.50	32.45	49.55	-17.10	AVG
0.4100	22.37	20.44	42.81	57.65	-14.84	QP
0.4100	11.66	20.44	32.10	47.65	-15.55	AVG
0.7460	20.91	20.44	41.35	56.00	-14.65	QP
0.7460	10.53	20.44	30.97	46.00	-15.03	AVG
1.1260	20.13	20.29	40.42	56.00	-15.58	QP
1.1260	9.86	20.29	30.15	46.00	-15.85	AVG
1.4260	19.42	20.28	39.70	56.00	-16.30	QP
1.4260	10.04	20.28	30.32	46.00	-15.68	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT:	Active Noise Cancelling Headphones	Model Name :	E11 TV
Temperature:	23.2°C	Relative Humidity:	51.4%
Pressure:	1010hPa	Phase :	N
Test Voltage :	DC 5V from Adapter AC 120V/60Hz	Test Mode:	Mode 1

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Remark
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1900	23.63	20.38	44.01	64.04	-20.03	QP
0.1900	13.23	20.38	33.61	54.04	-20.43	AVG
0.3420	22.01	20.48	42.49	59.15	-16.66	QP
0.3420	13.20	20.48	33.68	49.15	-15.47	AVG
0.5140	21.84	20.41	42.25	56.00	-13.75	QP
0.5140	12.10	20.41	32.51	46.00	-13.49	AVG
0.6620	20.75	20.49	41.24	56.00	-14.76	QP
0.6620	11.25	20.49	31.74	46.00	-14.26	AVG
1.0300	20.04	20.25	40.29	56.00	-15.71	QP
1.0300	10.54	20.25	30.79	46.00	-15.21	AVG
1.4180	20.16	20.25	40.41	56.00	-15.59	QP
1.4180	9.92	20.25	30.17	46.00	-15.83	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	24000/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Limits of Radiated Emission Measurement(Above 1000MHz)

Frequency(MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54


Remark :1. Emission level in dBuV/m=20 log (uV/m)
2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
3. For Frequency 9kHz~30MHz:
Distance extrapolation factor =40log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.
For Frequency above 30MHz:
Distance extrapolation factor =20log(Specific distance/ test distance)(dB);
Limit line=Specific limits(dBuV) + distance extrapolation factor.

7.2.3 Measuring Instruments


The Measuring equipment is listed in the section 6.3 of this test report.

7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz



7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 1 MHz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	1 MHz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

Freq. (MHz)	Ant.Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
	H/V	PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

■ Spurious Emission below 1GHz (30MHz to 1GHz)


EUT:	Active Noise Cancelling Headphones	Model Name :	E11 TV
Temperature:	24.3℃	Relative Humidity:	54.7%
Pressure:	1010hPa	Test Mode:	Mode 2
Test Voltage :	DC 5V from Adapter AC 120V/60Hz		

All the modulation modes have been tested, and the worst result was report as below:

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	54.2610	7.21	19.47	26.68	40.00	-13.32	QP
V	99.8777	8.03	17.69	25.72	43.50	-17.78	QP
V	416.1791	6.13	23.10	29.23	46.00	-16.77	QP
V	501.1790	6.73	24.53	31.26	46.00	-14.74	QP
V	774.1584	6.76	28.86	35.62	46.00	-10.38	QP
V	833.3170	6.29	29.72	36.01	46.00	-9.99	QP

Remark:


Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	50.4090	6.26	19.77	26.03	40.00	-13.97	QP
H	107.1337	6.53	17.84	24.37	43.50	-19.13	QP
H	189.7384	9.92	17.38	27.30	43.50	-16.20	QP
H	556.7743	7.21	25.54	32.75	46.00	-13.25	QP
H	670.4891	6.83	27.48	34.31	46.00	-11.69	QP
H	851.0353	6.52	29.87	36.39	46.00	-9.61	QP

Remark:

Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit



■ Spurious Emission Above 1GHz (1GHz to 25GHz)

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Read Level	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	dB/m	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
Low Channel (2402 MHz)(GFSK)--Above 1G									
4804.92	65.84	5.21	35.59	44.30	62.34	74.00	-11.66	Pk	Vertical
4804.92	50.28	5.21	35.59	44.30	46.78	54.00	-7.22	AV	Vertical
7206.71	65.84	6.48	36.27	44.60	63.99	74.00	-10.01	Pk	Vertical
7206.71	50.66	6.48	36.27	44.60	48.81	54.00	-5.19	AV	Vertical
4804.43	68.35	5.21	35.55	44.30	64.81	74.00	-9.19	Pk	Horizontal
4804.43	50.80	5.21	35.55	44.30	47.26	54.00	-6.74	AV	Horizontal
7206.36	65.44	5.21	35.55	44.52	61.68	74.00	-12.32	Pk	Horizontal
7206.36	52.27	6.48	36.27	44.52	50.50	54.00	-3.50	AV	Horizontal
Mid Channel (2441 MHz)(GFSK)--Above 1G									
4882.21	68.09	5.21	35.66	44.20	64.76	74.00	-9.24	Pk	Vertical
4882.21	50.81	5.21	35.66	44.20	47.48	54.00	-6.52	AV	Vertical
7323.04	65.93	7.10	36.50	44.43	65.10	74.00	-8.90	Pk	Vertical
7323.04	51.81	7.10	36.50	44.43	50.98	54.00	-3.02	AV	Vertical
4882.66	65.59	5.21	35.66	44.20	62.26	74.00	-11.74	Pk	Horizontal
4882.66	50.91	5.21	35.66	44.20	47.58	54.00	-6.42	AV	Horizontal
7324.39	68.75	7.10	36.50	44.43	67.92	74.00	-6.08	Pk	Horizontal
7324.39	51.46	7.10	36.50	44.43	50.63	54.00	-3.37	AV	Horizontal
High Channel (2480 MHz)(GFSK)-- Above 1G									
4959.67	64.52	5.21	35.52	44.21	61.04	74.00	-12.96	Pk	Vertical
4959.67	51.87	5.21	35.52	44.21	48.39	54.00	-5.61	AV	Vertical
7439.82	67.51	7.10	36.53	44.60	66.54	74.00	-7.46	Pk	Vertical
7439.82	52.15	7.10	36.53	44.60	51.18	54.00	-2.82	AV	Vertical
4960.62	67.74	5.21	35.52	44.21	64.26	74.00	-9.74	Pk	Horizontal
4960.62	52.32	5.21	35.52	44.21	48.84	54.00	-5.16	AV	Horizontal
7440.90	67.43	7.10	36.53	44.60	66.46	74.00	-7.54	Pk	Horizontal
7440.90	51.66	7.10	36.53	44.60	50.69	54.00	-3.31	AV	Horizontal

Note:

- (1) Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit
- (2) All other emissions more than 20dB below the limit.
- (3) Only the worst mode (GFSK) was recorded in the report.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/ Mode4	Test By:	Mary Hu

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Read Level	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
1Mbps Non-hopping 2402									
2310	66.12	2.97	27.80	43.80	53.09	74	-20.91	Pk	Vertical
2310	44.41	2.97	27.80	43.80	31.38	54	-22.62	AV	Vertical
2310	68.19	2.97	27.80	43.80	55.16	74	-18.84	Pk	Horizontal
2310	44.18	2.97	27.80	43.80	31.15	54	-22.85	AV	Horizontal
2390	68.58	3.14	27.21	43.80	55.13	74	-18.87	Pk	Vertical
2390	46.41	3.14	27.21	43.80	32.96	54	-21.04	AV	Vertical
2390	68.67	3.14	27.21	43.80	55.22	74	-18.78	Pk	Horizontal
2390	45.55	3.14	27.21	43.80	32.10	54	-21.90	AV	Horizontal
1Mbps Non-hopping 2480									
2483.5	66.73	3.58	27.70	44.00	54.01	74	-19.99	Pk	Vertical
2483.5	45.64	3.58	27.70	44.00	32.92	54	-21.08	AV	Vertical
2483.5	67.37	3.58	27.70	44.00	54.65	74	-19.35	Pk	Horizontal
2483.5	46.98	3.58	27.70	44.00	34.26	54	-19.74	AV	Horizontal
1Mbps hopping									
2310	66.12	2.97	27.80	43.80	53.09	74	-20.91	Pk	Vertical
2310	44.73	2.97	27.80	43.80	31.70	54	-22.30	AV	Vertical
2310	65.91	2.97	27.80	43.80	52.88	74	-21.12	Pk	Horizontal
2310	45.28	2.97	27.80	43.80	32.25	54	-21.75	AV	Horizontal
2390	67.84	3.14	27.21	43.80	54.39	74	-19.61	Pk	Vertical
2390	46.54	3.14	27.21	43.80	33.09	54	-20.91	AV	Vertical
2390	65.49	3.14	27.21	43.80	52.04	74	-21.96	Pk	Horizontal
2390	44.47	3.14	27.21	43.80	31.02	54	-22.98	AV	Horizontal
2483.5	66.49	3.58	27.70	44.00	53.77	74	-20.23	Pk	Vertical
2483.5	46.93	3.58	27.70	44.00	34.21	54	-19.79	AV	Vertical
2483.5	67.83	3.58	27.70	44.00	55.11	74	-18.89	Pk	Horizontal
2483.5	45.18	3.58	27.70	44.00	32.46	54	-21.54	AV	Horizontal
2Mbps Non-hopping 2402									
2310	65.89	2.97	27.80	43.80	52.86	74	-21.14	Pk	Vertical
2310	44.57	2.97	27.80	43.80	31.54	54	-22.46	AV	Vertical
2310	65.57	2.97	27.80	43.80	52.54	74	-21.46	Pk	Horizontal
2310	44.99	2.97	27.80	43.80	31.96	54	-22.04	AV	Horizontal
2390	66.47	3.14	27.21	43.80	53.02	74	-20.98	Pk	Vertical
2390	46.46	3.14	27.21	43.80	33.01	54	-20.99	AV	Vertical
2390	67.36	3.14	27.21	43.80	53.91	74	-20.09	Pk	Horizontal
2390	45.87	3.14	27.21	43.80	32.42	54	-21.58	Pk	Horizontal
2Mbps Non-hopping 2480									
2483.5	68.69	3.58	27.70	44.00	55.97	74	-18.03	Pk	Vertical
2483.5	46.82	3.58	27.70	44.00	34.10	54	-19.90	AV	Vertical

2483.5	65.54	3.58	27.70	44.00	52.82	74	-21.18	Pk	Horizontal
2483.5	45.06	3.58	27.70	44.00	32.34	54	-21.66	AV	Horizontal
2Mbps hopping									
2310	66.41	2.97	27.80	43.80	53.38	74	-20.62	Pk	Vertical
2310	46.52	2.97	27.80	43.80	33.49	54	-20.51	AV	Vertical
2310	64.86	2.97	27.80	43.80	51.83	74	-22.17	Pk	Horizontal
2310	44.46	2.97	27.80	43.80	31.43	54	-22.57	AV	Horizontal
2390	68.56	3.14	27.21	43.80	55.11	74	-18.89	Pk	Vertical
2390	46.90	3.14	27.21	43.80	33.45	54	-20.55	AV	Vertical
2390	67.56	3.14	27.21	43.80	54.11	74	-19.89	Pk	Horizontal
2390	44.39	3.14	27.21	43.80	30.94	54	-23.06	AV	Horizontal
2483.5	64.50	3.58	27.70	44.00	51.78	74	-22.22	Pk	Vertical
2483.5	45.77	3.58	27.70	44.00	33.05	54	-20.95	AV	Vertical
2483.5	64.51	3.58	27.70	44.00	51.79	74	-22.21	Pk	Horizontal
2483.5	46.46	3.58	27.70	44.00	33.74	54	-20.26	AV	Horizontal
3Mbps Non-hopping 2402									
2310	64.01	2.97	27.80	43.80	50.98	74	-23.02	Pk	Vertical
2310	44.61	2.97	27.80	43.80	31.58	54	-22.42	AV	Vertical
2310	67.85	2.97	27.80	43.80	54.82	74	-19.18	Pk	Horizontal
2310	44.46	2.97	27.80	43.80	31.43	54	-22.57	AV	Horizontal
2390	67.39	3.14	27.21	43.80	53.94	74	-20.06	Pk	Vertical
2390	45.79	3.14	27.21	43.80	32.34	54	-21.66	AV	Vertical
2390	68.04	3.14	27.21	43.80	54.59	74	-19.41	Pk	Horizontal
2390	44.04	3.14	27.21	43.80	30.59	54	-23.41	Pk	Horizontal
3Mbps Non-hopping 2480									
2483.5	65.19	3.58	27.70	44.00	52.47	74	-21.53	Pk	Vertical
2483.5	44.13	3.58	27.70	44.00	31.41	54	-22.59	AV	Vertical
2483.5	68.92	3.58	27.70	44.00	56.20	74	-17.80	Pk	Horizontal
2483.5	46.61	3.58	27.70	44.00	33.89	54	-20.11	AV	Horizontal
3Mbps hopping									
2310	68.77	2.97	27.80	43.80	55.74	74	-18.26	Pk	Vertical
2310	46.35	2.97	27.80	43.80	33.32	54	-20.68	AV	Vertical
2310	65.96	2.97	27.80	43.80	52.93	74	-21.07	Pk	Horizontal
2310	45.58	2.97	27.80	43.80	32.55	54	-21.45	AV	Horizontal
2390	64.76	3.14	27.21	43.80	51.31	74	-22.69	Pk	Vertical
2390	45.76	3.14	27.21	43.80	32.31	54	-21.69	AV	Vertical
2390	65.29	3.14	27.21	43.80	51.84	74	-22.16	Pk	Horizontal
2390	44.53	3.14	27.21	43.80	31.08	54	-22.92	AV	Horizontal
2483.5	68.08	3.58	27.70	44.00	55.36	74	-18.64	Pk	Vertical
2483.5	44.50	3.58	27.70	44.00	31.78	54	-22.22	AV	Vertical
2483.5	67.35	3.58	27.70	44.00	54.63	74	-19.37	Pk	Horizontal
2483.5	44.29	3.58	27.70	44.00	31.57	54	-22.43	AV	Horizontal

Note:

- (1) Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit
- (2) All other emissions more than 20dB below the limit.
- (3) Only the worst mode (GFSK) was recorded in the report.

■ Spurious Emission in Restricted Band 3260MHz-18000MHz

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Read Level	Cable loss	Antenna Factor	Preamplifier Factor	Emission Level	Limits	Margin	Remark	Comment
(MHz)	(dBμV)	(dB)	(dB/m)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
1Mbps Non-hopping									
3260	64.95	4.04	29.57	44.70	53.86	74	-20.14	Pk	Vertical
3260	45.91	4.04	29.57	44.70	34.82	54	-19.18	AV	Vertical
3260	66.44	4.04	29.57	44.70	55.35	74	-18.65	Pk	Horizontal
3260	45.89	4.04	29.57	44.70	34.80	54	-19.20	AV	Horizontal
3332	67.89	4.26	29.87	44.40	57.62	74	-16.38	Pk	Vertical
3332	44.10	4.26	29.87	44.40	33.83	54	-20.17	AV	Vertical
3332	68.30	4.26	29.87	44.40	58.03	74	-15.97	Pk	Horizontal
3332	46.83	4.26	29.87	44.40	36.56	54	-17.44	AV	Horizontal
17789	57.08	10.99	43.95	43.50	68.52	74	-5.48	Pk	Vertical
17789	37.47	10.99	43.95	43.50	48.91	54	-5.09	AV	Vertical
17957	58.69	11.81	43.69	44.60	69.59	74	-4.41	Pk	Horizontal
17957	37.77	11.81	43.69	44.60	48.67	54	-5.33	AV	Horizontal
1Mbps hopping									
3260	67.17	4.04	29.57	44.70	56.08	74	-17.92	Pk	Vertical
3260	45.71	4.04	29.57	44.70	34.62	54	-19.38	AV	Vertical
3260	67.63	4.04	29.57	44.70	56.54	74	-17.46	Pk	Horizontal
3260	44.28	4.04	29.57	44.70	33.19	54	-20.81	AV	Horizontal
3332	64.98	4.26	29.87	44.40	54.71	74	-19.29	Pk	Vertical
3332	46.33	4.26	29.87	44.40	36.06	54	-17.94	AV	Vertical
3332	64.88	4.26	29.87	44.40	54.61	74	-19.39	Pk	Horizontal
3332	45.63	4.26	29.87	44.40	35.36	54	-18.64	AV	Horizontal
17781	56.28	10.99	43.95	43.50	67.72	74	-6.28	Pk	Vertical
17781	36.08	10.99	43.95	43.50	47.52	54	-6.48	AV	Vertical
17955	58.17	11.81	43.69	44.60	69.07	74	-4.93	Pk	Horizontal
17955	35.73	11.81	43.69	44.60	46.63	54	-7.37	AV	Horizontal

Note:

- (1) Emission Level= Meter Reading+ Factor, Margin= Emission Level - Limit
- (2) All other emissions more than 20dB below the limit.
- (3) Only the worst case (GFSK) was recorded in the report.

7.3 NUMBER OF HOPPING CHANNEL

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.3.2 Conformance Limit

Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.3

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW : To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.3.6 Test Results

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode 5	Test By:	Mary Hu

Test data reference attachment.

7.4 HOPPING CHANNEL SEPARATION MEASUREMENT

7.4.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.4.2 Conformance Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies that are separated by 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Measurement Bandwidth or Channel Separation

RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.4.6 Test Results

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

Test data reference attachment.

7.5 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

7.5.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.5.2 Conformance Limit

The average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.4
The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
Set to the maximum power setting and enable the EUT transmit continuously.
The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings to determine the dwell time per hop:

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be $\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$, where T is the expected transmission time per hop.
- c) Sweep time: Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = $1/\text{hopping rate}$) should achieve this.
- d) Use a video trigger, where possible with a trigger delay, so that the start of the transmission is clearly observed. The trigger level might need adjustment to reduce the chance of triggering when the system hops on an adjacent channel.
- e) Detector function: Peak.
- f) Trace: Clear-write, single sweep.
- g) Place markers at the start of the first transmission on the channel and at the end of the last transmission. The dwell time per hop is the time between these two markers.

7.5.6 Test Results

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

Test data reference attachment.

7.6 20DB BANDWIDTH TEST

7.6.1 Applicable Standard

According to FCC Part 15.247(a)(1) and ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.6.2 Conformance Limit

No limit requirement.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 6.9.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq$ 1% of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.6.6 Test Results

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

Test data reference attachment.

7.7 PEAK OUTPUT POWER

7.7.1 Applicable Standard

According to FCC Part 15.247(b)(1) and ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.7.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.5.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq$ the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

7.7.6 Test Results

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2/Mode3/Mode4	Test By:	Mary Hu

Test data reference attachment.

7.8 CONDUCTED BAND EDGE MEASUREMENT

7.8.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024

7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024 clause 7.8.6. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT must have its hopping function enabled.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = 100KHz

VBW = 300KHz

Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.

7.8.6 Test Results

EUT:	Active Noise Cancelling Headphones	Model No.:	E11 TV
Temperature:	20 °C	Relative Humidity:	48%
Test Mode:	Mode2 /Mode4/Mode 5	Test By:	Mary Hu

Test data reference attachment.

7.9 SPURIOUS RF CONDUCTED EMISSION

7.9.1 Applicable Standard

According to FCC Part 15.247(d) and ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024.

7.9.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.9.4 Test Setup

Please refer to Section 6.1 of this test report.

7.9.5 Test Procedure

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured.
 - b) Set the RBW = 100 kHz.
 - c) Set the VBW $\geq [3 \times \text{RBW}]$.
 - d) Detector = peak.
 - e) Sweep time = auto couple.
 - f) Trace mode = max hold.
 - g) Allow trace to fully stabilize.
 - h) Use the peak marker function to determine the maximum amplitude level.
- Then the limit shall be attenuated by at least 20 dB relative to the maximum amplitude level in 100 kHz.

7.9.6 Test Results

Remark: The measurement frequency range is from 30MHzHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and bandege measurement data.

Test data reference attachment.

7.10 ANTENNA APPLICATION

7.10.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.10.2 Result

The EUT antenna is permanent attached PCB antenna (Gain: 3.5 dBi). It complies with the standard requirements.

7.11 FREQUENCY HOPPING SYSTEM (FHSS) EQUIPMENT REQUIREMENTS

7.11.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals. (g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section. (h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

7.11.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule. This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock. Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for FCC Part 15.247 rule.

7.11.3 EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below: Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.


8 TEST RESULTS


8.1 CONDUCTED OUTPUT POWER

Test Result


Modulation	Packet Type	Channel	Peak Output Power (dBm)	Limit (dBm)	Result
GFSK	DH5	0	-2.04	≤21	PASS
		39	-2.45		PASS
		78	-2.90		PASS
$\pi/4$ DQPSK	2-DH5	0	-2.01		PASS
		39	-2.41		PASS
		78	-2.82		PASS
8DPSK	3-DH5	0	-1.98		PASS
		39	-2.38		PASS
		78	-2.86		PASS

Test Graphs






Peak Output Power
8DPSK_Channel 0



Peak Output Power
8DPSK_Channel 39






Peak Output Power
8DPSK_Channel 78

8.2 20dB BANDWIDTH Test Result

Modulation	Channel	Center Frequency (MHz)	20 dB Bandwidth (MHz)
GFSK	0	2402 MHz	0.9335
	39	2441 MHz	0.8635
	78	2480 MHz	0.8857
$\pi/4$ DQPSK	0	2402 MHz	1.174
	39	2441 MHz	1.175
	78	2480 MHz	1.175
8DPSK	0	2402 MHz	1.164
	39	2441 MHz	1.182
	78	2480 MHz	1.178

Test Graphs







8.3 CARRIER FREQUENCIES SEPARATION Test Result


Modulation	Packet	Left Center frequency (MHz)	Right Center frequency (MHz)	Hopping Frequency Separation (MHz)	Limit (MHz)	Result
GFSK	DH5	2401.991	2402.9856	0.9946	0.622	PASS
GFSK	DH5	2439.9853	2440.985	0.9997	0.622	PASS
GFSK	DH5	2478.9565	2480.03	1.0735	0.622	PASS
$\pi/4$ DQPSK	2-DH5	2401.9838	2403.0084	1.0246	0.783	PASS
$\pi/4$ DQPSK	2-DH5	2439.9784	2440.9856	1.0072	0.783	PASS
$\pi/4$ DQPSK	2-DH5	2478.9844	2480.1446	1.1602	0.783	PASS
8DPSK	3-DH5	2401.9841	2402.9841	1.0000	0.788	PASS
8DPSK	3-DH5	2439.9877	2440.9847	0.9970	0.788	PASS
8DPSK	3-DH5	2478.985	2479.9949	1.0099	0.788	PASS

Test Graphs






8DPSK



8DPSK



8DPSK

8.4 CONDUCTED SPURIOUS & BAND EDGE EMISSION

Test Result

Non-Hopping

Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	0	2400.00	-53.874	-22.68	-31.194	PASS
			4803.64	-32.897	-22.68	-10.217	PASS
		39	4881.67	-32.450	-23.04	-9.410	PASS
			2483.50	-58.507	-23.49	-35.017	PASS
			4959.70	-29.616	-23.49	-6.126	PASS
$\pi/4$ DQPSK	2-DH5	0	2400.00	-55.626	-22.63	-32.996	PASS
			4803.64	-40.644	-22.63	-18.014	PASS
		39	4881.67	-38.671	-23.01	-15.661	PASS
			2483.50	-58.705	-23.4	-35.305	PASS
			4959.70	-39.378	-23.4	-15.978	PASS
8DPSK	3-DH5	0	2398.61	-56.236	-22.62	-33.616	PASS
			2400.00	-56.790	-22.62	-34.170	PASS
			4803.60	-35.206	-22.62	-12.586	PASS
		39	4881.67	-33.172	-23.0	-10.172	PASS
			2483.50	-58.542	-23.43	-35.112	PASS
		78	4959.70	-38.709	-23.43	-15.279	PASS


Note: input compensation coefficient (dB)= Cable Loss (dB)

Hopping


Hopping							
Modulation	Packet	Channel	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
GFSK	DH5	Hopping	2397.94	-53.363	-22.62	-30.743	PASS
			2400.00	-54.180	-22.62	-31.560	PASS
			2483.50	-56.959	-23.41	-33.549	PASS
π/4DQPSK	2-DH5		2400.00	-53.240	-22.73	-30.510	PASS
			2483.50	-57.365	-23.47	-33.895	PASS
8DPSK	3-DH5		2396.97	-54.176	-23.19	-30.986	PASS
			2400.00	-56.623	-23.19	-33.433	PASS
			2483.50	-57.970	-23.43	-34.540	PASS

Note: input compensation coefficient (dB)= Cable Loss (dB)


Test Graphs




Out Of Band Emission
GFSK_DH5_Channel 0




Out Of Band Emission
 $\pi/4$ DQPSK_2-DH5_Channel 0




30.0 MHz - 25000.0 MHz
GFSK DH5 Channel 0




30.0 MHz - 25000.0 MHz
π/4DQPSK 2-DH5 Channel 0




Out Of Band Emission
GFSK DH5 Channel 39




Out Of Band Emission
π/4DQPSK 2-DH5 Channel 39




30.0 MHz - 25000.0 MHz
GFSK DH5 Channel 39





30.0 MHz - 25000.0 MHz
π/4DQPSK 2-DH5 Channel 39




Out Of Band Emission
GFSK DH5 Channel 78




Out Of Band Emission
π/4DQPSK 2-DH5 Channel 78




30.0 MHz - 25000.0 MHz
GFSK_DH5_Channel 78




30.0 MHz - 25000.0 MHz
 π /4DQPSK_2-DH5_Channel 78




Out Of Band Emission
8DPSK_3-DH5_Channel 0




30.0 MHz - 25000.0 MHz
8DPSK_3-DH5_Channel 0




Out Of Band Emission
8DPSK_3-DH5_Channel 39




30.0 MHz - 25000.0 MHz
8DPSK_3-DH5_Channel 39




Out Of Band Emission
8DPSK_3-DH5_Channel 78




30.0 MHz - 25000.0 MHz
8DPSK_3-DH5_Channel 78



Out Of Band Emission(Left)
GFSK_DH5_Channel Hopping




Out Of Band Emission(Left)
 π /4DQPSK_2-DH5_Channel Hopping







Out Of Band Emission(Right)
GFSK_DH5_Channel Hopping



Out Of Band Emission(Right)
 $\pi/4$ DQPSK_2-DH5_Channel Hopping



Out Of Band Emission(Left)
8DPSK_3-DH5_Channel Hopping




Out Of Band Emission(Right)
8DPSK_3-DH5_Channel Hopping

8.5 DWELL TIME Test Result


Modulation	Packet	Channel	Pulse Width (ms)	Number of Pulses in 31.6 seconds	Dwell Time (ms)	Limit (ms)	Result
GFSK	DH1	Hopping	0.3756	315	118.31	< 400	PASS
	DH3		1.632	155	252.96		PASS
	DH5		2.880	109	313.92		PASS
$\pi/4$ DQPSK	2-DH1		0.3864	319	123.26		PASS
	2-DH3		1.644	157	258.11		PASS
	2-DH5		2.888	108	311.9		PASS
8DPSK	3-DH1		0.3876	319	123.64		PASS
	3-DH3		1.644	149	244.96		PASS
	3-DH5		2.888	116	335.01		PASS

Note: Dwell time=Pulse time(ms)*Number of Pulses in 31.6 seconds


Test Graphs




Pulse Width
GFSK_DH1




Number of Pulses in 31.6 seconds
GFSK_DH1




Pulse Width
GFSK_DH3



Number of Pulses in 31.6 seconds
GFSK_DH3




Pulse Width
GFSK_DH5




Number of Pulses in 31.6 seconds
GFSK_DH5


Certificate #4298.01




Pulse Width
 $\pi/4$ DQPSK 2-DH1




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK 2-DH1




Pulse Width
 $\pi/4$ DQPSK 2-DH3




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK 2-DH3




Pulse Width
 $\pi/4$ DQPSK 2-DH5




Number of Pulses in 31.6 seconds
 $\pi/4$ DQPSK 2-DH5



Pulse Width
8DPSK 3-DH1




Number of Pulses in 31.6 seconds
8DPSK 3-DH1




Pulse Width
8DPSK_3-DH3



Number of Pulses in 31.6 seconds
8DPSK_3-DH3



Pulse Width
8DPSK_3-DH5




Number of Pulses in 31.6 seconds
8DPSK_3-DH5

8.6 NUMBER OF HOPPING CHANNEL


Test Result

Modulation	Packet	Number of Hopping Channel	Limit	Result
GFSK	DH5	79	15	PASS
$\pi/4$ DQPSK	2-DH5	79	15	PASS
8DPSK	3-DH5	79	15	PASS


Test Graphs



Hopping Plot
GFSK



Hopping Plot
 $\pi/4$ DQPSK



Hopping Plot
8DPSK

END OF REPORT