


FCC PART 15C TEST REPORT FOR CERTIFICATION

On Behalf of

Shenzhen Shimu Technology Co., Ltd.

FCC ID: 2A402-S107X

Report Type: Original report	Product Type: Permanent Outdoor lights Gen2
Test Engineer: <u>Kelvin Liang</u> <i>Kelvin Liang</i>	
Report Number: <u>STD-JBO260303F-002</u>	
Report Date: <u>2026.09.10</u>	
Reviewed By: <u>Garman Mo</u> <i>Garman Mo</i>	
Prepared By: Bestway Compliance Co.,Ltd. Unit 301,Building 3, No. 178, Fenggang Section,Dongshen Road,Fenggang Town, Dongguan, Guangdong,China Tel: +86-769-82699983 www.bestway-compliance.com	



The device described above is tested by Bestway Compliance Co.,Ltd. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and Bestway Compliance Co.,Ltd. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements. This Report is made under FCC Part 2.1074. No modifications were required during testing to bring this product into compliance. This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Bestway Compliance Co.,Ltd.

This report does not imply product certification, approval, or endorsement by A2LA or any agency of the Federal Government.

TABLE OF CONTENTS

Description	Page
1. SUMMARY OF STANDARDS AND RESULTS	3
1.1. Description of Standards and Results	3
2. GENERAL INFORMATION	4
2.1. Description of Equipment Under Test	4
2.2. Feature of Equipment Under Test	5
2.3. Tested Supporting System Details	5
2.4. Test Information	6
2.5. Equipments Used during the Test	6
2.6. Test Facility	8
2.7. Measurement Uncertainty (95% confidence levels, k=2)	8
3. POWER LINE CONDUCTED EMISSION TEST	9
3.1. Block Diagram of Test Setup	9
3.2. Power Line Conducted Emission Test Limits	9
3.3. Test Procedure	9
3.4. Power Line Conducted Emission Test Result	9
4. RADIATED EMISSION TEST	34
4.1. Block Diagram of Test Setup	34
4.2. Radiated Emission Limit	35
4.3. Test Procedure	35
4.4. Radiated Emission Test Results	36
5. CONDUCTED SPURIOUS EMISSIONS	82
5.1. Block Diagram of Test Setup	82
5.2. Limit	82
5.3. Test Procedure	82
5.4. Test result	82
6. BAND EDGE COMPLIANCE TEST	104
6.1. Limit	104
6.2. Test Procedure	104
6.3. Test Results	104
7. 6dB Bandwidth Test	111
7.1. Block Diagram of Test Setup	111
7.2. Limit	111
7.3. Test Procedure	111
7.4. Test Results	111
8. OUTPUT POWER TEST	119
8.1. Block Diagram of Test Setup	119
8.2. Limit	119
8.3. Test Procedure	119
8.4. Test Results	119
9. POWER SPECTRAL DENSITY TEST	127
9.1. Block Diagram of Test Setup	127
9.2. Limit	127
9.3. Test Procedure	127
9.4. Test Results	127
10. ANTENNA REQUIREMENT	135
10.1. Standard Applicable	135
10.2. Antenna Connected Construction	135

1. SUMMARY OF STANDARDS AND RESULTS

1.1. Description of Standards and Results

The EUT has been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.205	PASS
Band Edge Compliance	FCC Part 15: 15.247(d)	PASS
Conducted spurious emissions	FCC Part 15: 15.247(d)	PASS
6dB Bandwidth Test	FCC Part 15: 15.247(a)(2)	PASS
Output Power	FCC Part 15: 15.247(b)(3)	PASS
Power Spectral Density	FCC Part 15: 15.247(e)	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

Note: Decision rule is the rule that describes how measurement uncertainty is accounted for when stating conformity with a specified requirement. When decision rule is applicable, please refer to the most updated version announced in our website:

<https://en.bestway-compliance.com/pages/decision-rule-of-compliance-with-specification>

2. GENERAL INFORMATION

2.1. Description of Equipment Under Test

Applicant:	Shenzhen Shimu Technology Co., Ltd.
Address:	Room 703, East Commercial Building, 222 Minzhi Avenue, Minkang Community, Minzhi Street, Longhua District, Shenzhen, Guangdong, China
Manufacturer:	Shenzhen Fitop Lighting Technology Co.Ltd
Address:	1st, 2nd, 3rd, 4th, and 5th floors of Building B, No. 4 Shitoushan Industrial Zone, Zhoushi Road, Langxin Community, Shiyan Street, Bao'an District, Shenzhen, Guangdong, China
Product Name:	Permanent Outdoor lights Gen2
Trade Mark:	ASAHOM
Test Model:	S107A, S107B, S107C, S107D, S107E,S107F
Model Declaration:	The internal circuits and structures of all models are exactly the same. The S107E and S107F use two power supplies and select the maximum power for testing. The S107A, S107B, S107C, and S107D all use one power supply. S107D is the one with the maximum power in the power supply, so a differential test was conducted.
Sample Type:	Prototype production
SN:	JBO260303-01;JBO260303-02;JBO260303-03; JBO260303-04;JBO260303-05;JBO260303-06
Date of Receipt:	2026.05.13
Date of Test:	2026.05.15-2026.09.10
Test Power Supply:	Input: AC 100-240V, 50/60Hz Output: DC 28.8V 2.5A (per adapter)

2.2.Feature of Equipment Under Test

Product Feature & Specification	
2.4GHz Wi-Fi	
Support Modes	802.11b/g/n(HT20)
Frequency Range	2412-2462MHz
Type of Modulation	802.11b for DSSS 802.11g/n for OFDM
Data Rate	802.11b: 11/5.5/2/1 Mbps; 802.11g: 54/48/36/24/18/12/9/6 Mbps; 802.11n: MCS0-MCS7
Channel Separation	5MHz

Antenna System

The following table information is provided by the customer

Wi-Fi	
Type of Antenna	FPC Antenna
Antenna number	1
Antenna Peak Gain	Peak Gain: 4.98dBi

2.3.Tested Supporting System Details

RF Test Tool: Wifi_Test_Tool_V1.8.0

1. Use the UART serial board to connect the Bluetooth correctly; RX —>TX; TX—>RX;
3.3V —>VCC; GND —>GND;
2. Connect the UART serial board to the computer
3. Click Serial port test tool to enter the fixed frequency test
4. Perform all tests at the default power level

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Lenovo	Notebook	X220i	428632C
Lenovo	Adapter	42T4420	N322

External I/O Cable

Cable Description	Length (m)	From Port	To	Cable Loss
Data Cable	0.1	EUT	Debug Board	0.5dB

2.4.Test Information

A special test software(The developer mode that comes with the device) was used to control EUT work in Continuous TX mode(The duty cycle of the test signal is 100%), and select test channel, wireless mode and data rate.

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)(see Note)	Channel	Frequency (MHz)
IEEE 802.11b	1	Low :CH1	2412
	1	Middle: CH6	2437
	1	High: CH11	2462
IEEE 802.11g	6	Low :CH1	2412
	6	Middle: CH6	2437
	6	High: CH11	2462
IEEE 802.11n HT20	MCS0	Low :CH1	2412
	MCS0	Middle: CH6	2437
	MCS0	High: CH11	2462
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.			

2.5.Equipments Used during the Test

Conducted Emissions

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Until	Cal. Interval
1.	Shielding Room	AUDIX	N/A	N/A	2026/12/20	3 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESR7	101487	2028/04/27	2 Year
3.	V-LISN	Rohde & Schwarz	NNLK 8122	8122-00128	2027/02/17	2 Year
4.	Coaxial cable CE	YuanDao	RG223	N/A	2027/04/27	1 Year
5.	Test Software	AUDIX	e3	V15922	N/A	N/A
Note: N/A means Not applicable.						

For frequency range 30MHz~1000MHz (In 3m Anechoic Chamber)

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Until	Cal. Interval
1.	Semi-anechoic chamber	AUDIX	N/A	N/A	2026/12/20	3 Year
2.	EMI Test Receiver	R&S	ESR7	101487	2028/04/27	2 Year
3.	Biconical Logarithmic Antenna	SCHWARDZBECK	VULB 9162	9162-104	2028/05/23	2 Year
4.	Coaxial cable RE	PEWC	CFD400NL	N/A	2027/04/27	1 Year
5.	Loop Antenna	Beijing Daze	ZN30900C	1062	2026/10/21	2 Year
6.	Test Software	AUDIX	e3	V15922	N/A	N/A
Note: N/A means Not applicable.						

For frequency range 1GHz~25GHz (In 3m Anechoic Chamber)

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Until	Cal. Interval
1.	Semi-anechoic chamber	AUDIX	N/A	N/A	2026/12/20	3 Year
2.	Spectrum Analyzer	R&S	FSP	100615	2027/04/27	1 Year
3.	Horn Antenna	SCHWARDZBEC K	BBHA 9170	895	2026/10/20	2 Year
4.	Horn Antenna	SCHWARDZBEC K	BBHA 9120 D	9120D-1515	2026/10/20	2 Year
5.	Broadband Preamplifier	SCHWARDZBEC K	BBV9718	9718-269	2028/04/27	2 Year
6.	Broadband Preamplifier	SKET	LNPA-1840	SK20191212 01	2028/04/27	2 Year
7.	RF Cable	SKET	RC-40G-K-M /K-M-0.6M	N/A	2027/04/27	1 Year
8.	RF Cable	SKET	RC-40G-K-M /K-M-8M	N/A	2027/04/27	1 Year
9.	Test Software	AUDIX	e3	V15922	N/A	N/A

Note: N/A means Not applicable.

RF Conducted Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Until	Cal. Interval
1.	Spectrum Analyzer	R&S	FSP	100615	2027/04/27	2 Year
2.	RF Cable	STD	/	/	/	/

2.6. Test Facility

Site Description


Name of Firm	:	Bestway Compliance Co.,Ltd. Unit 301,Building 3, No. 178, Fenggang Section,Dongshen Road,Fenggang Town, Dongguan, Guangdong,China
	:	Certificated by Industry Canada Registration Number: 34294 Valid Date: 2027/03/31
EMC Lab.	:	Certificated by FCC USA. Designation No.: CN1415 Valid Date: 2027/03/31
	:	

2.7.Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	2.90dB(150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	5.34dB(30M~1GHz, Distance: 3m)
Uncertainty for Radiation Emission test in 3m chamber(1GHz-40GHz)	4.14dB(1~6GHz, Distance: 3m)
	4.60dB(6~18GHz, Distance: 3m)
	4.94dB(18~40GHz, Distance: 3m)
Uncertainty for Output power test	1.34dB
Uncertainty for Bandwidth test	92.3kHz

3. POWER LINE CONDUCTED EMISSION TEST

3.1. Block Diagram of Test Setup



3.2. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.3. Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via PC connected to the power mains through a line impedance stabilization network (V-LISN). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESR7) is set at 9kHz.


The frequency range from 150kHz to 30MHz is checked.

3.4. Power Line Conducted Emission Test Result

Pass

Corrected Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
Margin (dB) = Limit (dBμV) – Corrected Amplitude (dBμV)


Model:	S107A
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.16	32.41	32.15	0.26	0.05	55.28	-22.87	Average
2	0.16	51.41	51.15	0.26	0.05	65.28	-13.87	QP
3	15.20	33.38	28.33	5.05	0.50	50.00	-16.62	Average
4	15.20	44.38	39.33	5.05	0.50	60.00	-15.62	QP
5	16.00	41.09	35.80	5.29	0.52	50.00	-8.91	Average
6	16.00	54.59	49.30	5.29	0.52	60.00	-5.41	QP
7	17.59	34.44	28.73	5.71	0.54	50.00	-15.56	Average
8	17.59	44.44	38.73	5.71	0.54	60.00	-15.56	QP
9	19.20	34.34	28.19	6.15	0.60	50.00	-15.66	Average
10	19.20	45.34	39.19	6.15	0.60	60.00	-14.66	QP
11	23.20	39.09	32.24	6.85	0.66	50.00	-10.91	Average
12	23.20	45.09	38.24	6.85	0.66	60.00	-14.91	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107A
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Cable Factor	Limit	Over	Remark
	MHz	dBuV	dBuV	dB	dB	dB	
1	0.15	34.36	34.08	0.28	0.05	56.00	-21.64 Average
2	0.15	50.36	50.08	0.28	0.05	66.00	-15.64 QP
3	16.00	38.50	33.35	5.15	0.52	50.00	-11.50 Average
4	16.00	48.50	43.35	5.15	0.52	60.00	-11.50 QP
5	17.59	35.41	29.77	5.64	0.54	50.00	-14.59 Average
6	17.59	45.41	39.77	5.64	0.54	60.00	-14.59 QP
7	20.00	37.88	31.52	6.36	0.63	50.00	-12.12 Average
8	20.00	44.88	38.52	6.36	0.63	60.00	-15.12 QP
9	23.20	38.76	31.91	6.85	0.66	50.00	-11.24 Average
10	23.20	44.76	37.91	6.85	0.66	60.00	-15.24 QP
11	24.00	36.67	29.71	6.96	0.67	50.00	-13.33 Average
12	24.00	43.67	36.71	6.96	0.67	60.00	-16.33 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107A
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.16	28.38	28.12	0.26	0.05	55.52	-27.14	Average
2	0.16	48.38	48.12	0.26	0.05	65.52	-17.14	QP
3	0.17	32.84	32.57	0.27	0.06	54.84	-22.00	Average
4	0.17	47.84	47.57	0.27	0.06	64.84	-17.00	QP
5	12.00	34.29	30.29	4.00	0.46	50.00	-15.71	Average
6	12.00	44.29	40.29	4.00	0.46	60.00	-15.71	QP
7	16.80	43.40	37.89	5.51	0.53	50.00	-6.60	Average
8	16.80	51.40	45.89	5.51	0.53	60.00	-8.60	QP
9	17.60	45.67	39.95	5.72	0.54	50.00	-4.33	Average
10	17.60	54.67	48.95	5.72	0.54	60.00	-5.33	QP
11	20.00	42.74	36.39	6.35	0.63	50.00	-7.26	Average
12	20.00	49.74	43.39	6.35	0.63	60.00	-10.26	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107A
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	34.36	34.08	0.28	0.05	56.00	-21.64	Average
2	0.15	46.36	46.08	0.28	0.05	66.00	-19.64	QP
3	0.21	28.16	27.87	0.29	0.06	53.27	-25.11	Average
4	0.21	43.16	42.87	0.29	0.06	63.27	-20.11	QP
5	16.80	44.38	38.98	5.40	0.53	50.00	-5.62	Average
6	16.80	53.38	47.98	5.40	0.53	60.00	-6.62	QP
7	17.60	45.49	39.85	5.64	0.54	50.00	-4.51	Average
8	17.60	54.49	48.85	5.64	0.54	60.00	-5.51	QP
9	19.20	42.94	36.81	6.13	0.60	50.00	-7.06	Average
10	19.20	51.94	45.81	6.13	0.60	60.00	-8.06	QP
11	20.00	41.04	34.68	6.36	0.63	50.00	-8.96	Average
12	20.00	49.04	42.68	6.36	0.63	60.00	-10.96	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107B
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	34.67	34.41	0.26	0.05	56.00	-21.33	Average
2	0.15	53.67	53.41	0.26	0.05	66.00	-12.33	QP
3	0.17	30.60	30.33	0.27	0.06	54.84	-24.24	Average
4	0.17	51.60	51.33	0.27	0.06	64.84	-13.24	QP
5	16.80	42.82	37.31	5.51	0.53	50.00	-7.18	Average
6	16.80	49.82	44.31	5.51	0.53	60.00	-10.18	QP
7	17.59	46.79	41.08	5.71	0.54	50.00	-3.21	Average
8	17.59	52.79	47.08	5.71	0.54	60.00	-7.21	QP
9	18.40	45.26	39.32	5.94	0.57	50.00	-4.74	Average
10	18.40	50.26	44.32	5.94	0.57	60.00	-9.74	QP
11	19.20	45.94	39.79	6.15	0.60	50.00	-4.06	Average
12	19.20	50.94	44.79	6.15	0.60	60.00	-9.06	QP

NotNote:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107B
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	33.33	33.05	0.28	0.05	56.00	-22.67	Average
2	0.15	55.33	55.05	0.28	0.05	66.00	-10.67	QP
3	16.80	42.92	37.51	5.41	0.53	50.00	-7.08	Average
4	16.80	50.92	45.51	5.41	0.53	60.00	-9.08	QP
5	17.59	46.83	41.19	5.64	0.54	50.00	-3.17	Average
6	17.59	54.83	49.19	5.64	0.54	60.00	-5.17	QP
7	19.20	44.36	38.23	6.13	0.60	50.00	-5.64	Average
8	19.20	48.36	42.23	6.13	0.60	60.00	-11.64	QP
9	20.00	40.43	34.07	6.36	0.63	50.00	-9.57	Average
10	20.00	52.43	46.07	6.36	0.63	60.00	-7.57	QP
11	23.16	42.78	35.94	6.84	0.66	50.00	-7.22	Average
12	23.16	47.78	40.94	6.84	0.66	60.00	-12.22	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107B
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.17	35.30	35.03	0.27	0.06	55.06	-19.76	Average
2	0.17	51.30	51.03	0.27	0.06	65.06	-13.76	QP
3	15.20	39.42	34.37	5.05	0.50	50.00	-10.58	Average
4	15.20	44.42	39.37	5.05	0.50	60.00	-15.58	QP
5	16.80	40.88	35.37	5.51	0.53	50.00	-9.12	Average
6	16.80	49.88	44.37	5.51	0.53	60.00	-10.12	QP
7	17.59	45.69	39.98	5.71	0.54	50.00	-4.31	Average
8	17.59	52.69	46.98	5.71	0.54	60.00	-7.31	QP
9	18.40	42.37	36.43	5.94	0.57	50.00	-7.63	Average
10	18.40	48.37	42.43	5.94	0.57	60.00	-11.63	QP
11	19.20	41.42	35.27	6.15	0.60	50.00	-8.58	Average
12	19.20	48.42	42.27	6.15	0.60	60.00	-11.58	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107B
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	34.25	33.97	0.28	0.05	56.00	-21.75	Average
2	0.15	53.25	52.97	0.28	0.05	66.00	-12.75	QP
3	0.17	35.49	35.20	0.29	0.06	55.06	-19.57	Average
4	0.17	50.49	50.20	0.29	0.06	65.06	-14.57	QP
5	16.00	40.96	35.81	5.15	0.52	50.00	-9.04	Average
6	16.00	46.96	41.81	5.15	0.52	60.00	-13.04	QP
7	16.80	43.95	38.55	5.40	0.53	50.00	-6.05	Average
8	16.80	53.95	48.55	5.40	0.53	60.00	-6.05	QP
9	17.60	41.59	35.95	5.64	0.54	50.00	-8.41	Average
10	17.60	49.59	43.95	5.64	0.54	60.00	-10.41	QP
11	19.20	43.13	37.00	6.13	0.60	50.00	-6.87	Average
12	19.20	49.13	43.00	6.13	0.60	60.00	-10.87	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107C
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Loss	Limit	Over	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.18	33.65	33.38	0.27	0.06	54.42	-20.77	Average
2	0.18	51.65	51.38	0.27	0.06	64.42	-12.77	QP
3	11.20	41.03	37.34	3.69	0.44	50.00	-8.97	Average
4	11.20	48.03	44.34	3.69	0.44	60.00	-11.97	QP
5	16.80	47.10	41.59	5.51	0.53	50.00	-2.90	Average
6	16.80	52.10	46.59	5.51	0.53	60.00	-7.90	QP
7	17.60	45.68	39.96	5.72	0.54	50.00	-4.32	Average
8	17.60	54.68	48.96	5.72	0.54	60.00	-5.32	QP
9	19.20	46.62	40.47	6.15	0.60	50.00	-3.38	Average
10	19.20	51.62	45.47	6.15	0.60	60.00	-8.38	QP
11	23.20	43.72	36.87	6.85	0.66	50.00	-6.28	Average
12	23.20	49.72	42.87	6.85	0.66	60.00	-10.28	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107C
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Cable Factor	Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.19	35.92	35.63	0.29	0.06	54.01	-18.09	Average
2	0.19	50.92	50.63	0.29	0.06	64.01	-13.09	QP
3	11.43	40.34	36.90	3.44	0.45	50.00	-9.66	Average
4	11.43	49.34	45.90	3.44	0.45	60.00	-10.66	QP
5	16.80	47.47	42.07	5.40	0.53	50.00	-2.53	Average
6	16.80	53.47	48.07	5.40	0.53	60.00	-6.53	QP
7	17.59	48.39	42.75	5.64	0.54	50.00	-1.61	Average
8	17.59	53.39	47.75	5.64	0.54	60.00	-6.61	QP
9	18.40	48.25	42.36	5.89	0.57	50.00	-1.75	Average
10	18.40	53.25	47.36	5.89	0.57	60.00	-6.75	QP
11	23.20	41.96	35.11	6.85	0.66	50.00	-8.04	Average
12	23.20	47.96	41.11	6.85	0.66	60.00	-12.04	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107C
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.16	33.14	32.88	0.26	0.05	55.28	-22.14	Average
2	0.16	52.14	51.88	0.26	0.05	65.28	-13.14	QP
3	0.28	37.51	37.23	0.28	0.06	50.80	-13.29	Average
4	0.28	49.51	49.23	0.28	0.06	60.80	-11.29	QP
5	0.64	32.51	32.18	0.33	0.09	46.00	-13.49	Average
6	0.64	42.51	42.18	0.33	0.09	56.00	-13.49	QP
7	11.20	41.05	37.36	3.69	0.44	50.00	-8.95	Average
8	11.20	48.05	44.36	3.69	0.44	60.00	-11.95	QP
9	17.59	45.54	39.83	5.71	0.54	50.00	-4.46	Average
10	17.59	51.54	45.83	5.71	0.54	60.00	-8.46	QP
11	18.40	41.28	35.34	5.94	0.57	50.00	-8.72	Average
12	18.40	46.28	40.34	5.94	0.57	60.00	-13.72	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107C
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.16	34.93	34.65	0.28	0.05	55.52	-20.59	Average
2	0.16	56.93	56.65	0.28	0.05	65.52	-8.59	QP
3	0.18	33.35	33.06	0.29	0.06	54.63	-21.28	Average
4	0.18	55.35	55.06	0.29	0.06	64.63	-9.28	QP
5	0.19	32.92	32.63	0.29	0.06	54.01	-21.09	Average
6	0.19	52.92	52.63	0.29	0.06	64.01	-11.09	QP
7	16.80	47.92	42.51	5.41	0.53	50.00	-2.08	Average
8	16.80	54.92	49.51	5.41	0.53	60.00	-5.08	QP
9	17.59	46.55	40.91	5.64	0.54	50.00	-3.45	Average
10	17.59	53.55	47.91	5.64	0.54	60.00	-6.45	QP
11	18.40	44.53	38.64	5.89	0.57	50.00	-5.47	Average
12	18.40	52.53	46.64	5.89	0.57	60.00	-7.47	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107D
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.19	39.51	39.24	0.27	0.06	54.01	-14.50	Average
2	0.19	52.51	52.24	0.27	0.06	64.01	-11.50	QP
3	0.27	39.92	39.64	0.28	0.06	51.07	-11.15	Average
4	0.27	51.92	51.64	0.28	0.06	61.07	-9.15	QP
5	0.40	30.93	30.64	0.29	0.07	47.91	-16.98	Average
6	0.40	47.93	47.64	0.29	0.07	57.91	-9.98	QP
7	0.55	34.05	33.73	0.32	0.09	46.00	-11.95	Average
8	0.55	48.05	47.73	0.32	0.09	56.00	-7.95	QP
9	11.62	40.04	36.18	3.86	0.45	50.00	-9.96	Average
10	11.62	48.04	44.18	3.86	0.45	60.00	-11.96	QP
11	22.69	46.77	39.99	6.78	0.66	50.00	-3.23	Average
12	22.69	53.17	46.39	6.78	0.66	60.00	-6.83	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107D
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.19	39.77	39.48	0.29	0.06	54.01	-14.24	Average
2	0.19	51.77	51.48	0.29	0.06	64.01	-12.24	QP
3	0.26	41.61	41.32	0.29	0.06	51.50	-9.89	Average
4	0.26	52.61	52.32	0.29	0.06	61.50	-8.89	QP
5	0.35	36.11	35.80	0.31	0.07	49.01	-12.90	Average
6	0.35	47.11	46.80	0.31	0.07	59.01	-11.90	QP
7	0.55	34.15	33.80	0.35	0.09	46.00	-11.85	Average
8	0.55	47.15	46.80	0.35	0.09	56.00	-8.85	QP
9	16.00	42.15	37.00	5.15	0.52	50.00	-7.85	Average
10	16.00	44.15	39.00	5.15	0.52	60.00	-15.85	QP
11	23.20	46.86	40.01	6.85	0.66	50.00	-3.14	Average
12	23.20	52.86	46.01	6.85	0.66	60.00	-7.14	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107D
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.19	39.26	38.99	0.27	0.06	54.01	-14.75	Average
2	0.19	53.26	52.99	0.27	0.06	64.01	-10.75	QP
3	0.26	37.60	37.32	0.28	0.06	51.35	-13.75	Average
4	0.26	48.60	48.32	0.28	0.06	61.35	-12.75	QP
5	0.66	33.68	33.35	0.33	0.09	46.00	-12.32	Average
6	0.66	45.68	45.35	0.33	0.09	56.00	-10.32	QP
7	16.00	41.64	36.35	5.29	0.52	50.00	-8.36	Average
8	16.00	47.64	42.35	5.29	0.52	60.00	-12.36	QP
9	19.20	42.26	36.11	6.15	0.60	50.00	-7.74	Average
10	19.20	46.26	40.11	6.15	0.60	60.00	-13.74	QP
11	22.40	40.22	33.49	6.73	0.65	50.00	-9.78	Average
12	22.40	48.22	41.49	6.73	0.65	60.00	-11.78	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107D
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.20	44.07	43.78	0.29	0.06	53.63	-9.56	Average
2	0.20	54.07	53.78	0.29	0.06	63.63	-9.56	QP
3	0.26	37.81	37.52	0.29	0.06	51.50	-13.69	Average
4	0.26	49.81	49.52	0.29	0.06	61.50	-11.69	QP
5	0.66	32.61	32.25	0.36	0.09	46.00	-13.39	Average
6	0.66	44.61	44.25	0.36	0.09	56.00	-11.39	QP
7	15.13	43.64	38.78	4.86	0.50	50.00	-6.36	Average
8	15.13	48.64	43.78	4.86	0.50	60.00	-11.36	QP
9	20.00	33.65	27.29	6.36	0.63	50.00	-16.35	Average
10	20.00	48.65	42.29	6.36	0.63	60.00	-11.35	QP
11	22.67	38.92	32.14	6.78	0.66	50.00	-11.08	Average
12	22.67	44.92	38.14	6.78	0.66	60.00	-15.08	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107E
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.19	36.56	36.29	0.27	0.06	54.21	-17.65	Average
2	0.19	49.56	49.29	0.27	0.06	64.21	-14.65	QP
3	4.80	39.92	38.50	1.42	0.29	46.00	-6.08	Average
4	4.80	52.62	51.20	1.42	0.29	56.00	-3.38	QP
5	5.60	44.87	43.18	1.69	0.30	50.00	-5.13	Average
6	5.60	50.87	49.18	1.69	0.30	60.00	-9.13	QP
7	9.60	46.06	43.01	3.05	0.40	50.00	-3.94	Average
8	9.60	55.66	52.61	3.05	0.40	60.00	-4.34	QP
9	16.80	46.00	40.49	5.51	0.53	50.00	-4.00	Average
10	16.80	51.00	45.49	5.51	0.53	60.00	-9.00	QP
11	19.20	46.00	39.85	6.15	0.60	50.00	-4.00	Average
12	19.20	52.00	45.85	6.15	0.60	60.00	-8.00	QP
13	24.00	45.08	38.12	6.96	0.67	50.00	-4.92	Average
14	24.00	54.08	47.12	6.96	0.67	60.00	-5.92	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107E
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Cable Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.20	35.46	35.17	0.29	0.06	53.63	-18.17	Average
2	0.20	50.46	50.17	0.29	0.06	63.63	-13.17	QP
3	6.40	43.22	40.82	2.40	0.31	50.00	-6.78	Average
4	6.40	50.22	47.82	2.40	0.31	60.00	-9.78	QP
5	7.20	44.97	42.33	2.64	0.33	50.00	-5.03	Average
6	7.20	51.97	49.33	2.64	0.33	60.00	-8.03	QP
7	9.60	44.51	41.78	2.73	0.40	50.00	-5.49	Average
8	9.60	50.51	47.78	2.73	0.40	60.00	-9.49	QP
9	16.80	40.10	34.70	5.40	0.53	50.00	-9.90	Average
10	16.80	53.00	47.60	5.40	0.53	60.00	-7.00	QP
11	19.20	44.54	38.41	6.13	0.60	50.00	-5.46	Average
12	19.20	51.54	45.41	6.13	0.60	60.00	-8.46	QP
13	27.20	44.28	36.88	7.40	0.72	50.00	-5.72	Average
14	27.20	50.28	42.88	7.40	0.72	60.00	-9.72	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107E
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.20	43.27	43.00	0.27	0.06	53.45	-10.18	Average
2	0.20	53.27	53.00	0.27	0.06	63.45	-10.18	QP
3	0.25	40.20	39.92	0.28	0.06	51.64	-11.44	Average
4	0.25	50.20	49.92	0.28	0.06	61.64	-11.44	QP
5	0.69	36.95	36.61	0.34	0.10	46.00	-9.05	Average
6	0.69	46.95	46.61	0.34	0.10	56.00	-9.05	QP
7	3.20	38.78	37.83	0.95	0.26	46.00	-7.22	Average
8	3.20	46.78	45.83	0.95	0.26	56.00	-9.22	QP
9	8.80	45.63	42.85	2.78	0.37	50.00	-4.37	Average
10	8.80	53.63	50.85	2.78	0.37	60.00	-6.37	QP
11	9.59	44.97	41.92	3.05	0.40	50.00	-5.03	Average
12	9.59	53.97	50.92	3.05	0.40	60.00	-6.03	QP
13	12.80	46.08	41.79	4.29	0.47	50.00	-3.92	Average
14	12.80	54.08	49.79	4.29	0.47	60.00	-5.92	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107E
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Cable Factor	Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.20	43.79	43.50	0.29	0.06	53.45	-9.66	Average
2	0.20	53.79	53.50	0.29	0.06	63.45	-9.66	QP
3	0.27	43.36	43.07	0.29	0.06	51.07	-7.71	Average
4	0.27	53.36	53.07	0.29	0.06	61.07	-7.71	QP
5	0.66	36.13	35.77	0.36	0.09	46.00	-9.87	Average
6	0.66	46.13	45.77	0.36	0.09	56.00	-9.87	QP
7	4.80	40.33	38.65	1.68	0.29	46.00	-5.67	Average
8	4.80	50.33	48.65	1.68	0.29	56.00	-5.67	QP
9	7.20	44.39	41.75	2.64	0.33	50.00	-5.61	Average
10	7.20	53.39	50.75	2.64	0.33	60.00	-6.61	QP
11	9.60	44.88	42.15	2.73	0.40	50.00	-5.12	Average
12	9.60	52.88	50.15	2.73	0.40	60.00	-7.12	QP
13	16.80	45.66	40.26	5.40	0.53	50.00	-4.34	Average
14	16.80	52.66	47.26	5.40	0.53	60.00	-7.34	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107F
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.18	29.47	29.20	0.27	0.06	54.63	-25.16	Average
2	0.18	47.47	47.20	0.27	0.06	64.63	-17.16	QP
3	0.64	31.05	30.72	0.33	0.09	46.00	-14.95	Average
4	0.64	41.05	40.72	0.33	0.09	56.00	-14.95	QP
5	7.50	41.75	39.47	2.28	0.33	50.00	-8.25	Average
6	7.50	48.75	46.47	2.28	0.33	60.00	-11.25	QP
7	9.60	41.34	38.29	3.05	0.40	50.00	-8.66	Average
8	9.60	49.34	46.29	3.05	0.40	60.00	-10.66	QP
9	10.40	43.35	39.98	3.37	0.43	50.00	-6.65	Average
10	10.40	49.35	45.98	3.37	0.43	60.00	-10.65	QP
11	23.20	45.50	38.66	6.84	0.66	50.00	-4.50	Average
12	23.20	53.50	46.66	6.84	0.66	60.00	-6.50	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107F
Test Voltage:	120Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.20	35.68	35.39	0.29	0.06	53.63	-17.95	Average
2	0.20	49.68	49.39	0.29	0.06	63.63	-13.95	QP
3	0.67	30.61	30.25	0.36	0.09	46.00	-15.39	Average
4	0.67	40.61	40.25	0.36	0.09	56.00	-15.39	QP
5	5.83	41.31	39.15	2.16	0.30	50.00	-8.69	Average
6	5.83	48.31	46.15	2.16	0.30	60.00	-11.69	QP
7	8.00	43.50	40.84	2.66	0.34	50.00	-6.50	Average
8	8.00	51.50	48.84	2.66	0.34	60.00	-8.50	QP
9	19.20	44.84	38.71	6.13	0.60	50.00	-5.16	Average
10	19.20	51.84	45.71	6.13	0.60	60.00	-8.16	QP
11	22.40	44.56	37.83	6.73	0.65	50.00	-5.44	Average
12	22.40	52.56	45.83	6.73	0.65	60.00	-7.44	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107F
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Line



	Freq	Level	Read Level	Cable Factor	Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.20	39.28	39.01	0.27	0.06	53.45	-14.17	Average
2	0.20	51.28	51.01	0.27	0.06	63.45	-12.17	QP
3	0.27	39.89	39.61	0.28	0.06	51.21	-11.32	Average
4	0.27	50.89	50.61	0.28	0.06	61.21	-10.32	QP
5	0.68	35.54	35.21	0.33	0.09	46.00	-10.46	Average
6	0.68	44.54	44.21	0.33	0.09	56.00	-11.46	QP
7	8.00	43.64	41.16	2.48	0.34	50.00	-6.36	Average
8	8.00	49.64	47.16	2.48	0.34	60.00	-10.36	QP
9	15.13	41.30	36.27	5.03	0.50	50.00	-8.70	Average
10	15.13	47.30	42.27	5.03	0.50	60.00	-12.70	QP
11	19.20	45.54	39.39	6.15	0.60	50.00	-4.46	Average
12	19.20	50.54	44.39	6.15	0.60	60.00	-9.46	QP
13	22.40	44.77	38.04	6.73	0.65	50.00	-5.23	Average
14	22.40	50.77	44.04	6.73	0.65	60.00	-9.23	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.

Model:	S107F
Test Voltage:	240Vac 60Hz
Test Date:	2026-08-13
Phase:	Neutral




	Freq	Level	Read Level	Cable Factor	Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.19	41.40	41.11	0.29	0.06	54.01	-12.61	Average
2	0.19	53.40	53.11	0.29	0.06	64.01	-10.61	QP
3	0.68	36.07	35.70	0.37	0.10	46.00	-9.93	Average
4	0.68	47.07	46.70	0.37	0.10	56.00	-8.93	QP
5	4.00	41.91	40.70	1.21	0.27	46.00	-4.09	Average
6	4.00	52.01	50.80	1.21	0.27	56.00	-3.99	QP
7	7.20	45.24	42.60	2.64	0.33	50.00	-4.76	Average
8	7.20	53.24	50.60	2.64	0.33	60.00	-6.76	QP
9	19.20	45.79	39.66	6.13	0.60	50.00	-4.21	Average
10	19.20	50.79	44.66	6.13	0.60	60.00	-9.21	QP
11	23.20	46.04	39.19	6.85	0.66	50.00	-3.96	Average
12	23.20	55.04	48.19	6.85	0.66	60.00	-4.96	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


4. RADIATED EMISSION TEST

4.1. Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz



4.2. Radiated Emission Limit

15.247&209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V/m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Remark : (1) Emission level $\text{dB}\mu\text{V} = 20 \log$ Emission level $\mu\text{V/m}$

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.3. Test Procedure

Frequency below 30MHz:

The EUT setup on the turn table which has 0.8 m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2013 regulation.

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)*2.4m(W)*0.3m(H) on the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horn

antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2013 on radiated emission Test.

The bandwidth of the EMI test receiver (R&S ESR7) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

4.4.Radiated Emission Test Results


PASS.


All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.


Note 1: Final Level= Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Note 2: The emissions (9kHz~30MHz) not reported for there is no emission be found.

Note 3: The emission levels of other frequencies(test frequency bang is 1GHz to 25GHz) are very lower than the limit and not show in test report.








Frequency: 30MHz~1GHz


Model:	S107A
Test Voltage:	120Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	120.28	23.37	7.63	15.74	1.02	43.50	-20.13	QP
2	170.19	27.07	11.49	15.58	1.20	43.50	-16.43	QP
3	250.30	31.30	11.79	19.51	1.44	46.00	-14.70	QP
4	316.59	28.26	7.23	21.03	1.63	46.00	-17.74	QP
5	451.14	33.50	9.43	24.07	1.98	46.00	-12.50	QP
6	475.50	31.34	7.03	24.31	1.93	46.00	-14.66	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107A
Test Voltage:	120Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Loss	Line	Limit
			dBuV	dB/m	dB	dBuV/m	dB
1	52.58	35.54	16.04	19.50	0.76	40.00	-4.46 QP
2	56.00	32.52	13.22	19.30	0.76	40.00	-7.48 QP
3	66.97	34.19	17.22	16.97	0.82	40.00	-5.81 QP
4	178.13	27.13	11.03	16.10	1.23	43.50	-16.37 QP
5	451.14	31.14	7.07	24.07	1.98	46.00	-14.86 QP
6	485.61	28.67	4.18	24.49	2.01	46.00	-17.33 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107A
Test Voltage:	240Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB
1	173.81	26.51	10.72	15.79	1.23	43.50	-16.99 QP
2	227.69	26.04	7.28	18.76	1.39	46.00	-19.96 QP
3	252.06	28.14	8.55	19.59	1.45	46.00	-17.86 QP
4	319.94	28.27	7.12	21.15	1.68	46.00	-17.73 QP
5	440.20	32.19	8.42	23.77	1.90	46.00	-13.81 QP
6	475.50	31.99	7.68	24.31	1.93	46.00	-14.01 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107A
Test Voltage:	240Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB
1	32.29	25.87	9.01	16.86	0.60	40.00	-14.13 QP
2	39.99	28.09	9.46	18.63	0.70	40.00	-11.91 QP
3	52.21	36.49	17.00	19.49	0.75	40.00	-3.51 QP
4	67.20	36.58	19.68	16.90	0.82	40.00	-3.42 QP
5	178.76	28.25	12.08	16.17	1.23	43.50	-15.25 QP
6	451.14	31.86	7.79	24.07	1.98	46.00	-14.14 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107B
Test Voltage:	120Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Loss	Line	Limit
			dBuV	dB/m	dB	dBuV/m	dB
1	119.86	25.04	9.24	15.80	1.01	43.50	-18.46
2	165.49	26.82	11.48	15.34	1.23	43.50	-16.68
3	178.76	26.31	10.14	16.17	1.23	43.50	-17.19
4	245.09	30.59	11.17	19.42	1.46	46.00	-15.41
5	312.18	28.16	7.21	20.95	1.64	46.00	-17.84
6	451.14	37.40	13.33	24.07	1.98	46.00	-8.60

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107B
Test Voltage:	120Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Loss	Line	Limit
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB
1	40.84	27.02	8.29	18.73	0.71	40.00	-12.98
2	48.50	29.80	10.00	19.80	0.76	40.00	-10.20
3	56.39	31.37	12.15	19.22	0.76	40.00	-8.63
4	66.73	35.35	18.28	17.07	0.82	40.00	-4.65
5	178.76	28.26	12.09	16.17	1.23	43.50	-15.24
6	440.20	32.13	8.36	23.77	1.90	46.00	-13.87
							QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107B
Test Voltage:	240Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Line	Limit	Remark
			dBuV	dB/m	dB	dBuV/m	dB
1	68.87	21.26	4.94	16.32	0.83	40.00	-18.74 QP
2	122.83	24.10	8.67	15.43	1.06	43.50	-19.40 QP
3	173.81	25.25	9.46	15.79	1.23	43.50	-18.25 QP
4	253.84	29.77	10.09	19.68	1.47	46.00	-16.23 QP
5	312.18	27.96	7.01	20.95	1.64	46.00	-18.04 QP
6	451.14	36.60	12.53	24.07	1.98	46.00	-9.40 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107B
Test Voltage:	240Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB
1	33.56	25.80	8.74	17.06	0.62	40.00	-14.20 QP
2	40.70	29.14	10.42	18.72	0.71	40.00	-10.86 QP
3	54.26	35.14	15.64	19.50	0.79	40.00	-4.86 QP
4	67.44	35.92	19.09	16.83	0.82	40.00	-4.08 QP
5	179.39	29.27	13.04	16.23	1.23	43.50	-14.23 QP
6	440.20	33.08	9.31	23.77	1.90	46.00	-12.92 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107C
Test Voltage:	120Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read Level	Cable Factor	Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	109.41	22.37	4.67	17.70	1.00	43.50	-21.13	QP
2	145.86	26.80	12.40	14.40	1.14	43.50	-16.70	QP
3	182.56	31.47	15.03	16.44	1.22	43.50	-12.03	QP
4	244.23	26.44	7.08	19.36	1.43	46.00	-19.56	QP
5	298.27	26.33	5.70	20.63	1.59	46.00	-19.67	QP
6	429.52	28.80	5.19	23.61	1.94	46.00	-17.20	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107C
Test Voltage:	120Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB
1	32.75	30.45	13.54	16.91	0.61	40.00	-9.55 QP
2	39.99	28.56	9.93	18.63	0.70	40.00	-11.44 QP
3	47.49	31.65	11.91	19.74	0.75	40.00	-8.35 QP
4	66.50	33.41	16.25	17.16	0.82	40.00	-6.59 QP
5	136.94	30.54	16.06	14.48	1.13	43.50	-12.96 QP
6	440.20	29.38	5.61	23.77	1.90	46.00	-16.62 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107C
Test Voltage:	240Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	71.83	21.18	6.04	15.14	0.87	40.00	-18.82	QP
2	107.89	20.58	2.84	17.74	0.99	43.50	-22.92	QP
3	146.37	24.97	10.53	14.44	1.14	43.50	-18.53	QP
4	192.42	32.48	14.95	17.53	1.27	43.50	-11.02	QP
5	292.06	28.14	7.64	20.50	1.59	46.00	-17.86	QP
6	463.97	32.47	8.25	24.22	1.97	46.00	-13.53	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107C
Test Voltage:	240Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Loss	Line	Limit
			dBuV	dB/m	dB	dBuV/m	dB
1	33.09	30.21	13.25	16.96	0.61	40.00	-9.79
2	39.99	30.13	11.50	18.63	0.70	40.00	-9.87
3	56.00	34.23	14.93	19.30	0.76	40.00	-5.77
4	67.20	32.99	16.09	16.90	0.82	40.00	-7.01
5	138.87	27.00	12.62	14.38	1.12	43.50	-16.50
6	441.74	28.77	4.98	23.79	1.89	46.00	-17.23
							QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107D
Test Voltage:	120Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read		Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Loss	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	114.92	25.43	8.53	16.90	1.04	43.50	-18.07	QP
2	178.76	33.84	17.67	16.17	1.23	43.50	-9.66	QP
3	195.82	32.78	14.93	17.85	1.31	43.50	-10.72	QP
4	257.42	25.59	5.82	19.77	1.46	46.00	-20.41	QP
5	306.75	27.32	6.49	20.83	1.62	46.00	-18.68	QP
6	463.97	32.18	7.96	24.22	1.97	46.00	-13.82	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107D
Test Voltage:	120Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Line	Limit	Remark
			dBuV	dB/m	dB	dBuV/m	dB
1	33.09	30.10	13.14	16.96	0.61	40.00	-9.90 QP
2	47.99	32.94	13.15	19.79	0.75	40.00	-7.06 QP
3	55.03	30.31	10.89	19.42	0.78	40.00	-9.69 QP
4	66.27	34.54	17.29	17.25	0.82	40.00	-5.46 QP
5	142.82	26.30	12.02	14.28	1.12	43.50	-17.20 QP
6	463.97	29.45	5.23	24.22	1.97	46.00	-16.55 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107D
Test Voltage:	240Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Loss	Line	Limit
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB
1	108.65	24.38	6.64	17.74	1.00	43.50	-19.12
2	121.55	23.15	7.56	15.59	1.05	43.50	-20.35
3	192.42	32.61	15.08	17.53	1.27	43.50	-10.89
4	284.98	28.39	8.05	20.34	1.57	46.00	-17.61
5	313.28	29.66	8.66	21.00	1.66	46.00	-16.34
6	440.20	37.60	13.83	23.77	1.90	46.00	-8.40
							QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107D
Test Voltage:	240Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Line	Limit	Remark
			dBuV	dB/m	dB	dBuV/m	dB
1	32.86	28.82	11.89	16.93	0.61	40.00	-11.18 QP
2	40.28	31.77	13.10	18.67	0.70	40.00	-8.23 QP
3	55.80	35.68	16.36	19.32	0.76	40.00	-4.32 QP
4	69.11	32.88	16.67	16.21	0.83	40.00	-7.12 QP
5	123.70	26.13	10.80	15.33	1.05	43.50	-17.37 QP
6	440.20	31.70	7.93	23.77	1.90	46.00	-14.30 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107E
Test Voltage:	120Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read Level	Cable Factor	Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	118.60	25.87	9.77	16.10	1.01	43.50	-17.63	QP
2	136.94	25.29	10.81	14.48	1.13	43.50	-18.21	QP
3	181.92	28.78	12.41	16.37	1.22	43.50	-14.72	QP
4	218.31	28.73	10.36	18.37	1.34	46.00	-17.27	QP
5	387.99	30.48	7.55	22.93	1.80	46.00	-15.52	QP
6	485.61	33.33	8.84	24.49	2.01	46.00	-12.67	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107E
Test Voltage:	120Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	35.87	34.49	16.95	17.54	0.65	40.00	-5.51	QP
2	42.75	32.03	12.86	19.17	0.71	40.00	-7.97	QP
3	56.39	31.95	12.73	19.22	0.76	40.00	-8.05	QP
4	68.15	35.03	18.43	16.60	0.82	40.00	-4.97	QP
5	118.60	31.02	14.92	16.10	1.01	43.50	-12.48	QP
6	125.45	30.36	15.19	15.17	1.06	43.50	-13.14	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107E
Test Voltage:	240Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Line	Limit	Remark
			dBuV	dB/m	dB	dBuV/m	dB
1	119.86	27.89	12.09	15.80	1.01	43.50	-15.61 QP
2	178.13	28.82	12.72	16.10	1.23	43.50	-14.68 QP
3	284.98	32.34	12.00	20.34	1.57	46.00	-13.66 QP
4	311.09	30.00	9.09	20.91	1.62	46.00	-16.00 QP
5	386.63	32.78	9.85	22.93	1.83	46.00	-13.22 QP
6	485.61	33.09	8.60	24.49	2.01	46.00	-12.91 QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107E
Test Voltage:	240Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	36.77	31.80	14.06	17.74	0.66	40.00	-8.20	QP
2	42.90	35.21	15.99	19.22	0.71	40.00	-4.79	QP
3	52.21	33.84	14.35	19.49	0.75	40.00	-6.16	QP
4	67.91	36.36	19.67	16.69	0.82	40.00	-3.64	QP
5	120.70	32.77	17.06	15.71	1.03	43.50	-10.73	QP
6	244.23	26.45	7.09	19.36	1.43	46.00	-19.55	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107F
Test Voltage:	120Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	103.81	25.29	7.39	17.90	0.96	43.50	-18.21	QP
2	120.28	28.74	13.00	15.74	1.02	43.50	-14.76	QP
3	183.84	32.82	16.15	16.67	1.24	43.50	-10.68	QP
4	203.52	29.28	11.07	18.21	1.35	43.50	-14.22	QP
5	379.91	30.51	7.70	22.81	1.84	46.00	-15.49	QP
6	475.50	32.12	7.81	24.31	1.93	46.00	-13.88	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107F
Test Voltage:	120Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read	Cable	Limit	Over	
	MHz	dBuV/m	Level	Factor	Loss	Line	Limit
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB
1	36.77	33.56	15.82	17.74	0.66	40.00	-6.44
2	43.20	35.29	16.02	19.27	0.71	40.00	-4.71
3	49.53	33.43	13.67	19.76	0.77	40.00	-6.57
4	65.57	35.69	18.20	17.49	0.82	40.00	-4.31
5	120.28	32.77	17.03	15.74	1.02	43.50	-10.73
6	497.68	27.72	2.89	24.83	2.11	46.00	-18.28

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.


Model:	S107F
Test Voltage:	240Vac 60Hz
Polarization:	Horizontal



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	118.19	27.59	11.44	16.15	1.02	43.50	-15.91	QP
2	190.41	29.69	12.31	17.38	1.28	43.50	-13.81	QP
3	279.04	33.18	12.99	20.19	1.54	46.00	-12.82	QP
4	305.68	29.24	8.43	20.81	1.63	46.00	-16.76	QP
5	387.99	31.41	8.48	22.93	1.80	46.00	-14.59	QP
6	475.50	33.23	8.92	24.31	1.93	46.00	-12.77	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.

Model:	S107F
Test Voltage:	240Vac 60Hz
Polarization:	Vertical



	Freq	Level	Read Level	Cable Factor	Limit Loss	Over Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	36.64	33.47	15.75	17.72	0.66	40.00	-6.53	QP
2	43.66	35.96	16.64	19.32	0.71	40.00	-4.04	QP
3	54.45	35.21	15.73	19.48	0.79	40.00	-4.79	QP
4	71.08	35.00	19.70	15.30	0.88	40.00	-5.00	QP
5	121.12	32.45	16.78	15.67	1.04	43.50	-11.05	QP
6	497.68	27.87	3.04	24.83	2.11	46.00	-18.13	QP

Note:Pre-scan all test modes, found worst case at 802.11b 2412MHz, and so only show the test result of 802.11b 2412MHz.

Frequency: 1GHz~18GHz											
Test Date					2026-05-15						
802.11b					CH01						
Horizontal											
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	1986.00	40.33	44.70	26.37	3.76	34.50	-4.37	74.00	-33.67	Peak
	2	4808.00	64.71	63.02	31.52	5.87	35.70	1.69	74.00	-9.29	Peak
	3	9534.00	46.99	34.60	38.36	8.12	34.09	12.39	74.00	-27.01	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	5216.00	25.65	23.14	31.80	6.12	35.41	2.51	54.00	-28.35	Average
	2	8242.00	32.80	22.30	37.05	7.57	34.12	10.50	54.00	-21.20	Average
	3	9364.00	35.02	22.51	38.59	8.05	34.13	12.51	54.00	-18.98	Average
Vertical											
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4808.00	66.55	64.86	31.52	5.87	35.70	1.69	74.00	-7.45	Peak
	2	7222.00	65.36	55.96	36.06	7.13	33.79	9.40	74.00	-8.64	Peak
	3	9636.00	61.90	49.33	38.47	8.17	34.07	12.57	74.00	-12.10	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4808.00	37.60	36.16	31.27	5.87	35.70	1.44	54.00	-16.40	Average
	2	8038.00	31.74	21.34	37.01	7.49	34.10	10.40	54.00	-22.26	Average
	3	10724.00	36.86	22.22	39.85	8.65	33.86	14.64	54.00	-17.14	Average

802.11b				CH06						
Horizontal			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	2258.00	39.06	42.58	27.53	3.99	35.04	-3.52	74.00	-34.94 Peak
	2	4876.00	56.37	54.57	31.55	5.91	35.66	1.80	74.00	-17.63 Peak
	3	11472.00	49.92	34.54	40.24	8.99	33.85	15.38	74.00	-24.08 Peak
			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	8004.00	32.17	21.80	37.00	7.47	34.10	10.37	54.00	-21.83 Average
Vertical	2	9330.00	34.88	22.41	38.56	8.04	34.13	12.47	54.00	-19.12 Average
	3	11166.00	37.00	21.67	40.30	8.85	33.82	15.33	54.00	-17.00 Average
			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4842.00	66.99	65.20	31.58	5.89	35.68	1.79	74.00	-7.01 Peak
	2	7324.00	66.46	56.87	36.25	7.17	33.83	9.59	74.00	-7.54 Peak
	3	9738.00	65.08	52.32	38.60	8.21	34.05	12.76	74.00	-8.92 Peak
			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4876.00	35.09	33.49	31.35	5.91	35.66	1.60	54.00	-18.91 Average
	2	9330.00	34.97	22.50	38.56	8.04	34.13	12.47	54.00	-19.03 Average
	3	11200.00	36.93	21.60	40.28	8.87	33.82	15.33	54.00	-17.07 Average

802.11b					CH11							
Horizontal			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1		1986.00	38.16	42.53	26.37	3.76	34.50	-4.37	74.00	-35.84	Peak
	2		4910.00	53.25	51.40	31.56	5.93	35.64	1.85	74.00	-20.75	Peak
	3		6576.00	43.05	35.93	34.40	6.84	34.12	7.12	74.00	-30.95	Peak
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1		8038.00	32.39	21.99	37.01	7.49	34.10	10.40	54.00	-21.61	Average
	2		9364.00	35.04	22.53	38.59	8.05	34.13	12.51	54.00	-18.96	Average
	3		11574.00	36.83	21.68	39.97	9.04	33.86	15.15	54.00	-17.17	Average
Vertical			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1		4910.00	62.57	60.72	31.56	5.93	35.64	1.85	74.00	-11.43	Peak
	2		7392.00	59.42	49.71	36.37	7.20	33.86	9.71	74.00	-14.58	Peak
	3		9840.00	56.88	44.14	38.52	8.25	34.03	12.74	74.00	-17.12	Peak
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1		4910.00	32.45	30.77	31.39	5.93	35.64	1.68	54.00	-21.55	Average
	2		9364.00	35.10	22.59	38.59	8.05	34.13	12.51	54.00	-18.90	Average
	3		11166.00	37.01	21.68	40.30	8.85	33.82	15.33	54.00	-16.99	Average

802.11g				CH01						
Horizontal			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	1986.00	39.77	44.14	26.37	3.76	34.50	-4.37	74.00	-34.23 Peak
	2	4842.00	55.25	53.46	31.58	5.89	35.68	1.79	74.00	-18.75 Peak
	3	9364.00	46.83	34.68	38.23	8.05	34.13	12.15	74.00	-27.17 Peak
			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	5250.00	25.87	23.26	31.85	6.14	35.38	2.61	54.00	-28.13 Average
Vertical	2	9364.00	34.97	22.46	38.59	8.05	34.13	12.51	54.00	-19.03 Average
	3	11370.00	36.89	21.61	40.18	8.94	33.84	15.28	54.00	-17.11 Average
			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4842.00	67.29	65.50	31.58	5.89	35.68	1.79	74.00	-6.71 Peak
	2	7222.00	65.15	55.75	36.06	7.13	33.79	9.40	74.00	-8.85 Peak
	3	9670.00	60.15	47.50	38.54	8.18	34.07	12.65	74.00	-13.85 Peak
			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4808.00	32.27	30.83	31.27	5.87	35.70	1.44	54.00	-21.73 Average
	2	9330.00	34.96	22.49	38.56	8.04	34.13	12.47	54.00	-19.04 Average
	3	11166.00	36.88	21.55	40.30	8.85	33.82	15.33	54.00	-17.12 Average

802.11g				CH06							
Horizontal				Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark	
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		
	1	1986.00	39.35	43.72	26.37	3.76	34.50	-4.37	74.00	-34.65	Peak
	2	4876.00	55.29	53.49	31.55	5.91	35.66	1.80	74.00	-18.71	Peak
	3	7290.00	44.34	34.76	36.24	7.16	33.82	9.58	74.00	-29.66	Peak
				Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark	
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		
	1	4876.00	30.83	29.23	31.35	5.91	35.66	1.60	54.00	-23.17	Average
Vertical	2	9364.00	34.97	22.46	38.59	8.05	34.13	12.51	54.00	-19.03	Average
	3	10996.00	36.76	21.40	40.39	8.77	33.80	15.36	54.00	-17.24	Average
				Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark	
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		
	1	4876.00	66.96	65.16	31.55	5.91	35.66	1.80	74.00	-7.04	Peak
	2	7324.00	65.46	55.87	36.25	7.17	33.83	9.59	74.00	-8.54	Peak
	3	9738.00	61.27	48.51	38.60	8.21	34.05	12.76	74.00	-12.73	Peak
Vertical				Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark	
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		
	1	4876.00	31.83	30.23	31.35	5.91	35.66	1.60	54.00	-22.17	Average
	2	9364.00	35.01	22.50	38.59	8.05	34.13	12.51	54.00	-18.99	Average
	3	11166.00	36.90	21.57	40.30	8.85	33.82	15.33	54.00	-17.10	Average

802.11g					CH11						
Horizontal											
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4910.00	55.43	53.58	31.56	5.93	35.64	1.85	74.00	-18.57	Peak
	2	7392.00	45.07	35.36	36.37	7.20	33.86	9.71	74.00	-28.93	Peak
	3	9364.00	46.92	34.77	38.23	8.05	34.13	12.15	74.00	-27.08	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	8004.00	32.03	21.66	37.00	7.47	34.10	10.37	54.00	-21.97	Average
2	9364.00	34.77	22.26	38.59	8.05	34.13	12.51	54.00	-19.23	Average	
3	11200.00	36.92	21.59	40.28	8.87	33.82	15.33	54.00	-17.08	Average	
Vertical											
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4944.00	66.31	64.23	31.76	5.95	35.63	2.08	74.00	-7.69	Peak
	2	7392.00	65.61	55.90	36.37	7.20	33.86	9.71	74.00	-8.39	Peak
	3	9840.00	57.64	44.90	38.52	8.25	34.03	12.74	74.00	-16.36	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4910.00	29.06	27.38	31.39	5.93	35.64	1.68	54.00	-24.94	Average
2	9330.00	35.02	22.55	38.56	8.04	34.13	12.47	54.00	-18.98	Average	
3	11166.00	36.79	21.46	40.30	8.85	33.82	15.33	54.00	-17.21	Average	

802.11n(HT20)					CH01						
Horizontal	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	1986.00	39.45	43.82	26.37	3.76	34.50	-4.37	74.00	-34.55	Peak
	2	4808.00	55.36	53.67	31.52	5.87	35.70	1.69	74.00	-18.64	Peak
	3	10826.00	48.74	33.94	39.93	8.70	33.83	14.80	74.00	-25.26	Peak
	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	7800.00	31.40	21.28	36.76	7.38	34.02	10.12	54.00	-22.60	Average
	2	9364.00	35.06	22.55	38.59	8.05	34.13	12.51	54.00	-18.94	Average
	3	11574.00	36.66	21.51	39.97	9.04	33.86	15.15	54.00	-17.34	Average
Vertical	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4842.00	67.36	65.57	31.58	5.89	35.68	1.79	74.00	-6.64	Peak
	2	7222.00	62.19	52.79	36.06	7.13	33.79	9.40	74.00	-11.81	Peak
	3	9636.00	59.92	47.35	38.47	8.17	34.07	12.57	74.00	-14.08	Peak
	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4808.00	30.49	29.05	31.27	5.87	35.70	1.44	54.00	-23.51	Average
	2	9364.00	35.02	22.51	38.59	8.05	34.13	12.51	54.00	-18.98	Average
	3	11370.00	37.06	21.78	40.18	8.94	33.84	15.28	54.00	-16.94	Average

802.11n(HT20)					CH06						
Horizontal	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark	
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		
	1	4842.00	55.31	53.52	31.58	5.89	35.68	1.79	74.00	-18.69	Peak
	2	7290.00	48.37	38.79	36.24	7.16	33.82	9.58	74.00	-25.63	Peak
	3	11812.00	48.91	34.00	39.65	9.14	33.88	14.91	74.00	-25.09	Peak
Vertical	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark	
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		
	1	7834.00	31.27	21.10	36.80	7.40	34.03	10.17	54.00	-22.73	Average
	2	9364.00	35.14	22.63	38.59	8.05	34.13	12.51	54.00	-18.86	Average
	3	11370.00	36.85	21.57	40.18	8.94	33.84	15.28	54.00	-17.15	Average
Vertical	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark	
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		
	1	4842.00	67.20	65.41	31.58	5.89	35.68	1.79	74.00	-6.80	Peak
	2	7324.00	62.37	52.78	36.25	7.17	33.83	9.59	74.00	-11.63	Peak
	3	9772.00	57.41	44.64	38.60	8.22	34.05	12.77	74.00	-16.59	Peak
Vertical	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark	
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		
	1	4876.00	28.97	27.37	31.35	5.91	35.66	1.60	54.00	-25.03	Average
	2	9364.00	34.80	22.29	38.59	8.05	34.13	12.51	54.00	-19.20	Average
	3	11132.00	37.04	21.69	40.32	8.84	33.81	15.35	54.00	-16.96	Average

802.11n(HT20)					CH11						
Horizontal	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	1986.00	37.13	41.50	26.37	3.76	34.50	-4.37	74.00	-36.87	Peak
	2	4910.00	49.16	47.31	31.56	5.93	35.64	1.85	74.00	-24.84	Peak
	3	11234.00	49.12	33.83	40.23	8.88	33.82	15.29	74.00	-24.88	Peak
	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	7664.00	31.41	21.46	36.60	7.32	33.97	9.95	54.00	-22.59	Average
	2	9330.00	35.13	22.66	38.56	8.04	34.13	12.47	54.00	-18.87	Average
	3	10758.00	36.98	22.25	39.92	8.66	33.85	14.73	54.00	-17.02	Average
Vertical	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4910.00	66.98	65.13	31.56	5.93	35.64	1.85	74.00	-7.02	Peak
	2	7358.00	60.79	51.21	36.23	7.19	33.84	9.58	74.00	-13.21	Peak
	3	9840.00	52.86	40.12	38.52	8.25	34.03	12.74	74.00	-21.14	Peak
	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	4910.00	28.23	26.55	31.39	5.93	35.64	1.68	54.00	-25.77	Average
	2	9364.00	35.34	22.83	38.59	8.05	34.13	12.51	54.00	-18.66	Average
	3	11166.00	36.85	21.52	40.30	8.85	33.82	15.33	54.00	-17.15	Average

Frequency: 18GHz~25GHz

Test Date

2026-05-15

802.11b

CH01

Horizontal

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20506.000	46.37	50.98	37.80	12.79	55.20	-4.61	74.00	-27.63	Peak
2	21850.000	47.11	51.57	37.50	13.24	55.20	-4.46	74.00	-26.89	Peak
3	22886.000	47.14	51.01	37.95	13.51	55.33	-3.87	74.00	-26.86	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20506.000	34.55	39.16	37.80	12.79	55.20	-4.61	54.00	-19.45	Average
2	21850.000	34.60	39.06	37.50	13.24	55.20	-4.46	54.00	-19.40	Average
3	22886.000	34.84	38.71	37.95	13.51	55.33	-3.87	54.00	-19.16	Average

Vertical

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20506.000	34.55	39.16	37.80	12.79	55.20	-4.61	54.00	-19.45	Average
2	21850.000	34.60	39.06	37.50	13.24	55.20	-4.46	54.00	-19.40	Average
3	22886.000	34.84	38.71	37.95	13.51	55.33	-3.87	54.00	-19.16	Average

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20506.000	34.62	39.23	37.80	12.79	55.20	-4.61	54.00	-19.38	Average
2	21850.000	33.99	38.45	37.50	13.24	55.20	-4.46	54.00	-20.01	Average
3	22886.000	33.82	37.69	37.95	13.51	55.33	-3.87	54.00	-20.18	Average

802.11b					CH06																																																													
Horizontal	<table><tr><td></td><td>Freq</td><td>Level</td><td>Read Level</td><td>Ant Factor</td><td>Cable Loss</td><td>Preamp Factor</td><td></td><td>Limit Line</td><td>Over Limit</td><td>Remark</td></tr><tr><td></td><td>MHz</td><td>dBuV/m</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB/m</td><td>dBuV/m</td><td>dB</td><td></td></tr><tr><td>1</td><td>20394.000</td><td>45.17</td><td>49.78</td><td>37.84</td><td>12.75</td><td>55.20</td><td>-4.61</td><td>74.00</td><td>-28.83</td><td>Peak</td></tr><tr><td>2</td><td>21220.000</td><td>45.78</td><td>50.44</td><td>37.51</td><td>13.03</td><td>55.20</td><td>-4.66</td><td>74.00</td><td>-28.22</td><td>Peak</td></tr><tr><td>3</td><td>22410.000</td><td>45.01</td><td>49.22</td><td>37.66</td><td>13.39</td><td>55.26</td><td>-4.21</td><td>74.00</td><td>-28.99</td><td>Peak</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	20394.000	45.17	49.78	37.84	12.75	55.20	-4.61	74.00	-28.83	Peak	2	21220.000	45.78	50.44	37.51	13.03	55.20	-4.66	74.00	-28.22	Peak	3	22410.000	45.01	49.22	37.66	13.39	55.26	-4.21	74.00	-28.99	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	20394.000	45.17	49.78	37.84	12.75	55.20	-4.61	74.00	-28.83	Peak																																																							
	2	21220.000	45.78	50.44	37.51	13.03	55.20	-4.66	74.00	-28.22	Peak																																																							
	3	22410.000	45.01	49.22	37.66	13.39	55.26	-4.21	74.00	-28.99	Peak																																																							
	<table><tr><td></td><td>Freq</td><td>Level</td><td>Read Level</td><td>Ant Factor</td><td>Cable Loss</td><td>Preamp Factor</td><td></td><td>Limit Line</td><td>Over Limit</td><td>Remark</td></tr><tr><td></td><td>MHz</td><td>dBuV/m</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB/m</td><td>dBuV/m</td><td>dB</td><td></td></tr><tr><td>1</td><td>20394.000</td><td>34.49</td><td>39.10</td><td>37.84</td><td>12.75</td><td>55.20</td><td>-4.61</td><td>54.00</td><td>-19.51</td><td>Average</td></tr><tr><td>2</td><td>21220.000</td><td>34.66</td><td>39.32</td><td>37.51</td><td>13.03</td><td>55.20</td><td>-4.66</td><td>54.00</td><td>-19.34</td><td>Average</td></tr><tr><td>3</td><td>22410.000</td><td>34.56</td><td>38.77</td><td>37.66</td><td>13.39</td><td>55.26</td><td>-4.21</td><td>54.00</td><td>-19.44</td><td>Average</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	20394.000	34.49	39.10	37.84	12.75	55.20	-4.61	54.00	-19.51	Average	2	21220.000	34.66	39.32	37.51	13.03	55.20	-4.66	54.00	-19.34	Average	3	22410.000	34.56	38.77	37.66	13.39	55.26	-4.21	54.00	-19.44	Average
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	20394.000	34.49	39.10	37.84	12.75	55.20	-4.61	54.00	-19.51	Average																																																							
2	21220.000	34.66	39.32	37.51	13.03	55.20	-4.66	54.00	-19.34	Average																																																								
3	22410.000	34.56	38.77	37.66	13.39	55.26	-4.21	54.00	-19.44	Average																																																								
Vertical	<table><tr><td></td><td>Freq</td><td>Level</td><td>Read Level</td><td>Ant Factor</td><td>Cable Loss</td><td>Preamp Factor</td><td></td><td>Limit Line</td><td>Over Limit</td><td>Remark</td></tr><tr><td></td><td>MHz</td><td>dBuV/m</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB/m</td><td>dBuV/m</td><td>dB</td><td></td></tr><tr><td>1</td><td>20394.000</td><td>44.30</td><td>48.91</td><td>37.84</td><td>12.75</td><td>55.20</td><td>-4.61</td><td>74.00</td><td>-29.70</td><td>Peak</td></tr><tr><td>2</td><td>21220.000</td><td>46.02</td><td>50.68</td><td>37.51</td><td>13.03</td><td>55.20</td><td>-4.66</td><td>74.00</td><td>-27.98</td><td>Peak</td></tr><tr><td>3</td><td>22410.000</td><td>45.07</td><td>49.28</td><td>37.66</td><td>13.39</td><td>55.26</td><td>-4.21</td><td>74.00</td><td>-28.93</td><td>Peak</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	20394.000	44.30	48.91	37.84	12.75	55.20	-4.61	74.00	-29.70	Peak	2	21220.000	46.02	50.68	37.51	13.03	55.20	-4.66	74.00	-27.98	Peak	3	22410.000	45.07	49.28	37.66	13.39	55.26	-4.21	74.00	-28.93	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	20394.000	44.30	48.91	37.84	12.75	55.20	-4.61	74.00	-29.70	Peak																																																							
	2	21220.000	46.02	50.68	37.51	13.03	55.20	-4.66	74.00	-27.98	Peak																																																							
	3	22410.000	45.07	49.28	37.66	13.39	55.26	-4.21	74.00	-28.93	Peak																																																							
	<table><tr><td></td><td>Freq</td><td>Level</td><td>Read Level</td><td>Ant Factor</td><td>Cable Loss</td><td>Preamp Factor</td><td></td><td>Limit Line</td><td>Over Limit</td><td>Remark</td></tr><tr><td></td><td>MHz</td><td>dBuV/m</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB/m</td><td>dBuV/m</td><td>dB</td><td></td></tr><tr><td>1</td><td>20394.000</td><td>33.49</td><td>38.10</td><td>37.84</td><td>12.75</td><td>55.20</td><td>-4.61</td><td>54.00</td><td>-20.51</td><td>Average</td></tr><tr><td>2</td><td>21220.000</td><td>33.92</td><td>38.58</td><td>37.51</td><td>13.03</td><td>55.20</td><td>-4.66</td><td>54.00</td><td>-20.08</td><td>Average</td></tr><tr><td>3</td><td>22410.000</td><td>34.71</td><td>38.92</td><td>37.66</td><td>13.39</td><td>55.26</td><td>-4.21</td><td>54.00</td><td>-19.29</td><td>Average</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	20394.000	33.49	38.10	37.84	12.75	55.20	-4.61	54.00	-20.51	Average	2	21220.000	33.92	38.58	37.51	13.03	55.20	-4.66	54.00	-20.08	Average	3	22410.000	34.71	38.92	37.66	13.39	55.26	-4.21	54.00	-19.29	Average
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	20394.000	33.49	38.10	37.84	12.75	55.20	-4.61	54.00	-20.51	Average																																																							
2	21220.000	33.92	38.58	37.51	13.03	55.20	-4.66	54.00	-20.08	Average																																																								
3	22410.000	34.71	38.92	37.66	13.39	55.26	-4.21	54.00	-19.29	Average																																																								

802.11b					CH11																																																													
Horizontal	<table><tr><th></th><th>Freq</th><th>Level</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Factor</th><th>Limit Line</th><th>Over Limit</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dBuV/m</th><th>dB</th><th></th></tr><tr><td>1</td><td>19918.000</td><td>45.87</td><td>50.54</td><td>38.00</td><td>12.58</td><td>55.25</td><td>-4.67</td><td>74.00</td><td>-28.13</td><td>Peak</td></tr><tr><td>2</td><td>21234.000</td><td>46.19</td><td>50.85</td><td>37.51</td><td>13.03</td><td>55.20</td><td>-4.66</td><td>74.00</td><td>-27.81</td><td>Peak</td></tr><tr><td>3</td><td>22438.000</td><td>46.00</td><td>50.19</td><td>37.68</td><td>13.40</td><td>55.27</td><td>-4.19</td><td>74.00</td><td>-28.00</td><td>Peak</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	19918.000	45.87	50.54	38.00	12.58	55.25	-4.67	74.00	-28.13	Peak	2	21234.000	46.19	50.85	37.51	13.03	55.20	-4.66	74.00	-27.81	Peak	3	22438.000	46.00	50.19	37.68	13.40	55.27	-4.19	74.00	-28.00	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	19918.000	45.87	50.54	38.00	12.58	55.25	-4.67	74.00	-28.13	Peak																																																							
	2	21234.000	46.19	50.85	37.51	13.03	55.20	-4.66	74.00	-27.81	Peak																																																							
	3	22438.000	46.00	50.19	37.68	13.40	55.27	-4.19	74.00	-28.00	Peak																																																							
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Factor</th><th>Limit Line</th><th>Over Limit</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dBuV/m</th><th>dB</th><th></th></tr><tr><td>1</td><td>19918.000</td><td>33.05</td><td>37.72</td><td>38.00</td><td>12.58</td><td>55.25</td><td>-4.67</td><td>54.00</td><td>-20.95</td><td>Average</td></tr><tr><td>2</td><td>21234.000</td><td>34.22</td><td>38.88</td><td>37.51</td><td>13.03</td><td>55.20</td><td>-4.66</td><td>54.00</td><td>-19.78</td><td>Average</td></tr><tr><td>3</td><td>22438.000</td><td>33.58</td><td>37.77</td><td>37.68</td><td>13.40</td><td>55.27</td><td>-4.19</td><td>54.00</td><td>-20.42</td><td>Average</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	19918.000	33.05	37.72	38.00	12.58	55.25	-4.67	54.00	-20.95	Average	2	21234.000	34.22	38.88	37.51	13.03	55.20	-4.66	54.00	-19.78	Average	3	22438.000	33.58	37.77	37.68	13.40	55.27	-4.19	54.00	-20.42	Average
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	19918.000	33.05	37.72	38.00	12.58	55.25	-4.67	54.00	-20.95	Average																																																							
2	21234.000	34.22	38.88	37.51	13.03	55.20	-4.66	54.00	-19.78	Average																																																								
3	22438.000	33.58	37.77	37.68	13.40	55.27	-4.19	54.00	-20.42	Average																																																								
Vertical	<table><tr><th></th><th>Freq</th><th>Level</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Factor</th><th>Limit Line</th><th>Over Limit</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dBuV/m</th><th>dB</th><th></th></tr><tr><td>1</td><td>19918.000</td><td>44.46</td><td>49.13</td><td>38.00</td><td>12.58</td><td>55.25</td><td>-4.67</td><td>74.00</td><td>-29.54</td><td>Peak</td></tr><tr><td>2</td><td>21234.000</td><td>44.76</td><td>49.42</td><td>37.51</td><td>13.03</td><td>55.20</td><td>-4.66</td><td>74.00</td><td>-29.24</td><td>Peak</td></tr><tr><td>3</td><td>22438.000</td><td>45.55</td><td>49.74</td><td>37.68</td><td>13.40</td><td>55.27</td><td>-4.19</td><td>74.00</td><td>-28.45</td><td>Peak</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	19918.000	44.46	49.13	38.00	12.58	55.25	-4.67	74.00	-29.54	Peak	2	21234.000	44.76	49.42	37.51	13.03	55.20	-4.66	74.00	-29.24	Peak	3	22438.000	45.55	49.74	37.68	13.40	55.27	-4.19	74.00	-28.45	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	19918.000	44.46	49.13	38.00	12.58	55.25	-4.67	74.00	-29.54	Peak																																																							
	2	21234.000	44.76	49.42	37.51	13.03	55.20	-4.66	74.00	-29.24	Peak																																																							
	3	22438.000	45.55	49.74	37.68	13.40	55.27	-4.19	74.00	-28.45	Peak																																																							
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Read Level</th><th>Ant Factor</th><th>Cable Loss</th><th>Preamp Factor</th><th>Factor</th><th>Limit Line</th><th>Over Limit</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB/m</th><th>dBuV/m</th><th>dB</th><th></th></tr><tr><td>1</td><td>19918.000</td><td>33.15</td><td>37.82</td><td>38.00</td><td>12.58</td><td>55.25</td><td>-4.67</td><td>54.00</td><td>-20.85</td><td>Average</td></tr><tr><td>2</td><td>21234.000</td><td>34.34</td><td>39.00</td><td>37.51</td><td>13.03</td><td>55.20</td><td>-4.66</td><td>54.00</td><td>-19.66</td><td>Average</td></tr><tr><td>3</td><td>22438.000</td><td>33.54</td><td>37.73</td><td>37.68</td><td>13.40</td><td>55.27</td><td>-4.19</td><td>54.00</td><td>-20.46</td><td>Average</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	19918.000	33.15	37.82	38.00	12.58	55.25	-4.67	54.00	-20.85	Average	2	21234.000	34.34	39.00	37.51	13.03	55.20	-4.66	54.00	-19.66	Average	3	22438.000	33.54	37.73	37.68	13.40	55.27	-4.19	54.00	-20.46	Average
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	19918.000	33.15	37.82	38.00	12.58	55.25	-4.67	54.00	-20.85	Average																																																							
2	21234.000	34.34	39.00	37.51	13.03	55.20	-4.66	54.00	-19.66	Average																																																								
3	22438.000	33.54	37.73	37.68	13.40	55.27	-4.19	54.00	-20.46	Average																																																								

802.11g					CH01																																																													
Horizontal	<table><tr><td></td><td>Freq</td><td>Level</td><td>Read Level</td><td>Ant Factor</td><td>Cable Loss</td><td>Preamp Factor</td><td>Factor</td><td>Limit Line</td><td>Over Limit</td><td>Remark</td></tr><tr><td></td><td>MHz</td><td>dBuV/m</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB/m</td><td>dBuV/m</td><td>dB</td><td></td></tr><tr><td>1</td><td>20170.000</td><td>44.64</td><td>49.23</td><td>37.93</td><td>12.68</td><td>55.20</td><td>-4.59</td><td>74.00</td><td>-29.36</td><td>Peak</td></tr><tr><td>2</td><td>21920.000</td><td>43.56</td><td>48.00</td><td>37.50</td><td>13.26</td><td>55.20</td><td>-4.44</td><td>74.00</td><td>-30.44</td><td>Peak</td></tr><tr><td>3</td><td>23124.000</td><td>45.35</td><td>49.05</td><td>38.10</td><td>13.57</td><td>55.37</td><td>-3.70</td><td>74.00</td><td>-28.65</td><td>Peak</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	20170.000	44.64	49.23	37.93	12.68	55.20	-4.59	74.00	-29.36	Peak	2	21920.000	43.56	48.00	37.50	13.26	55.20	-4.44	74.00	-30.44	Peak	3	23124.000	45.35	49.05	38.10	13.57	55.37	-3.70	74.00	-28.65	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	20170.000	44.64	49.23	37.93	12.68	55.20	-4.59	74.00	-29.36	Peak																																																							
	2	21920.000	43.56	48.00	37.50	13.26	55.20	-4.44	74.00	-30.44	Peak																																																							
	3	23124.000	45.35	49.05	38.10	13.57	55.37	-3.70	74.00	-28.65	Peak																																																							
	<table><tr><td></td><td>Freq</td><td>Level</td><td>Read Level</td><td>Ant Factor</td><td>Cable Loss</td><td>Preamp Factor</td><td>Factor</td><td>Limit Line</td><td>Over Limit</td><td>Remark</td></tr><tr><td></td><td>MHz</td><td>dBuV/m</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB/m</td><td>dBuV/m</td><td>dB</td><td></td></tr><tr><td>1</td><td>20170.000</td><td>33.48</td><td>38.07</td><td>37.93</td><td>12.68</td><td>55.20</td><td>-4.59</td><td>54.00</td><td>-20.52</td><td>Average</td></tr><tr><td>2</td><td>21920.000</td><td>33.36</td><td>37.80</td><td>37.50</td><td>13.26</td><td>55.20</td><td>-4.44</td><td>54.00</td><td>-20.64</td><td>Average</td></tr><tr><td>3</td><td>23124.000</td><td>34.46</td><td>38.16</td><td>38.10</td><td>13.57</td><td>55.37</td><td>-3.70</td><td>54.00</td><td>-19.54</td><td>Average</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	20170.000	33.48	38.07	37.93	12.68	55.20	-4.59	54.00	-20.52	Average	2	21920.000	33.36	37.80	37.50	13.26	55.20	-4.44	54.00	-20.64	Average	3	23124.000	34.46	38.16	38.10	13.57	55.37	-3.70	54.00	-19.54	Average
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	20170.000	33.48	38.07	37.93	12.68	55.20	-4.59	54.00	-20.52	Average																																																							
2	21920.000	33.36	37.80	37.50	13.26	55.20	-4.44	54.00	-20.64	Average																																																								
3	23124.000	34.46	38.16	38.10	13.57	55.37	-3.70	54.00	-19.54	Average																																																								
Vertical	<table><tr><td></td><td>Freq</td><td>Level</td><td>Read Level</td><td>Ant Factor</td><td>Cable Loss</td><td>Preamp Factor</td><td>Factor</td><td>Limit Line</td><td>Over Limit</td><td>Remark</td></tr><tr><td></td><td>MHz</td><td>dBuV/m</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB/m</td><td>dBuV/m</td><td>dB</td><td></td></tr><tr><td>1</td><td>20170.000</td><td>44.33</td><td>48.92</td><td>37.93</td><td>12.68</td><td>55.20</td><td>-4.59</td><td>74.00</td><td>-29.67</td><td>Peak</td></tr><tr><td>2</td><td>21836.000</td><td>44.43</td><td>48.89</td><td>37.50</td><td>13.24</td><td>55.20</td><td>-4.46</td><td>74.00</td><td>-29.57</td><td>Peak</td></tr><tr><td>3</td><td>23124.000</td><td>45.13</td><td>48.83</td><td>38.10</td><td>13.57</td><td>55.37</td><td>-3.70</td><td>74.00</td><td>-28.87</td><td>Peak</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	20170.000	44.33	48.92	37.93	12.68	55.20	-4.59	74.00	-29.67	Peak	2	21836.000	44.43	48.89	37.50	13.24	55.20	-4.46	74.00	-29.57	Peak	3	23124.000	45.13	48.83	38.10	13.57	55.37	-3.70	74.00	-28.87	Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	20170.000	44.33	48.92	37.93	12.68	55.20	-4.59	74.00	-29.67	Peak																																																							
	2	21836.000	44.43	48.89	37.50	13.24	55.20	-4.46	74.00	-29.57	Peak																																																							
	3	23124.000	45.13	48.83	38.10	13.57	55.37	-3.70	74.00	-28.87	Peak																																																							
	<table><tr><td></td><td>Freq</td><td>Level</td><td>Read Level</td><td>Ant Factor</td><td>Cable Loss</td><td>Preamp Factor</td><td>Factor</td><td>Limit Line</td><td>Over Limit</td><td>Remark</td></tr><tr><td></td><td>MHz</td><td>dBuV/m</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB/m</td><td>dBuV/m</td><td>dB</td><td></td></tr><tr><td>1</td><td>20170.000</td><td>33.62</td><td>38.21</td><td>37.93</td><td>12.68</td><td>55.20</td><td>-4.59</td><td>54.00</td><td>-20.38</td><td>Average</td></tr><tr><td>2</td><td>21920.000</td><td>32.60</td><td>37.04</td><td>37.50</td><td>13.26</td><td>55.20</td><td>-4.44</td><td>54.00</td><td>-21.40</td><td>Average</td></tr><tr><td>3</td><td>23124.000</td><td>33.42</td><td>37.12</td><td>38.10</td><td>13.57</td><td>55.37</td><td>-3.70</td><td>54.00</td><td>-20.58</td><td>Average</td></tr></table>												Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB		1	20170.000	33.62	38.21	37.93	12.68	55.20	-4.59	54.00	-20.38	Average	2	21920.000	32.60	37.04	37.50	13.26	55.20	-4.44	54.00	-21.40	Average	3	23124.000	33.42	37.12	38.10	13.57	55.37	-3.70	54.00	-20.58	Average
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark																																																							
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB																																																								
	1	20170.000	33.62	38.21	37.93	12.68	55.20	-4.59	54.00	-20.38	Average																																																							
2	21920.000	32.60	37.04	37.50	13.26	55.20	-4.44	54.00	-21.40	Average																																																								
3	23124.000	33.42	37.12	38.10	13.57	55.37	-3.70	54.00	-20.58	Average																																																								

802.11g					CH06							
Horizontal			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20114.000	45.89	50.48	37.95	12.66	55.20	-4.59	74.00	-28.11	Peak	
	2	21094.000	45.48	50.13	37.56	12.99	55.20	-4.65	74.00	-28.52	Peak	
	3	22760.000	45.96	49.89	37.90	13.48	55.31	-3.93	74.00	-28.04	Peak	
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20114.000	32.95	37.54	37.95	12.66	55.20	-4.59	54.00	-21.05	Average	
	2	21094.000	33.70	38.35	37.56	12.99	55.20	-4.65	54.00	-20.30	Average	
	3	22760.000	33.28	37.21	37.90	13.48	55.31	-3.93	54.00	-20.72	Average	
Vertical			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20114.000	43.91	48.50	37.95	12.66	55.20	-4.59	74.00	-30.09	Peak	
	2	21094.000	44.56	49.21	37.56	12.99	55.20	-4.65	74.00	-29.44	Peak	
	3	22760.000	43.92	47.85	37.90	13.48	55.31	-3.93	74.00	-30.08	Peak	
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20114.000	32.84	37.43	37.95	12.66	55.20	-4.59	54.00	-21.16	Average	
	2	21094.000	34.05	38.70	37.56	12.99	55.20	-4.65	54.00	-19.95	Average	
	3	22760.000	32.85	36.78	37.90	13.48	55.31	-3.93	54.00	-21.15	Average	

802.11g					CH11							
Horizontal			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20170.000	44.48	49.07	37.93	12.68	55.20	-4.59	74.00	-29.52	Peak	
	2	21836.000	45.07	49.53	37.50	13.24	55.20	-4.46	74.00	-28.93	Peak	
	3	23026.000	45.50	49.28	38.02	13.55	55.35	-3.78	74.00	-28.50	Peak	
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20170.000	34.11	38.70	37.93	12.68	55.20	-4.59	54.00	-19.89	Average	
	2	21836.000	34.08	38.54	37.50	13.24	55.20	-4.46	54.00	-19.92	Average	
	3	23026.000	34.71	38.49	38.02	13.55	55.35	-3.78	54.00	-19.29	Average	
Vertical			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20170.000	44.14	48.73	37.93	12.68	55.20	-4.59	74.00	-29.86	Peak	
	2	21836.000	44.56	49.02	37.50	13.24	55.20	-4.46	74.00	-29.44	Peak	
	3	23026.000	47.00	50.78	38.02	13.55	55.35	-3.78	74.00	-27.00	Peak	
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20170.000	33.05	37.64	37.93	12.68	55.20	-4.59	54.00	-20.95	Average	
	2	21836.000	33.26	37.72	37.50	13.24	55.20	-4.46	54.00	-20.74	Average	
	3	23026.000	34.23	38.01	38.02	13.55	55.35	-3.78	54.00	-19.77	Average	


802.11n(HT20)				CH01						
Horizontal			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20548.000	46.01	50.63	37.78	12.80	55.20	-4.62	74.00	-27.99 Peak
	2	21458.000	46.15	50.74	37.50	13.11	55.20	-4.59	74.00	-27.85 Peak
	3	22998.000	45.56	49.37	38.00	13.54	55.35	-3.81	74.00	-28.44 Peak
			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20548.000	32.61	37.23	37.78	12.80	55.20	-4.62	54.00	-21.39 Average
Vertical	2	21458.000	32.51	37.10	37.50	13.11	55.20	-4.59	54.00	-21.49 Average
	3	22988.000	33.03	36.84	38.00	13.54	55.35	-3.81	54.00	-20.97 Average
			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20548.000	44.09	48.71	37.78	12.80	55.20	-4.62	74.00	-29.91 Peak
	2	21458.000	43.97	48.56	37.50	13.11	55.20	-4.59	74.00	-30.03 Peak
	3	22988.000	43.96	47.77	38.00	13.54	55.35	-3.81	74.00	-30.04 Peak
			Read	Ant	Cable	Preamp		Limit	Over	
	Freq	Level	Level	Factor	Loss	Factor	Factor	Line	Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20548.000	32.50	37.12	37.78	12.80	55.20	-4.62	54.00	-21.50 Average
	2	21458.000	32.42	37.01	37.50	13.11	55.20	-4.59	54.00	-21.58 Average
	3	22988.000	33.18	36.99	38.00	13.54	55.35	-3.81	54.00	-20.82 Average

802.11n(HT20)					CH06						
Horizontal	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20366.000	43.73	48.34	37.85	12.74	55.20	-4.61	74.00	-30.27	Peak
	2	21780.000	43.85	48.33	37.50	13.22	55.20	-4.48	74.00	-30.15	Peak
	3	23040.000	44.67	48.45	38.03	13.55	55.36	-3.78	74.00	-29.33	Peak
	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20366.000	33.52	38.13	37.85	12.74	55.20	-4.61	54.00	-20.48	Average
	2	21780.000	32.47	36.95	37.50	13.22	55.20	-4.48	54.00	-21.53	Average
	3	23040.000	33.96	37.74	38.03	13.55	55.36	-3.78	54.00	-20.04	Average
Vertical	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20366.000	44.21	48.82	37.85	12.74	55.20	-4.61	74.00	-29.79	Peak
	2	21780.000	44.96	49.44	37.50	13.22	55.20	-4.48	74.00	-29.04	Peak
	3	23040.000	44.68	48.46	38.03	13.55	55.36	-3.78	74.00	-29.32	Peak
	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20366.000	33.31	37.92	37.85	12.74	55.20	-4.61	54.00	-20.69	Average
	2	21780.000	33.58	38.06	37.50	13.22	55.20	-4.48	54.00	-20.42	Average
	3	23040.000	33.98	37.76	38.03	13.55	55.36	-3.78	54.00	-20.02	Average

802.11n(HT20)					CH11						
Horizontal	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20170.000	44.85	49.44	37.93	12.68	55.20	-4.59	74.00	-29.15	Peak
	2	20940.000	45.56	50.21	37.62	12.93	55.20	-4.65	74.00	-28.44	Peak
	3	22676.000	45.57	49.57	37.84	13.46	55.30	-4.00	74.00	-28.43	Peak
	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20170.000	32.33	36.92	37.93	12.68	55.20	-4.59	54.00	-21.67	Average
	2	20940.000	32.74	37.39	37.62	12.93	55.20	-4.65	54.00	-21.26	Average
	3	22676.000	32.46	36.46	37.84	13.46	55.30	-4.00	54.00	-21.54	Average
Vertical	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20170.000	43.42	48.01	37.93	12.68	55.20	-4.59	74.00	-30.58	Peak
	2	20940.000	43.28	47.93	37.62	12.93	55.20	-4.65	74.00	-30.72	Peak
	3	22676.000	43.95	47.95	37.84	13.46	55.30	-4.00	74.00	-30.05	Peak
	Freq		Level	Read Level	Ant Factor	Cable Loss	Preamp Factor		Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
	1	20170.000	32.73	37.32	37.93	12.68	55.20	-4.59	54.00	-21.27	Average
	2	20940.000	33.52	38.17	37.62	12.93	55.20	-4.65	54.00	-20.48	Average
	3	22676.000	33.17	37.17	37.84	13.46	55.30	-4.00	54.00	-20.83	Average

5. CONDUCTED SPURIOUS EMISSIONS

5.1. Block Diagram of Test Setup



5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.3. Test Procedure

Use the test method described in ANSI C63.10:

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions with peak detector.

Note: The cable loss and attenuator loss were offset into spectrum analyzer as an amplitude offset.

5.4. Test result

PASS (The testing data was attached in the next pages.)

Note 1: Final Level = Spectrum Analyzer Read Level + Cable Loss


Page 83 of 135

Page 84 of 135

Page 85 of 135

Page 86 of 135


CH01
Above 1GHz



Date: 2.SEP.2026 19:52:13

Page 88 of 135


CH06
Above 1GHz



Date: 2.SEP.2026 19:56:23

Page 90 of 135


CH11
Above 1GHz



Date: 2.SEP.2026 19:58:51

Page 92 of 135


CH01
Above 1GHz



Date: 2.SEP.2026 20:03:28

Page 94 of 135


CH06
Above 1GHz



Date: 2.SEP.2026 20:08:04

Page 96 of 135


CH11
Above 1GHz



Date: 2.SEP.2026 20:10:28

Page 98 of 135


CH01
Above 1GHz



Date: 2.SEP.2026 20:15:31

Page 100 of 135


CH06
Above 1GHz



Date: 2.SEP.2026 20:20:00

Page 102 of 135

CH11
Above 1GHz



Date: 2.SEP.2026 20:22:37

6. BAND EDGE COMPLIANCE TEST

6.1.Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

6.2.Test Procedure

Use the test method described in ANSI C63.10 clause 6.10:

1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO

6.3.Test Results

Pass (The testing data was attached in the next pages.)

Note 1: Final Level = Spectrum Analyzer Read Level + Cable Loss

802.11b					CH01							
Horizontal			Freq	Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1		2310.00	33.91	37.37	-3.46	27.66	4.03	35.15	74.00	-40.09	Peak
	2		2390.00	40.61	44.18	-3.57	27.66	4.09	35.32	74.00	-33.39	Peak
	3		2400.00	54.57	58.11	-3.54	27.70	4.10	35.34	74.00	-19.43	Peak
			Freq	Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1		2310.00	16.08	19.94	-3.86	27.26	4.03	35.15	54.00	-37.92	Average
	2		2390.00	17.27	21.10	-3.83	27.40	4.09	35.32	54.00	-36.73	Average
	3		2400.00	23.19	27.01	-3.82	27.42	4.10	35.34	54.00	-30.81	Average

802.11b					CH01							
Vertical			Freq	Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1		2310.00	39.53	42.99	-3.46	27.66	4.03	35.15	74.00	-34.47	Peak
	2		2390.00	50.04	53.61	-3.57	27.66	4.09	35.32	74.00	-23.96	Peak
	3		2400.00	68.75	72.29	-3.54	27.70	4.10	35.34	74.00	-5.25	Peak
			Freq	Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1		2310.00	17.07	20.93	-3.86	27.26	4.03	35.15	54.00	-36.93	Average
	2		2390.00	21.53	25.36	-3.83	27.40	4.09	35.32	54.00	-32.47	Average
	3		2400.00	38.81	42.63	-3.82	27.42	4.10	35.34	54.00	-15.19	Average

802.11b				CH11							
Horizontal			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1		2483.50	36.66	40.44	27.57	4.17	35.52	-3.78	74.00	-37.34 Peak
	2		2500.00	33.98	37.75	27.60	4.18	35.55	-3.77	74.00	-40.02 Peak
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1		2483.50	20.95	24.73	27.57	4.17	35.52	-3.78	54.00	-33.05 Average
	2		2500.00	16.21	19.98	27.60	4.18	35.55	-3.77	54.00	-37.79 Average

802.11b				CH11							
Vertical			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1		2483.50	43.06	46.84	27.57	4.17	35.52	-3.78	74.00	-30.94 Peak
	2		2500.00	36.87	40.64	27.60	4.18	35.55	-3.77	74.00	-37.13 Peak
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1		2483.50	23.72	27.50	27.57	4.17	35.52	-3.78	54.00	-30.28 Average
	2		2500.00	20.79	24.56	27.60	4.18	35.55	-3.77	54.00	-33.21 Average

802.11g					CH01						
Horizontal											
		Freq	Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1	2310.00	34.91	38.37	-3.46	27.66	4.03	35.15	74.00	-39.09	Peak
	2	2390.00	56.69	60.26	-3.57	27.66	4.09	35.32	74.00	-17.31	Peak
	3	2400.00	68.76	72.30	-3.54	27.70	4.10	35.34	74.00	-5.24	Peak
		Freq	Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1	2310.00	15.95	19.81	-3.86	27.26	4.03	35.15	54.00	-38.05	Average
2	2390.00	18.11	21.94	-3.83	27.40	4.09	35.32	54.00	-35.89	Average	
3	2400.00	24.94	28.76	-3.82	27.42	4.10	35.34	54.00	-29.06	Average	

802.11g					CH01							
Vertical			Freq	Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1	2310.00	40.74	44.20	-3.46	27.66	4.03	35.15	74.00	-33.26	Peak	
	2	2390.00	63.36	66.93	-3.57	27.66	4.09	35.32	74.00	-10.64	Peak	
	3	2400.00	67.17	70.71	-3.54	27.70	4.10	35.34	74.00	-6.83	Peak	
			Freq	Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1	2310.00	19.13	22.99	-3.86	27.26	4.03	35.15	54.00	-34.87	Average	
	2	2390.00	25.53	29.36	-3.83	27.40	4.09	35.32	54.00	-28.47	Average	
	3	2400.00	38.05	41.87	-3.82	27.42	4.10	35.34	54.00	-15.95	Average	

802.11g				CH11							
Horizontal			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1		2483.50	52.80	56.58	27.57	4.17	35.52	-3.78	74.00	-21.20 Peak
	2		2500.00	42.28	46.05	27.60	4.18	35.55	-3.77	74.00	-31.72 Peak
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1		2483.50	20.65	24.43	27.57	4.17	35.52	-3.78	54.00	-33.35 Average
	2		2500.00	18.89	22.66	27.60	4.18	35.55	-3.77	54.00	-35.11 Average

802.11g				CH11							
Vertical			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1		2483.50	65.88	69.66	27.57	4.17	35.52	-3.78	74.00	-8.12 Peak
	2		2500.00	48.26	52.03	27.60	4.18	35.55	-3.77	74.00	-25.74 Peak
			Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
			MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1		2483.50	24.71	28.49	27.57	4.17	35.52	-3.78	54.00	-29.29 Average
	2		2500.00	21.65	25.42	27.60	4.18	35.55	-3.77	54.00	-32.35 Average

802.11n(HT20)						CH01					
Horizontal	Freq		Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1	2310.00	35.97	39.43	-3.46	27.66	4.03	35.15	74.00	-38.03	Peak
	2	2390.00	56.23	59.80	-3.57	27.66	4.09	35.32	74.00	-17.77	Peak
	3	2400.00	60.87	64.41	-3.54	27.70	4.10	35.34	74.00	-13.13	Peak
	Freq		Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1	2310.00	16.35	20.21	-3.86	27.26	4.03	35.15	54.00	-37.65	Average
	2	2390.00	18.09	21.92	-3.83	27.40	4.09	35.32	54.00	-35.91	Average
	3	2400.00	23.55	27.37	-3.82	27.42	4.10	35.34	54.00	-30.45	Average


802.11n(HT20)						CH01					
Vertical	Freq		Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1	2310.00	42.12	45.58	-3.46	27.66	4.03	35.15	74.00	-31.88	Peak
	2	2390.00	61.32	64.89	-3.57	27.66	4.09	35.32	74.00	-12.68	Peak
	3	2400.00	68.02	71.56	-3.54	27.70	4.10	35.34	74.00	-5.98	Peak
	Freq		Level	Read Level	Factor	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
	MHz		dBuV/m	dBuV	dB/m	dB/m	dB	dB	dBuV/m	dB	
	1	2310.00	15.11	18.97	-3.86	27.26	4.03	35.15	54.00	-38.89	Average
	2	2390.00	23.13	26.96	-3.83	27.40	4.09	35.32	54.00	-30.87	Average
	3	2400.00	35.87	39.69	-3.82	27.42	4.10	35.34	54.00	-18.13	Average

802.11n(HT20)				CH11						
Horizontal		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1	2483.50	48.58	52.36	27.57	4.17	35.52	-3.78	74.00	-25.42 Peak
	2	2500.00	41.29	45.06	27.60	4.18	35.55	-3.77	74.00	-32.71 Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1	2483.50	22.22	26.00	27.57	4.17	35.52	-3.78	54.00	-31.78 Average
	2	2500.00	15.38	19.15	27.60	4.18	35.55	-3.77	54.00	-38.62 Average

802.11n(HT20)				CH11						
Vertical		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1	2483.50	62.29	66.07	27.57	4.17	35.52	-3.78	74.00	-11.71 Peak
	2	2500.00	46.56	50.33	27.60	4.18	35.55	-3.77	74.00	-27.44 Peak
		Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Limit Line	Over Limit	Remark
		MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB
	1	2483.50	21.19	24.97	27.57	4.17	35.52	-3.78	54.00	-32.81 Average
	2	2500.00	19.41	23.18	27.60	4.18	35.55	-3.77	54.00	-34.59 Average

7. 6dB Bandwidth Test

7.1. Block Diagram of Test Setup



7.2. Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

7.3. Test Procedure

Use the test method described in ANSI C63.10 Section 11.8.2:

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

7.4. Test Results

Pass

Note 1: Final Level = Spectrum Analyzer Read Level + Cable Loss

Test Mode	CH	-6dB bandwidth (MHz)	Limit (KHz)
11b	CH01	9.06	≥ 500
	CH06	9.42	
	CH11	9.48	
11g	CH01	17.22	≥ 500
	CH06	17.28	
	CH11	17.28	
11n HT20	CH01	17.10	≥ 500
	CH06	18.00	
	CH11	18.06	
Conclusion : PASS			

802.11b

Ref 20 dBm *Att 30 dB SWT 2.5 ms 9.060000000 MHz

RBW 300 kHz Delta 3 [T1] -0.32 dB

VBW 1 MHz

Marker 1 [T1] 6.23 dBm 2.407560000 GHz

Marker 2 [T1] 11.88 dBm 2.412180000 GHz

Offset 3.5 dB

1 PK MAXH

Center 2.412 GHz 3 MHz/ Span 30 MHz

Date: 2.SEP.2026 17:22:29

1 PR
MAXH

Ref 20 dBm *Att 30 dB RBW 300 kHz Delta 3 [T1] VBW 1 MHz SWT 2.5 ms 0.64 dB 9.420000000 MHz

20 Offset 3.3 dB

10

0

-10

-20

-30

-40

-50

-60

-70

-80

Center 2.437 GHz 3 MHz/ Span 30 MHz

Marker 1 [T1] 5.06 dBm 2.432200000 GHz


Marker 2 [T1] 11.48 dBm 2.435600000 GHz

P1 5.48 dBm

3dB

Date: 2.SEP.2026 17:23:39


CH11



Date: 2.SEP.2026 17:24:56


Type:802.11g

CH01




Date: 2.SEP.2026 17:33:47

CH06



Date: 2.SEP.2026 17:34:57

CH11




Date: 2.SEP.2026 17:36:18

Type:


802.11n(HT20)

CH01




Date: 2.SEP.2026 17:38:04

CH06



Date: 2.SEP.2026 17:39:44


CH11



Date: 2.SEP.2026 17:40:45

8. OUTPUT POWER TEST

8.1. Block Diagram of Test Setup



8.2. Limit

FCC Part 15C 15.247 b(3):

For systems using digital modulation in the 2400—2483.5MHz, The Peak output Power shall not exceed 1W(30dBm), As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level.

8.3. Test Procedure

- 1, Connected the EUT's antenna port to Spectrum Analyzer.
- 2, Use the test method described in ANSI C63.10 clause 11.9.2.2.2:
 - 1) Set span to at least 1.5 times the OBW.
 - 2) Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
 - 3) Set VBW $\geq [3 \times \text{RBW}]$.
 - 4) Number of points in sweep $\geq [2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing $\leq \text{RBW} / 2$, so that narrowband signals are not lost between frequency bins.).
 - 5) Sweep time = auto.
 - 6) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
 - 7) If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at the maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no OFF intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run."
 - 8) Trace average at least 100 traces in power averaging (rms) mode.
 - 9) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

Note: The cable loss needs to be compensated into the data.

8.4. Test Results

Pass

Note 1: Final Level = Spectrum Analyzer Read Level + Cable Loss

Test Mode	CH	Output power (dBm)	Limit (dBm)
11b	CH01	15.58	≤ 30
	CH06	15.44	
	CH11	15.73	
11g	CH01	14.58	≤ 30
	CH06	14.37	
	CH11	14.78	
11n HT20	CH01	13.39	≤ 30
	CH06	13.24	
	CH11	13.63	

802.11b




Date: 2.SEP.2026 19:24:38



Date: 2.SEP.2026 19:25:06


CH11



Date: 2.SEP.2026 19:25:27


802.11g

CH01




Date: 2.SEP.2026 19:26:02

CH06



Date: 2.SEP.2026 19:26:23


CH11



Type:


802.11n(HT20)

CH01




Date: 2.SEP.2026 19:46:02

CH06



Date: 2.SEP.2026 19:46:21


CH11



Date: 2.SEP.2026 19:46:42

9. POWER SPECTRAL DENSITY TEST

9.1. Block Diagram of Test Setup



9.2. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

9.3. Test Procedure

Use the test method described in ANSI C63.10 clause 11.10.2:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

9.4. Test Results

Pass

Note 1: Final Level = Spectrum Analyzer Read Level + Cable Loss

Test Mode	CH	Power density (dBm/3KHz)	Limit (dBm/3KHz)
11b	CH01	-7.46	8
	CH06	-6.82	
	CH11	-7.12	
11g	CH01	-10.48	8
	CH06	-11.25	
	CH11	-10.95	
11n HT20	CH01	-11.27	8
	CH06	-13.41	
	CH11	-12.49	
Conclusion : PASS			

802.11b

Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] -7.46 dBm
 VBW 10 kHz SWT 3.4 s 2.412060000 GHz

20 Offset 3.8 dB

1 Pk
 MAX

3dB

Center 2.412 GHz 3 MHz/ Span 30 MHz

Date: 2.SEP.2026 17:44:10

Ref 20 dBm *Att 30 dB RBW 3 kHz Marker 1 [T1] -6.82 dBm
 VBW 10 kHz SWT 3.4 s 2.436100000 GHz

20 Offset 3.0 dB

1 PK
MAXH


1

3 MHz/

Span 30 MHz

Date: 2.SEP.2026 17:45:54

CH11



Date: 2.SEP.2026 17:46:25

802.11g

Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 {T1 } -10.48 dBm
 VBW 10 kHz SWT 3.4 s 2.410920000 GHz

20 Offset 3.8 dB

1 PK
MAXH

1

30 MHz

Center 2.412 GHz 3 MHz/ Span 30 MHz

Date: 2.SEP.2026 17:56:45

Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] -11.25 dBm
 VBW 10 kHz SWT 3.4 s 2.436340000 GHz

20 Offset 3.3 dB


1 PK
MAXH

1

Center 2.437 GHz 3 MHz/ Span 30 MHz

Date: 2.SEP.2026 17:57:10

CH11



Date: 2.SEP.2026 17:57:33

802.11n(HT20)

Ref 20 dBm *Att 30 dB *RBW 3 kHz Marker 1 {T1 } VBW 10 kHz -11.27 dBm SWT 3.4 s 2.413200000 GHz

20 Offset 3.8 dB

1 PK MAX

1

Center 2.412 GHz 3 MHz/ Span 30 MHz

Date: 2.SEP.2026 17:58:04

Ref 20 dBm *Att 30 dB *RBW 3 kHz VBW 10 kHz Marker 1 [T1] -13.41 dBm 2.436340000 GHz


20 Offset 3.3 dB

1 PK MAXH

Center 2.437 GHz 3 MHz/ Span 30 MHz

Date: 2.SEP.2026 17:58:40

CH11



Date: 2.SEP.2026 17:59:20

10.ANTENNA REQUIREMENT

10.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. Antenna Connected Construction

The antennas used for this product are FPC antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 4.98dBi.

..... End of Report