FCC PART 15C TEST REPORT FOR CERTIFICATION

On Behalf of

Shenzhen Shimu Technology Co., Ltd.
****

FCC ID：2A4O2-S108X

Report Type:	**Product Type:**
Original report	Permanent Outdoor lights Pro Gen2

Test Engineer: **Kelvin Liang** Kelvin Liang

Report Number: **STD-JBO260303F-003**

Report Date: **2026.09.04**

Reviewed By: **Garman Mo** Garman Mo

Prepared By: Bestway Compliance Co.,Ltd.
Unit 301,Building 3, No. 178, Fenggang Section,Dongshen Road,Fenggang Town, Dongguan, Guangdong,China
Tel: +86-769-82699983
www.bestway-compliance.com

BESTWAY COMPLIANCE CO., LTD. 东莞百世威技术有限公司 (stamp)

The device described above is tested by Bestway Compliance Co.,Ltd. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and Bestway Compliance Co.,Ltd. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements. This Report is made under FCC Part 2.1074. No modifications were required during testing to bring this product into compliance. This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Bestway Compliance Co.,Ltd.

This report does not imply product certification, approval, or endorsement by A2LA or any agency of the Federal Government.

TABLE OF CONTENTS

Description Page

1. SUMMARY OF STANDARDS AND RESULTS 3
1.1. Description of Standards and Results 3
2. GENERAL INFORMATION 4
2.1. Description of Equipment Under Test 4
2.2. Feature of Equipment Under Test 5
2.3. Tested Supporting System Details 5
2.4. Test Information 6
2.5. Equipments Used during the Test 6
2.6. Test Facility 8
2.7. Measurement Uncertainty (95% confidence levels, k=2) 8
3. POWER LINE CONDUCTED EMISSION TEST 9
3.1. Block Diagram of Test Setup 9
3.2. Power Line Conducted Emission Test Limits 9
3.3. Test Procedure 9
3.4. Power Line Conducted Emission Test Result 9
4. RADIATED EMISSION TEST 22
4.1. Block Diagram of Test Setup 22
4.2. Radiated Emission Limit 23
4.3. Test Procedure 23
4.4. Radiated Emission Test Results 24
5. CONDUCTED SPURIOUS EMISSIONS 43
5.1. Block Diagram of Test Setup 43
5.2. Limit 43
5.3. Test Procedure 43
5.4. Test result 43
6. BAND EDGE COMPLIANCE TEST 51
6.1. Limit 51
6.2. Test Procedure 51
6.3. Test Results 51
7. 6dB Bandwidth Test 54
7.1. Block Diagram of Test Setup 54
7.2. Limit 54
7.3. Test Procedure 54
7.4. Test Results 54
8. OUTPUT POWER TEST 55
8.1. Limit (FCC Part 15C 15.247 b(3)) 57
8.2. Test Procedure 57
8.3. Test Results 57
9. POWER SPECTRAL DENSITY TEST 60
9.1. Limit 60
9.2. Test Procedure 60
9.3. Test Results 60
10. ANTENNA REQUIREMENT 63
10.1. Standard Applicable 63
10.2. Antenna Connected Construction 63

1. SUMMARY OF STANDARDS AND RESULTS

1.1.Description of Standards and Results

The EUT has been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	**Standard**	**Results**
Power Line Conducted Emission	FCC Part 15: 15.207	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.205	PASS
Band Edge Compliance	FCC Part 15: 15.247(d)	PASS
Conducted spurious emissions	FCC Part 15: 15.247(d)	PASS
6dB Bandwidth Test	FCC Part 15: 15.247(a)	PASS
Peak Output Power	FCC Part 15: 15.247(b)	PASS
Power Spectral Density	FCC Part 15: 15.247(e)	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

Note: Decision rule is the rule that describes how measurement uncertainty is accounted for when stating conformity with a specified requirement. When decision rule is applicable, please refer to the most updated version announced in our website:
https://en.bestway-compliance.com/pages/decision-rule-of-compliance-with-specification

2. GENERAL INFORMATION

2.1.Description of Equipment Under Test

Applicant:	Shenzhen Shimu Technology Co., Ltd.
Address:	Room 703, East Commercial Building, 222 Minzhi Avenue, Minkang Community, Minzhi Street, Longhua District, Shenzhen, Guangdong, China
Manufacturer:	Shenzhen Fitop Lighting Technology Co.Ltd
Address:	1st, 2nd, 3rd, 4th, and 5th floors of Building B, No. 4 Shitoushan Industrial Zone, Zhoushi Road, Langxin Community, Shiyan Street, Bao'an District, Shenzhen, Guangdong, China
Product Name:	Permanent Outdoor lights Pro Gen2
Trade Mark:	ASAHOM
Test Model:	S108A, S108B, S108C, S108D, S108E, S108F
Model Declaration:	The internal circuits and structures of all models are exactly the same. The S108E and S108F use two power supplies and select the maximum power for testing. The S108A, S108B, S108C, and S108D all use one power supply. S108D is the one with the maximum power in the power supply, so a differential test was conducted.
Sample Type:	Prototype production
SN:	JBO260303-09, JBO260303-10, JBO260303-11, JBO260303-12, JBO260303-13, JBO260303-14
Date of Receipt:	2026.06.13
Date of Test:	2026.06.25-2026.09.03
Test Power Supply:	Input: AC 100-130V, 50/60Hz Output: DC 29.5V 3.39A (per adapter)

2.2. Feature of Equipment Under Test

Product Feature & Specification	
BLE	
Hardware version	N/A
Software version	EspRFTestTool_v3.6
Modulation Type	GFSK
Operating Frequency Range	The frequency range used is 2402MHz-2480MHz(40)channels
Data Transmission Rate	1Mbps
Bluetooth Version	Bluetooth LE V5.2

Antenna System

BLE	
Type of Antenna	FPC Antenna
Antenna Peak Gain	Peak Gain: 4.98dBi

2.3. Tested Supporting System Details

RF Test Tool: EspRFTestTool_v3.6

1. Use the UART serial board to connect the Bluetooth correctly; RX —>TX; TX—>RX; 3.3V —>VCC; GND —>GND;
2. Connect the UART serial board to the computer
3. Click Serial port test tool to enter the fixed frequency test
4. Perform all tests at the default power level

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Lenovo	Notebook	X220i	428632C
Lenovo	Adapter	42T4420	N322

External I/O Cable

Cable Description	Length (m)	From Port	To
Data Cable	0.1	EUT	Debug Board

2.4.Test Information

Frequency band(MHz)				2402-2480			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

2.5.Equipments Used during the Test

Conducted Emissions

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Until	Cal. Interval
1.	Shielding Room	AUDIX	N/A	N/A	2026/12/20	3 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESR7	101487	2028/04/27	2 Year
3.	V-LISN	Rohde & Schwarz	NNLK 8122	8122-00128	2027/02/17	2 Year
4.	Coaxial cable CE	YuanDao	RG223	N/A	2027/04/27	1 Year
5.	Test Software	AUDIX	e3	V15922	N/A	N/A
Note: N/A means Not applicable.						

For frequency range 30MHz~1000MHz (In 3m Anechoic Chamber)

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Until	Cal. Interval
1.	Semi-anechoic chamber	AUDIX	N/A	N/A	2026/12/20	3 Year
2.	EMI Test Receiver	R&S	ESR7	101487	2028/04/27	2 Year
3.	Biconical Logarithmic Antenna	SCHWARDZBECK	VULB 9162	9162-104	2028/05/23	2 Year
4.	Coaxial cable RE	PEWC	CFD400NL	N/A	2027/04/27	1 Year
5.	Loop Antenna	Beijing Daze	ZN30900C	1062	2026/10/21	2 Year
6.	Test Software	AUDIX	e3	V15922	N/A	N/A
Note: N/A means Not applicable.						

For frequency range above 1GHz (In 3m Anechoic Chamber)

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Until	Cal. Interval
1.	Semi-anechoic chamber	AUDIX	N/A	N/A	2026/12/20	3 Year
2.	Spectrum Analyzer	R&S	FSP	100615	2027/04/27	1 Year
3.	Horn Antenna	SCHWARDZBECK	BBHA 9170	895	2026/10/20	2 Year
4.	Horn Antenna	SCHWARDZBECK	BBHA 9120 D	9120D-1515	2026/10/20	2 Year
5.	Broadband Preamplifier	SCHWARDZBECK	BBV9718	9718-269	2028/04/27	2 Year
6.	Broadband Preamplifier	SKET	LNPA-1840	SK2019121201	2028/04/27	2 Year
7.	RF Cable	SKET	RC-40G-K-M/K-M-0.6M	N/A	2027/04/27	1 Year
8.	RF Cable	SKET	RC-40G-K-M/K-M-8M	N/A	2027/04/27	1 Year
9.	Test Software	AUDIX	e3	V15922	N/A	N/A
Note: N/A means Not applicable.						

RF Conducted Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Until	Cal. Interval
1.	Spectrum Analyzer	R&S	FSP	100615	2027/04/27	2 Year
2.	RF Cable	STD	/	/	/	/

2.6. Test Facility

Site Description

Name of Firm	:	Bestway Compliance Co.,Ltd. Unit 301,Building 3, No. 178, Fenggang Section,Dongshen Road,Fenggang Town, Dongguan, Guangdong,China
EMC Lab.	:	Certificated by Industry Canada Registration Number: 34294 Valid Date: 2027/03/31
	:	Certificated by FCC USA. Designation No.: CN1415 Valid Date: 2027/03/31

2.7.Measurement Uncertainty (95% confidence levels, k=2)

Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	2.90dB(150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	5.34dB(30M~1GHz, Distance: 3m)
Uncertainty for Radiation Emission test in 3m chamber(1GHz-40GHz)	4.14dB(1~6GHz, Distance: 3m)
	4.60dB(6~18GHz, Distance: 3m)
	4.94dB(18~40GHz, Distance: 3m)
Uncertainty for Output power test	1.34dB
Uncertainty for Bandwidth test	92.3kHz

3. POWER LINE CONDUCTED EMISSION TEST

3.1.Block Diagram of Test Setup



3.2.Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

3.3.Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via PC connected to the power mains through a line impedance stabilization network (V-LISN). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2020 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESR7) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4.Power Line Conducted Emission Test Result

Model:	**S108A**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Line**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.17	28.96	28.69	0.27	0.06	55.06	-26.10	Average
2	0.17	36.96	36.69	0.27	0.06	65.06	-28.10	QP
3	0.19	29.84	29.57	0.27	0.06	54.01	-24.17	Average
4	0.19	35.84	35.57	0.27	0.06	64.01	-28.17	QP
5	0.42	19.77	19.48	0.29	0.07	47.54	-27.77	Average
6	0.42	33.77	33.48	0.29	0.07	57.54	-23.77	QP
7	12.41	40.71	36.55	4.16	0.47	50.00	-9.29	Average
8	12.41	45.71	41.55	4.16	0.47	60.00	-14.29	QP
9	14.48	38.01	33.17	4.84	0.49	50.00	-11.99	Average
10	14.48	43.01	38.17	4.84	0.49	60.00	-16.99	QP
11	28.23	33.89	26.36	7.53	0.73	50.00	-16.11	Average
12	28.23	42.89	35.36	7.53	0.73	60.00	-17.11	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108A**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Neutral**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.17	32.12	31.83	0.29	0.06	54.84	-22.72	Average
2	0.17	41.12	40.83	0.29	0.06	64.84	-23.72	QP
3	0.19	34.20	33.91	0.29	0.06	54.01	-19.81	Average
4	0.19	41.20	40.91	0.29	0.06	64.01	-22.81	QP
5	0.26	30.15	29.86	0.29	0.06	51.50	-21.35	Average
6	0.26	37.15	36.86	0.29	0.06	61.50	-24.35	QP
7	0.34	22.74	22.43	0.31	0.07	49.12	-26.38	Average
8	0.34	32.74	32.43	0.31	0.07	59.12	-26.38	QP
9	12.41	35.96	32.10	3.86	0.47	50.00	-14.04	Average
10	12.41	42.96	39.10	3.86	0.47	60.00	-17.04	QP
11	28.55	31.96	24.39	7.57	0.74	50.00	-18.04	Average
12	28.55	41.96	34.39	7.57	0.74	60.00	-18.04	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108B**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Line**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	25.14	24.88	0.26	0.05	56.00	-30.86	Average
2	0.15	47.14	46.88	0.26	0.05	66.00	-18.86	QP
3	0.36	25.48	25.19	0.29	0.07	48.69	-23.21	Average
4	0.36	36.48	36.19	0.29	0.07	58.69	-22.21	QP
5	0.45	22.13	21.83	0.30	0.08	46.85	-24.72	Average
6	0.45	34.13	33.83	0.30	0.08	56.85	-22.72	QP
7	10.35	40.73	37.39	3.34	0.43	50.00	-9.27	Average
8	10.35	46.73	43.39	3.34	0.43	60.00	-13.27	QP
9	14.48	36.11	31.27	4.84	0.49	50.00	-13.89	Average
10	14.48	43.11	38.27	4.84	0.49	60.00	-16.89	QP
11	26.54	37.47	30.16	7.31	0.70	50.00	-12.53	Average
12	26.54	46.47	39.16	7.31	0.70	60.00	-13.53	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108B**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Neutral**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	26.44	26.16	0.28	0.05	56.00	-29.56	Average
2	0.15	45.44	45.16	0.28	0.05	66.00	-20.56	QP
3	0.23	28.45	28.16	0.29	0.06	52.41	-23.96	Average
4	0.23	42.45	42.16	0.29	0.06	62.41	-19.96	QP
5	0.27	26.08	25.79	0.29	0.06	51.07	-24.99	Average
6	0.27	40.08	39.79	0.29	0.06	61.07	-20.99	QP
7	10.35	37.90	34.97	2.93	0.43	50.00	-12.10	Average
8	10.35	42.90	39.97	2.93	0.43	60.00	-17.10	QP
9	13.79	32.40	28.01	4.39	0.48	50.00	-17.60	Average
10	13.79	40.40	36.01	4.39	0.48	60.00	-19.60	QP
11	27.26	34.61	27.21	7.40	0.72	50.00	-15.39	Average
12	27.26	42.61	35.21	7.40	0.72	60.00	-17.39	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108C**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Line**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	25.46	25.20	0.26	0.05	56.00	-30.54	Average
2	0.15	39.46	39.20	0.26	0.05	66.00	-26.54	QP
3	0.29	22.85	22.57	0.28	0.06	50.54	-27.69	Average
4	0.29	38.85	38.57	0.28	0.06	60.54	-21.69	QP
5	7.58	39.96	37.64	2.32	0.33	50.00	-10.04	Average
6	7.58	47.96	45.64	2.32	0.33	60.00	-12.04	QP
7	8.28	37.67	35.09	2.58	0.35	50.00	-12.33	Average
8	8.28	45.67	43.09	2.58	0.35	60.00	-14.33	QP
9	11.03	40.16	36.53	3.63	0.44	50.00	-9.84	Average
10	11.03	47.16	43.53	3.63	0.44	60.00	-12.84	QP
11	27.29	42.50	35.09	7.41	0.72	50.00	-7.50	Average
12	27.29	51.50	44.09	7.41	0.72	60.00	-8.50	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108C**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Neutral**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.15	25.05	24.77	0.28	0.05	56.00	-30.95	Average
2	0.15	42.05	41.77	0.28	0.05	66.00	-23.95	QP
3	0.23	29.42	29.13	0.29	0.06	52.41	-22.99	Average
4	0.23	41.42	41.13	0.29	0.06	62.41	-20.99	QP
5	0.33	24.55	24.24	0.31	0.07	49.34	-24.79	Average
6	0.33	38.55	38.24	0.31	0.07	59.34	-20.79	QP
7	8.28	37.20	34.53	2.67	0.35	50.00	-12.80	Average
8	8.28	43.20	40.53	2.67	0.35	60.00	-16.80	QP
9	15.17	39.36	34.49	4.87	0.50	50.00	-10.64	Average
10	15.17	45.36	40.49	4.87	0.50	60.00	-14.64	QP
11	27.58	38.35	30.91	7.44	0.72	50.00	-11.65	Average
12	27.58	47.35	39.91	7.44	0.72	60.00	-12.65	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108D**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Line**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.21	23.60	23.33	0.27	0.06	53.27	-29.67	Average
2	0.21	36.60	36.33	0.27	0.06	63.27	-26.67	QP
3	0.28	22.95	22.67	0.28	0.06	50.80	-27.85	Average
4	0.28	37.95	37.67	0.28	0.06	60.80	-22.85	QP
5	0.32	28.37	28.08	0.29	0.07	49.68	-21.31	Average
6	0.32	36.37	36.08	0.29	0.07	59.68	-23.31	QP
7	7.58	45.39	43.07	2.32	0.33	50.00	-4.61	Average
8	7.58	52.39	50.07	2.32	0.33	60.00	-7.61	QP
9	17.24	39.69	34.06	5.63	0.54	50.00	-10.31	Average
10	17.24	45.69	40.06	5.63	0.54	60.00	-14.31	QP
11	27.85	42.75	35.26	7.49	0.73	50.00	-7.25	Average
12	27.85	50.75	43.26	7.49	0.73	60.00	-9.25	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108D**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Neutral**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.22	28.28	27.99	0.29	0.06	52.74	-24.46	Average
2	0.22	42.28	41.99	0.29	0.06	62.74	-20.46	QP
3	0.32	27.34	27.03	0.31	0.07	49.68	-22.34	Average
4	0.32	39.34	39.03	0.31	0.07	59.68	-20.34	QP
5	7.59	36.77	34.13	2.64	0.33	50.00	-13.23	Average
6	7.59	43.77	41.13	2.64	0.33	60.00	-16.23	QP
7	10.35	35.52	32.59	2.93	0.43	50.00	-14.48	Average
8	10.35	43.52	40.59	2.93	0.43	60.00	-16.48	QP
9	13.79	35.96	31.57	4.39	0.48	50.00	-14.04	Average
10	13.79	42.96	38.57	4.39	0.48	60.00	-17.04	QP
11	27.24	39.21	31.81	7.40	0.72	50.00	-10.79	Average
12	27.24	50.21	42.81	7.40	0.72	60.00	-9.79	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108E**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Line**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	4.83	42.37	40.94	1.43	0.29	46.00	-3.63	Average
2	4.83	50.37	48.94	1.43	0.29	56.00	-5.63	QP
3	11.03	37.18	33.55	3.63	0.44	50.00	-12.82	Average
4	11.03	48.18	44.55	3.63	0.44	60.00	-11.82	QP
5	15.17	43.68	38.64	5.04	0.50	50.00	-6.32	Average
6	15.17	49.68	44.64	5.04	0.50	60.00	-10.32	QP
7	17.24	41.45	35.82	5.63	0.54	50.00	-8.55	Average
8	17.24	47.45	41.82	5.63	0.54	60.00	-12.55	QP
9	23.88	39.03	32.09	6.94	0.67	50.00	-10.97	Average
10	23.88	49.03	42.09	6.94	0.67	60.00	-10.97	QP
11	29.94	38.27	30.53	7.74	0.76	50.00	-11.73	Average
12	29.94	47.27	39.53	7.74	0.76	60.00	-12.73	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108E**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Neutral**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	0.22	25.84	25.55	0.29	0.06	52.74	-26.90	Average
2	0.22	38.84	38.55	0.29	0.06	62.74	-23.90	QP
3	4.83	42.07	40.38	1.69	0.29	46.00	-3.93	Average
4	4.83	51.07	49.38	1.69	0.29	56.00	-4.93	QP
5	11.72	40.00	36.44	3.56	0.45	50.00	-10.00	Average
6	11.72	45.00	41.44	3.56	0.45	60.00	-15.00	QP
7	17.24	39.42	33.88	5.54	0.54	50.00	-10.58	Average
8	17.24	44.42	38.88	5.54	0.54	60.00	-15.58	QP
9	23.94	36.43	29.48	6.95	0.67	50.00	-13.57	Average
10	23.94	45.43	38.48	6.95	0.67	60.00	-14.57	QP
11	29.55	34.84	27.16	7.68	0.75	50.00	-15.16	Average
12	29.55	43.84	36.16	7.68	0.75	60.00	-16.16	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108F**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Line**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	8.27	38.80	36.22	2.58	0.35	50.00	-11.20	Average
2	8.27	43.80	41.22	2.58	0.35	60.00	-16.20	QP
3	8.96	42.42	39.58	2.84	0.38	50.00	-7.58	Average
4	8.96	47.42	44.58	2.84	0.38	60.00	-12.58	QP
5	10.34	43.88	40.54	3.34	0.43	50.00	-6.12	Average
6	10.34	49.88	46.54	3.34	0.43	60.00	-10.12	QP
7	15.17	46.85	41.81	5.04	0.50	50.00	-3.15	Average
8	15.17	55.55	50.51	5.04	0.50	60.00	-4.45	QP
9	22.91	38.24	31.43	6.81	0.66	50.00	-11.76	Average
10	22.91	48.24	41.43	6.81	0.66	60.00	-11.76	QP
11	27.75	39.96	32.49	7.47	0.72	50.00	-10.04	Average
12	27.75	47.96	40.49	7.47	0.72	60.00	-12.04	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108F**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Phase:	**Neutral**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	dB	dBuV	dB	
1	8.28	42.19	39.52	2.67	0.35	50.00	-7.81	Average
2	8.28	47.19	44.52	2.67	0.35	60.00	-12.81	QP
3	10.34	43.03	40.11	2.92	0.43	50.00	-6.97	Average
4	10.34	48.03	45.11	2.92	0.43	60.00	-11.97	QP
5	14.40	39.90	35.29	4.61	0.49	50.00	-10.10	Average
6	14.40	43.90	39.29	4.61	0.49	60.00	-16.10	QP
7	15.16	44.01	39.14	4.87	0.50	50.00	-5.99	Average
8	15.16	51.01	46.14	4.87	0.50	60.00	-8.99	QP
9	23.87	36.52	29.57	6.95	0.67	50.00	-13.48	Average
10	23.87	44.52	37.57	6.95	0.67	60.00	-15.48	QP
11	28.31	38.97	31.44	7.53	0.73	50.00	-11.03	Average
12	28.31	47.97	40.44	7.53	0.73	60.00	-12.03	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

4. RADIATED EMISSION TEST

4.1.Block Diagram of Test Setup

For frequency range 30MHz-1000MHz



For frequency range above 1GHz



4.2.Radiated Emission Limit

15.247&209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark : (1) Emission level dBμV = 20 log Emission level μV/m
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.3.Test Procedure

Frequency below 30MHz:
The EUT setup on the turn table which has 0.8m height to the ground. The turn table rotated 360 degrees and antenna fixed to 1 m to find the maximum emission level. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10-2020 regulation.

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)*2.4m(W)*0.3m(H) on the ground . The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and

let it working in test mode, then test it.EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horm antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2020 on radiated emission Test.

The bandwidth of the EMI test receiver (R&S ESR7) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

4.4. Radiated Emission Test Results

PASS.

Note 1: Final Level= Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
Note 2: The emissions (9kHz~30MHz) not reported for there is no emission be found.
Note 3: The emission levels of other frequencies(test frequency bang is above 1GHz) are very lower than the limit and not show in test report.

Frequency: 30MHz~1GHz	
Model:	**S108A**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-15**
Polarization:	**Horizontal**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	113.32	23.34	6.24	17.10	1.01	43.50	-20.16	QP
2	171.99	27.48	11.80	15.68	1.22	43.50	-16.02	QP
3	193.09	32.25	14.70	17.55	1.28	43.50	-11.25	QP
4	281.01	25.78	5.54	20.24	1.55	46.00	-20.22	QP
5	375.94	35.64	12.94	22.70	1.81	46.00	-10.36	QP
6	451.14	33.28	9.21	24.07	1.98	46.00	-12.72	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108A**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Polarization:	**Vertical**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	36.51	27.76	10.07	17.69	0.66	40.00	-12.24	QP
2	46.18	28.08	8.41	19.67	0.73	40.00	-11.92	QP
3	63.31	23.70	5.55	18.15	0.80	40.00	-16.30	QP
4	112.13	24.56	7.26	17.30	0.99	43.50	-18.94	QP
5	180.65	27.22	10.92	16.30	1.24	43.50	-16.28	QP
6	416.18	27.56	4.04	23.52	1.93	46.00	-18.44	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108B**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Polarization:	**Horizontal**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	116.54	24.14	7.57	16.57	1.04	43.50	-19.36	QP
2	147.40	23.59	9.10	14.49	1.13	43.50	-19.91	QP
3	198.59	33.90	15.79	18.11	1.29	43.50	-9.60	QP
4	283.98	30.58	10.25	20.33	1.58	46.00	-15.42	QP
5	375.94	36.62	13.92	22.70	1.81	46.00	-9.38	QP
6	413.27	34.97	11.52	23.45	1.91	46.00	-11.03	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108B**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Polarization:	**Vertical**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	35.13	29.25	11.93	17.32	0.65	40.00	-10.75	QP
2	45.86	29.21	9.56	19.65	0.72	40.00	-10.79	QP
3	65.34	26.15	8.59	17.56	0.82	40.00	-13.85	QP
4	113.32	26.09	8.99	17.10	1.01	43.50	-17.41	QP
5	193.09	26.14	8.59	17.55	1.28	43.50	-17.36	QP
6	416.18	28.52	5.00	23.52	1.93	46.00	-17.48	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108C**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-15**
Polarization:	**Horizontal**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	176.27	35.46	19.47	15.99	1.23	43.50	-8.04	QP
2	195.14	37.06	19.28	17.78	1.31	43.50	-6.44	QP
3	204.24	35.75	17.54	18.21	1.35	43.50	-7.75	QP
4	217.54	35.77	17.40	18.37	1.36	46.00	-10.23	QP
5	375.94	36.36	13.66	22.70	1.81	46.00	-9.64	QP
6	413.27	35.08	11.63	23.45	1.91	46.00	-10.92	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108C**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-15**
Polarization:	**Vertical**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	33.80	32.38	15.26	17.12	0.63	40.00	-7.62	QP
2	42.15	29.80	10.79	19.01	0.72	40.00	-10.20	QP
3	46.34	31.87	12.20	19.67	0.73	40.00	-8.13	QP
4	56.39	27.14	7.92	19.22	0.76	40.00	-12.86	QP
5	112.92	26.61	9.44	17.17	1.00	43.50	-16.89	QP
6	202.81	27.43	9.21	18.22	1.36	43.50	-16.07	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108D**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Polarization:	**Horizontal**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	114.11	24.98	8.01	16.97	1.03	43.50	-18.52	QP
2	153.74	29.09	14.38	14.71	1.18	43.50	-14.41	QP
3	198.59	37.11	19.00	18.11	1.29	43.50	-6.39	QP
4	312.18	35.35	14.40	20.95	1.64	46.00	-10.65	QP
5	375.94	34.44	11.74	22.70	1.81	46.00	-11.56	QP
6	422.06	33.94	10.33	23.61	1.94	46.00	-12.06	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108D**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Polarization:	**Vertical**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	32.98	27.41	10.47	16.94	0.61	40.00	-12.59	QP
2	46.18	31.02	11.35	19.67	0.73	40.00	-8.98	QP
3	65.34	28.20	10.64	17.56	0.82	40.00	-11.80	QP
4	115.32	27.42	10.56	16.86	1.04	43.50	-16.08	QP
5	190.41	27.53	10.15	17.38	1.28	43.50	-15.97	QP
6	419.11	29.19	5.68	23.51	1.86	46.00	-16.81	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108E**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Polarization:	**Horizontal**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	109.41	23.85	6.15	17.70	1.00	43.50	-19.65	QP
2	190.41	38.98	21.60	17.38	1.28	43.50	-4.52	QP
3	199.99	39.74	21.60	18.14	1.28	43.50	-3.76	QP
4	218.31	38.57	20.20	18.37	1.34	46.00	-7.43	QP
5	251.18	37.55	17.99	19.56	1.45	46.00	-8.45	QP
6	401.84	33.68	10.40	23.28	1.87	46.00	-12.32	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108E**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Polarization:	**Vertical**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	32.98	27.93	10.99	16.94	0.61	40.00	-12.07	QP
2	48.16	30.93	11.14	19.79	0.75	40.00	-9.07	QP
3	72.59	28.97	14.11	14.86	0.86	40.00	-11.03	QP
4	113.32	26.10	9.00	17.10	1.01	43.50	-17.40	QP
5	207.85	32.82	14.56	18.26	1.34	43.50	-10.68	QP
6	407.51	29.43	6.08	23.35	1.88	46.00	-16.57	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108F**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-16**
Polarization:	**Horizontal**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	78.41	24.68	10.88	13.80	0.90	40.00	-15.32	QP
2	115.73	26.75	9.93	16.82	1.04	43.50	-16.75	QP
3	192.42	37.65	20.12	17.53	1.27	43.50	-5.85	QP
4	210.05	36.54	18.20	18.34	1.38	43.50	-6.96	QP
5	306.75	32.25	11.42	20.83	1.62	46.00	-13.75	QP
6	410.38	34.14	10.79	23.35	1.87	46.00	-11.86	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Model:	**S108F**
Test Voltage:	**120Vac 60Hz**
Test Date:	**2026-08-15**
Polarization:	**Vertical**



	Freq	Level	Read Level	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dBuV/m	dB	
1	36.51	30.98	13.29	17.69	0.66	40.00	-9.02	QP
2	44.74	31.65	12.16	19.49	0.70	40.00	-8.35	QP
3	69.60	29.82	13.83	15.99	0.85	40.00	-10.18	QP
4	112.92	29.84	12.67	17.17	1.00	43.50	-13.66	QP
5	205.68	31.67	13.48	18.19	1.32	43.50	-11.83	QP
6	410.38	28.61	5.26	23.35	1.87	46.00	-17.39	QP

Note:Pre-testing all test modes and channels, and find the channel 2402MHz is the worst case, so only the worst case is included in this test report.

Frequency: 1GHz~18GHz	
Test Date:	**2026-07-01**
GFSK-1Mbps	**CH00**

Horizontal

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3278.000	45.90	49.07	28.49	4.80	36.46	-3.17	74.00	-28.10	Peak
2	4808.000	48.13	46.44	31.52	5.87	35.70	1.69	74.00	-25.87	Peak
3	7120.000	43.78	34.55	35.90	7.08	33.75	9.23	74.00	-30.22	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3278.000	22.83	26.00	28.49	4.80	36.46	-3.17	54.00	-31.17	Average
2	4808.000	28.02	26.33	31.52	5.87	35.70	1.69	54.00	-25.98	Average
3	7120.000	30.84	21.61	35.90	7.08	33.75	9.23	54.00	-23.16	Average

Vertical

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3278.000	45.90	49.07	28.49	4.80	36.46	-3.17	74.00	-28.10	Peak
2	4808.000	49.60	47.91	31.52	5.87	35.70	1.69	74.00	-24.40	Peak
3	7120.000	43.78	34.55	35.90	7.08	33.75	9.23	74.00	-30.22	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3278.000	23.93	27.10	28.49	4.80	36.46	-3.17	54.00	-30.07	Average
2	4808.000	27.81	26.12	31.52	5.87	35.70	1.69	54.00	-26.19	Average
3	7120.000	30.81	21.58	35.90	7.08	33.75	9.23	54.00	-23.19	Average

GFSK-1Mbps	CH19

Horizontal

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3244.000	39.17	42.28	28.59	4.78	36.48	-3.11	74.00	-34.83	Peak
2	4876.000	53.75	51.95	31.55	5.91	35.66	1.80	74.00	-20.25	Peak
3	10928.000	48.22	32.96	40.33	8.74	33.81	15.26	74.00	-25.78	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3244.000	22.20	25.31	28.59	4.78	36.48	-3.11	54.00	-31.80	Average
2	4876.000	25.14	23.34	31.55	5.91	35.66	1.80	54.00	-28.86	Average
3	10928.000	36.46	21.20	40.33	8.74	33.81	15.26	54.00	-17.54	Average

Vertical

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3244.000	44.90	48.01	28.59	4.78	36.48	-3.11	74.00	-29.10	Peak
2	4876.000	56.08	54.28	31.55	5.91	35.66	1.80	74.00	-17.92	Peak
3	10928.000	49.00	33.74	40.33	8.74	33.81	15.26	74.00	-25.00	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3244.000	22.22	25.33	28.59	4.78	36.48	-3.11	54.00	-31.78	Average
2	4876.000	29.55	27.75	31.55	5.91	35.66	1.80	54.00	-24.45	Average
3	10928.000	36.54	21.28	40.33	8.74	33.81	15.26	54.00	-17.46	Average

GFSK-1Mbps	CH39

Horizontal

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3312.000	40.72	43.86	28.47	4.83	36.44	-3.14	74.00	-33.28	Peak
2	4944.000	53.91	51.83	31.76	5.95	35.63	2.08	74.00	-20.09	Peak
3	9296.000	45.54	33.45	38.21	8.02	34.14	12.09	74.00	-28.46	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3312.000	21.99	25.13	28.47	4.83	36.44	-3.14	54.00	-32.01	Average
2	4944.000	28.04	25.96	31.76	5.95	35.63	2.08	54.00	-25.96	Average
3	9296.000	33.41	21.32	38.21	8.02	34.14	12.09	54.00	-20.59	Average

Vertical

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3312.000	44.11	47.25	28.47	4.83	36.44	-3.14	74.00	-29.89	Peak
2	4944.000	53.95	51.87	31.76	5.95	35.63	2.08	74.00	-20.05	Peak
3	9296.000	46.44	34.35	38.21	8.02	34.14	12.09	74.00	-27.56	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	3312.000	23.31	26.45	28.47	4.83	36.44	-3.14	54.00	-30.69	Average
2	4944.000	30.32	28.24	31.76	5.95	35.63	2.08	54.00	-23.68	Average
3	9296.000	33.72	21.63	38.21	8.02	34.14	12.09	54.00	-20.28	Average

Frequency: 18GHz~25GHz	
Test Date:	**2026-07-01**
GFSK-1Mbps	**CH00**

Horizontal

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20800.000	43.61	48.24	37.68	12.89	55.20	-4.63	74.00	-30.39	Peak
2	22410.000	44.46	48.67	37.66	13.39	55.26	-4.21	74.00	-29.54	Peak
3	23278.000	44.44	48.00	38.22	13.61	55.39	-3.56	74.00	-29.56	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20170.000	33.33	37.92	37.93	12.68	55.20	-4.59	54.00	-20.67	Average
2	21290.000	33.67	38.32	37.50	13.05	55.20	-4.65	54.00	-20.33	Average
3	22480.000	33.73	37.90	37.69	13.41	55.27	-4.17	54.00	-20.27	Average

Vertical

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20800.000	44.83	49.46	37.68	12.89	55.20	-4.63	74.00	-29.17	Peak
2	22410.000	44.27	48.48	37.66	13.39	55.26	-4.21	74.00	-29.73	Peak
3	23278.000	44.39	47.95	38.22	13.61	55.39	-3.56	74.00	-29.61	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20800.000	32.60	37.23	37.68	12.89	55.20	-4.63	54.00	-21.40	Average
2	22410.000	33.63	37.84	37.66	13.39	55.26	-4.21	54.00	-20.37	Average
3	23278.000	33.69	37.25	38.22	13.61	55.39	-3.56	54.00	-20.31	Average

GFSK-1Mbps	CH19

Horizontal

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20422.000	45.57	50.18	37.83	12.76	55.20	-4.61	74.00	-28.43	Peak
2	21486.000	45.91	50.49	37.50	13.12	55.20	-4.58	74.00	-28.09	Peak
3	23124.000	45.85	49.55	38.10	13.57	55.37	-3.70	74.00	-28.15	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20422.000	33.36	37.97	37.83	12.76	55.20	-4.61	54.00	-20.64	Average
2	21486.000	32.81	37.39	37.50	13.12	55.20	-4.58	54.00	-21.19	Average
3	23124.000	33.99	37.69	38.10	13.57	55.37	-3.70	54.00	-20.01	Average

Vertical

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20422.000	44.03	48.64	37.83	12.76	55.20	-4.61	74.00	-29.97	Peak
2	21486.000	43.41	47.99	37.50	13.12	55.20	-4.58	74.00	-30.59	Peak
3	23124.000	44.91	48.61	38.10	13.57	55.37	-3.70	74.00	-29.09	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20422.000	32.73	37.34	37.83	12.76	55.20	-4.61	54.00	-21.27	Average
2	21486.000	32.75	37.33	37.50	13.12	55.20	-4.58	54.00	-21.25	Average
3	23124.000	34.17	37.87	38.10	13.57	55.37	-3.70	54.00	-19.83	Average

GFSK-1Mbps	CH39

Horizontal

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20170.000	44.46	49.05	37.93	12.68	55.20	-4.59	74.00	-29.54	Peak
2	21164.000	44.21	48.87	37.53	13.01	55.20	-4.66	74.00	-29.79	Peak
3	22872.000	43.42	47.29	37.95	13.51	55.33	-3.87	74.00	-30.58	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20170.000	33.24	37.83	37.93	12.68	55.20	-4.59	54.00	-20.76	Average
2	21164.000	33.95	38.61	37.53	13.01	55.20	-4.66	54.00	-20.05	Average
3	22872.000	33.85	37.72	37.95	13.51	55.33	-3.87	54.00	-20.15	Average

Vertical

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20170.000	43.62	48.21	37.93	12.68	55.20	-4.59	74.00	-30.38	Peak
2	21164.000	44.44	49.10	37.53	13.01	55.20	-4.66	74.00	-29.56	Peak
3	22872.000	43.93	47.80	37.95	13.51	55.33	-3.87	74.00	-30.07	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	20170.000	32.75	37.34	37.93	12.68	55.20	-4.59	54.00	-21.25	Average
2	21164.000	33.43	38.09	37.53	13.01	55.20	-4.66	54.00	-20.57	Average
3	22872.000	33.13	37.00	37.95	13.51	55.33	-3.87	54.00	-20.87	Average

5. CONDUCTED SPURIOUS EMISSIONS

5.1.Block Diagram of Test Setup



5.2.Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

5.3.Test Procedure

Use the test method descried in ANSI C63.10:
The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions with peak detector.

Note: The cable loss and attenuator loss were offset into spectrum analyzer as an amplitude offset.

5.4.Test result

PASS (The testing data was attached in the next pages.)

Test Item:	SE	Type:	GFSK-1Mbps
CH00	 Date: 3.SEP.2026 17:10:00		
CH39	 Date: 3.SEP.2026 17:24:50		

Test Item:	SE	Type:	GFSK-1Mbps
CH00 Reference level	 Date: 3.SEP.2026 17:03:33		
CH00 30MHz-1GMHz	 Date: 3.SEP.2026 17:07:07		

CH00 Above 1GHz	 Date: 3.SEP.2026 17:08:16

Test Item:	SE	Type:	GFSK-1Mbps
CH19 Reference level	 Date: 3.SEP.2026 17:17:46		
CH19 30MHz-1GMHz	 Date: 3.SEP.2026 17:18:51		

CH19 Above 1GHz	 Date: 3.SEP.2026 17:20:00

Test Item:	SE	Type:	GFSK-1Mbps
CH39 Reference level	 Date: 3.SEP.2026 17:21:29		
CH39 30MHz-1GMHz	 Date: 3.SEP.2026 17:22:42		

CH39 Above 1GHz	 Date: 3.SEP.2026 17:23:24

6. BAND EDGE COMPLIANCE TEST

6.1. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

6.2. Test Procedure

Use the test method descried in ANSI C63.10 clause 6.10:

1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.

2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.

3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

(a) PEAK: RBW=1MHz; VBW=3MHz; Sweep=AUTO
(b) AVERAGE: RBW=1MHz; VBW=10Hz; Sweep=AUTO

6.3. Test Results

Pass (The testing data was attached in the next pages.)

GFSK-1Mbps | **CH00**

Horizontal

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	2310.000	33.73	37.19	27.66	4.03	35.15	-3.46	74.00	-40.27	Peak
2	2390.000	32.22	35.79	27.66	4.09	35.32	-3.57	74.00	-41.78	Peak
3	2400.000	56.71	60.25	27.70	4.10	35.34	-3.54	74.00	-17.29	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	2310.000	20.97	24.43	27.66	4.03	35.15	-3.46	54.00	-33.03	Average
2	2390.000	21.70	25.27	27.66	4.09	35.32	-3.57	54.00	-32.30	Average
3	2400.000	48.49	52.03	27.70	4.10	35.34	-3.54	54.00	-5.51	Average

GFSK-1Mbps | **CH00**

Vertical

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	2310.000	33.50	36.96	27.66	4.03	35.15	-3.46	74.00	-40.50	Peak
2	2390.000	34.27	37.84	27.66	4.09	35.32	-3.57	74.00	-39.73	Peak
3	2400.000	60.01	63.55	27.70	4.10	35.34	-3.54	74.00	-13.99	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	2310.000	21.02	24.48	27.66	4.03	35.15	-3.46	54.00	-32.98	Average
2	2390.000	21.36	24.93	27.66	4.09	35.32	-3.57	54.00	-32.64	Average
3	2400.000	50.14	53.68	27.70	4.10	35.34	-3.54	54.00	-3.86	Average

GFSK-1Mbps	CH39

Horizontal

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	2483.500	45.91	49.69	27.57	4.17	35.52	-3.78	74.00	-28.09	Peak
2	2500.000	32.83	36.60	27.60	4.18	35.55	-3.77	74.00	-41.17	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	2483.500	36.24	40.02	27.57	4.17	35.52	-3.78	54.00	-17.76	Average
2	2500.000	17.97	21.74	27.60	4.18	35.55	-3.77	54.00	-36.03	Average

GFSK-1Mbps	CH39

Vertical

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	2483.500	45.60	49.38	27.57	4.17	35.52	-3.78	74.00	-28.40	Peak
2	2500.000	33.65	37.42	27.60	4.18	35.55	-3.77	74.00	-40.35	Peak

	Freq	Level	Read Level	Ant Factor	Cable Loss	Preamp Factor	Factor	Limit Line	Over Limit	Remark
	MHz	dBuV/m	dBuV	dB/m	dB	dB	dB/m	dBuV/m	dB	
1	2483.500	31.83	35.61	27.57	4.17	35.52	-3.78	54.00	-22.17	Average
2	2500.000	22.33	26.10	27.60	4.18	35.55	-3.77	54.00	-31.67	Average

7. 6dB Bandwidth Test

7.1.Block Diagram of Test Setup



7.2.Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

7.3.Test Procedure

Use the test method descried in ANSI C63.10 Section 11.8.2:
1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

7.4.Test Results

Test Mode	CH	-6dB bandwidth (KHz)	Limit (KHz)
GFSK-1Mbps	CH00	648	≧500
	CH19	666	
	CH39	660	
Conclusion：PASS			

Type:	GFSK-1Mbps
CH00	 Date: 3.SEP.2026 16:08:05
CH19	 Date: 3.SEP.2026 16:09:22

CH39	 Date: 3.SEP.2026 16:10:42

8. OUTPUT POWER TEST

8.1.Limit (FCC Part 15C 15.247 b(3))

For systems using digital modulation in the 2400—2483.5MHz, The Peak output Power shall not exceed 1W(30dBm), As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level.

8.2.Test Procedure

1, Connected the EUT's antenna port to Spectrum Analyzer.

2, Use the test method descried in ANSI C63.10:

1) Set span to at least 1.5 times the OBW.
2) Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
3) Set VBW ≥ [3 × RBW].
4) Sweep time = auto.
5) Detector = peak
6) Trace mode = max hold
7) Allow trace to fully stabilize; Use peak marker function to determine the peak amplitude level.

Note: The cable loss needs to be compensated into the data.

8.3.Test Results

Pass

Test Mode	CH	Output power		Limit	
		(dBm)	(W)	(dBm)	(W)
GFSK-1Mbps	CH00	9.94	0.0099	30	1
	CH19	9.97	0.0099		
	CH39	10.56	0.0114		

Type:	GFSK-1Mbps
CH00	 Date: 3.SEP.2026 16:12:28
CH19	 Date: 3.SEP.2026 16:12:54

CH39	 Date: 3.SEP.2026 16:13:11

9. POWER SPECTRAL DENSITY TEST

9.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

9.2. Test Procedure

Use the test method descried in ANSI C63.10 clause 11.10.2:

a) Set analyzer center frequency to DTS channel center frequency.
b) Set the span to 1.5 times the DTS bandwidth.
c) Set the RBW to 3 kHz ≤ RBW ≤ 100 kHz.
d) Set the VBW ≥ [3 × RBW].
e) Detector = peak.
f) Sweep time = auto couple.
g) Trace mode = max hold.
h) Allow trace to fully stabilize.
i) Use the peak marker function to determine the maximum amplitude level within the RBW.
j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

9.3. Test Results

Pass

Test Mode	Channel	Power density (dBm/3KHz)	Limit (dBm/3KHz)
GFSK-1Mbps	CH00	-6.12	8
	CH19	-6.18	
	CH39	-5.46	
Conclusion：PASS			

Type:	GFSK-1Mbps
CH00	 Date: 3.SEP.2026 16:14:39
CH19	 Date: 3.SEP.2026 16:15:02

CH39	 Date: 3.SEP.2026 16:15:26

10. ANTENNA REQUIREMENT

10.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2. Antenna Connected Construction

The antennas used for this product are FPC Antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 4.98dBi.

End of Report