

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15 SUBPART E 15.407

Report Reference No......: **MTWG22020077-R3**

FCC ID.....: **2A4OAJQ-HL001**

Compiled by

(position+printed name+signature)..: File administrators Alisa Luo

Supervised by

(position+printed name+signature)..: Test Engineer Sunny Deng

Approved by

(position+printed name+signature)..: Manager Yvette Zhou

Date of issue.....: February 24,2022

Representative Laboratory Name ..: **Shenzhen Most Technology Service Co., Ltd.**

Address.....: No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park,
Nanshan, Shenzhen, Guangdong, China.

Applicant's name: **ZHONGSHAN HANLIN ELECTRICAL APPLIANCE CO., LTD.**

Address: Floor 2 & Floor 3,B Zone,No.20 East shangheng Street,
SuichengVillage,Dongfeng Town,Zhongshan City,Guangdong
Province,China.

Test specification

Standard: **FCC Part 15 Subpart E 15.407**

Shenzhen Most Technology Service Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Most Technology Service Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Most Technology Service Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Induction cooker

Trade Mark: N/A

Manufacturer.....: **ZHONGSHAN HANLIN ELECTRICAL APPLIANCE CO., LTD.**

Model/Type reference.....: JQ-HL001

Listed Models: N/A

Ratings: AC 120V/60Hz

Modulation: OFDM

Frequency.....: From 5180MHz-5240MHz; 5745MHz-5825MHz

Hardware version: V1.0.3

Software version: V1.0.3

Result.....: **PASS**

TEST REPORT

Equipment under Test : Induction cooker

Model /Type : JQ-HL001

Listed Models : N/A

Remark : N/A

Applicant : **ZHONGSHAN HANLIN ELECTRICAL APPLIANCE CO., LTD.**

Address : Floor 2 & Floor 3,B Zone,No.20 East shangheng Street,
SuichengVillage,Dongfeng Town,Zhongshan City,Guangdong
Province,China.

Manufacturer : **ZHONGSHAN HANLIN ELECTRICAL APPLIANCE CO., LTD.**

Address : Floor 2 & Floor 3,B Zone,No.20 East shangheng Street,
SuichengVillage,Dongfeng Town,Zhongshan City,Guangdong
Province,China.

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1</u>	<u>REVISION HISTORY</u>	<u>4</u>
<u>2</u>	<u>TEST STANDARDS</u>	<u>5</u>
<u>3</u>	<u>SUMMARY</u>	<u>6</u>
3.1	General Remarks	6
3.2	Product Description	6
3.3	Equipment Under Test	6
3.4	Short description of the Equipment under Test (EUT)	6
3.5	EUT operation mode	7
3.6	Block Diagram of Test Setup	7
3.1	Test Item (Equipment Under Test) Description*	7
3.2	Auxiliary Equipment (AE) Description	7
3.3	Antenna Information*	7
3.4	Related Submittal(s) / Grant (s)	8
3.5	Modifications	8
<u>4</u>	<u>TEST ENVIRONMENT</u>	<u>9</u>
4.1	Address of the test laboratory	9
4.2	Test Facility	9
4.3	Environmental conditions	9
4.4	Test Description	10
4.5	Statement of the measurement uncertainty	10
4.6	Equipments Used during the Test	11
<u>5</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>12</u>
5.1	AC Power Conducted Emission	12
5.2	Radiated Emissions	15
5.3	Conduction spurious emission	23
5.4	Maximum Conducted Average Output Power	30
5.5	Power Spectral Density	32
5.6	Emission Bandwidth (26dBm Bandwidth)	37
5.7	Minimum Emission Bandwidth (6dBm Bandwidth)	40
5.8	Frequency Stability	43
5.9	Duty Cycle Information	46
<u>6</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>48</u>
<u>7</u>	<u>PHOTOS OF THE EUT</u>	<u>49</u>

1 Revision History

Revision	Issue Date	Revisions	Revised By
00	2022-02-24	Initial Issue	Alisa Luo

2 TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15 Subpart E](#)—Unlicensed National Information Infrastructure Devices

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB789033 D02](#): General UNII Test Procedures New Rules v01r02

3 SUMMARY

3.1 General Remarks

Date of receipt of test sample	:	2022.02.16
Testing commenced on	:	2022.02.16
Testing concluded on	:	2022.02.24

3.2 Product Description

Product Description:	Induction cooker			
Model:	JQ-HL001			
Power supply:	AC 120V/60Hz			
Testing sample ID:	MT21010198			
WIFI				
Supported type:	20MHz system	40MHz system	80MHz system	160MHz system
	802.11a 802.11n	802.11n	N/A	N/A
Operation frequency:	5180MHz-5240MHz 5745MHz-5825MHz	5190MHz-5230MHz 5755MHz-5795MHz	N/A	N/A
Modulation:	OFDM	OFDM	N/A	N/A
Antenna type:	IPEX External Antenna			
Antenna gain:	5180MHz-5240MHz:3.3dBi, 5745MHz-5825MHz:3.3dBi			

3.3 Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

AC 120V/60Hz

3.4 Short description of the Equipment under Test (EUT)

This is a Induction cooker

For more details, refer to the user's manual of the EUT.

3.5 EUT operation mode

The Applicant provides communication tools software (AT command) to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing.
All test performed at the low, middle and high of operational frequency range of each mode.

Operation Frequency List WIFI on 5G Band:

Operating band	20MHz		40MHz	
	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII 1 (5150MHz-5250MHz)	36	5180	38	5190
	40	5200		
	44	5220	46	5230
	48	5240		
U-NII 3 (5725MHz-5850MHz)	149	5745	151	5755
	153	5765		
	157	5785	159	5795
	161	5805		
	165	5825	--	--

Note: The line display in grey is those Channels/Frequencies select to test in this report for each operation mode.

3.6 Block Diagram of Test Setup



3.1 Test Item (Equipment Under Test) Description*

Short designation	EUT Name	EUT Description	Serial number	Hardware status	Software status
EUT A					
EUT B					

*: declared by the applicant. According to customers information EUTs A and B are the same devices.

3.2 Auxiliary Equipment (AE) Description

AE short designation	EUT Name (if available)	EUT Description	Serial number (if available)	Software (if used)
AE 1	-			
AE 2	-			

3.3 Antenna Information*

Short designation	Antenna Name	Antenna Type	Frequency Range	Serial number	Antenna Peak Gain
Antenna 1	---	PCB antenna	5180MHz-5240MHz 5745MHz-5825MHz	---	3.3dBi
Antenna 2					

*: declared by the applicant.

3.4 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

3.5 Modifications

No modifications were implemented to meet testing criteria.

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

Shenzhen Most Technology Service Co., Ltd.

No.5, 2nd Langshan Road, North District, Hi-tech Industrial Park, Nanshan, Shenzhen, Guangdong, China.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

4.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 0031192610

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

A2LA-Lab Cert. No.: 6343.01

Shenzhen Most Technology Service Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

4.3 Environmental conditions

Radiated Emission:

Temperature:	23 ° C
Humidity:	48 %
Atmospheric pressure:	950-1050mbar

AC Main Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

Conducted testing:

Temperature:	24 ° C
Humidity:	45 %
Atmospheric pressure:	950-1050mbar

4.4 Test Description

FCC Requirement		
FCC Part 15.207	AC Power Conducted Emission	N/A
FCC Part 15.407(a)	Emission Bandwidth(26dBm Bandwidth)	PASS ^{Note1}
FCC Part 15.407(e)	Minimum Emission Bandwidth(6dBm Bandwidth)	PASS ^{Note2}
FCC Part 15.407(a)	Maximum Conducted Output Power	PASS
FCC Part 15.407(a)	Peak Power Spectral Density	PASS
FCC Part 15.407(g)	Frequency Stability	PASS
FCC Part 15.407(b)	Undesirable emission	PASS
FCC Part 15.407(b)/15.205/15.209	Radiated Emissions	PASS
FCC Part 15.407(h)	Dynamic Frequency Selection	N/A ^{Note 3}
FCC Part 15.203/15.247(b)	Antenna Requirement	PASS

Note 1: Apply to U-NII 1, U-NII 2A, and U-NII 2C band.

Note 2: Apply to U-NII 3 band only.

Note 3: This device not work in DFS band.

Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Conducted Output Power Power Spectral Density Emission Bandwidth(26dBm Bandwidth) Minimum Emission Bandwidth(6dBm Bandwidth) Undesirable emission Frequency Stability	11a/OFDM	54 Mbps
	11n(20MHz) /OFDM	MCS0
	11n(40MHz) /OFDM	MCS0

4.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Most Technology Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Most Technology Service Co., Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 Db	(1)
Radiated Emission	1~18GHz	4.32 Db	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.6 Equipments Used during the Test


Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N.	R&S	ENV216	100093	2021/04/19	1 Year
2	Three-phase artificial power network	Schwarzback Mess	NNLK8129	8129178	2021/04/19	1 Year
3.	Receiver	R&S	ESCI	100492	2021/04/7	1 Year
4	Receiver	R&S	ESPI	101202	2021/04/7	1 Year
5	Spectrum analyzer	Agilent	9020A	MT-E306	2021/04/7	1 Year
6	Bilong Antenna	Sunol Sciences	JB3	A121206	2021/03/14	1 Year
7	Horn antenna	HF Antenna	HF Antenna	MT-E158	2021/04/7	1 Year
8	Loop antenna	Beijing Daze	ZN30900B	/	2021/04/16	1 Year
9	Horn antenna	R&S	OBH100400	26999002	2021/04/16	1 Year
10	Wireless Communication Test Set	R&S	CMW500	/	2021/04/15	1 Year
11	Spectrum analyzer	R&S	FSP	100019	2021/04/15	1 Year
12	High gain antenna	Schwarzbeck	LB-180400KF	MT-E389	2021/03/14	1 Year
13	Preamplifier	Schwarzbeck	BBV 9743	MT-E390	2021/03/14	1 Year
14	Pre-amplifier	EMCI	EMC051845S E	MT-E391	2021/03/14	1 Year
15	Pre-amplifier	Agilent	83051A	MT-E392	2021/03/14	1 Year
16	High pass filter unit	Tonscend	JS0806-F	MT-E393	2021/03/14	1 Year
17	RF Cable(below1GHz)	Times	9kHz-1GHz	MT-E394	2021/03/14	1 Year
18	RF Cable(above 1GHz)	Times	1-40G	MT-E395	2021/03/14	1 Year
19	RF Cable (9KHz-40GHz)	Tonscend	170660	N/A	2021/03/14	1 Year

Note: The Cal.Interval was one year.

5 TEST CONDITIONS AND RESULTS

5.1 AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50


* Decreases with the logarithm of the frequency.


TEST RESULTS

Remark:

1. WIFI 5G modes were test at 802.11a, 802.11n(20), 802.11n(40)(Low, Middle, and High channel); only the worst result of 802.11a Middle Channel was reported as below:

2.





5.2 Radiated Emissions

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Undesirable emission limits

Requirement	Limit(EIRP)	Limit (Field strength at 3m) ^{Note1}
15.407(b)(1)	PK:-27(dBm/MHz)	PK:68.2(dBμV/m)
15.407(b)(2)		
15.407(b)(3)		
15.407(b)(4)		

Note1: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$


- (5) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209
- (6) In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	20log(2400/F(KHz))+40log(300/3)	2400/F(KHz)
0.49-1.705	3	20log(24000/F(KHz))+ 40log(30/3)	24000/F(KHz)
1.705-30	3	20log(30)+ 40log(30/3)	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.
- Radiated emission test frequency band from 9KHz to 40GHz.
- The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

- Setting test receiver/spectrum as following table states:


Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak


TEST RESULTS

Remark:

- This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
- All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for below 1GHz test, only the worst case 802.11a low channel of U-NII 1 band was recorded.
- All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for above 1GHz test, only the worst case 802.11a was recorded.
- Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
- Remark: Result=Reading value+Factor

For 30MHz-1GHz





For 1GHz to 40GHz

Note: All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for above 1GHz test, only the worst case 802.11a was recorded.

U-NII 1

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Antenna Factor (dB)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
802.11a Mode -5180MHz									
V	3550	56.64	29.03	5.24	36.4	54.51	68.2	13.69	PK
V	3550	43.24	29.03	5.24	36.4	41.11	54	12.89	AV
H	3550	54.11	29.03	5.24	36.4	51.98	68.2	16.22	PK
H	3550	47.11	29.03	5.24	36.4	44.98	54	9.02	AV
V	10360	36.5	39.41	11.45	34.28	53.08	68.2	15.12	PK
V	10360	23.98	39.41	11.45	34.28	40.56	54	13.44	AV
H	10360	34.5	39.41	11.45	34.28	51.08	68.2	17.12	PK
H	10360	28.64	39.41	11.45	34.28	45.22	54	8.78	AV
802.11a Mode -5200MHz									
V	3550	52.91	29.03	5.24	36.4	50.78	68.2	17.42	PK
V	3550	44.01	29.03	5.24	36.4	41.88	54	12.12	AV
H	3550	53.92	29.03	5.24	36.4	51.79	68.2	16.41	PK
H	3550	48.51	29.03	5.24	36.4	46.38	54	7.62	AV
V	10400	36.43	39.42	11.47	34.28	53.04	68.2	15.16	PK
V	10400	26.04	39.42	11.47	34.28	42.65	54	11.35	AV
H	10400	34.97	39.42	11.47	34.28	51.58	68.2	16.62	PK
H	10400	27.04	39.42	11.47	34.28	43.65	54	10.35	AV
802.11b Mode -5240MHz									
V	3550	52.4	29.03	5.24	36.4	50.27	68.2	17.93	PK
V	3550	42.66	29.03	5.24	36.4	40.53	54	13.47	AV
H	3550	54.94	29.03	5.24	36.4	52.81	68.2	15.39	PK
H	3550	46.68	29.03	5.24	36.4	44.55	54	9.45	AV
V	10480	36.47	39.43	11.47	34.28	53.09	68.2	15.11	PK
V	10480	27.08	39.43	11.47	34.28	43.7	54	10.3	AV
H	10480	34.85	39.43	11.47	34.28	51.47	68.2	16.73	PK
H	10480	27.82	39.43	11.47	34.28	44.44	54	9.56	AV

U-NII 3

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Antenna Factor (dB)	Cable loss (dB)	Preamp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
802.11a Mode -5500MHz									
V	5086	52.01	32.84	5.24	36.4	53.69	68.2	14.51	PK
V	5086	40.2	32.84	5.24	36.4	41.88	54	12.12	AV
H	5086	49.44	32.84	5.24	36.4	51.12	68.2	17.08	PK
H	5086	42.96	32.84	5.24	36.4	44.64	54	9.36	AV
V	11490	36.24	39.52	11.47	34.28	52.95	68.2	15.25	PK
V	11490	25.09	39.52	11.47	34.28	41.8	54	12.2	AV
H	11490	34.77	39.52	11.47	34.28	51.48	68.2	16.72	PK
H	11490	27.12	39.52	11.47	34.28	43.83	54	10.17	AV
802.11a Mode -5600MHz									
V	5086	51.36	32.84	5.24	36.4	53.04	68.2	15.16	PK
V	5086	38.33	32.84	5.24	36.4	40.01	54	13.99	AV
H	5086	49.56	32.84	5.24	36.4	51.24	68.2	16.96	PK
H	5086	44.11	32.84	5.24	36.4	45.79	54	8.21	AV
V	11570	36.09	39.52	11.47	34.28	52.8	68.2	15.4	PK
V	11570	25.59	39.52	11.47	34.28	42.3	54	11.7	AV
H	11570	34.94	39.52	11.47	34.28	51.65	68.2	16.55	PK
H	11570	27.43	39.52	11.47	34.28	44.14	54	9.86	AV
802.11b Mode -5700MHz									
V	5086	50.63	32.84	5.24	36.4	52.31	68.2	15.89	PK
V	5086	39.91	32.84	5.24	36.4	41.59	54	12.41	AV
H	5086	50.71	32.84	5.24	36.4	52.39	68.2	15.81	PK
H	5086	43.24	32.84	5.24	36.4	44.92	54	9.08	AV
V	11650	36.15	39.52	11.47	34.28	52.86	68.2	15.34	PK
V	11650	25.43	39.52	11.47	34.28	42.14	54	11.86	AV
H	11650	35.43	39.52	11.47	34.28	52.14	68.2	16.06	PK
H	11650	27.53	39.52	11.47	34.28	44.24	54	9.76	AV

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Radiated Band Edge Test:

All 802.11a / 802.11n (HT20) / 802.11n (HT40) modes have been tested for above 1GHz test, only the worst case 802.11a was recorded.

U-NII 1

Polar (H/V)	Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
802.11a									
V	5150	53.97	31.22	7.62	36.5	56.31	74	17.69	PK
V	5150	37.85	31.22	7.62	36.5	40.19	54	13.81	AV
H	5150	53.86	31.22	7.62	36.5	56.2	74	17.8	PK
H	5150	44.25	31.22	7.62	36.5	46.59	54	7.41	AV
V	5350	54.85	31.56	7.83	35.82	58.42	74	15.58	PK
V	5350	39.24	31.56	7.83	35.82	42.81	54	11.19	AV
H	5350	54.7	31.56	7.83	35.82	58.27	74	15.73	PK
H	5350	42.2	31.56	7.83	35.82	45.77	54	8.23	AV

U-NII 3

Polar (H/V)	Frequency	Meter Reading	Antenna Factor	Cable loss	Preamp factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
802.11a									
V	5460	54.02	31.62	7.89	35.76	57.77	74	16.23	PK
V	5460	37.3	31.62	7.89	35.76	41.05	54	12.95	AV
H	5460	54.17	31.62	7.89	35.76	57.92	74	16.08	PK
H	5460	41.76	31.62	7.89	35.76	45.51	54	8.49	AV
V	5850	53.39	31.71	7.92	35.55	57.47	74	16.53	PK
V	5850	38.26	31.71	7.92	35.55	42.34	54	11.66	AV
H	5850	55.56	31.71	7.92	35.55	59.64	74	14.36	PK
H	5850	39.54	31.71	7.92	35.55	43.62	54	10.38	AV

5.3 Conduction spurious emission

Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


Allow the trace to stabilize


Test Configuration



TEST RESULTS

U-NII 1





CH48

802.11n(HT40)



CH38



CH46

U-NII 3

802.11a



CH149

CH157



CH165


802.11n(HT20)



CH149



CH157



CH165

802.11n(HT40)



CH151



CH159

U-NII 1

HP8594C Spectrum Analyzer / Sweep SA

Marker 2 5.150000000000 GHz

PRO: Fast Trg: Free Run Atten: 30 dB

Avg Type: Log-Pwr AvgHold>100/100

04/11/21 PM6:23, 2022

TRAC2 2.0 x 5.0 PWR (dBm) DET: NORM

10 dB/div Ref 20.00 dBm

Start 4.5000 GHz Stop 5.0000 GHz

#Res BW 1.0 MHz #VBW 3.0 MHz Sweep 1.200 ms (1001 pts)

Mkr2 5.1500 GHz -38.004 dBm

MARK	FREQ (GHz)	AMPL (dBm)	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	5.1811 GHz	-38.884 dBm			
2	5.1500 GHz	-38.004 dBm			


Left bandedge



Right bandedge

[illegible]

Left bandedge



Right bandedge

Signal Spectrum Analyzer - Supt SA

Marker 1 5.188800000000 GHz

PRB: Fast IF Gain: Low Trig Freq Run Attenu: 20 dB

Avg Type: Log-Pwr AvgHold: 100/100

04/13/06 14:00:23, 2003

Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Delta

Mkr1 5.1888 GHz -9.750 dBm

Ref 20.00 dBm

10 dBdV Log

Start 4.5000 GHz #VBW 3.0 MHz Sweep 1.200 ms (1001 pts)

Stop 5.2000 GHz

Res BW 1.0 MHz

Mkr	Mode	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	F	5.1888 GHz	-9.750 dBm			
2	N	1	F	5.1500 GHz	-42.908 dBm			
3								
4								
5								
6								
7								
8								
9								
10								
11								

Mkr --CF

Mkr --Ref LV

More

1 of 2


Left bandedge




Right bandedge

U-NII 3


802.11a



802.11n(HT20)



802.11n(HT40)



5.4 Maximum Conducted Average Output Power

Limit

For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.


For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

Test Configuration



Test Results**U-NII 1**

Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11a	36	12.10	24.00	Pass
	40	12.12		
	48	12.00		
802.11n(HT20)	36	11.10	24.00	Pass
	40	12.21		
	48	12.22		
802.11n(HT40)	38	12.05	24.00	Pass
	46	12.01		

U-NII 3

Type	Channel	Output power (dBm)	Limit (dBm)	Result
802.11a	149	12.42	30.00	Pass
	157	12.52		
	165	12.25		
802.11n(HT20)	149	12.10	30.00	Pass
	157	12.11		
	165	12.15		
802.11n(HT40)	151	11.95	30.00	Pass
	159	11.85		

5.5 Power Spectral Density

Limit

(1) For the band 5.15 - 5.25 GHz.

(i) For an outdoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(ii) For an indoor access point operating in the band 5.15 - 5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 MHz band. ^{note1}

(iii) For fixed point-to-point access points operating in the band 5.15 - 5.25 GHz, transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi.

(iv) For mobile and portable client devices in the 5.15 - 5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(2) For the 5.25 - 5.35 GHz and 5.47 - 5.725 GHz bands, the peak power spectral density shall not exceed 11 dBm in any 1 MHz band. ^{note1}

(3) For the band 5.725 - 5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500 kHz band. ^{note1, note2}


Note1: If transmitting antennas of directional gain greater than 6 dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note2: Fixed point - to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW = 1MHz for U-NII 1, U-NII 2A, U-NII C band and 510KHz for U-NII 3 band.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to encompass the entire EBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.

Test Configuration



Test Results

Type	Bands	Channel	Power Spectral Density (dBm/MHz)	Limit (dBm/MHz)	Result
802.11a	U-NII 1	36	7.147	17.0	Pass
		40	7.885		
		48	7.489		
802.11n (HT20)	U-NII 1	36	6.922		
		40	6.539		
		48	7.907		
802.11n (HT40)	U-NII 1	38	0.650		
		46	4.350		

Type	Bands	Channel	Power Spectral Density (dBm/300KHz)	Power Spectral Density (dBm/500KHz)	Limit (dBm/500KHz)	Result
802.11a	U-NII 3	149	8.143	10.363	30.0	Pass
		157	7.504	9.724		
		165	5.629	7.849		
802.11n (HT20)	U-NII 3	149	6.676	8.896		
		157	6.079	8.299		
		165	5.710	7.93		
802.11n (HT40)	U-NII 3	151	3.782	6.002		
		159	-0.767	1.453		

Remark: P.S.D(dBm/500KHz)= P.S.D(dBm/300KHz)+10 log (500 kHz/300KHz).

Test plot as follows:

802.11a

U-NII 1



U-NII 3



CH36



CH149



CH40



CH157



CH48

CH165

802.11n(HT20)

U-NII 1



U-NII 3



CH36



CH149



CH40



CH157



CH48

CH165

U-NII 3



CH151



CH159

5.6 Emission Bandwidth (26dBm Bandwidth)


Limit

N/A

Test Procedure

1. Set resolution bandwidth (RBW) = approximately 1 % of the EBW.
2. Set the video bandwidth (VBW) > RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW / EBW ratio is approximately 1 %.

Test Configuration




Test Results

Type	Bands	Channel	26dB Bandwidth (MHz)	Limit (MHz)	Result
802.11a	U-NII 1	36	27.10	N/A	Pass
		40	29.79		
		48	28.04		
802.11n(HT20)	U-NII 1	36	26.33		
		40	27.13		
		48	29.85		
802.11n(HT40)	U-NII 1	38	41.42		
		46	35.95		

Test plot as follows:

U-NII 1




CH36

CH36

CH40

CH40

802.11n(HT40)



CH38



CH46

5.7 Minimum Emission Bandwidth (6dBm Bandwidth)


Limit

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth 3 x RBW.
3. Detector = Peak.
4. Trace mode = Max hold.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Configuration




Test Results


Type	Bands	Channel	6dB Bandwidth (MHz)	Limit (KHz)	Result
802.11a	U-NII 3	149	14.50	≥500KHz	Pass
		157	15.89		
		165	16.21		
802.11n(HT20)	U-NII 3	149	15.17		
		157	17.33		
		165	16.37		
802.11n(HT40)	U-NII 3	151	35.46		
		159	33.63		

Test plot as follows:

802.11a




802.11n(HT20)




CH149



CH149



CH157



CH157



CH165




CH165



802.11n(HT40)



CH151




CH159

5.8 Frequency Stability

LIMIT

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

TEST CONFIGURATION



TEST PROCEDURE

Frequency Stability under Temperature Variations:

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20°C operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30°C. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10°C increased per stage until the highest temperature of +50°C reached.

Frequency Stability under Voltage Variations:

Set chamber temperature to 20°C. Use a variable AC power supply / DC power source to power the EUT and set the voltage to rated voltage. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and recorded the frequency.

Reduce the input voltage to specify extreme voltage variation ($\pm 15\%$) and endpoint, record the maximum frequency change.

TEST RESULTS

Record worst case as below:

Reference Frequency: 802.11ac channel=36 frequency=5180MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		MHz	ppm		
120	-30	0.013	2.51	Within the band of operation	Pass
	-20	0.014	2.70		
	-10	0.015	2.90		
	0	0.015	2.90		
	10	0.016	3.09		
	20	0.013	2.51		
	30	0.016	3.09		
	40	0.015	2.90		
	50	0.014	2.70		
240	25	0.015	2.90	Within the band of operation	Pass
110	25	0.013	2.51		


Reference Frequency: 802.11ac channel=58 frequency=5290MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		MHz	ppm		
120	-30	0.012	2.27	Within the band of operation	Pass
	-20	0.013	2.46		
	-10	0.014	2.65		
	0	0.012	2.27		
	10	0.015	2.84		
	20	0.014	2.65		
	30	0.016	3.02		
	40	0.012	2.27		
	50	0.016	3.02		
240	25	0.015	2.84	Within the band of operation	Pass
110	25	0.016	3.02		

Reference Frequency: 802.11ac channel=122 frequency=5610MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		MHz	ppm		
120	-30	0.012	2.14	Within the band of operation	Pass
	-20	0.013	2.32		
	-10	0.012	2.14		
	0	0.015	2.67		
	10	0.014	2.50		
	20	0.013	2.32		
	30	0.013	2.32		
	40	0.015	2.67		
	50	0.012	2.14		
240	25	0.014	2.50	Within the band of operation	Pass
110	25	0.012	2.14		


Reference Frequency: 802.11ac channel=149 frequency=5745MHz					
Voltage (V)	Temperature (°C)	Frequency error		Limit (ppm)	Result
		MHz	ppm		
120	-30	0.016	2.79	Within the band of operation	Pass
	-20	0.015	2.61		
	-10	0.014	2.44		
	0	0.014	2.44		
	10	0.014	2.44		
	20	0.016	2.79		
	30	0.016	2.79		
	40	0.012	2.09		
	50	0.013	2.26		
240	25	0.014	2.44	Within the band of operation	Pass
110	25	0.015	2.61		

5.9 Duty Cycle Information


U-NII 1				
Test Mode	Maximum Achievable Duty Cycle (x) = On / (On+Off)			Duty Cycle Correction Factor [dB]
	On Time [ms]	(On+Off) Time [ms]	x	
a	0.360	0.396	90.91%	0.062
n20	1.290	1.338	96.41%	0.051
n40	0.636	0.690	92.17%	0.062



U-NII 3				
Test Mode	Maximum Achievable Duty Cycle (x) = On / (On+Off)			Duty Cycle Correction Factor [dB]
	On Time [ms]	(On+Off) Time [ms]	x	
a	0.262	0.306	85.62%	0.060
n20	1.290	1.339	96.34%	0.060
n40	0.636	0.678	93.81%	0.058



6 Test Setup Photos of the EUT



7 Photos of the EUT

see photo report.

***** End of Report *****