



# FCC Part 15C Test Report

## FCC ID:2A4QY-ALMH01

Applicant: AMLifestyle LLC

Address: 250 College Park Dr. Upland, CA 91786

Manufacturer: Shenzhen Jingwah Kaoge Communication Technology Co.,Ltd.

Address: 4th Floor, B3 Building, Xujing Chang Science and Technology Industrial Park, 39 Haoye Road, Fuhai Street, Baoan Dis., Shen zhen, Guang Dong, China

EUT: Smart Helmet

Trade Mark: Almarix

Model Number: ALM-H01  
ALM-H02, ALM-H03, ALM-H04, ZNTK-001, ZNTK-002, ZNTK-003

Date of Receipt: Jan. 21, 2022

Test Date: Jan. 21, 2022 – Feb. 14, 2022

Date of Report: Feb. 14, 2022

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 C 15.247  
ANSI C63.10:2013

Test Result: Pass

Report Number: DL-20220209008E

Prepared (Test Engineer): Pxing Huang

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



*This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.*



| Table of Contents                                           | Page      |
|-------------------------------------------------------------|-----------|
| <b>1 . SUMMARY OF TEST RESULTS</b>                          | <b>4</b>  |
| 1.1 MEASUREMENT UNCERTAINTY                                 | 4         |
| <b>2 . GENERAL INFORMATION</b>                              | <b>5</b>  |
| 2.1 GENERAL DESCRIPTION OF EUT                              | 5         |
| 2.2 DESCRIPTION OF TEST MODES                               | 6         |
| 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 7         |
| 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)            | 7         |
| 2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING            | 7         |
| 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS                      | 8         |
| <b>3 . EMC EMISSION TEST</b>                                | <b>9</b>  |
| 3.1 CONDUCTED EMISSION MEASUREMENT                          | 9         |
| 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS                  | 9         |
| 3.1.2 TEST PROCEDURE                                        | 9         |
| 3.1.3 DEVIATION FROM TEST STANDARD                          | 9         |
| 3.1.4 TEST SETUP                                            | 10        |
| 3.1.5 EUT OPERATING CONDITIONS                              | 10        |
| 3.1.6 TEST RESULTS                                          | 10        |
| 3.2 RADIATED EMISSION MEASUREMENT                           | 13        |
| 3.2.1 RADIATED EMISSION LIMITS                              | 13        |
| 3.2.2 TEST PROCEDURE                                        | 14        |
| 3.2.3 DEVIATION FROM TEST STANDARD                          | 14        |
| 3.2.4 TEST SETUP                                            | 14        |
| 3.2.5 EUT OPERATING CONDITIONS                              | 15        |
| 3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)                  | 16        |
| 3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)                   | 17        |
| 3.2.8 TEST RESULTS (1GHZ~25GHZ)                             | 19        |
| 3.3 RADIATED BAND EMISSION MEASUREMENT                      | 25        |
| 3.3.1 TEST REQUIREMENT:                                     | 25        |
| 3.3.2 TEST PROCEDURE                                        | 25        |
| 3.3.3 DEVIATION FROM TEST STANDARD                          | 25        |
| 3.3.4 TEST SETUP                                            | 26        |
| 3.3.5 EUT OPERATING CONDITIONS                              | 26        |
| <b>4 . PEAK OUTPUT POWER</b>                                | <b>39</b> |
| 4.1 APPLIED PROCEDURES / LIMIT                              | 39        |
| 4.1.1 TEST PROCEDURE                                        | 39        |
| 4.1.2 DEVIATION FROM STANDARD                               | 39        |
| 4.1.3 TEST SETUP                                            | 39        |
| 4.1.4 EUT OPERATION CONDITIONS                              | 39        |



| Table of Contents               | Page |
|---------------------------------|------|
| 4.1.5 TEST RESULTS              | 40   |
| 5 . POWER SPECTRAL DENSITY TEST | 43   |
| 5.1 APPLIED PROCEDURES / LIMIT  | 43   |
| 5.1.1 TEST PROCEDURE            | 43   |
| 5.1.2 DEVIATION FROM STANDARD   | 43   |
| 5.1.3 TEST SETUP                | 43   |
| 5.1.4 EUT OPERATION CONDITIONS  | 43   |
| 5.1.5 TEST RESULTS              | 44   |
| 6 . 6DB BANDWIDTH TEST          | 47   |
| 6.1 APPLIED PROCEDURES / LIMIT  | 47   |
| 6.1.1 TEST PROCEDURE            | 47   |
| 6.1.2 DEVIATION FROM STANDARD   | 47   |
| 6.1.3 TEST SETUP                | 47   |
| 6.1.4 EUT OPERATION CONDITIONS  | 47   |
| 6.1.5 TEST RESULTS              | 48   |
| 7 . ANTENNA REQUIREMENT         | 51   |
| 7.1 STANDARD REQUIREMENT        | 51   |
| 7.2 EUT ANTENNA                 | 51   |
| 8 . TEST SEUUP PHOTO            | 52   |
| 9 . EUT PHOTO                   | 54   |



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.247) , Subpart C |                            |          |        |
|---------------------------------|----------------------------|----------|--------|
| Standard Section                | Test Item                  | Judgment | Remark |
| 15.207                          | Conducted Emission         | PASS     |        |
| 15.247(c)                       | Radiated Spurious Emission | PASS     |        |
| 15.205                          | Band Edge Emission         | PASS     |        |
| 15.247(b)(1)                    | Peak Output Power          | PASS     |        |
| 15.247(a)(2)                    | 6dB Bandwidth              | PASS     |        |
| 15.247(d)                       | Power Spectral Density     | PASS     |        |
| 15.203                          | Antenna Requirement        | PASS     |        |

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

### 1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  providing a level of confidence of approximately 95 %.

| No. | Item                         | Uncertainty               |
|-----|------------------------------|---------------------------|
| 1   | Conducted Emission Test      | $\pm 2.56\text{dB}$       |
| 2   | RF power,conducted           | $\pm 0.42\text{dB}$       |
| 3   | Spurious emissions,conducted | $\pm 2.76\text{dB}$       |
| 4   | All emissions,radiated(<1G)  | $\pm 3.65\text{dB}$       |
| 5   | All emissions,radiated(>1G)  | $\pm 4.89\text{dB}$       |
| 6   | Temperature                  | $\pm 0.5^{\circ}\text{C}$ |
| 7   | Humidity                     | $\pm 2\%$                 |



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                        |                                                                                                                  |
|------------------------|------------------------------------------------------------------------------------------------------------------|
| Product Name:          | Smart Helmet                                                                                                     |
| Trademark              | Almarix                                                                                                          |
| Model No.:             | ALM-H01<br>ALM-H02, ALM-H03, ALM-H04, ZNTK-001, ZNTK-002, ZNTK-003                                               |
| Model Difference       | All samples are the same except the model name, so we prepare "ALM-H01" for test only.                           |
| Operation Frequency:   | 2412~2462 MHz for 802.11b/g/nHT20<br>2422~2452 MHz for 802.11nHT40                                               |
| Channel numbers:       | 11 Channels for 802.11b/g/n(HT20)<br>7 channels for 802.11nHT40                                                  |
| Channel separation:    | 5MHz                                                                                                             |
| Modulation technology: | 802.11b: DSSS (CCK, DQPSK, DBPSK)<br>802.11g/n(20): DSSS (CCK, DQPSK,DBPSK)+OFDM<br>(QPSK, BPSK, 16-QAM, 64-QAM) |
| Rate of Transmitter    | 802.11b: 11/5.5/2/1Mbps<br>802.11g: 54/48/36/24/18/12/9/6Mbps<br>802.11n: up to 150Mbps                          |
| Antenna Type:          | Internal Antenna                                                                                                 |
| Antenna gain:          | 1.2dBi                                                                                                           |
| Power supply:          | DC 3.7V from battery<br>DC 5V from charger                                                                       |

Note:

- 1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- 2.The EUT's all information provided by client.



## 2. Channel List(802.11b/g/nHT20)

| Channel | Frequency (GHz) | Channel | Frequency (GHz) |
|---------|-----------------|---------|-----------------|
| 01      | 2.412           | 07      | 2.442           |
| 02      | 2.417           | 08      | 2.447           |
| 03      | 2.422           | 09      | 2.452           |
| 04      | 2.427           | 10      | 2.457           |
| 05      | 2.432           | 11      | 2.462           |
| 06      | 2.437           |         |                 |

## Channel List(802.11nHT40)

| Channel | Frequency (GHz) | Channel | Frequency (GHz) |
|---------|-----------------|---------|-----------------|
| 03      | 2.422           | 07      | 2.442           |
| 04      | 2.427           | 08      | 2.447           |
| 05      | 2.432           | 09      | 2.452           |
| 06      | 2.437           |         |                 |

## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode                  | Description                |
|-------------------------------|----------------------------|
| Mode 1                        | 802.11b CH1/ CH6/ CH11     |
| Mode 2                        | 802.11g CH1/ CH6/ CH11     |
| Mode 3                        | 802.11nHT20 CH1/ CH6/ CH11 |
| Mode 4                        | 802.11nHT40 CH3/ CH6/ CH09 |
| Mode 5                        | Link Mode                  |
| <b>For Conducted Emission</b> |                            |
| Final Test Mode               | Description                |
| Mode 5                        | Link Mode                  |
| <b>For Radiated Emission</b>  |                            |
| Final Test Mode               | Description                |
| Mode 1                        | 802.11b CH1/ CH6/ CH11     |
| Mode 2                        | 802.11g CH1/ CH6/ CH11     |
| Mode 3                        | 802.11nHT20 CH1/ CH6/ CH11 |
| Mode 4                        | 802.11nHT40 CH3/ CH6/ CH09 |
| Mode 5                        | Link Mode                  |


Note: 1. The measurements are performed at the highest, middle, lowest available channels.

2. During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.




### 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

#### Radiated Spurious Emission Test



#### Conducted Spurious Emission Test



### 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment    | Model/Type No. | Series No. | Note |
|------|--------------|----------------|------------|------|
| E-1  | Smart Helmet | ALM-H01        | N/A        | EUT  |
| E-2  | Adapter      | HW-0502000E    | N/A        |      |

| Item | Shielded Type | Ferrite Core | Length | Note          |
|------|---------------|--------------|--------|---------------|
| C1   | No            | No           | 0.5m   | Mini USB Line |

Note:

- (1) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

### 2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

| Max output power Setting  |                           |         |              |              |
|---------------------------|---------------------------|---------|--------------|--------------|
| Test software Version     | Test program: AXDN-0002.0 |         |              |              |
| Mode                      | 802.11b                   | 802.11g | 802.11n HT20 | 802.11n HT40 |
| Data Rate                 | 1Mbps                     | 1Mbps   | MSC0         | MSC0         |
| Power Setting of Softwave | 60                        | 60      | 60           | 66           |



## 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

### Radiation test, Band-edge test and 6db bandwidth test equipment

| Item | Equipment                        | Manufacturer    | Type No.  | Serial No. | Last calibration | Calibrated until |
|------|----------------------------------|-----------------|-----------|------------|------------------|------------------|
| 1    | Spectrum Analyzer (9kHz-26.5GHz) | Agilent         | E4408B    | MY50140780 | Dec. 07, 2021    | Dec. 06, 2022    |
| 2    | Test Receiver (9kHz-7GHz)        | R&S             | ESRP7     | 101393     | Dec. 07, 2021    | Dec. 06, 2022    |
| 3    | Bilog Antenna (30MHz-1GHz)       | R&S             | VULB9162  | 00306      | Dec. 07, 2021    | Dec. 06, 2022    |
| 4    | Horn Antenna (1GHz-18GHz)        | Schwarzbeck     | BBHA9120D | 02139      | Dec. 07, 2021    | Dec. 06, 2022    |
| 5    | Horn Antenna (18GHz-40GHz)       | A.H. Systems    | SAS-574   | 588        | Dec. 07, 2021    | Dec. 06, 2022    |
| 6    | Amplifier (9KHz-6GHz)            | Schwarzbeck     | BBV9743B  | 00153      | Dec. 07, 2021    | Dec. 06, 2022    |
| 7    | Amplifier (1GHz-18GHz)           | EMEC            | EM01G8GA  | 00270      | Dec. 07, 2021    | Dec. 06, 2022    |
| 8    | Amplifier (18GHz-40GHz)          | Quanjuda        | DLE-161   | 97         | Dec. 07, 2021    | Dec. 06, 2022    |
| 9    | Loop Antenna (9KHz-30MHz)        | Schwarzbeck     | FMZB1519B | 00014      | Dec. 07, 2021    | Dec. 06, 2022    |
| 10   | RF cables1 (9kHz-1GHz)           | ChengYu         | 966       | 004        | Dec. 07, 2021    | Dec. 06, 2022    |
| 11   | RF cables2 (1GHz-40GHz)          | ChengYu         | 966       | 003        | Dec. 07, 2021    | Dec. 06, 2022    |
| 12   | Antenna connector                | Florida RF Labs | N/A       | RF 01#     | Dec. 07, 2021    | Dec. 06, 2022    |
| 13   | Power probe                      | KEYSIGHT        | U2021XA   | MY55210018 | Dec. 07, 2021    | Dec. 06, 2022    |
| 14   | Signal Analyzer 9kHz-26.5GHz     | Agilent         | N9020A    | MY55370280 | Dec. 07, 2021    | Dec. 06, 2022    |
| 15   | Test Receiver 20kHz-40GHz        | R&S             | ESU 40    | 100376     | Dec. 07, 2021    | Dec. 06, 2022    |
| 16   | D.C. Power Supply                | LongWei         | PS-305D   | 010964729  | Dec. 07, 2021    | Dec. 06, 2022    |

### Conduction Test equipment

| Item | Equipment         | Manufacturer | Type No. | Serial No. | Last calibration | Calibrated until |
|------|-------------------|--------------|----------|------------|------------------|------------------|
| 1    | 843 Shielded Room | ChengYu      | 843 Room | 843        | Nov. 25, 2019    | Nov. 24, 2022    |
| 2    | EMI Receiver      | R&S          | ESR      | 101421     | Dec. 07, 2021    | Dec. 06, 2022    |
| 3    | LISN              | R&S          | ENV216   | 102417     | Dec. 07, 2021    | Dec. 06, 2022    |
| 4    | 843 Cable 1#      | ChengYu      | CE Cable | 001        | Dec. 07, 2021    | Dec. 06, 2022    |

### Other

| Item | Name                         | Manufacturer | Model   | Software version |
|------|------------------------------|--------------|---------|------------------|
| 1    | EMC Conduction Test System   | FALA         | EZ_EMCC | EMC-CON 3A1.1    |
| 2    | EMC radiation test system    | FALA         | EZ_EMCC | FA-03A2          |
| 3    | RF test system               | MAIWEI       | MTS8310 | 2.0.0.0          |
| 4    | RF communication test system | MAIWEI       | MTS8200 | 2.0.0.0          |



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

| FREQUENCY (MHz) | Limit (dBuV) |           | Standard |
|-----------------|--------------|-----------|----------|
|                 | Quasi-peak   | Average   |          |
| 0.15 -0.5       | 66 - 56 *    | 56 - 46 * | FCC      |
| 0.50 -5.0       | 50.00        | 6.00      | FCC      |
| 5.0 -30.0       | 60.00        | 50.00     | FCC      |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |

##### 3.1.2 TEST PROCEDURE


- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

##### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation



### 3.1.4 TEST SETUP



**Note: 1.Support units were connected to second LISN.**

**2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes**

### 3.1.5 EUT OPERATING CONDITIONS


The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

### 3.1.6 TEST RESULTS



|                |              |                    |        |
|----------------|--------------|--------------------|--------|
| Temperature:   | 25 °C        | Relative Humidity: | 54%    |
| Pressure:      | 1010hPa      | Phase :            | L      |
| Test Voltage : | AC 120V/60Hz | Test Mode:         | Mode 5 |




Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

| No.  | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F | Remark |
|------|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|--------|
| 1    | 0.2174          | 41.29          | 9.60        | 50.89        | 62.92        | 12.03       | QP       | P   |        |
| 2    | 0.2174          | 10.86          | 9.60        | 20.46        | 52.92        | 32.46       | AVG      | P   |        |
| 3    | 0.5292          | 41.93          | 9.39        | 51.32        | 56.00        | 4.68        | QP       | P   |        |
| 4    | 0.5292          | 19.59          | 9.39        | 28.98        | 46.00        | 17.02       | AVG      | P   |        |
| 5    | 0.6764          | 37.93          | 9.54        | 47.47        | 56.00        | 8.53        | QP       | P   |        |
| 6    | 0.6764          | 12.51          | 9.54        | 22.05        | 46.00        | 23.95       | AVG      | P   |        |
| 7    | 2.4765          | 35.74          | 9.40        | 45.14        | 56.00        | 10.86       | QP       | P   |        |
| 8    | 2.4765          | 14.10          | 9.40        | 23.50        | 46.00        | 22.50       | AVG      | P   |        |
| 9    | 8.1371          | 37.73          | 9.92        | 47.65        | 60.00        | 12.35       | QP       | P   |        |
| 10   | 8.1371          | 20.33          | 9.92        | 30.25        | 50.00        | 19.75       | AVG      | P   |        |
| 11 * | 11.1254         | 45.41          | 10.05       | 55.46        | 60.00        | 4.54        | QP       | P   |        |
| 12   | 11.1254         | 31.66          | 10.05       | 41.71        | 50.00        | 8.29        | AVG      | P   |        |



|                |              |                    |        |
|----------------|--------------|--------------------|--------|
| Temperature:   | 25 °C        | Relative Humidity: | 54%    |
| Pressure:      | 1010hPa      | Phase :            | N      |
| Test Voltage : | AC 120V/60Hz | Test Mode:         | Mode 5 |



Remark:

Margin = Limit – Level, Correct Factor = Cable lose + LISN insertion loss, Level= Reading + Correct factor

| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB) | Level (dBuV) | Limit (dBuV) | Margin (dB) | Detector | P/F | Remark |
|-----|-----------------|----------------|-------------|--------------|--------------|-------------|----------|-----|--------|
| 1   | 0.2615          | 20.08          | 9.16        | 29.24        | 51.38        | 22.14       | AVG      | P   |        |
| 2   | 0.2630          | 40.14          | 9.16        | 49.30        | 61.34        | 12.04       | QP       | P   |        |
| 3   | 0.2630          | 25.78          | 9.16        | 34.94        | 51.34        | 16.40       | AVG      | P   |        |
| 4   | 0.4560          | 40.54          | 9.49        | 50.03        | 56.77        | 6.74        | QP       | P   |        |
| 5   | 0.4560          | 23.44          | 9.49        | 32.93        | 46.77        | 13.84       | AVG      | P   |        |
| 6   | 0.9415          | 38.91          | 9.53        | 48.44        | 56.00        | 7.56        | QP       | P   |        |
| 7   | 0.9415          | 22.98          | 9.53        | 32.51        | 46.00        | 13.49       | AVG      | P   |        |
| 8   | 2.6160          | 34.87          | 9.98        | 44.85        | 56.00        | 11.15       | QP       | P   |        |
| 9 * | 11.1165         | 43.50          | 10.23       | 53.73        | 60.00        | 6.27        | QP       | P   |        |
| 10  | 11.1165         | 30.31          | 10.23       | 40.54        | 50.00        | 9.46        | AVG      | P   |        |
| 11  | 13.9062         | 40.86          | 10.32       | 51.18        | 60.00        | 8.82        | QP       | P   |        |
| 12  | 13.9062         | 24.24          | 10.32       | 34.56        | 50.00        | 15.44       | AVG      | P   |        |



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies<br>(MHz) | Field Strength<br>(microvolt/meter) | Measurement Distance<br>(meters) |
|----------------------|-------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                         | 300                              |
| 0.490~1.705          | 24000/F(KHz)                        | 30                               |
| 1.705~30.0           | 30                                  | 30                               |
| 30~88                | 100                                 | 3                                |
| 88~216               | 150                                 | 3                                |
| 216~960              | 200                                 | 3                                |
| Above 960            | 500                                 | 3                                |

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) |         |
|-----------------|------------------------|---------|
|                 | PEAK                   | AVERAGE |
| Above 1000      | 74                     | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter                    | Setting                                          |
|---------------------------------------|--------------------------------------------------|
| Attenuation                           | Auto                                             |
| Start Frequency                       | 1000 MHz                                         |
| Stop Frequency                        | 25GHz                                            |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |



### 3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 0.8 metre( Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



### (C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

|              |          |                    |              |
|--------------|----------|--------------------|--------------|
| Temperature: | 20°C     | Relative Humidity: | 48%          |
| Pressure:    | 1010 hPa | Test Voltage :     | AC 120V/60Hz |
| Test Mode :  | Mode 5   | Polarization :     | --           |

| Freq. | Reading  | Limit    | Margin | State |
|-------|----------|----------|--------|-------|
| (MHz) | (dBuV/m) | (dBuV/m) | (dB)   | P/F   |
| --    | --       | --       | --     | PASS  |
| --    | --       | --       | --     | PASS  |

**NOTE:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.

**3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)**

|                |              |                    |            |
|----------------|--------------|--------------------|------------|
| Temperature:   | 26℃          | Relative Humidity: | 54%        |
| Pressure:      | 1010 hPa     | Polarization :     | Horizontal |
| Test Voltage : | AC 120V/60Hz |                    |            |
| Test Mode :    | Mode 5       |                    |            |



| No. | Mk. | Freq.    | Reading | Correct | Measure- | Limit | Over  |          |
|-----|-----|----------|---------|---------|----------|-------|-------|----------|
|     |     | MHz      | Level   | Factor  | ment     |       |       | Detector |
|     |     |          | dBuV    | dB      | dBuV/m   | dB/m  | dB    |          |
| 1   |     | 54.4515  | 36.73   | -13.69  | 23.04    | 40.00 | 16.96 | QP       |
| 2   |     | 68.1512  | 37.02   | -16.70  | 20.32    | 40.00 | 19.68 | QP       |
| 3   |     | 205.6750 | 38.63   | -15.76  | 22.87    | 43.50 | 20.63 | QP       |
| 4   | *   | 239.9873 | 49.14   | -14.32  | 34.82    | 46.00 | 11.18 | QP       |
| 5   |     | 319.9368 | 39.80   | -12.18  | 27.62    | 46.00 | 18.38 | QP       |
| 6   |     | 687.1506 | 36.92   | -4.77   | 32.15    | 46.00 | 13.85 | QP       |


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



|                |              |                    |          |
|----------------|--------------|--------------------|----------|
| Temperature:   | 26°C         | Relative Humidity: | 54%      |
| Pressure:      | 1010 hPa     | Polarization :     | Vertical |
| Test Voltage : | AC 120V/60Hz |                    |          |
| Test Mode :    | Mode 5       |                    |          |



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dB/m | Over<br>dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|----------|
| 1   |     | 49.8813      | 37.06                    | -13.31                  | 23.75                      | 40.00         | 16.25      | QP       |
| 2   |     | 106.0126     | 36.53                    | -17.71                  | 18.82                      | 43.50         | 24.68      | QP       |
| 3   |     | 239.9873     | 48.31                    | -14.32                  | 33.99                      | 46.00         | 12.01      | QP       |
| 4   |     | 460.7271     | 40.78                    | -9.17                   | 31.61                      | 46.00         | 14.39      | QP       |
| 5   |     | 568.6126     | 40.43                    | -7.15                   | 33.28                      | 46.00         | 12.72      | QP       |
| 6   | *   | 869.1300     | 36.45                    | -1.91                   | 34.54                      | 46.00         | 11.46      | QP       |

## Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;

**3.2.8 TEST RESULTS (1GHZ~25GHZ)**

802.11b

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2412 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 4824      | 67.16            | 50.65             | 6.88          | 31.29             | 54.68             | 74       | -19.32 | PK               |
| V                        | 4824      | 55.25            | 50.65             | 6.88          | 31.29             | 42.77             | 54       | -11.23 | AV               |
| V                        | 7236      | 66.28            | 49.98             | 7.16          | 36.63             | 60.09             | 74       | -13.91 | PK               |
| V                        | 7236      | 46.19            | 49.98             | 7.16          | 36.63             | 40                | 54       | -14    | AV               |
| V                        | 16087     | 48.65            | 51.53             | 11.34         | 41.52             | 49.98             | 74       | -24.02 | PK               |
| H                        | 4824      | 66.04            | 50.65             | 6.88          | 31.29             | 53.56             | 74       | -20.44 | PK               |
| H                        | 4824      | 55.15            | 50.65             | 6.88          | 31.29             | 42.67             | 54       | -11.33 | AV               |
| H                        | 7236      | 69.23            | 49.98             | 7.16          | 36.63             | 63.04             | 74       | -10.96 | PK               |
| H                        | 7236      | 45.57            | 49.98             | 7.16          | 36.63             | 39.38             | 54       | -14.62 | AV               |
| H                        | 16087     | 48.16            | 51.53             | 11.34         | 41.52             | 49.49             | 74       | -24.51 | PK               |
| operation frequency:2437 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 4874      | 67.17            | 50.67             | 6.89          | 31.38             | 54.77             | 74       | -19.23 | PK               |
| V                        | 4874      | 55.32            | 50.67             | 6.89          | 31.38             | 42.92             | 54       | -11.08 | AV               |
| V                        | 7311      | 69.54            | 50.02             | 7.24          | 36.63             | 63.39             | 74       | -10.61 | PK               |
| V                        | 7311      | 46.82            | 50.02             | 7.24          | 36.63             | 40.67             | 54       | -13.33 | AV               |
| V                        | 16087     | 48.36            | 51.53             | 11.34         | 41.52             | 49.69             | 74       | -24.31 | PK               |
| H                        | 4874      | 66.28            | 50.67             | 6.89          | 31.38             | 53.88             | 74       | -20.12 | PK               |
| H                        | 4874      | 55.34            | 50.67             | 6.89          | 31.38             | 42.94             | 54       | -11.06 | AV               |
| H                        | 7311      | 69.23            | 50.02             | 7.24          | 36.63             | 63.08             | 74       | -10.92 | PK               |
| H                        | 7311      | 47.54            | 50.02             | 7.24          | 36.63             | 41.39             | 54       | -12.61 | AV               |
| H                        | 16087     | 48.56            | 51.53             | 11.34         | 41.52             | 49.89             | 74       | -24.11 | PK               |
| operation frequency:2462 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 4924      | 68.17            | 50.79             | 6.83          | 31.36             | 55.57             | 74       | -18.43 | PK               |
| V                        | 4924      | 55.35            | 50.79             | 6.83          | 31.36             | 42.75             | 54       | -11.25 | AV               |
| V                        | 7386      | 69.23            | 50.11             | 7.25          | 36.58             | 62.95             | 74       | -11.05 | PK               |
| V                        | 7386      | 46.24            | 50.11             | 7.25          | 36.58             | 39.96             | 54       | -14.04 | AV               |
| V                        | 16087     | 49.08            | 51.53             | 11.34         | 41.52             | 50.41             | 74       | -23.59 | PK               |
| H                        | 4924      | 67.34            | 50.79             | 6.83          | 31.36             | 54.74             | 74       | -19.26 | PK               |
| H                        | 4924      | 55.05            | 50.79             | 6.83          | 31.36             | 42.45             | 54       | -11.55 | AV               |
| H                        | 7386      | 67.18            | 50.11             | 7.25          | 36.58             | 60.9              | 74       | -13.1  | PK               |
| H                        | 7386      | 48.68            | 50.11             | 7.25          | 36.58             | 42.4              | 54       | -11.6  | AV               |
| H                        | 16087     | 49.54            | 51.53             | 11.34         | 41.52             | 50.87             | 74       | -23.13 | PK               |

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g

| Polar<br>(H/V)                                                                                                                           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|------------------------------------------------------------------------------------------------------------------------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                                                                                                                                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2412                                                                                                                 |           |                  |                   |               |                   |                   |          |        |                  |
| V                                                                                                                                        | 4824      | 67.54            | 50.65             | 6.88          | 31.29             | 55.06             | 74       | -18.94 | PK               |
| V                                                                                                                                        | 4824      | 55.36            | 50.65             | 6.88          | 31.29             | 42.88             | 54       | -11.12 | AV               |
| V                                                                                                                                        | 7236      | 66.15            | 49.98             | 7.16          | 36.63             | 59.96             | 74       | -14.04 | PK               |
| V                                                                                                                                        | 7236      | 46.55            | 49.98             | 7.16          | 36.63             | 40.36             | 54       | -13.64 | AV               |
| V                                                                                                                                        | 16087     | 49.82            | 51.53             | 11.34         | 41.52             | 51.15             | 74       | -22.85 | PK               |
| H                                                                                                                                        | 4824      | 69.14            | 50.65             | 6.88          | 31.29             | 56.66             | 74       | -17.34 | PK               |
| H                                                                                                                                        | 4824      | 52.56            | 50.65             | 6.88          | 31.29             | 40.08             | 54       | -13.92 | AV               |
| H                                                                                                                                        | 7236      | 66.24            | 49.98             | 7.16          | 36.63             | 60.05             | 74       | -13.95 | PK               |
| H                                                                                                                                        | 7236      | 47.33            | 49.98             | 7.16          | 36.63             | 41.14             | 54       | -12.86 | AV               |
| H                                                                                                                                        | 16087     | 47.27            | 51.53             | 11.34         | 41.52             | 48.6              | 74       | -25.4  | PK               |
| operation frequency:2437                                                                                                                 |           |                  |                   |               |                   |                   |          |        |                  |
| V                                                                                                                                        | 4874      | 67.26            | 50.67             | 6.89          | 31.38             | 54.86             | 74       | -19.14 | PK               |
| V                                                                                                                                        | 4874      | 55.14            | 50.67             | 6.89          | 31.38             | 42.74             | 54       | -11.26 | AV               |
| V                                                                                                                                        | 7311      | 66.25            | 50.02             | 7.24          | 36.63             | 60.1              | 74       | -13.9  | PK               |
| V                                                                                                                                        | 7311      | 46.33            | 50.02             | 7.24          | 36.63             | 40.18             | 54       | -13.82 | AV               |
| V                                                                                                                                        | 16087     | 48.48            | 51.53             | 11.34         | 41.52             | 49.81             | 74       | -24.19 | PK               |
| H                                                                                                                                        | 4874      | 66.34            | 50.67             | 6.89          | 31.38             | 53.94             | 74       | -20.06 | PK               |
| H                                                                                                                                        | 4874      | 55.16            | 50.67             | 6.89          | 31.38             | 42.76             | 54       | -11.24 | AV               |
| H                                                                                                                                        | 7311      | 65.54            | 50.02             | 7.24          | 36.63             | 59.39             | 74       | -14.61 | PK               |
| H                                                                                                                                        | 7311      | 47.33            | 50.02             | 7.24          | 36.63             | 41.18             | 54       | -12.82 | AV               |
| H                                                                                                                                        | 16087     | 48.75            | 51.53             | 11.34         | 41.52             | 50.08             | 74       | -23.92 | PK               |
| operation frequency:2462                                                                                                                 |           |                  |                   |               |                   |                   |          |        |                  |
| V                                                                                                                                        | 4924      | 67.16            | 50.79             | 6.83          | 31.36             | 54.56             | 74       | -19.44 | PK               |
| V                                                                                                                                        | 4924      | 55.34            | 50.79             | 6.83          | 31.36             | 42.74             | 54       | -11.26 | AV               |
| V                                                                                                                                        | 7386      | 66.23            | 50.11             | 7.25          | 36.58             | 59.95             | 74       | -14.05 | PK               |
| V                                                                                                                                        | 7386      | 47.45            | 50.11             | 7.25          | 36.58             | 41.17             | 54       | -12.83 | AV               |
| V                                                                                                                                        | 16087     | 46.06            | 51.53             | 11.34         | 41.52             | 47.39             | 74       | -26.61 | PK               |
| H                                                                                                                                        | 4924      | 66.34            | 50.79             | 6.83          | 31.36             | 53.74             | 74       | -20.26 | PK               |
| H                                                                                                                                        | 4924      | 54.56            | 50.79             | 6.83          | 31.36             | 41.96             | 54       | -12.04 | AV               |
| H                                                                                                                                        | 7386      | 65.34            | 50.11             | 7.25          | 36.58             | 59.06             | 74       | -14.94 | PK               |
| H                                                                                                                                        | 7386      | 45.15            | 50.11             | 7.25          | 36.58             | 38.87             | 54       | -15.13 | AV               |
| H                                                                                                                                        | 16087     | 47.23            | 51.53             | 11.34         | 41.52             | 48.56             | 74       | -25.44 | PK               |
| Remark:                                                                                                                                  |           |                  |                   |               |                   |                   |          |        |                  |
| 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,<br>Margin= Emission Level - Limit                       |           |                  |                   |               |                   |                   |          |        |                  |
| 2. If peak below the average limit, the average emission was no test.                                                                    |           |                  |                   |               |                   |                   |          |        |                  |
| 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value<br>has no need to be reported. |           |                  |                   |               |                   |                   |          |        |                  |



802.11n HT20

| Polar<br>(H/V)           | Frequency<br>(MHz) | Meter<br>Reading<br>(dBuV) | Pre-<br>amplifier<br>(dB) | Cable<br>Loss<br>(dB) | Antenna<br>Factor<br>(dB/m) | Emission<br>Level<br>(dBuV/m) | Limits<br>(dBuV/m) | Margin<br>(dB) | Detector<br>Type |
|--------------------------|--------------------|----------------------------|---------------------------|-----------------------|-----------------------------|-------------------------------|--------------------|----------------|------------------|
| operation frequency:2412 |                    |                            |                           |                       |                             |                               |                    |                |                  |
| V                        | 4824               | 66.25                      | 50.65                     | 6.88                  | 31.29                       | 53.77                         | 74                 | -20.23         | PK               |
| V                        | 4824               | 55.03                      | 50.65                     | 6.88                  | 31.29                       | 42.55                         | 54                 | -11.45         | AV               |
| V                        | 7236               | 66.67                      | 49.98                     | 7.16                  | 36.63                       | 60.48                         | 74                 | -13.52         | PK               |
| V                        | 7236               | 46.45                      | 49.98                     | 7.16                  | 36.63                       | 40.26                         | 54                 | -13.74         | AV               |
| V                        | 16087              | 46.53                      | 51.53                     | 11.34                 | 41.52                       | 47.86                         | 74                 | -26.14         | PK               |
| H                        | 4824               | 66.24                      | 50.65                     | 6.88                  | 31.29                       | 53.76                         | 74                 | -20.24         | PK               |
| H                        | 4824               | 55.15                      | 50.65                     | 6.88                  | 31.29                       | 42.67                         | 54                 | -11.33         | AV               |
| H                        | 7236               | 64.16                      | 49.98                     | 7.16                  | 36.63                       | 57.97                         | 74                 | -16.03         | PK               |
| H                        | 7236               | 47.73                      | 49.98                     | 7.16                  | 36.63                       | 41.54                         | 54                 | -12.46         | AV               |
| H                        | 16087              | 47.31                      | 51.53                     | 11.34                 | 41.52                       | 48.64                         | 74                 | -25.36         | PK               |
| operation frequency:2437 |                    |                            |                           |                       |                             |                               |                    |                |                  |
| V                        | 4874               | 66.35                      | 50.67                     | 6.89                  | 31.38                       | 53.95                         | 74                 | -20.05         | PK               |
| V                        | 4874               | 54.15                      | 50.67                     | 6.89                  | 31.38                       | 41.75                         | 54                 | -12.25         | AV               |
| V                        | 7311               | 65.16                      | 50.02                     | 7.24                  | 36.63                       | 59.01                         | 74                 | -14.99         | PK               |
| V                        | 7311               | 47.33                      | 50.02                     | 7.24                  | 36.63                       | 41.18                         | 54                 | -12.82         | AV               |
| V                        | 16087              | 47.14                      | 51.53                     | 11.34                 | 41.52                       | 48.47                         | 74                 | -25.53         | PK               |
| H                        | 4874               | 65.12                      | 50.67                     | 6.89                  | 31.38                       | 52.72                         | 74                 | -21.28         | PK               |
| H                        | 4874               | 53.28                      | 50.67                     | 6.89                  | 31.38                       | 40.88                         | 54                 | -13.12         | AV               |
| H                        | 7311               | 65.53                      | 50.02                     | 7.24                  | 36.63                       | 59.38                         | 74                 | -14.62         | PK               |
| H                        | 7311               | 46.24                      | 50.02                     | 7.24                  | 36.63                       | 40.09                         | 54                 | -13.91         | AV               |
| H                        | 16087              | 46.75                      | 51.53                     | 11.34                 | 41.52                       | 48.08                         | 74                 | -25.92         | PK               |
| operation frequency:2462 |                    |                            |                           |                       |                             |                               |                    |                |                  |
| V                        | 4924               | 67.13                      | 50.79                     | 6.83                  | 31.36                       | 54.53                         | 74                 | -19.47         | PK               |
| V                        | 4924               | 54.47                      | 50.79                     | 6.83                  | 31.36                       | 41.87                         | 54                 | -12.13         | AV               |
| V                        | 7386               | 64.31                      | 50.11                     | 7.25                  | 36.58                       | 58.03                         | 74                 | -15.97         | PK               |
| V                        | 7386               | 46.15                      | 50.11                     | 7.25                  | 36.58                       | 39.87                         | 54                 | -14.13         | AV               |
| V                        | 16087              | 48.43                      | 51.53                     | 11.34                 | 41.52                       | 49.76                         | 74                 | -24.24         | PK               |
| H                        | 4924               | 67.24                      | 50.79                     | 6.83                  | 31.36                       | 54.64                         | 74                 | -19.36         | PK               |
| H                        | 4924               | 54.53                      | 50.79                     | 6.83                  | 31.36                       | 41.93                         | 54                 | -12.07         | AV               |
| H                        | 7386               | 65.15                      | 50.11                     | 7.25                  | 36.58                       | 58.87                         | 74                 | -15.13         | PK               |
| H                        | 7386               | 47.27                      | 50.11                     | 7.25                  | 36.58                       | 40.99                         | 54                 | -13.01         | AV               |
| H                        | 16087              | 47.35                      | 51.53                     | 11.34                 | 41.52                       | 48.68                         | 74                 | -25.32         | PK               |

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT40

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2422 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 4844      | 66.16            | 50.67             | 6.89          | 31.32             | 53.7              | 74       | -20.3  | PK               |
| V                        | 4844      | 55.24            | 50.67             | 6.89          | 31.32             | 42.78             | 54       | -11.22 | AV               |
| V                        | 7266      | 66.57            | 50.01             | 7.15          | 36.62             | 60.33             | 74       | -13.67 | PK               |
| V                        | 7266      | 46.43            | 50.01             | 7.15          | 36.62             | 40.19             | 54       | -13.81 | AV               |
| V                        | 16087     | 46.66            | 51.53             | 11.34         | 41.52             | 47.99             | 74       | -26.01 | PK               |
| H                        | 4844      | 66.31            | 50.67             | 6.89          | 31.32             | 53.85             | 74       | -20.15 | PK               |
| H                        | 4844      | 55.54            | 50.67             | 6.89          | 31.32             | 43.08             | 54       | -10.92 | AV               |
| H                        | 7266      | 64.34            | 50.01             | 7.15          | 36.62             | 58.1              | 74       | -15.9  | PK               |
| H                        | 7266      | 47.57            | 50.01             | 7.15          | 36.62             | 41.33             | 54       | -12.67 | AV               |
| H                        | 16087     | 47.68            | 51.53             | 11.34         | 41.52             | 49.01             | 74       | -24.99 | PK               |
| operation frequency:2437 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 4874      | 66.55            | 50.67             | 6.89          | 31.38             | 54.15             | 74       | -19.85 | PK               |
| V                        | 4874      | 54.43            | 50.67             | 6.89          | 31.38             | 42.03             | 54       | -11.97 | AV               |
| V                        | 7311      | 65.23            | 50.02             | 7.24          | 36.63             | 59.08             | 74       | -14.92 | PK               |
| V                        | 7311      | 46.37            | 50.02             | 7.24          | 36.63             | 40.22             | 54       | -13.78 | AV               |
| V                        | 16087     | 47.25            | 51.53             | 11.34         | 41.52             | 48.58             | 74       | -25.42 | PK               |
| H                        | 4874      | 65.61            | 50.67             | 6.89          | 31.38             | 53.21             | 74       | -20.79 | PK               |
| H                        | 4874      | 53.22            | 50.67             | 6.89          | 31.38             | 40.82             | 54       | -13.18 | AV               |
| H                        | 7311      | 65.47            | 50.02             | 7.24          | 36.63             | 59.32             | 74       | -14.68 | PK               |
| H                        | 7311      | 47.25            | 50.02             | 7.24          | 36.63             | 41.1              | 54       | -12.9  | AV               |
| H                        | 16087     | 46.16            | 51.53             | 11.34         | 41.52             | 47.49             | 74       | -26.51 | PK               |
| operation frequency:2452 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 4904      | 67.34            | 50.76             | 6.81          | 31.31             | 54.7              | 74       | -19.3  | PK               |
| V                        | 4904      | 54.64            | 50.76             | 6.81          | 31.31             | 42                | 54       | -12    | AV               |
| V                        | 7356      | 64.28            | 50.08             | 7.21          | 36.52             | 57.93             | 74       | -16.07 | PK               |
| V                        | 7356      | 47.06            | 50.08             | 7.21          | 36.52             | 40.71             | 54       | -13.29 | AV               |
| V                        | 16087     | 48.41            | 51.53             | 11.34         | 41.52             | 49.74             | 74       | -24.26 | PK               |
| H                        | 4904      | 67.35            | 50.76             | 6.81          | 31.31             | 54.71             | 74       | -19.29 | PK               |
| H                        | 4904      | 54.37            | 50.76             | 6.81          | 31.31             | 41.73             | 54       | -12.27 | AV               |
| H                        | 7356      | 65.46            | 50.08             | 7.21          | 36.52             | 59.11             | 74       | -14.89 | PK               |
| H                        | 7356      | 46.39            | 50.08             | 7.21          | 36.52             | 40.04             | 54       | -13.96 | AV               |
| H                        | 16087     | 47.15            | 51.53             | 11.34         | 41.52             | 48.48             | 74       | -25.52 | PK               |

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.




For Conducted

During the test, pre-scan the all modulation, and found the 802.11b mode which it is worse case.

Test channel:


Lowest channel



0.03GHz~25GHz

Test channel:

Middle channel




0.03GHz~25GHz



Test channel:

Highest channel



0.03GHz~25GHz



### 3.3 RADIATED BAND EMISSION MEASUREMENT

#### 3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) |         |
|-----------------|------------------------|---------|
|                 | PEAK                   | AVERAGE |
| Above 1000      | 74                     | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter                    | Setting                                          |
|---------------------------------------|--------------------------------------------------|
| Attenuation                           | Auto                                             |
| Start Frequency                       | 2300MHz                                          |
| Stop Frequency                        | 2520                                             |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |

#### 3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


#### 3.3.3 DEVIATION FROM TEST STANDARD

No deviation



### 3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



### 3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



### 3.3.6 TEST RESULT

802.11b

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2412 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2390      | 76.43            | 52.12             | 2.73          | 27.38             | 54.42             | 74       | -19.58 | PK               |
| V                        | 2390      | 65.16            | 52.12             | 2.73          | 27.38             | 43.15             | 54       | -10.85 | AV               |
| V                        | 2400      | 76.57            | 52.16             | 2.78          | 27.41             | 54.6              | 74       | -19.4  | PK               |
| V                        | 2400      | 64.35            | 52.16             | 2.78          | 27.41             | 42.38             | 54       | -11.62 | AV               |
| H                        | 2390      | 76.16            | 52.12             | 2.73          | 27.38             | 54.15             | 74       | -19.85 | PK               |
| H                        | 2390      | 65.35            | 52.12             | 2.73          | 27.38             | 43.34             | 54       | -10.66 | AV               |
| H                        | 2400      | 76.43            | 52.16             | 2.78          | 27.41             | 54.46             | 74       | -19.54 | PK               |
| H                        | 2400      | 65.55            | 52.16             | 2.78          | 27.41             | 43.58             | 54       | -10.42 | AV               |

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2462 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2483.5    | 76.65            | 52.23             | 2.86          | 27.44             | 54.72             | 74       | -19.28 | PK               |
| V                        | 2483.5    | 65.84            | 52.23             | 2.86          | 27.44             | 43.91             | 54       | -10.09 | AV               |
| V                        | 2500      | 76.59            | 52.26             | 2.88          | 27.49             | 54.7              | 74       | -19.3  | PK               |
| V                        | 2500      | 64.23            | 52.26             | 2.88          | 27.49             | 42.34             | 54       | -11.66 | AV               |
| H                        | 2483.5    | 76.13            | 52.23             | 2.86          | 27.44             | 54.2              | 74       | -19.8  | PK               |
| H                        | 2483.5    | 65.66            | 52.23             | 2.86          | 27.44             | 43.73             | 54       | -10.27 | AV               |
| H                        | 2500      | 76.23            | 52.26             | 2.88          | 27.49             | 54.34             | 74       | -19.66 | PK               |
| H                        | 2500      | 65.35            | 52.26             | 2.88          | 27.49             | 43.46             | 54       | -10.54 | AV               |

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11g

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2412 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2390      | 76.45            | 52.12             | 2.73          | 27.38             | 54.44             | 74       | -19.56 | PK               |
| V                        | 2390      | 65.67            | 52.12             | 2.73          | 27.38             | 43.66             | 54       | -10.34 | AV               |
| V                        | 2400      | 76.04            | 52.16             | 2.78          | 27.41             | 54.07             | 74       | -19.93 | PK               |
| V                        | 2400      | 64.16            | 52.16             | 2.78          | 27.41             | 42.19             | 54       | -11.81 | AV               |
| H                        | 2390      | 76.21            | 52.12             | 2.73          | 27.38             | 54.2              | 74       | -19.8  | PK               |
| H                        | 2390      | 65.14            | 52.12             | 2.73          | 27.38             | 43.13             | 54       | -10.87 | AV               |
| H                        | 2400      | 76.23            | 52.16             | 2.78          | 27.41             | 54.26             | 74       | -19.74 | PK               |
| H                        | 2400      | 65.19            | 52.16             | 2.78          | 27.41             | 43.22             | 54       | -10.78 | AV               |

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2462 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2483.5    | 76.33            | 52.23             | 2.86          | 27.44             | 54.4              | 74       | -19.6  | PK               |
| V                        | 2483.5    | 65.15            | 52.23             | 2.86          | 27.44             | 43.22             | 54       | -10.78 | AV               |
| V                        | 2500      | 76.26            | 52.26             | 2.88          | 27.49             | 54.37             | 74       | -19.63 | PK               |
| V                        | 2500      | 65.25            | 52.26             | 2.88          | 27.49             | 43.36             | 54       | -10.64 | AV               |
| H                        | 2483.5    | 76.17            | 52.23             | 2.86          | 27.44             | 54.24             | 74       | -19.76 | PK               |
| H                        | 2483.5    | 65.35            | 52.23             | 2.86          | 27.44             | 43.42             | 54       | -10.58 | AV               |
| H                        | 2500      | 76.26            | 52.26             | 2.88          | 27.49             | 54.37             | 74       | -19.63 | PK               |
| H                        | 2500      | 65.15            | 52.26             | 2.88          | 27.49             | 43.26             | 54       | -10.74 | AV               |

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT20

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2412 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2390      | 76.24            | 52.12             | 2.73          | 27.38             | 54.23             | 74       | -19.77 | PK               |
| V                        | 2390      | 65.16            | 52.12             | 2.73          | 27.38             | 43.15             | 54       | -10.85 | AV               |
| V                        | 2400      | 77.53            | 52.16             | 2.78          | 27.41             | 55.56             | 74       | -18.44 | PK               |
| V                        | 2400      | 65.25            | 52.16             | 2.78          | 27.41             | 43.28             | 54       | -10.72 | AV               |
| H                        | 2390      | 77.37            | 52.12             | 2.73          | 27.38             | 55.36             | 74       | -18.64 | PK               |
| H                        | 2390      | 65.23            | 52.12             | 2.73          | 27.38             | 43.22             | 54       | -10.78 | AV               |
| H                        | 2400      | 76.45            | 52.16             | 2.78          | 27.41             | 54.48             | 74       | -19.52 | PK               |
| H                        | 2400      | 65.16            | 52.16             | 2.78          | 27.41             | 43.19             | 54       | -10.81 | AV               |

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2462 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2483.5    | 77.26            | 52.23             | 2.86          | 27.44             | 55.33             | 74       | -18.67 | PK               |
| V                        | 2483.5    | 65.67            | 52.23             | 2.86          | 27.44             | 43.74             | 54       | -10.26 | AV               |
| V                        | 2500      | 76.53            | 52.26             | 2.88          | 27.49             | 54.64             | 74       | -19.36 | PK               |
| V                        | 2500      | 65.36            | 52.26             | 2.88          | 27.49             | 43.47             | 54       | -10.53 | AV               |
| H                        | 2483.5    | 77.34            | 52.23             | 2.86          | 27.44             | 55.41             | 74       | -18.59 | PK               |
| H                        | 2483.5    | 65.23            | 52.23             | 2.86          | 27.44             | 43.3              | 54       | -10.7  | AV               |
| H                        | 2500      | 76.18            | 52.26             | 2.88          | 27.49             | 54.29             | 74       | -19.71 | PK               |
| H                        | 2500      | 66.05            | 52.26             | 2.88          | 27.49             | 44.16             | 54       | -9.84  | AV               |

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



802.11n HT40

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2422 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2390      | 76.14            | 52.12             | 2.73          | 27.38             | 54.13             | 74       | -19.87 | PK               |
| V                        | 2390      | 65.36            | 52.12             | 2.73          | 27.38             | 43.35             | 54       | -10.65 | AV               |
| V                        | 2400      | 77.67            | 52.16             | 2.78          | 27.41             | 55.7              | 74       | -18.3  | PK               |
| V                        | 2400      | 65.55            | 52.16             | 2.78          | 27.41             | 43.58             | 54       | -10.42 | AV               |
| H                        | 2390      | 77.61            | 52.12             | 2.73          | 27.38             | 55.6              | 74       | -18.4  | PK               |
| H                        | 2390      | 65.24            | 52.12             | 2.73          | 27.38             | 43.23             | 54       | -10.77 | AV               |
| H                        | 2400      | 76.65            | 52.16             | 2.78          | 27.41             | 54.68             | 74       | -19.32 | PK               |
| H                        | 2400      | 65.36            | 52.16             | 2.78          | 27.41             | 43.39             | 54       | -10.61 | AV               |

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2452 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2483.5    | 77.55            | 52.23             | 2.86          | 27.44             | 55.62             | 74       | -18.38 | PK               |
| V                        | 2483.5    | 65.33            | 52.23             | 2.86          | 27.44             | 43.4              | 54       | -10.6  | AV               |
| V                        | 2500      | 76.85            | 52.26             | 2.88          | 27.49             | 54.96             | 74       | -19.04 | PK               |
| V                        | 2500      | 65.86            | 52.26             | 2.88          | 27.49             | 43.97             | 54       | -10.03 | AV               |
| H                        | 2483.5    | 77.35            | 52.23             | 2.86          | 27.44             | 55.42             | 74       | -18.58 | PK               |
| H                        | 2483.5    | 65.27            | 52.23             | 2.86          | 27.44             | 43.34             | 54       | -10.66 | AV               |
| H                        | 2500      | 76.66            | 52.26             | 2.88          | 27.49             | 54.77             | 74       | -19.23 | PK               |
| H                        | 2500      | 66.14            | 52.26             | 2.88          | 27.49             | 44.25             | 54       | -9.75  | AV               |

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.