

RF EXPOSURE EVALUATION

EUT Specification

EUT	Smart Watch
Model Number	V2
Series Model	V3, V6, V5, V7, V8, V9, V10, Series 9, WATCH9, V600, V700, VC10, V800, VC20, V900, VC21, VC30, VC40
FCC ID	2A4T8-V2
Antenna gain (Max)	-2.94dBi
Operation Frequency	2402-2480MHz
Rating	5V,100mA Battery: DC 3.7V, 260mAh
Classification Per Stipulated Test Standard	§ 15.247(i), § 2.1093
Modulation	GFSK, 2GFSK, $\pi/4$ -DQPSK, 8DPSK
Max. output power	BR+EDR: 7.86dBm(0.0061W), BLE: -5.13dBm(0.0003W)

Test Requirement:

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by §2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

One antenna is available for the EUT. The minimum separation distance is 5mm.

BR+EDR:

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
2402	GFSK	6.78	7±1	8	1.955764	3
2441	GFSK	5.37	5±1	6	1.243981	3
2480	GFSK	4.15	4±1	5	0.995992	3
2402	Π/4-DQPSK	7.4	7±1	8	1.955764	3
2441	Π/4-DQPSK	6	6±1	7	1.566080	3
2480	Π/4-DQPSK	4.81	5±1	6	1.253880	3
2402	8DPSK	7.86	8±1	9	2.462161	3
2441	8DPSK	6.62	7±1	8	1.971578	3
2480	8DPSK	5.41	5±1	6	1.253880	3

BLE:

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
2402	GFSK	-5.19	-4±1	-3	0.155352	3
2440	GFSK	-5.25	-4±1	-3	0.156576	3
2480	GFSK	-5.86	-3±1	-2	0.198727	3
2402	2GFSK	-5.13	-4±1	-3	0.155352	3
2440	2GFSK	-5.22	-3±1	-2	0.197117	3
2480	2GFSK	-5.85	-3±1	-2	0.198727	3

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

Signature:



Shawn Wen

Date: 2023-09-01