



# FCC Part 15C Test Report

## FCC ID: 2A4UX-K188

Applicant: Shenzhen Jingrui Weiye Technology Co., Ltd.

Address: 7/f, building B, Tea Tree Phase II, Gushu Sanwei industrial zone, Xixiang Street, Bao 'an district, Shenzhen

Manufacturer: Shenzhen Jingrui Weiye Technology Co., Ltd.

Address: 7/f, building B, Tea Tree Phase II, Gushu Sanwei industrial zone, Xixiang Street, Bao 'an district, Shenzhen

EUT: MP3

Trade Mark: N/A

Model Number: K188

Date of Receipt: Feb. 23, 2022

Test Date: Feb. 23, 2022 - Mar. 01 , 2022

Date of Report: Mar. 01 , 2022

Prepared By: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

Applicable Standards: FCC PART 15 C 15.247  
ANSI C63.10: 2013

Test Result: Pass

Report Number: DL-20220225017

Prepared (Test Engineer): Pxing Huang

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



*This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.*



## Table of Contents

## Page

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>1. SUMMARY OF TEST RESULTS.....</b>                           | <b>5</b>  |
| 1.1 MEASUREMENT UNCERTAINTY.....                                 | 5         |
| <b>2. GENERAL INFORMATION.....</b>                               | <b>6</b>  |
| 2.1 GENERAL DESCRIPTION OF EUT.....                              | 6         |
| 2.2 DESCRIPTION OF TEST MODES.....                               | 7         |
| 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED..... | 7         |
| 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE).....            | 7         |
| 2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING.....            | 7         |
| 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS.....                      | 8         |
| <b>3. EMC EMISSION TEST.....</b>                                 | <b>9</b>  |
| 3.1 CONDUCTED EMISSION MEASUREMENT.....                          | 9         |
| 3.2 POWER LINE CONDUCTED EMISSION Limits.....                    | 9         |
| 3.3TEST PROCEDURE.....                                           | 9         |
| 3.4 DEVIATION FROM TEST STANDARD.....                            | 9         |
| 3.5 TEST SETUP.....                                              | 10        |
| 3.6 EUT OPERATING CONDITIONS.....                                | 10        |
| 3.7 TEST RESULTS.....                                            | 10        |
| <b>4. RADIATED EMISSION MEASUREMENT.....</b>                     | <b>13</b> |
| 4.1 RADIATED EMISSION LIMITS.....                                | 13        |
| 4.2 TEST PROCEDURE.....                                          | 14        |
| 4.3 DEVIATION FROM TEST STANDARD.....                            | 14        |
| 4.4 TEST SETUP.....                                              | 14        |
| 4.5 EUT OPERATING CONDITIONS.....                                | 15        |
| 4.6 TEST RESULTS.....                                            | 15        |
| <b>5. RADIATED BAND EMISSION MEASUREMENT.....</b>                | <b>19</b> |
| 5.1 TEST REQUIREMENT:.....                                       | 19        |
| 5.2 TEST PROCEDURE.....                                          | 19        |
| 5.3 DEVIATION FROM TEST STANDARD.....                            | 19        |
| 5.4 TEST SETUP.....                                              | 20        |
| 5.5 EUT OPERATING CONDITIONS.....                                | 20        |
| 5.6 TEST RESULT.....                                             | 21        |

**Table of Contents****Page**

|                                                |           |
|------------------------------------------------|-----------|
| <b>6. PEAK OUTPUT POWER.....</b>               | <b>22</b> |
| 6.1 APPLIED PROCEDURES / LIMIT.....            | 22        |
| 6.2 TEST PROCEDURE.....                        | 22        |
| 6.3 DEVIATION FROM STANDARD.....               | 22        |
| 6.4 TEST SETUP.....                            | 22        |
| 6.5 EUT OPERATION CONDITIONS.....              | 22        |
| 6.6 TEST RESULTS.....                          | 22        |
| <b>7. POWER SPECTRAL DENSITY TEST.....</b>     | <b>23</b> |
| 7.1 APPLIED PROCEDURES / LIMIT.....            | 23        |
| 7.2 TEST PROCEDURE.....                        | 23        |
| 7.3 DEVIATION FROM STANDARD.....               | 23        |
| 7.4 TEST SETUP.....                            | 23        |
| 7.5 EUT OPERATION CONDITIONS.....              | 23        |
| 7.6 TEST RESULTS.....                          | 23        |
| <b>8. 6DB BANDWIDTH TEST.....</b>              | <b>26</b> |
| 8.1 APPLIED PROCEDURES / LIMIT.....            | 26        |
| 8.2 TEST PROCEDURE.....                        | 26        |
| 8.3 DEVIATION FROM STANDARD.....               | 26        |
| 8.4 TEST SETUP.....                            | 26        |
| 8.5 EUT OPERATION CONDITIONS.....              | 26        |
| 8.6 TEST RESULTS.....                          | 26        |
| <b>9. OUT OF BAND EMISSIONS TEST.....</b>      | <b>27</b> |
| 9.1 APPLIED PROCEDURES / LIMIT.....            | 29        |
| 9.2 TEST PROCEDURE.....                        | 29        |
| 9.3 DEVIATION FROM STANDARD.....               | 29        |
| 9.4 TEST SETUP.....                            | 29        |
| 9.5 EUT OPERATION CONDITIONS.....              | 29        |
| 9.6 TEST RESULTS.....                          | 29        |
| <b>10. SPURIOUS RF CONDUCTED EMISSION.....</b> | <b>31</b> |
| 10.1 APPLIED PROCEDURES / LIMIT.....           | 31        |
| 10.2 TEST PROCEDURE.....                       | 31        |



| Table of Contents                   | Page      |
|-------------------------------------|-----------|
| 10.3 DEVIATION FROM STANDARD.....   | 31        |
| 10.4 TEST SETUP.....                | 31        |
| 10.5 EUT OPERATION CONDITIONS.....  | 31        |
| 10.6 TEST RESULTS.....              | 32        |
| <b>11. ANTENNA REQUIREMENT.....</b> | <b>35</b> |
| 11.1 STANDARD REQUIREMENT.....      | 35        |
| 11.2 EUT ANTENNA.....               | 35        |
| <b>12. TEST SEUUP PHOTO.....</b>    | <b>36</b> |



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.247) , Subpart C |                             |          |        |
|---------------------------------|-----------------------------|----------|--------|
| Standard Section                | Test Item                   | Judgment | Remark |
| 15.207                          | Conducted Emission          | N/A      |        |
| 15.247(c)                       | Radiated Spurious Emission  | PASS     |        |
| 15.205                          | Band Edge Emission          | PASS     |        |
| 15.247(b)(1)                    | Peak Output Power           | PASS     |        |
| 15.247(a)(2)                    | 6dB Bandwidth               | PASS     |        |
| 15.247(e)                       | Power Spectral Density      | PASS     |        |
| 15.247(d)                       | Band edge measurements      | PASS     |        |
| 15.247(d)                       | Conducted Spurious Emission | PASS     |        |
| 15.203                          | Antenna Requirement         | PASS     |        |

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

### 1.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  providing a level of confidence of approximately 95 %.

| No. | Item                         | Uncertainty               |
|-----|------------------------------|---------------------------|
| 1   | Conducted Emission Test      | $\pm 2.56\text{dB}$       |
| 2   | RF power,conducted           | $\pm 0.42\text{dB}$       |
| 3   | Spurious emissions,conducted | $\pm 2.76\text{dB}$       |
| 4   | All emissions,radiated(<1G)  | $\pm 3.65\text{dB}$       |
| 5   | All emissions,radiated(>1G)  | $\pm 4.89\text{dB}$       |
| 6   | Temperature                  | $\pm 0.5^{\circ}\text{C}$ |
| 7   | Humidity                     | $\pm 2\%$                 |

### 1.2 TEST FACILITY

Shenzhen DL Testing Technology Co., Ltd.

Add.: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China

FCC Test Firm Registration Number: 854456

Designation Number: CN1307

IC Registered No.: CN0118



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                      |                     |
|----------------------|---------------------|
| Product Name:        | MP3                 |
| Trademark:           | N/A                 |
| Model No.:           | K188                |
| Sample No.:          | DL-20220225017 #1   |
| Operation Frequency: | 2402~2480 MHz       |
| Channel Numbers:     | 40 Channels for BLE |
| Channel Separation:  | 2MHz                |
| Modulation Type:     | GFSK                |
| Antenna Type:        | PCB Antenna         |
| Antenna Gain:        | 0 dBi               |
| Power Supply:        | DC 3.7V Battery     |

Note:

1.For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.The EUT's all information provided by client.

3.Channel List

| Channel List |                 |         |                 |         |                 |         |                 |
|--------------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| Channel      | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 00           | 2402            | 10      | 2422            | 20      | 2442            | 30      | 2462            |
| 01           | 2404            | 11      | 2424            | 21      | 2444            | 31      | 2464            |
| 02           | 2406            | 12      | 2426            | 22      | 2446            | 32      | 2466            |
| 03           | 2408            | 13      | 2428            | 23      | 2448            | 33      | 2468            |
| 04           | 2410            | 14      | 2430            | 24      | 2450            | 34      | 2470            |
| 05           | 2412            | 15      | 2432            | 25      | 2452            | 35      | 2472            |
| 06           | 2414            | 16      | 2434            | 26      | 2454            | 36      | 2474            |
| 07           | 2416            | 17      | 2436            | 27      | 2456            | 37      | 2476            |
| 08           | 2418            | 18      | 2438            | 28      | 2458            | 38      | 2478            |
| 09           | 2420            | 19      | 2440            | 29      | 2460            | 39      | 2480            |




## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode   | Description |
|----------------|-------------|
| Low Channel    | 2402MHz     |
| Middle Channel | 2440MHz     |
| High Channel   | 2480MHz     |

## 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



## 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Model/Type No. | Series No. | Note |
|------|-----------|----------------|------------|------|
| 1    | Notebook  | Lenovo G475    | GB14477457 | AE   |
|      |           |                |            |      |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|------|
|      |               |              |        |      |

Note: For detachable type I/O cable should be specified the length in cm in 『Length』 column.

## 2.5 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the end product.

| Max output power Setting |                                     |   |
|--------------------------|-------------------------------------|---|
| Test software Version    | Test Program: RTL8762x_RF Test Tool | / |



## 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

### Radiation test, Band-edge test and 6db bandwidth test equipment

| Item | Equipment                        | Manufacturer    | Type No.  | Serial No. | Last calibration | Calibrated until |
|------|----------------------------------|-----------------|-----------|------------|------------------|------------------|
| 1    | Spectrum Analyzer (9kHz-26.5GHz) | Agilent         | E4408B    | MY50140780 | Dec. 06, 2021    | Dec. 05, 2022    |
| 2    | Test Receiver (9kHz-7GHz)        | R&S             | ESRP7     | 101393     | Dec. 06, 2021    | Dec. 05, 2022    |
| 3    | Bilog Antenna (30MHz-1GHz)       | R&S             | VULB9162  | 00306      | Dec. 06, 2021    | Dec. 05, 2022    |
| 4    | Horn Antenna (1GHz-18GHz)        | Schwarzbeck     | BBHA9120D | 02139      | Dec. 06, 2021    | Dec. 05, 2022    |
| 5    | Horn Antenna (18GHz-40GHz)       | A.H. Systems    | SAS-574   | 588        | Dec. 06, 2021    | Dec. 05, 2022    |
| 6    | Amplifier (9KHz-6GHz)            | Schwarzbeck     | BBV9743B  | 00153      | Dec. 06, 2021    | Dec. 05, 2022    |
| 7    | Amplifier (1GHz-18GHz)           | EMEC            | EM01G8GA  | 00270      | Dec. 06, 2021    | Dec. 05, 2022    |
| 8    | Amplifier (18GHz-40GHz)          | Quanjuda        | DLE-161   | 97         | Dec. 06, 2021    | Dec. 05, 2022    |
| 9    | Loop Antenna (9KHz-30MHz)        | Schwarzbeck     | FMZB1519B | 00014      | Dec. 06, 2021    | Dec. 05, 2022    |
| 10   | RF cables1 (9kHz-1GHz)           | ChengYu         | 966       | 004        | Dec. 06, 2021    | Dec. 05, 2022    |
| 11   | RF cables2 (1GHz-40GHz)          | ChengYu         | 966       | 003        | Dec. 06, 2021    | Dec. 05, 2022    |
| 12   | Antenna connector                | Florida RF Labs | N/A       | RF 01#     | Dec. 06, 2021    | Dec. 05, 2022    |
| 13   | Power probe                      | KEYSIGHT        | U2021XA   | MY55210018 | Dec. 06, 2021    | Dec. 05, 2022    |
| 14   | Signal Analyzer 9kHz-26.5GHz     | Agilent         | N9020A    | MY55370280 | Dec. 06, 2021    | Dec. 05, 2022    |
| 15   | Test Receiver 20kHz-40GHz        | R&S             | ESU 40    | 100376     | Dec. 06, 2021    | Dec. 05, 2022    |
| 16   | D.C. Power Supply                | LongWei         | PS-305D   | 010964729  | Dec. 06, 2021    | Dec. 05, 2022    |

### Conduction Test equipment

| Item | Equipment         | Manufacturer | Type No.  | Serial No. | Last calibration | Calibrated until |
|------|-------------------|--------------|-----------|------------|------------------|------------------|
| 1    | 843 Shielded Room | ChengYu      | 843 Room  | 843        | Nov. 25, 2019    | Nov. 24, 2022    |
| 2    | EMI Receiver      | R&S          | ESR       | 101421     | Dec. 06, 2021    | Dec. 05, 2022    |
| 3    | LISN              | Schwarzbeck  | NNLK 8128 | 5089       | Dec. 06, 2021    | Dec. 05, 2022    |
| 4    | 843 Cable 1#      | ChengYu      | CE Cable  | 001        | Dec. 06, 2021    | Dec. 05, 2022    |

### Other

| Item | Name                         | Manufacturer | Model   | Software version |
|------|------------------------------|--------------|---------|------------------|
| 1    | EMC Conduction Test System   | e3           | EMC32   | e3 190613(V9)    |
| 2    | EMC radiation test system    | e3           | EMC32   | e3 190613(V9)    |
| 3    | RF test system               | MAIWEI       | MTS8310 | 2.0.0.0          |
| 4    | RF communication test system | MAIWEI       | MTS8200 | 2.0.0.0          |



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

#### 3.2 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

| FREQUENCY (MHz) | Limit (dBuV) |           | Standard |
|-----------------|--------------|-----------|----------|
|                 | Quasi-peak   | Average   |          |
| 0.15 -0.5       | 66 - 56 *    | 56 - 46 * | FCC      |
| 0.50 -5.0       | 56.00        | 46.00     | FCC      |
| 5.0 -30.0       | 60.00        | 50.00     | FCC      |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |


#### 3.3 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 3.4 DEVIATION FROM TEST STANDARD

No deviation

### 3.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


### 3.6 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

### 3.7 TEST RESULTS




|                |              |                    |     |
|----------------|--------------|--------------------|-----|
| Temperature:   | 25 °C        | Relative Humidity: | 54% |
| Pressure:      | 1010hPa      | Phase :            | L   |
| Test Voltage : | AC 120V/60Hz |                    |     |



|    | Freq   | Level | Limit | Over   | Remark  |
|----|--------|-------|-------|--------|---------|
|    | MHz    | dBuV  | Line  | Limit  |         |
|    |        |       | dBuV  | dB     |         |
| 1  | 0.396  | 37.44 | 47.95 | -10.51 | Average |
| 2  | 0.396  | 43.57 | 57.95 | -14.38 | QP      |
| 3  | 0.555  | 41.58 | 46.00 | -4.42  | Average |
| 4  | 0.555  | 46.84 | 56.00 | -9.16  | QP      |
| 5  | 0.585  | 41.06 | 46.00 | -4.94  | Average |
| 6  | 0.585  | 46.79 | 56.00 | -9.21  | QP      |
| 7  | 0.658  | 42.37 | 46.00 | -3.63  | Average |
| 8  | 0.658  | 51.24 | 56.00 | -4.76  | QP      |
| 9  | 0.694  | 39.83 | 46.00 | -6.17  | Average |
| 10 | 0.694  | 46.83 | 56.00 | -9.17  | QP      |
| 11 | 10.452 | 34.83 | 50.00 | -15.17 | Average |
| 12 | 10.452 | 47.81 | 60.00 | -12.19 | QP      |



|                |              |                    |     |
|----------------|--------------|--------------------|-----|
| Temperature:   | 25 °C        | Relative Humidity: | 54% |
| Pressure:      | 1010hPa      | Phase :            | N   |
| Test Voltage : | AC 120V/60Hz |                    |     |



|    | Freq   | Level | Limit | Over   |         |
|----|--------|-------|-------|--------|---------|
|    | MHz    | dBuV  | Line  | Limit  | Remark  |
| 1  | 0.396  | 37.56 | 47.95 | -10.39 | Average |
| 2  | 0.396  | 42.57 | 57.95 | -15.38 | QP      |
| 3  | 0.555  | 41.43 | 46.00 | -4.57  | Average |
| 4  | 0.555  | 46.87 | 56.00 | -9.13  | QP      |
| 5  | 0.665  | 42.25 | 46.00 | -3.75  | Average |
| 6  | 0.665  | 52.79 | 56.00 | -3.21  | QP      |
| 7  | 0.923  | 34.36 | 46.00 | -11.64 | Average |
| 8  | 0.923  | 39.62 | 56.00 | -16.38 | QP      |
| 9  | 1.585  | 34.21 | 46.00 | -11.79 | Average |
| 10 | 1.585  | 38.64 | 56.00 | -17.36 | QP      |
| 11 | 10.452 | 34.23 | 50.00 | -15.77 | Average |
| 12 | 10.452 | 46.75 | 60.00 | -13.25 | QP      |



#### 4. RADIATED EMISSION MEASUREMENT

##### 4.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies<br>(MHz) | Field Strength<br>(micovolts/meter) | Measurement Distance<br>(meters) |
|----------------------|-------------------------------------|----------------------------------|
| 0.009~0.490          | 2400/F(KHz)                         | 300                              |
| 0.490~1.705          | 24000/F(KHz)                        | 30                               |
| 1.705~30.0           | 30                                  | 30                               |
| 30~88                | 100                                 | 3                                |
| 88~216               | 150                                 | 3                                |
| 216~960              | 200                                 | 3                                |
| Above 960            | 500                                 | 3                                |

##### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) |         |
|-----------------|------------------------|---------|
|                 | PEAK                   | AVERAGE |
| Above 1000      | 74                     | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter                    | Setting                                          |
|---------------------------------------|--------------------------------------------------|
| Attenuation                           | Auto                                             |
| Start Frequency                       | 1000 MHz                                         |
| Stop Frequency                        | 25GHz                                            |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter     | Setting                          |
|------------------------|----------------------------------|
| Attenuation            | Auto                             |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |



## 4.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre( Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

## 4.3 DEVIATION FROM TEST STANDARD


No deviation

## 4.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



### (C) Radiated Emission Test-Up Frequency Above 1GHz



## 4.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

## 4.6 TEST RESULTS


Note: 1. All modes were tested at Low, Middle, and High channel, only the worst result of GFSK Low Channel was reported.

2. By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, and test data recorded in this report.



## Below 1GHz Test Results

|                |                                   |                    |            |
|----------------|-----------------------------------|--------------------|------------|
| Temperature:   | 26℃                               | Relative Humidity: | 54%        |
| Pressure:      | 1010 hPa                          | Polarization :     | Horizontal |
| Test Voltage : | DC 3.7V                           |                    |            |
| Test Mode :    | Transmitting mode of GFSK 2402MHz |                    |            |



|   | Freq   | Read  | Antenna | Cable | Limit  | Over   |           |
|---|--------|-------|---------|-------|--------|--------|-----------|
|   | MHz    | Level | Factor  | Loss  | Line   | Limit  | Remark    |
|   | MHz    | dBuV  | dB/m    | dB    | dBuV/m | dBuV/m | dB        |
| 1 | 32.91  | 7.89  | 17.08   | 0.27  | 25.24  | 40.00  | -14.76 QP |
| 2 | 94.02  | 19.44 | 9.30    | 0.16  | 28.90  | 43.50  | -14.60 QP |
| 3 | 126.03 | 24.44 | 8.38    | 0.21  | 33.03  | 43.50  | -10.47 QP |
| 4 | 188.11 | 23.62 | 10.16   | 0.27  | 34.05  | 43.50  | -9.45 QP  |
| 5 | 310.33 | 20.72 | 14.09   | 0.67  | 35.48  | 46.00  | -10.52 QP |
| 6 | 358.83 | 18.64 | 16.11   | 0.80  | 35.55  | 46.00  | -10.45 QP |


Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



|                |                                   |                    |          |
|----------------|-----------------------------------|--------------------|----------|
| Temperature:   | 26℃                               | Relative Humidity: | 54%      |
| Pressure:      | 1010 hPa                          | Polarization :     | Vertical |
| Test Voltage : | DC 3.7V                           |                    |          |
| Test Mode :    | Transmitting mode of GFSK 2402MHz |                    |          |



|     | Freq   | Read  | Antenna | Cable |        | Limit  | Over   |        |
|-----|--------|-------|---------|-------|--------|--------|--------|--------|
|     | MHz    | Level | Factor  | Loss  | Level  | Line   | Limit  | Remark |
|     | MHz    | dBuV  | dB/m    | dB    | dBuV/m | dBuV/m | dB     |        |
| 1   | 34.85  | 16.36 | 15.94   | 0.23  | 32.53  | 40.00  | -7.47  | QP     |
| 2 ! | 45.52  | 23.91 | 10.64   | 0.12  | 34.67  | 40.00  | -5.33  | QP     |
| 3   | 55.22  | 24.52 | 8.02    | 0.13  | 32.67  | 40.00  | -7.33  | QP     |
| 4 ! | 80.44  | 27.96 | 8.05    | 0.15  | 36.16  | 40.00  | -3.84  | QP     |
| 5   | 127.00 | 23.54 | 8.36    | 0.21  | 32.11  | 43.50  | -11.39 | QP     |
| 6   | 319.06 | 18.06 | 14.33   | 0.69  | 33.08  | 46.00  | -12.92 | QP     |

Remark:

Correct Factor = Cable loss + Antenna factor – Preamplifier;

Level = Reading Level + Correct Factor; Margin = Limit – Level;



## Above 1GHz Test Results

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2402 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 4804.00   | 61.74            | 51.74             | 3.08          | 31.25             | 44.33             | 74.00    | -29.67 | PK               |
| V                        | 4804.00   | 45.83            | 51.74             | 3.08          | 31.25             | 28.42             | 54.00    | -25.58 | AV               |
| V                        | 7206.00   | 68.90            | 49.98             | 7.16          | 36.63             | 62.71             | 74.00    | -11.29 | PK               |
| V                        | 7206.00   | 53.07            | 49.98             | 7.16          | 36.63             | 46.88             | 54.00    | -7.12  | AV               |
| V                        | 16086.00  | 48.93            | 51.53             | 11.34         | 41.52             | 50.26             | 74.00    | -23.74 | PK               |
| H                        | 4804.00   | 61.94            | 51.74             | 3.08          | 31.25             | 44.53             | 74.00    | -29.47 | PK               |
| H                        | 4804.00   | 46.03            | 51.74             | 3.08          | 31.25             | 28.62             | 54.00    | -25.38 | AV               |
| H                        | 7206.00   | 67.34            | 49.98             | 7.16          | 36.63             | 61.15             | 74.00    | -12.85 | PK               |
| H                        | 7206.00   | 53.31            | 49.98             | 7.16          | 36.63             | 47.12             | 54.00    | -6.88  | AV               |
| H                        | 16086.00  | 49.09            | 51.53             | 11.34         | 41.52             | 50.42             | 74.00    | -23.58 | PK               |
| operation frequency:2440 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 4880.00   | 60.99            | 51.77             | 3.03          | 31.34             | 43.59             | 74.00    | -30.41 | PK               |
| V                        | 4880.00   | 45.19            | 51.77             | 3.03          | 31.34             | 27.79             | 54.00    | -26.21 | AV               |
| V                        | 7320.00   | 69.08            | 50.02             | 7.24          | 36.63             | 62.93             | 74.00    | -11.07 | PK               |
| V                        | 7320.00   | 53.13            | 50.02             | 7.24          | 36.63             | 46.98             | 54.00    | -7.02  | AV               |
| V                        | 16087.00  | 48.50            | 51.53             | 11.34         | 41.52             | 49.83             | 74.00    | -24.17 | PK               |
| H                        | 4880.00   | 61.09            | 51.77             | 3.03          | 31.34             | 43.69             | 74.00    | -30.31 | PK               |
| H                        | 4880.00   | 45.29            | 51.77             | 3.03          | 31.34             | 27.89             | 54.00    | -26.11 | AV               |
| H                        | 7320.00   | 69.27            | 50.02             | 7.24          | 36.63             | 63.12             | 74.00    | -10.88 | PK               |
| H                        | 7320.00   | 53.34            | 50.02             | 7.24          | 36.63             | 47.19             | 54.00    | -6.81  | AV               |
| H                        | 16087.00  | 48.56            | 51.53             | 11.34         | 41.52             | 49.89             | 74.00    | -24.11 | PK               |
| operation frequency:2480 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 4960.00   | 61.76            | 51.69             | 3.05          | 31.39             | 44.51             | 74       | -29.49 | PK               |
| V                        | 4960.00   | 45.83            | 51.69             | 3.05          | 31.39             | 28.58             | 54       | -25.42 | AV               |
| V                        | 7440.00   | 68.90            | 50.11             | 7.25          | 36.58             | 62.62             | 74       | -11.38 | PK               |
| V                        | 7440.00   | 53.06            | 50.11             | 7.25          | 36.58             | 46.78             | 54       | -7.22  | AV               |
| V                        | 16087.00  | 48.90            | 51.53             | 11.34         | 41.52             | 50.23             | 74       | -23.77 | PK               |
| H                        | 4960.00   | 61.91            | 51.69             | 3.05          | 31.39             | 44.66             | 74       | -29.34 | PK               |
| H                        | 4960.00   | 45.98            | 51.69             | 3.05          | 31.39             | 28.73             | 54       | -25.27 | AV               |
| H                        | 7440.00   | 67.28            | 50.11             | 7.25          | 36.58             | 61.00             | 74       | -13.00 | PK               |
| H                        | 7440.00   | 54.24            | 50.11             | 7.25          | 36.58             | 47.96             | 54       | -6.04  | AV               |
| H                        | 16087.00  | 49.01            | 51.53             | 11.34         | 41.52             | 50.34             | 74       | -23.66 | PK               |

## Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-Amplifier,  
Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.



## 5. RADIATED BAND EMISSION MEASUREMENT

### 5.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Limit (dBuV/m) (at 3M) |         |
|-----------------|------------------------|---------|
|                 | PEAK                   | AVERAGE |
| Above 1000      | 74                     | 54      |

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter                    | Setting                                          |
|---------------------------------------|--------------------------------------------------|
| Attenuation                           | Auto                                             |
| Start Frequency                       | 2300MHz                                          |
| Stop Frequency                        | 2520                                             |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |

### 5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 5.3 DEVIATION FROM TEST STANDARD

No deviation

## 5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



## 5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

**5.6 TEST RESULT**

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2402 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2390.00   | 76.32            | 52.12             | 2.73          | 27.38             | 54.31             | 74       | -19.69 | PK               |
| V                        | 2390.00   | 65.03            | 52.12             | 2.73          | 27.38             | 43.02             | 54       | -10.98 | AV               |
| V                        | 2400.00   | 76.49            | 52.16             | 2.78          | 27.41             | 54.52             | 74       | -19.48 | PK               |
| V                        | 2400.00   | 63.84            | 52.16             | 2.78          | 27.41             | 41.87             | 54       | -12.13 | AV               |
| H                        | 2390.00   | 76.23            | 52.12             | 2.73          | 27.38             | 54.22             | 74       | -19.78 | PK               |
| H                        | 2390.00   | 64.79            | 52.12             | 2.73          | 27.38             | 42.78             | 54       | -11.22 | AV               |
| H                        | 2400.00   | 76.11            | 52.16             | 2.78          | 27.41             | 54.14             | 74       | -19.86 | PK               |
| H                        | 2400.00   | 64.98            | 52.16             | 2.78          | 27.41             | 43.01             | 54       | -10.99 | AV               |

| Polar<br>(H/V)           | Frequency | Meter<br>Reading | Pre-<br>amplifier | Cable<br>Loss | Antenna<br>Factor | Emission<br>Level | Limits   | Margin | Detector<br>Type |
|--------------------------|-----------|------------------|-------------------|---------------|-------------------|-------------------|----------|--------|------------------|
|                          | (MHz)     | (dBuV)           | (dB)              | (dB)          | (dB/m)            | (dBuV/m)          | (dBuV/m) | (dB)   |                  |
| operation frequency:2480 |           |                  |                   |               |                   |                   |          |        |                  |
| V                        | 2483.50   | 75.99            | 52.23             | 2.86          | 27.44             | 54.06             | 74       | -19.94 | PK               |
| V                        | 2483.50   | 64.7             | 52.23             | 2.86          | 27.44             | 42.77             | 54       | -11.23 | AV               |
| V                        | 2500.00   | 75.67            | 52.26             | 2.88          | 27.49             | 53.78             | 74       | -20.22 | PK               |
| V                        | 2500.00   | 63.8             | 52.26             | 2.88          | 27.49             | 41.91             | 54       | -12.09 | AV               |
| H                        | 2483.50   | 76.22            | 52.23             | 2.86          | 27.44             | 54.29             | 74       | -19.71 | PK               |
| H                        | 2483.50   | 65.48            | 52.23             | 2.86          | 27.44             | 43.55             | 54       | -10.45 | AV               |
| H                        | 2500.00   | 76.23            | 52.26             | 2.88          | 27.49             | 54.34             | 74       | -19.66 | PK               |
| H                        | 2500.00   | 64.93            | 52.26             | 2.88          | 27.49             | 43.04             | 54       | -10.96 | AV               |

**Remark:**

1. Emission Level = Reading Level+Antenna Factor+Cable loss-Preamp Factor.
2. Over Limit= Absolute Level - Limit.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has not to be reported.
4. EUT Pre-scan X/Y/Z orientation, only worst case is presented in the report (Z orientation)



## 6. PEAK OUTPUT POWER

### 6.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C |                   |                 |                       |        |
|---------------------------------|-------------------|-----------------|-----------------------|--------|
| Section                         | Test Item         | Limit           | Frequency Range (MHz) | Result |
| 15.247 (b)(3)                   | Peak Output Power | 1 watt or 30dBm | 2400-2483.5           | PASS   |

### 6.2 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below,

### 6.3 DEVIATION FROM STANDARD

No deviation.

### 6.4 TEST SETUP



### 6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

### 6.6 TEST RESULTS

| Test Mode | Channel | Peak Power[dBm] | Conducted Limit[dBm] | Verdict |
|-----------|---------|-----------------|----------------------|---------|
| GFSK      | 2402    | -1.65           | ≤30                  | PASS    |
|           | 2440    | -0.17           | ≤30                  | PASS    |
|           | 2480    | 0.74            | ≤30                  | PASS    |



## 7. POWER SPECTRAL DENSITY TEST

### 7.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C |                        |                        |                       |        |
|---------------------------------|------------------------|------------------------|-----------------------|--------|
| Section                         | Test Item              | Limit                  | Frequency Range (MHz) | Result |
| 15.247                          | Power Spectral Density | 8 dBm<br>(in any 3KHz) | 2400-2483.5           | PASS   |

| Spectrum Parameters | Setting                           |
|---------------------|-----------------------------------|
| Attenuation         | Auto                              |
| Span Frequency      | = the frequency band of operation |
| RB                  | RBW $\geq$ 3kHz                   |
| VB                  | VBW $\geq$ 3RBW                   |
| Detector            | Peak                              |
| Trace               | Max Hold                          |
| Sweep Time          | Auto                              |

### 7.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

### 7.3 DEVIATION FROM STANDARD

No deviation.

### 7.4 TEST SETUP





### 7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

### 7.6 TEST RESULTS

| TestMode | Channel | Result[dBm/3kHz] | Limit[dBm/3kHz] | Verdict |
|----------|---------|------------------|-----------------|---------|
| GFSK     | 2402    | -10.853          | $\leq 8$        | PASS    |
|          | 2440    | -8.683           | $\leq 8$        | PASS    |
|          | 2480    | -7.705           | $\leq 8$        | PASS    |







## 8. 6DB BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C |           |                      |                      |        |
|---------------------------------|-----------|----------------------|----------------------|--------|
| Section                         | Test Item | Limit                | Frequency Range(MHz) | Result |
| 15.247(a)(2)                    | Bandwidth | $\geq 500\text{KHz}$ | 2400-2483.5          | PASS   |

### 8.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

### 8.3 DEVIATION FROM STANDARD

No deviation.

### 8.4 TEST SETUP



### 8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

### 8.6 TEST RESULTS

| Test Mode | Channel | DTS BW [MHz] | Limit[MHz] | Verdict |
|-----------|---------|--------------|------------|---------|
| GFSK      | 2402    | 0.6552       | 0.5        | PASS    |
|           | 2440    | 0.6814       | 0.5        | PASS    |
|           | 2480    | 0.6979       | 0.5        | PASS    |



## BLE\_Ant1\_2402



## BLE\_Ant1\_2440







## 9. OUT OF BAND EMISSIONS TEST

### 9.1 APPLIED PROCEDURES / LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### 9.2 TEST PROCEDURE

1. Set RBW = 100kHz.
2. Set the video bandwidth (VBW)  $\geq 3$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.

### 9.3 DEVIATION FROM STANDARD

No deviation.

### 9.4 TEST SETUP



### 9.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

### 9.6 TEST RESULTS


| Test Mode | ChName | Channel | Result[dB] | Limit[dB] | Verdict |
|-----------|--------|---------|------------|-----------|---------|
| GFSK      | Low    | 2402    | 42.069     | > 20      | PASS    |
|           | High   | 2480    | 49.150     | > 20      | PASS    |



## BLE\_Ant1\_Low\_2402



## BLE\_Ant1\_Low\_2480





## 10. SPURIOUS RF CONDUCTED EMISSION

### 10.1 APPLIED PROCEDURES / LIMIT

1. Below -20dB of the highest emission level in operating band.
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.
3. For below 30MHz, For 9KHz-150kHz, 150K-10MHz, We use the RBW 1KHz, 10KHz, So the limit need to be calculated by " $10\lg(BW1/BW2)$ ". for example For 9KHz-150kHz, RBW 1KHz, The Limit = the highest emission level -  $20 - 10\lg(100/1) =$  the highest emission level - 40.

### 10.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW)  $\geq$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.

### 10.3 DEVIATION FROM STANDARD

No deviation.

### 10.4 TEST SETUP






### 10.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




## 10.6 TEST RESULTS







## BLE Ant1 2480 0~Reference



## BLE Ant1 2480 30~25000





## **11. ANTENNA REQUIREMENT**

### **11.1 STANDARD REQUIREMENT**



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **11.2 EUT ANTENNA**

The EUT antenna is PCB antenna,. It comply with the standard requirement.

## 12. TEST SEUUP PHOTO

### Radiated Measurement Photos





### Conducted Measurement Photos



\*\*\*\*\* END OF REPORT \*\*\*\*\*