

RF Exposure Requirements

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: yongkangshihuarandianqiyouxiangongsi
Address of applicant: kangzhuanglu 196hao, zhiyingzhen, yongkangshi, zhejiangsheng

Manufacturer: yongkangshihuarandianqiyouxiangongsi
Address of manufacturer: kangzhuanglu 196hao, zhiyingzhen, yongkangshi, zhejiangsheng

General Description of EUT	
Product Name:	vibration plate
Brand Name:	AXV
Model No.:	FR-78
Adding Model(s):	FR-118, FR-138, FR-198, FR-268, FR-88, FR-278, FR-288, FR-298, FR-318
Rated Voltage:	AC 120V, 60Hz
Power Adapter:	/
Software Version:	/
Hardware Version:	/
Serial Number:	76453HY76709
FCC ID:	2A4YL-FR

Technical Characteristics of EUT	
Bluetooth Version:	V4.2 (BDR/EDR mode)
Frequency Range:	2402-2480MHz
RF Output Power:	3.90dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79
Channel Separation:	1MHz
Type of Antenna:	PCB
Antenna Gain:	2.5dBi

1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

1.3 Calculation Method

Bluetooth

Tx frequency range: 2402~2480MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: 3.90dBm

RF channel transmit frequency: 2402MHz

Result: 0.76

Limit: 3.0

So the transmitter complies with the RF exposure requirements and the SAR is not required.