Appendix B RF Test Data

RF Test Data for BT (BLE) (Conducted Measurement)

Product Name: RF Wireless module

Trade Mark: INNOCN

Test Model: AW.S905D3.03

Environmental Conditions

Temperature:	25.4° C
Relative Humidity:	51.6%
ATM Pressure:	100.0 kPa
Test Engineer:	Simba Huang
Supervised by:	Seal Chen

Contents

Page

COVER PAGE

1 Duty Cycle....3
1.1 Test Result....3
1.2 Test Graphs....4
2 Maximum Conducted Output Power....7
2.1 Test Result....7
2.2 Test Graphs....8
3 -6dB Bandwidth....11
3.1 Test Result....11
3.2 Test Graphs....12
4 Maximum Power Spectral Density Level....15
4.1 Test Result....15
4.2 Test Graphs....16
5 Band Edge....19
5.1 Test Result....19
5.2 Test Graphs....20
6 Conducted RF Spurious Emission....24
6.1 Test Result....24
6.2 Test Graphs....25
7 Restrict Band....31
7.1 Test Result....31
7.2 Test Graphs....32

1 Duty Cycle

1.1 Test Result

Mode	Frequency (MHz)	Duty Cycle (%)	1/T (kHz)
BLE 1M	2402	62.63	2.63
BLE 1M	2440	62.4	2.63
BLE 1M	2480	62.39	2.63
BLE 2M	2402	57.79	0.93
BLE 2M	2440	57.63	0.93
BLE 2M	2480	57.43	0.93

1.2 Test Graphs

Test Graphs
BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



BLE 2M 2402MHz



BLE 2M 2440MHz



BLE 2M 2480MHz



2 Maximum Conducted Output Power

2.1 Test Result

Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
BLE 1M	2402	3.26	30	Pass
BLE 1M	2440	3.28	30	Pass
BLE 1M	2480	3.57	30	Pass
BLE 2M	2402	3.31	30	Pass
BLE 2M	2440	3.28	30	Pass
BLE 2M	2480	3.61	30	Pass

2.2 Test Graphs

Test Graphs
BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



BLE 2M 2402MHz



BLE 2M 2440MHz



BLE 2M 2480MHz



3 -6dB Bandwidth

3.1 Test Result

Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
BLE 1M	2402	0.675	0.5	Pass
BLE 1M	2440	0.711	0.5	Pass
BLE 1M	2480	0.711	0.5	Pass
BLE 2M	2402	1.378	0.5	Pass
BLE 2M	2440	1.347	0.5	Pass
BLE 2M	2480	1.373	0.5	Pass

3.2 Test Graphs

Test Graphs

BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



BLE 2M 2402MHz



BLE 2M 2440MHz



BLE 2M 2480MHz



4 Maximum Power Spectral Density Level

4.1 Test Result

Mode	Frequency (MHz)	Conducted PSD (dBm/3-100kHz)	Limit (dBm/3kHz)	Verdict
BLE 1M	2402	-12.81	≤8	Pass
BLE 1M	2440	-12.84	≤8	Pass
BLE 1M	2480	-12.42	≤8	Pass
BLE 2M	2402	-16.59	≤8	Pass
BLE 2M	2440	-16.62	≤8	Pass
BLE 2M	2480	-16.22	≤8	Pass

4.2 Test Graphs

Test Graphs
BLE 1M 2402MHz



BLE 1M 2440MHz



BLE 1M 2480MHz



BLE 2M 2402MHz



BLE 2M 2440MHz



BLE 2M 2480MHz



5 Band Edge

5.1 Test Result

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-58.1	-20	Pass
BLE 1M	2480	-57.14	-20	Pass
BLE 2M	2402	-55.65	-20	Pass
BLE 2M	2480	-55.43	-20	Pass

5.2 Test Graphs

Test Graphs

BLE 1M 2402MHz Ref



BLE 1M 2402MHz Emission



BLE 1M 2480MHz Ref



BLE 1M 2480MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47975 GHz	2.84 dBm		
M2		1	2.4835 GHz	-57.07 dBm		
M3		1	2.5 GHz	-58.50 dBm		
M4		1	2.4845 GHz	-54.81 dBm		

BLE 2M 2402MHz Ref



BLE 2M 2402MHz Emission



BLE 2M 2480MHz Ref



BLE 2M 2480MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.48015 GHz	0.86 dBm		
M2		1	2.4835 GHz	-57.49 dBm		
M3		1	2.5 GHz	-55.35 dBm		
M4		1	2.4849 GHz	-55.31 dBm		

6 Conducted RF Spurious Emission

6.1 Test Result

Mode	Frequency (MHz)	Max Value (dBc)	Limit (dBc)	Verdict
BLE 1M	2402	-47.6	-20	Pass
BLE 1M	2440	-47.43	-20	Pass
BLE 1M	2480	-48.85	-20	Pass
BLE 2M	2402	-45.29	-20	Pass
BLE 2M	2440	-46.83	-20	Pass
BLE 2M	2480	-45.17	-20	Pass

6.2 Test Graphs

Test Graphs

BLE 1M 2402MHz Ref



BLE 1M 2402MHz Emission



BLE 1M 2440MHz Ref



BLE 1M 2440MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.45 GHz	0.58 dBm		
M2		1	17.659 GHz	-46.06 dBm		
M3		1	4.9799 GHz	-52.60 dBm		
M4		1	7.2563 GHz	-52.51 dBm		
M5		1	9.9298 GHz	-51.59 dBm		

BLE 1M 2480MHz Ref



BLE 1M 2480MHz Emission



BLE 2M 2402MHz Ref



BLE 2M 2402MHz Emission



BLE 2M 2440MHz Ref



BLE 2M 2440MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.45 GHz	-3.13 dBm		
M2		1	19.3531 GHz	-45.92 dBm		
M3		1	4.7152 GHz	-53.53 dBm		
M4		1	7.124 GHz	-52.99 dBm		
M5		1	9.771 GHz	-51.91 dBm		

BLE 2M 2480MHz Ref



BLE 2M 2480MHz Emission



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.476 GHz	-1.49 dBm		
M2		1	19.3531 GHz	-45.26 dBm		
M3		1	4.9534 GHz	-52.31 dBm		
M4		1	7.5739 GHz	-52.51 dBm		
M5		1	10.0092 GHz	-50.69 dBm		

7 Restrict Band

7.1 Test Result

Mode	Frequency (MHz)	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
BLE 1M	2402	2310	-44.5	3	53.76	Peak	74	Pass
BLE 1M	2402	2310	-53.83	3	44.43	Average	54	Pass
BLE 1M	2402	2339.472	-42.66	3	55.6	Peak	74	Pass
BLE 1M	2402	2338.224	-52.35	3	45.91	Average	54	Pass
BLE 1M	2402	2390	-48.38	3	49.88	Peak	74	Pass
BLE 1M	2402	2390	-55.67	3	42.59	Average	54	Pass
BLE 1M	2480	2483.5	-46.57	3	51.69	Peak	74	Pass
BLE 1M	2480	2483.5	-53.53	3	44.73	Average	54	Pass
BLE 1M	2480	2490.208	-44.04	3	54.22	Peak	74	Pass
BLE 1M	2480	2489.152	-52.98	3	45.28	Average	54	Pass
BLE 1M	2480	2500	-46.94	3	51.32	Peak	74	Pass
BLE 1M	2480	2500	-55.73	3	42.53	Average	54	Pass
BLE 2M	2402	2310	-45.44	3	52.82	Peak	74	Pass
BLE 2M	2402	2310	-54.65	3	43.61	Average	54	Pass
BLE 2M	2402	2338.224	-43.43	3	54.83	Peak	74	Pass
BLE 2M	2402	2338.416	-52.84	3	45.42	Average	54	Pass
BLE 2M	2402	2390	-47.5	3	50.76	Peak	74	Pass
BLE 2M	2402	2390	-56.42	3	41.84	Average	54	Pass
BLE 2M	2480	2483.5	-43.05	3	55.21	Peak	74	Pass
BLE 2M	2480	2483.5	-50.5	3	47.76	Average	54	Pass
BLE 2M	2480	2484.088	-42.41	3	55.85	Peak	74	Pass
BLE 2M	2480	2483.512	-50.5	3	47.76	Average	54	Pass
BLE 2M	2480	2500	-47.83	3	50.43	Peak	74	Pass
BLE 2M	2480	2500	-56.28	3	41.98	Average	54	Pass

7.2 Test Graphs

Test Graphs

BLE 1M 2402MHz Peak



BLE 1M 2402MHz Average



BLE 1M 2480MHz Peak



BLE 1M 2480MHz Average



BLE 2M 2402MHz Peak



BLE 2M 2402MHz Average



BLE 2M 2480MHz Peak



BLE 2M 2480MHz Average



---The End---