

样品承认书

Version: V1.0

Supplier sample production confirmation: (stamp required)

Formulate	Confirm	Approve	Quality	Stamp
代庆蓉	龙超群	傅梁成	曹光平	

Customer approval:

Project confirmation	Project approval	Quality confirmation	Quality approval	Confirmation date



1. Graphic for reference



Figure 2 0.8*20mmBT

Name	ANTENNA
Model	LT13
Frequency	2.4Ghz
Input impedance	50Ω
Allowed power	5mW
Working temp.	-25 ~ +65 °C
Storage temp.	-40 ~ +85 °C
Weight	0.25g
Antenna gain	2dBi

2. OTA(Free Space)

Channel	TRP (dBm)	TIS (dBm)
0	6.3	-91.1
39	6.5	-91.3
78	6.6	-91.2



3. BT Test

Test term	Environment	Max pairing distance	BT Call distance	
BT	Office	16-18m	10-12m	






注:

规格: 直径0.80*长度20.0mm

芯线需上锡

第三角法						机种		日期	页码	1 of 1
φ~10	±0.10	○	0.02	品名	蓝牙天线		设计		审核	
10~20	±0.12	◎	0.03	料号						
20~40	±0.15	⊥	0.02	材质			审核	long		
40~	±0.20	∇	0.04	表面处理				制程		
		∇	0.02	表面处理			确认			
材料规格图纸	位置			外觀处理			单位	比例	版本	REV:A

5.Field

Bluetooth 0 TRP**Bluetooth 0 TRP H****Bluetooth 39 TRP****Bluetooth 39 TRP H****Bluetooth 78 TRP****Bluetooth 78 TRP H**