



KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

RF Exposure Evaluation

FCC ID: 2A54U-DTNOI7MAX

REQUIREMENT

KDB447498 D01 General RF Exposure Guidance v07, Clause 4.3.1(a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

TEST RESULT

☒ **Passed**

☐ **Not Applicable**

BT

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Maximum Output Power (mW)	Calculating data	Limit	Results
DH5	2402	3.42	4±1	5	3.16	0.9802	3.00	Pass
	2441	4.03	5±1	6	3.98	1.2440		
	2480	3.64	4±1	5	3.16	0.9960		
2DH5	2402	3.90	4±1	5	3.16	0.9802		
	2441	4.59	5±1	6	3.98	1.2440		
	2480	4.10	5±1	6	3.98	1.2539		
3DH5	2402	4.28	5±1	6	3.98	1.2340		
	2441	4.66	5±1	6	3.98	1.2440		
	2480	4.50	5±1	6	3.98	1.2539		



KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

BLE

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Maximum Output Power (mW)	Calculating data	Limit	Results
GFSK_1M	2402	3.43	4±1	5	3.16	0.9802	3.00	Pass
	2440	3.06	4±1	5	3.16	0.9879		
	2480	3.19	4±1	5	3.16	0.9960		
GFSK_2M	2402	3.46	4±1	5	3.16	0.9802		
	2440	3.07	4±1	5	3.16	0.9879		
	2480	3.21	4±1	5	3.16	0.9960		

Note:

-The maximum antenna gain is -0.7dBi.

-The exposure safety distance is less than 5mm.

-BLE and BT can transmit simultaneously: $0.996+1.2539=2.2499<3$,so SAR evaluation is not required.

--THE END--