

RF Exposure Evaluation

Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in KDB 447498 D01 V06 and 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

f = frequency in MHz

Friis transmission formula: $Pd = (Pout * G) / (4 * \pi * r^2)$

Where

Pd = power density in mW/cm², **Pout** = output power to antenna in mW;

G = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

$$EIRP = E_{Meas} + 20 \log(d_{Meas}) - 104.7$$

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dB μ V/m

d_{Meas} is the measurement distance, in m

Test Result of RF Exposure Evaluation

wifi 2.4G mode

Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b	16.65	46.2381	0.0236	1.0	PASS
802.11g	14.99	31.5500	0.0161	1.0	PASS
802.11n HT20	13.87	24.3781	0.0125	1.0	PASS
802.11n HT40	13.50	22.3872	0.0114	1.0	PASS

Remark: antenna gain=4.10dBi

For BLE

Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
0.75	1.1885	0.0006	1.0	PASS

Remark: antenna gain=4.10dBi

For EDR

Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
3.69	2.3388	0.0012	1.0	PASS

Remark: antenna gain=4.10dBi

wifi 5G mode:

Band	Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
Band 1	802.11a	15.463	35.1803	0.0180	1.0	PASS
	802.11n HT20	15.411	34.7616	0.0178	1.0	PASS
	802.11n HT40	15.325	34.0800	0.0174	1.0	PASS
	802.11ac HT20	15.388	34.5780	0.0177	1.0	PASS
	802.11ac HT40	15.322	34.0565	0.0174	1.0	PASS
	802.11ac HT80	12.804	19.0722	0.0098	1.0	PASS

Remark: antenna gain=4.10dBi

Band	Channel	Output power to antenna (dBm)	Output power to antenna (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
Band 4	802.11a	16.133	41.0488	0.0292	1.0	PASS
	802.11n HT20	16.697	46.7412	0.0332	1.0	PASS
	802.11n HT40	15.95	39.3550	0.0280	1.0	PASS
	802.11ac HT20	16.631	46.0363	0.0327	1.0	PASS
	802.11ac HT40	16.001	39.8199	0.0283	1.0	PASS
	802.11ac HT80	14.538	28.4315	0.0202	1.0	PASS

Remark: antenna gain=5.53dBi

For Simultaneous transmitting, 1): The sum of the ratios of the spatially averaged results to the applicable frequency dependent MPE limits = $0.0236/1 + 0.0006/1 + 0.0012/1 + 0.0180/1 + 0.0332/1 = 0.0766 < 1$ Since the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in the device is ≤ 1.0 , the EUT is considered to satisfy MPE compliance for simultaneous transmission operations.