



30MHz-3G

Start Freq 3.000000000 GHz
Mkr1 24.054 GHz
-45.605 dBm
Center Freq 14.000000000 GHz
Start Freq 3.000000000 GHz
Stop Freq 25.000000000 GHz
CF Step 2.200000000 GHz
Freq Offset 0 Hz
Scale Type
Start 3.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 2.103 s (1001 pts)

30MHz-3G

Start Freq 3.000000000 GHz
Mkr1 23.658 GHz
-45.388 dBm
Center Freq 14.000000000 GHz
Start Freq 3.000000000 GHz
Stop Freq 25.000000000 GHz
CF Step 2.200000000 GHz
Freq Offset 0 Hz
Scale Type
Start 3.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 2.103 s (1001 pts)

3G-25G

Start Freq 3.000000000 GHz
Mkr1 24.054 GHz
-45.605 dBm
Center Freq 14.000000000 GHz
Start Freq 3.000000000 GHz
Stop Freq 25.000000000 GHz
CF Step 2.200000000 GHz
Freq Offset 0 Hz
Scale Type
Start 3.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 2.103 s (1001 pts)

3G-25G

Start Freq 3.000000000 GHz
Mkr1 23.658 GHz
-45.388 dBm
Center Freq 14.000000000 GHz
Start Freq 3.000000000 GHz
Stop Freq 25.000000000 GHz
CF Step 2.200000000 GHz
Freq Offset 0 Hz
Scale Type
Start 3.000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 2.103 s (1001 pts)


8DPSK (CH00)




8DPSK (CH39)




reference



reference



30MHz-3G



30MHz-3G




3G-25G

3G-25G

8DPSK (CH78)



reference




30MHz-3G




3G-25G

Band-edge Measurements for RF Conducted Emissions:

GFSK



Left Band edge hopping off




Right Band edge hopping off



Left Band edge hopping on




Right Band edge hopping on

$\pi/4$ DQPSK

Left Band edge hopping off


Right Band edge hopping off




Left Band edge hopping on

Right Band edge hopping on


8DPSK



Left Band edge hopping off



Right Band edge hopping off



Left Band edge hopping on



Right Band edge hopping on

4.9 Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

4.10 Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction



The maximum gain of antenna was 2.5 dBi.



Remark: The antenna gain is provided by the customer, if the data provided by the customer is not accurate, Shenzhen GUOREN Certification Technology Service Co., Ltd. does not assume any responsibility.




5 Test Setup Photos of the EUT





6 Photos of the EUT














***** End of Report *****