



FCC TEST REPORT

FCC ID: 2A595YH-6289

Product	:	3-key RGB Color Changing Controller
Model Name	:	YH-6289, YH-6285
Brand	:	N/A
Report No.	:	PTC26041802912 E-FC01
Prepared for		
Dongguan Yihong Hardware electronics Co., LTD		
Room 901, No. 2, Shangheng Road, Chang'an Town, Dongguan City, Guangdong Province, 523880 China		
Prepared by		
Precise Testing & Certification Co., Ltd		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China		



1 TEST RESULT CERTIFICATION

Applicant's name : Dongguan Yihong Hardware electronics Co., LTD
Address : Room 901, No. 2, Shangheng Road, Chang'an Town, Dongguan City, Guangdong Province, 523880 China
Manufacture's name : Dongguan Yihong Hardware electronics Co., LTD
Address : Room 901, No. 2, Shangheng Road, Chang'an Town, Dongguan City, Guangdong Province, 523880 China
Product name : 3-key RGB Color Changing Controller
Model name : YH-6289, YH-6285
Standards : FCC CFR47 Part 15 Section 15.247
Test procedure : ANSI C63.10-2020+COR.1-2023
Test Date : May 04, 2026 to May 30, 2026
Date of Issue : May 30, 2026
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Jack Zhou'.

Jack zhou / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Simon Pu'.

Simon Pu / Manager



Contents

	Page
1 TEST RESULT CERTIFICATION	2
2 TEST SUMMARY	5
2.1 TEST SITE	6
3 GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF E.U.T.	7
3.2 CHANNEL LIST	8
4 EQUIPMENT DURING TEST	9
4.1 EQUIPMENTS LIST	9
4.2 MEASUREMENT UNCERTAINTY	12
4.3 DESCRIPTION OF SUPPORT UNITS	13
5 CONDUCTED EMISSION	14
5.1 E.U.T. OPERATION	14
5.2 EUT SETUP	14
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	15
5.4 MEASUREMENT PROCEDURE	15
5.5 CONDUCTED EMISSION LIMIT	15
5.6 MEASUREMENT RECEIVER PARAMETERS:	16
5.7 CONDUCTED EMISSION TEST RESULT	16
6 RADIATED SPURIOUS EMISSIONS	21
6.1 EUT OPERATION	21
6.2 TEST SETUP	22
6.3 SPECTRUM ANALYZER SETUP	23
6.4 TEST PROCEDURE	24
6.5 SUMMARY OF TEST RESULTS	26
7 CONDUCT BAND EDGE AND SPURIOUS EMISSIONS MEASUREMENT	39
7.1 TEST PROCEDURE	39
7.3 TEST RESULT	41
8 6DB BANDWIDTH MEASUREMENT	47



TEST PROCEDURE	47
TEST SETUP	47
TEST RESULT	47
9 MAXIMUM PEAK OUTPUT POWER	52
9.1 TEST PROCEDURE	52
9.2 TEST SETUP	52
9.3 TEST RESULT	52
10 POWER SPECTRAL DENSITY	56
10.1 TEST PROCEDURE	56
10.2 TEST SETUP	56
10.3 TEST RESULT	56
11 ANTENNA APPLICATION	61
11.1 ANTENNA REQUIREMENT	61
11.2 RESULT	61
12 TEST SETUP	62
13 EUT PHOTOS	66



2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(3)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS



Report No.: PTC26041802912 E-FC01

2.1 Test Site

Precise Testing & Certification Co., Ltd

Address: Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A

FCC Designation Number: CN1219



3 General Information

3.1 General Description of E.U.T.

Product Name	:	3-key RGB Color Changing Controller
Model name	:	YH-6289
Additional Model	:	YH-6285
Models difference	:	The circuit diagram, PCB layout, and overall design are identical; only the input parameters and ports differ. The YH-62891 uses a 5.5*2.1mm input port. The YH-6285 uses a USB input port.
Specification	:	BLE
Operating frequency	:	2402-2480MHz
Modulation	:	GFSK
Number of Channel	:	40 channels
Antenna installation	:	PCB Antenna
Antenna Gain	:	0 dBi
Power supply	:	YH-6289 Input: DC 12V/2A; YH-6285 Input:DC 5V/2A
Hardware Version	:	YH-06182-2.0
Software Version	:	YH-06285-5.0
Data rate	:	1Mbps, 2Mbps



3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2020+COR.1-2023 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.



4 Equipment During Test

4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
MXG Signal Analyzer	Agilent	N9020A	SER MY5111038	10Hz-26.5GHz	Aug. 14, 2025	1 Year
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	Aug. 14, 2025	1 Year
Power Meter	Anritsu	ML2495A	0949003	300MHz-40GHz	Aug. 14, 2025	1 Year
Power Sensor	Anritsu	MA2411B	0917017	300MHz-40GHz	Aug. 14, 2025	1 Year
DC power Supply	Agilent	E3642A	MY52420017	0-8V,5A/0-20 ,2.5A	Aug. 14, 2025	1 Year
Humidity Chamber	AISRY	ASR-HW2-1000	20230926003	-40°C-150°C	Feb. 23 ,2025	1Year
Test S/W	Tonscend	JS1120-3	/	/	/	/

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Last Calibration	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESPI7	101671	9KHz-7GHz	Aug. 14, 2025	1 Year
Loop Antenna	Schwarzbeck	FMZB 1519	192	9 KHz -30MHz	Nov. 27, 2025	1 Year
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	25MHz-2GHz	Sep. 09, 2025	1 Year
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	9KHz-1GHz	Mar. 21, 2025	1 Year
Cable	IMRO	AK-9515E(9m)	Cable-L	9KHz-3GHz	Aug. 14, 2025	1 Year
Spectrum Analyzer	Rohde&Schwarz	FSV40	6625-01-588-5515	9KHz-40GHz	Aug. 14, 2025	1 Year



Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1246	1GHz-18GHz	Dec. 11, 2025	1 Year
Power Amplifier	ZHINAN	ZN3380C	15002	1GHz-26.5GHz	Aug. 14, 2025	1 Year
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-1066	15GHz-40GHz	Jun. 24, 2025	1 Year
Amplifier	SCHWARZBECK	BBV 9721	9721-205	18GHz-40GHz	Jun. 23, 2025	1 Year
Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	Aug. 14, 2025	1 Year
Power Amplifier	ZHINAN	ZN3380C	15002	1GHz-26.5GHz	Aug. 14, 2025	1 Year
RF Cable	R&S	R204	R21X	1GHz-40GHz	Aug. 14, 2025	1 Year
Test S/W	Tonscend	TS+	/	/	/	/



Report No.: PTC26041802912 E-FC01

Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Characteristics	Calibration Date	Calibration Interval
EMI Test Receiver	Rohde&Schwarz	ESCI3	101417	9KHz-3GHz	Aug. 14, 2025	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	102453	9KHz-300MHz	Oct. 29, 2025	1 Year
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	9KHz-300MHz	Oct. 29, 2025	1 Year
Limiter	R&S	ESH3-Z2	0357.8810.54-102808-NB	0Hz-30MHz	Aug. 14, 2025	1 Year
RF Switch	DIAMOND ANTENNA	CX-210	/	0.09MHz-6GHz	Mar. 21,2025	1 Year
Test S/W	Tonscend	JS32-CE	/	/	/	/



4.2 Measurement Uncertainty

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameter	Uncertainty
RF output power, conducted	$\pm 1.0\text{dB}$
Power Spectral Density, conducted	$\pm 2.2\text{dB}$
Radio Frequency	$\pm 1 \times 10^{-6}$
Bandwidth	$\pm 1.5 \times 10^{-6}$
Time	$\pm 2\%$
Duty Cycle	$\pm 2\%$
Temperature	$\pm 1^\circ\text{C}$
Humidity	$\pm 5\%$
DC and low frequency voltages	$\pm 3\%$
Conducted Emissions (150kHz~30MHz)	$\pm 3.64\text{dB}$
Radiated Emission(9kHz~30MHz)	$\pm 3.15\text{dB}$
Radiated Emission(30MHz~1GHz)	$\pm 5.03\text{dB}$
Radiated Emission(1GHz~25GHz)	$\pm 4.74\text{dB}$



4.3 Description of Support Units

Equipment	Model No.	Manufacturer	Series No.	Specifications
Power Adapter	SG-120200024AU	Guangdong sengu Technology Co., Ltd.	E525389	Output:12V=2A
Adapter	Model: PS65B150Y3000S	Telling Telecommunication Holding Co., Ltd	60592-C6	Output:5V=2A
Test fixture	YH-1068K1RXXGXX- BHDL-V31SN3035203 7	YIHONG	/	/
LED Strip	L5	YIHONG	/	/
LED Strip	L12	YIHONG	/	/

5 Conducted Emission

Test Requirement	: FCC CFR 47 Part 15 Section 15.207
Test Method	: ANSI C63.10-2020+COR.1-2023
Test Result	: PASS
Frequency Range	: 150kHz to 30MHz
Class/Severity	: Class B


5.1 E.U.T. Operation

Operating Environment :


Temperature	: 25.5 °C
Humidity	: 51 % RH
Atmospheric Pressure	: 101.2kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10-2020+COR.1-2023.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. Place the EUT on a non-conductive tabletop at a height of 80 cm. A vertical conductive shielding wall is located 40 cm behind the EUT.
2. The excess length of the power cord between the EUT and the LISN receptacle (or ac power receptacle where a LISN cannot be used), or an adapter or extension cord connected to and measured with the LISN shall be folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
3. EUT shall be placed at a distance of 80 cm from the LISN (or power receptacle where a LISN cannot be used) and connected thereto by a power lead or appropriate connection no more than 1 m long.
4. The equipment shall be arranged and installed in compliance with the standards, and operated in a manner that maximizes its emission characteristics in normal applications, with the six highest points on the waveform recorded.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.



5.6 Measurement Receiver Parameters:

Receiver Parameters	Setting
Start Frequency	150kHz
Stop Frequency	30MHz
IF Bandwidth	9 kHz

5.7 Conducted Emission Test Result


PASS.

Conducted emission at both 120V & 240V is assessed, and emission at 120V represents the worst case. All the modulation modes were tested the data of the worst mode (BLE_2M_2440MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.



Model: YH-6289 Input: DC 12V/2A

Line -120V/60Hz:




Final Data List

NO.	Freq. [MHz]	QP Reading [dBμV]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.173	41.45	9.98	51.43	64.84	13.41	25.99	35.97	54.84	18.87	PASS
2	0.218	36.83	9.97	46.80	62.91	16.11	25.86	35.83	52.91	17.08	PASS
3	0.276	34.39	9.98	44.37	60.94	16.57	21.77	31.75	50.94	19.19	PASS
4	0.497	32.45	9.98	42.43	56.06	13.63	22.77	32.75	46.06	13.31	PASS
5	1.257	27.35	10.00	37.35	56.00	18.65	17.18	27.18	46.00	18.82	PASS
6	7.589	27.47	10.19	37.66	60.00	22.34	16.94	27.13	50.00	22.87	PASS



Neutral -120V/60Hz:




Final Data List

NO.	Freq. [MHz]	QP Reading [dBμV]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.173	41.28	9.95	51.23	64.84	13.61	27.93	37.88	54.84	16.96	PASS
2	0.222	37.77	9.95	47.72	62.74	15.02	23.48	33.43	52.74	19.31	PASS
3	0.308	32.58	9.95	42.53	60.04	17.51	21.59	31.54	50.04	18.50	PASS
4	0.488	32.23	9.94	42.17	56.21	14.04	23.09	33.03	46.21	13.18	PASS
5	1.275	27.64	9.97	37.61	56.00	18.39	17.40	27.37	46.00	18.63	PASS
6	7.971	26.35	10.15	36.50	60.00	23.50	17.30	27.45	50.00	22.55	PASS



Model: YH-6285 Input:DC 5V/2A

Line -120V/60Hz:




Final Data List

NO.	Freq. [MHz]	QP Reading [dBμV]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.519	40.72	9.98	50.70	56.00	5.30	30.98	40.96	46.00	5.04	PASS
2	0.996	35.29	10.00	45.29	56.00	10.71	24.38	34.38	46.00	11.62	PASS
3	1.464	35.10	10.00	45.10	56.00	10.90	22.75	32.75	46.00	13.25	PASS
4	2.265	35.22	10.02	45.24	56.00	10.76	22.54	32.56	46.00	13.44	PASS
5	4.083	36.86	10.08	46.94	56.00	9.06	23.74	33.82	46.00	12.18	PASS
6	19.041	38.96	10.52	49.48	60.00	10.52	22.65	33.17	50.00	16.83	PASS



Neutral -120V/60Hz:



Final Data List

NO.	Freq. [MHz]	QP Reading [dBμV]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.515	41.17	9.94	51.11	56.00	4.89	30.45	40.39	46.00	5.61	PASS
2	1.037	36.08	9.96	46.04	56.00	9.96	22.96	32.92	46.00	13.08	PASS
3	1.487	34.99	9.97	44.96	56.00	11.04	22.52	32.49	46.00	13.51	PASS
4	2.319	35.49	9.99	45.48	56.00	10.52	22.69	32.68	46.00	13.32	PASS
5	3.998	35.98	10.04	46.02	56.00	9.98	23.41	33.45	46.00	12.55	PASS
6	18.884	36.99	10.42	47.41	60.00	12.59	23.10	33.52	50.00	16.48	PASS



6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.209 & 15.247
Test Method : ANSI C63.10-2020+COR.1-2023
Test Result : PASS
Measurement Distance : 3m
Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation


Operating Environment :

Temperature : 23.5 °C
Humidity : 51.1 % RH
Atmospheric Pressure : 101.2kPa


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

	Frequency	Detector	RBW	VBW	Remark
Receiver Setup	Below 30MHz	--	10kHz	10kHz	--
	30MHz ~ 1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value



6.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2020+COR.1-2023.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.
8. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



For Average Measurement:

VBW=10Hz, when duty cycle is no less than 98 percent.

$VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(μ s)	1/T(KHz)	Average Correction Factor	VBW Setting
2402-2480	100	-	-	0	10Hz



6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over Limit (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40 \log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.


Test Frequency: 30MHz ~ 1GHz

Pass.

Please refer to the following test plots for the worst test mode (BLE_2M_GFSK (CH00: 2402MHz)).



YH-6289 Input: DC 12V/2A;
Antenna Polarization: Horizontal BLE_2M_GFSK(CH00: 2402MHz)




Final Data List[QP]								
NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	51.58	29.45	-9.90	19.55	40.00	20.45	Horizontal	PASS
2	113.42	36.7	-10.47	26.23	43.50	17.27	Horizontal	PASS
3	144.70	33.88	-8.18	25.70	43.50	17.80	Horizontal	PASS
4	216.00	35.99	-9.94	26.05	43.50	17.45	Horizontal	PASS
5	921.67	25.73	7.59	33.32	46.00	12.68	Horizontal	PASS
6	996.36	25.59	9.14	34.73	54.00	19.27	Horizontal	PASS

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor, All modes have been tested. Only the worst mode(BLE_2M) is recorded in the report.



Antenna Polarization: Vertical BLE_2M_GFSK GFSK(CH00: 2402MHz)




Final Data List[QP]								
NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	45.76	34.38	-9.63	24.75	40.00	15.25	Vertical	PASS
2	54.98	34.8	-10.34	24.46	40.00	15.54	Vertical	PASS
3	150.77	32.64	-7.95	24.69	43.50	18.81	Vertical	PASS
4	195.63	34.89	-10.68	24.21	43.50	19.29	Vertical	PASS
5	946.17	26.72	8.19	34.91	46.00	11.09	Vertical	PASS
6	999.52	26.48	9.17	35.65	54.00	18.35	Vertical	PASS

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor, All modes have been tested.
Only the worst mode(BLE_2M) is recorded in the report.



YH-6285 Input: DC 5V/2A

Antenna Polarization: Horizontal BLE_2M_GFSK(CH00: 2402MHz)




Final Data List[QP]								
NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	47.95	29.85	-9.75	20.10	40.00	19.90	Horizontal	PASS
2	202.66	31.4	-10.82	20.58	43.50	22.92	Horizontal	PASS
3	256.01	32.02	-8.00	24.02	46.00	21.98	Horizontal	PASS
4	495.12	25.95	-1.20	24.75	46.00	21.25	Horizontal	PASS
5	937.19	25.84	8.09	33.93	46.00	12.07	Horizontal	PASS
6	990.06	25.15	8.97	34.12	54.00	19.88	Horizontal	PASS

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor



Antenna Polarization: Vertical BLE_2M_GFSK(CH00: 2402MHz)



Final Data List[QP]								
NO.	Freq. [MHz]	QP Reading [dBμV/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	30.73	40.12	-10.14	29.98	40.00	10.02	Vertical	PASS
2	48.19	42.75	-9.78	32.97	40.00	7.03	Vertical	PASS
3	467.71	25.67	-1.82	23.85	46.00	22.15	Vertical	PASS
4	783.45	26.46	4.84	31.30	46.00	14.70	Vertical	PASS
5	910.03	26.1	7.19	33.29	46.00	12.71	Vertical	PASS
6	977.93	25.99	8.74	34.73	54.00	19.27	Vertical	PASS

Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor, All modes have been tested.

Only the worst mode(BLE_2M) is recorded in the report.



Test Frequency 1GHz-25GHz:

YH-6289 Input: DC 12V/2A:

Test Mode: CH00 BLE_2M_GFSK					Test channel:Low Channel (2402MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804	44.68	34.04	6.58	34.09	51.21	74	-22.79	V
7206	42.49	37.11	7.73	34.5	52.83	74	-21.17	V
9608	38.39	39.31	9.23	34.79	52.14	74	-21.86	V
4804	45.79	34.04	6.58	34.09	52.32	74	-21.68	H
7206	36.23	37.11	7.73	34.5	46.57	74	-27.43	H
9608	40.25	39.31	9.23	34.79	54.00	74	-20.00	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804	33.53	34.04	6.58	34.09	40.06	54	-13.94	V
7206	29.45	37.11	7.73	34.5	39.79	54	-14.21	V
9608	23.57	39.31	9.23	34.79	37.32	54	-16.68	V
4804	31.56	34.04	6.58	34.09	38.09	54	-15.91	H
7206	28.38	37.11	7.73	34.5	38.72	54	-15.28	H
9608	26.00	39.31	9.23	34.79	39.75	54	-14.25	H



YH-6289 Input: DC 12V/2A:

Test Mode: CH19 BLE_2M_GFSK					Test channel:Middle Channel (2440MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	42.77	34.38	6.69	34.09	49.75	74	-24.25	V
7320	40.00	37.22	7.78	34.53	50.47	74	-23.53	V
9760	34.54	39.46	9.35	34.8	48.55	74	-25.45	V
4880	40.71	34.38	6.69	34.09	47.69	74	-26.31	H
7320	37.00	37.22	7.78	34.53	47.47	74	-26.53	H
9760	37.47	39.46	9.35	34.8	51.48	74	-22.52	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	31.65	34.38	6.69	34.09	38.63	54	-15.37	V
7320	28.81	37.22	7.78	34.53	39.28	54	-14.72	V
9760	25.30	39.46	9.35	34.8	39.31	54	-14.69	V
4880	31.60	34.38	6.69	34.09	38.58	54	-15.42	H
7320	27.92	37.22	7.78	34.53	38.39	54	-15.61	H
9760	25.11	39.46	9.35	34.8	39.12	54	-14.88	H



YH-6289 Input: DC 12V/2A:

Test Mode: CH39 BLE_2M_GFSK					Test channel:High Channel (2480MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804	44.02	34.04	6.58	34.09	50.55	74	-23.45	V
7206	41.64	37.11	7.73	34.5	51.98	74	-22.02	V
9608	37.58	39.31	9.23	34.79	51.33	74	-22.67	V
4804	46.09	34.04	6.58	34.09	52.62	74	-21.38	H
7206	37.04	37.11	7.73	34.5	47.38	74	-26.62	H
9608	40.10	39.31	9.23	34.79	53.85	74	-20.15	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4804	32.70	34.04	6.58	34.09	39.23	54	-14.77	V
7206	28.34	37.11	7.73	34.5	38.68	54	-15.32	V
9608	25.64	39.31	9.23	34.79	39.39	54	-14.61	V
4804	33.39	34.04	6.58	34.09	39.92	54	-14.08	H
7206	27.96	37.11	7.73	34.5	38.30	54	-15.70	H
9608	24.59	39.31	9.23	34.79	38.34	54	-15.66	H



YH-6285 Input: DC 5V/2A:

Test Mode: CH00 BLE_2M_GFSK					Test channel:Low Channel (2402MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	42.99	34.38	6.69	34.09	49.97	74	-24.03	V
7320	39.94	37.22	7.78	34.53	50.41	74	-23.59	V
9760	33.58	39.46	9.35	34.8	47.59	74	-26.41	V
4880	41.73	34.38	6.69	34.09	48.71	74	-25.29	H
7320	37.09	37.22	7.78	34.53	47.56	74	-26.44	H
9760	36.59	39.46	9.35	34.8	50.60	74	-23.40	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	33.04	34.38	6.69	34.09	40.02	54	-13.98	V
7320	27.91	37.22	7.78	34.53	38.38	54	-15.62	V
9760	24.04	39.46	9.35	34.8	38.05	54	-15.95	V
4880	33.25	34.38	6.69	34.09	40.23	54	-13.77	H
7320	26.56	37.22	7.78	34.53	37.03	54	-16.97	H
9760	25.89	39.46	9.35	34.8	39.90	54	-14.10	H



YH-6285 Input: DC 5V/2A:

Test Mode: CH19 BLE_2M_GFSK					Test channel:Middle Channel (2440MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	42.79	34.38	6.69	34.09	49.77	74	-24.23	V
7320	40.94	37.22	7.78	34.53	51.41	74	-22.59	V
9760	33.50	39.46	9.35	34.8	47.51	74	-26.49	V
4880	41.06	34.38	6.69	34.09	48.04	74	-25.96	H
7320	37.95	37.22	7.78	34.53	48.42	74	-25.58	H
9760	37.80	39.46	9.35	34.8	51.81	74	-22.19	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4880	32.16	34.38	6.69	34.09	39.14	54	-14.86	V
7320	29.38	37.22	7.78	34.53	39.85	54	-14.15	V
9760	24.24	39.46	9.35	34.8	38.25	54	-15.75	V
4880	34.23	34.38	6.69	34.09	41.21	54	-12.79	H
7320	27.34	37.22	7.78	34.53	37.81	54	-16.19	H
9760	25.61	39.46	9.35	34.8	39.62	54	-14.38	H



YH-6285 Input: DC 5V/2A:

Test Mode: CH39 BLE_2M_GFSK					Test channel:High Channel (2480MHz)			
Peak Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960	41.79	34.72	6.68	34.09	49.10	74	-24.90	V
7440	39.70	37.34	6.73	34.57	49.20	74	-24.80	V
9920	34.38	39.62	6.81	34.81	46.00	74	-28.00	V
4960	41.77	34.72	6.68	34.09	49.08	74	-24.92	H
7440	37.11	37.34	6.73	34.57	46.61	74	-27.39	H
9920	36.72	39.62	6.81	34.81	48.34	74	-25.66	H
Average Value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.
4960	33.72	34.72	6.68	34.09	41.03	54	-12.97	V
7440	29.27	37.34	6.73	34.57	38.77	54	-15.23	V
9920	23.83	39.62	6.81	34.81	35.45	54	-18.55	V
4960	32.76	34.72	6.68	34.09	40.07	54	-13.93	H
7440	27.61	37.34	6.73	34.57	37.11	54	-16.89	H
9920	24.76	39.62	6.81	34.81	36.38	54	-17.62	H

Note: 1. The testing has been conformed to $10 \times 2480\text{MHz} = 24800\text{MHz}$.

2. All other emissions more than 30dB below the limit.

3. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin=Emission Level-Limit

4. All modes have been tested. Only the worst mode(BLE_2M) is recorded in the report.



Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

YH-6289 Input: DC 12V/2A:

Test Mode: BLE_2M_Channel 2402MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2310	48.53	28.67	6.72	37.26	46.66	74	-27.34	H	Peak
2390	59.53	28.08	6.81	37.12	57.30	74	-16.70	H	Peak
2310	47.63	28.67	6.72	37.26	45.76	74	-28.24	V	Peak
2390	54.73	28.08	6.81	37.12	52.50	74	-21.50	V	Peak
2310	40.28	28.67	6.72	37.26	38.41	54	-15.59	H	AV
2390	44.46	28.08	6.81	37.12	42.23	54	-11.77	H	AV
2310	39.25	28.67	6.72	37.26	37.38	54	-16.62	V	AV
2390	45.34	28.08	6.81	37.12	43.11	54	-10.89	V	AV

Test Mode: BLE_2M_Channel 2480MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2483.5	59.54	27.38	6.15	36.29	56.78	74	-17.22	H	Peak
2500	49.81	27.43	6.68	36.79	47.13	74	-26.87	H	Peak
2483.5	60.33	27.38	6.15	36.29	57.57	74	-16.43	V	Peak
2500	48.56	27.43	6.68	36.79	45.88	74	-28.12	V	Peak
2483.5	42.83	27.38	6.15	36.29	40.07	54	-13.93	H	AV
2500	40.16	27.43	6.68	36.79	37.48	54	-16.52	H	AV
2483.5	43.81	27.38	6.15	36.29	41.05	54	-12.95	V	AV
2500	39.99	27.43	6.68	36.79	37.31	54	-16.69	V	AV



YH-6285 Input: DC 5V/2A

Test Mode: BLE_2M_Channel 2402MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2310	48.43	28.67	6.72	37.26	46.56	74	-27.44	H	Peak
2390	60.88	28.08	6.81	37.12	58.65	74	-15.35	H	Peak
2310	47.07	28.67	6.72	37.26	45.20	74	-28.80	V	Peak
2390	55.50	28.08	6.81	37.12	53.27	74	-20.73	V	Peak
2310	40.09	28.67	6.72	37.26	38.22	54	-15.78	H	AV
2390	43.82	28.08	6.81	37.12	41.59	54	-12.41	H	AV
2310	39.69	28.67	6.72	37.26	37.82	54	-16.18	V	AV
2390	44.66	28.08	6.81	37.12	42.43	54	-11.57	V	AV

Test Mode: BLE_2M_Channel 2480MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2483.5	59.99	27.38	6.15	36.29	57.23	74	-16.77	H	Peak
2500	48.77	27.43	6.68	36.79	46.09	74	-27.91	H	Peak
2483.5	59.11	27.38	6.15	36.29	56.35	74	-17.65	V	Peak
2500	49.47	27.43	6.68	36.79	46.79	74	-27.21	V	Peak
2483.5	42.26	27.38	6.15	36.29	39.50	54	-14.50	H	AV
2500	39.58	27.43	6.68	36.79	36.90	54	-17.10	H	AV
2483.5	43.89	27.38	6.15	36.29	41.13	54	-12.87	V	AV
2500	39.93	27.43	6.68	36.79	37.25	54	-16.75	V	AV

Note: All modes have been tested. Only the worst mode(BLE_2M) is recorded in the report.



7 Conduct Band Edge And Spurious Emissions Measurement

Test Requirement	: Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method	: ANSI C63.10-2020+COR.1-2023
Test Limit	: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.1 Test Procedure

Reference Level:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum; Set to the maximum power setting and enable the EUT transmit continuously.
2. Establish a reference level by using the following procedure:
 - a) Set instrument center frequency to DTS channel center frequency.
 - b) Set the span to ≥ 1.5 times the DTS bandwidth.
 - c) Set the RBW = 100 kHz.
 - d) Set the VBW $\geq [3 \times \text{RBW}]$.
 - e) Detector = peak.
 - f) Sweep time = No faster than coupled (auto) time.
 - g) Trace mode = max-hold.
 - h) Allow trace to fully stabilize.
 - i) Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level

Spurious Emissions Measurement:

Establish an emission level by using the following procedure:

- a) Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.


NOTE—the number of points can also be increased for large spans to retain frequency resolution

- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = No faster than coupled (auto) time.
- f) Trace mode = max-hold.
- g) Allow trace to fully stabilize.



h) Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11. Report the three highest emissions relative to the limit.

7.2 Test Setup






7.3 Test Result

Test Mode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-6.24	-41.93	≤ -26.24	PASS
BLE_1M	Ant1	High	2480	-5.47	-41.86	≤ -25.47	PASS
BLE_2M	Ant1	Low	2402	-5.71	-39.43	≤ -25.71	PASS
BLE_2M	Ant1	High	2480	-7.05	-42.15	≤ -27.05	PASS




Test Graphs:


BLE_1M-Ant1-2402-PASS




BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2480-PASS







Band edge:

Test Mode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-6.24	-41.93	≤-26.24	PASS
BLE_1M	Ant1	High	2480	-5.47	-41.86	≤-25.47	PASS
BLE_2M	Ant1	Low	2402	-5.71	-39.43	≤-25.71	PASS
BLE_2M	Ant1	High	2480	-7.05	-42.15	≤-27.05	PASS


BLE_1M-Ant1-2402-PASS




BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2480-PASS





8 6dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10-2020+COR.1-2023

Test Limit : Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure


6dB Bandwidth:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- 2.steps for the first option are as follows:
 - a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
 - b) Set the VBW $\geq [3 \times \text{RBW}]$.
 - c) Detector = peak.
 - d) Trace mode = max-hold.
 - e) Sweep = No faster than coupled (auto) time.
 - f) Allow the trace to stabilize.
 - g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

Occupied bandwidth:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 1% to 5% of the OBW, VBW = approximately three times the RBW.

Test Setup




Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.644	2401.696	2402.340	0.5	PASS
BLE_1M	Ant1	2440	0.648	2439.688	2440.336	0.5	PASS
BLE_1M	Ant1	2480	0.712	2479.648	2480.360	0.5	PASS
BLE_2M	Ant1	2402	1.116	2401.448	2402.564	0.5	PASS



BLE_2M	Ant1	2440	1.072	2439.464	2440.536	0.5	PASS
BLE_2M	Ant1	2480	1.220	2479.356	2480.576	0.5	PASS

Test Graphs:





BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2440-PASS



BLE_2M-Ant1-2480-PASS





9 Maximum Peak Output Power

Test Requirement : FCC CFR47 Part 15 Section 15.247


Test Method : ANSI C63.10-2020+COR.1-2023

Test Limit : Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

9.1 Test Procedure

1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Measure the conducted output power and record the results in the test report.

9.2 Test Setup



9.3 Test Result

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-4.69	≤30	-4.69	≤36	PASS
BLE_1M	Ant1	2440	-4.43	≤30	-4.43	≤36	PASS
BLE_1M	Ant1	2480	-4.23	≤30	-4.23	≤36	PASS
BLE_2M	Ant1	2402	-4.62	≤30	-4.62	≤36	PASS
BLE_2M	Ant1	2440	-4.25	≤30	-4.25	≤36	PASS
BLE_2M	Ant1	2480	-4.12	≤30	-4.12	≤36	PASS



Test Graphs:

BLE_1M-Ant1-2402-PASS



BLE_1M-Ant1-2440-PASS



BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2440-PASS



BLE_2M-Ant1-2480-PASS






10 Power Spectral density

Test Requirement	: FCC CFR47 Part 15 Section 15.247
Test Method	: ANSI C63.10-2020+COR.1-2023
Test Limit	: Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

10.2 Test Setup




10.3 Test Result

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-21.93	≤8.00	PASS
BLE_1M	Ant1	2440	-21.53	≤8.00	PASS
BLE_1M	Ant1	2480	-21.33	≤8.00	PASS
BLE_2M	Ant1	2402	-24.05	≤8.00	PASS
BLE_2M	Ant1	2440	-23.71	≤8.00	PASS
BLE_2M	Ant1	2480	-23.51	≤8.00	PASS



Test Graphs:





BLE_1M-Ant1-2480-PASS




BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2440-PASS



BLE_2M-Ant1-2480-PASS





11 Antenna Application

11.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2 Result


The EUT'S antenna, permanent attached antenna, is PCB Antenna . The antenna's gain is 0 dBi and meets the requirement.

12 Test Setup

YH-6289 Input: DC 12V/2A Conducted Emissions




YH-6289 Input: DC 12V/2A Radiated Spurious Emissions
Test Frequency From 30MHz-1GHz







YH-6289 Input: DC 12V/2A Test frequency from Above 1GHz



YH-6285 Input: DC 5V/2A Conducted Emissions



YH-6285 Input: DC 5V/2A Radiated Spurious Emissions
Test Frequency From 30MHz-1GHz



YH-6285 Input: DC 5V/2A Test frequency from Above 1GHz



13 EUT Photos

YH-6289



YH-6289



YH-6289




YH-6289



YH-6289




YH-6289




YH-6289




YH-6289




YH-6289



YH-6289




YH-6289



YH-6285




YH-6285



YH-6285




YH-6285



YH-6285



Report No.: PTC26041802912 E-FC01




YH-6285




YH-6285




YH-6285




YH-6285



YH-6285



YH-6285



*****THE END REPORT*****