

TEST REPORT

Report No.: BCTC2504677421-3E

Applicant: EASTERN CCTV USA LLC

Product Name: Outdoor Wall Lantern Camera

Test Model: JN-OL4A

Tested Date: 2025-04-07 to 2025-05-12

Issued Date: 2025-05-20

Shenzhen BCTC Testing Co., Ltd.



FCC ID: 2A5AF-JNOL4

Product Name: Outdoor Wall Lantern Camera

Trademark: Jarnex

Model/Type Ref.: JN-OL4A,JN-OL4A1,JN-OL4A2,JN-OL4A3,JN-OL4A4,JN-OL4A5,JN-OL4A6,
JN-OL4A7,JN-OL4A8,JN-OL4A9

Prepared For: EASTERN CCTV USA LLC

Address: 50 COMMERCIAL ST PLAINVIEW, New York 11803, United States

Manufacturer: SZ POWER TECHNOLOGY CO., LTD

Address: Plant building 201, Huanguan Zhong Road 102, Songyuanxia Community, Guanhu
Street, Longhua District, ShenZhen, China

Prepared By: Shenzhen BCTC Testing Co., Ltd

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng,
Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2025-04-07


Sample tested Date: 2025-04-07 to 2025-05-12

Report No.: BCTC2504677421-3E

Test Standards: FCC Part15 15.407
ANSI C63.10-2013
KDB 662911 D01 v02r01
KDB 789033 D02 v02r01

Test Results: PASS

Tested by:



Brave Zeng/ Project Handler

Approved by:




Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table of Content

Test Report Declaration	Page
1. Version	5
2. Test Summary	6
3. Measurement Uncertainty	7
4. Product Information and Test Setup	8
4.1 Product Information	8
4.2 Test Setup Configuration	9
4.3 Support Equipment	9
4.4 Channel List	9
4.5 Test Mode	10
4.6 Table Of Parameters Of Text Software Setting	10
5. Test Facility And Test Instrument Used	11
5.1 Test Facility	11
5.2 Test Instrument Used	11
6. Conducted Emissions	13
6.1 Block Diagram Of Test Setup	13
6.2 Limit	13
6.3 Test Procedure	13
6.4 EUT Operating Conditions	14
6.5 Test Result	15
7. Radiated Emissions	17
7.1 Block Diagram Of Test Setup	17
7.2 Limit	18
7.3 Test Procedure	19
7.4 EUT Operating Conditions	20
7.5 Test Result	20
8. Power Spectral Density Test	32
8.1 Block Diagram Of Test Setup	32
8.2 Limit	32
8.3 Test Procedure	33
8.4 EUT Operating Conditions	33
8.5 Test Result	34
9. 26dB & 6dB & 99% Emission Bandwidth	44
9.1 Block Diagram Of Test Setup	44
9.2 Limit	44
9.3 Test Procedure	44
9.4 EUT Operating Conditions	44
9.5 Test Result	45
10. Maximum Conducted Output Power	64
10.1 Block Diagram Of Test Setup	64
10.2 Limit	64
10.3 Test Procedure	64
10.4 EUT Operating Conditions	65
10.5 Test Result	66


11. Out Of Band Emissions	68
11.1 Block Diagram Of Test Setup.....	68
11.2 Limit	68
11.3 Test Procedure	68
11.4 EUT Operating Conditions	68
11.5 Test Result.....	68
12. Spurious RF Conducted Emissions.....	75
12.1 Block Diagram Of Test Setup.....	75
12.2 Limit	75
12.3 Test Procedure	75
12.4 Test Result.....	75
13. Frequency Stability Measurement	84
13.1 Block Diagram Of Test Setup.....	84
13.2 Limit	84
13.3 Test Procedure	84
13.4 Test Result.....	85
14. Duty Cycle Of Test Signal	91
14.1 Standard Requirement	91
14.2 Formula.....	91
14.3 Test Procedure	91
14.4 Test Result.....	91
15. Antenna Requirement	92
15.1 Limit	92
15.2 Test Result.....	92
16. EUT Test Setup Photographs.....	93



TEST
TO
OVER
t Sea

1. Version

Report No.	Issue Date	Description	Approved
BCTC2504677421-3E	2025-05-20	Original	Valid



2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	Spurious Radiated Emissions	15.209(a), 15.407 (b)	PASS
2	Conducted Emission	15.207	PASS
3	26 dB and 99% Emission Bandwidth	15.407 (a)	PASS
4	Minimum 6 dB bandwidth	15.407(e)	PASS
5	Maximum Conducted Output Power	15.407 (a)	PASS
6	Band Edge	15.407(b)	PASS
7	Power Spectral Density	15.407 (a)	PASS
8	Spurious Emissions at Antenna Terminals	15.407(b)	PASS
9	Antenna Requirement	15.203	PASS

CO. LTD.

3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(9kHz-30MHz)	U=3.7dB
2	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
3	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
4	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
5	Conducted Emission(150kHz-30MHz)	U=3.20dB
6	Conducted Adjacent channel power	U=1.38dB
7	Conducted output power uncertainty Above 1G	U=1.576dB
8	Conducted output power uncertainty below 1G	U=1.28dB
9	humidity uncertainty	U=5.3%
10	Temperature uncertainty	U=0.59°C

4. Product Information and Test Setup


4.1 Product Information

Model/Type Ref.:	JN-OL4A,JN-OL4A1,JN-OL4A2,JN-OL4A3,JN-OL4A4,JN-OL4A5,JN-OL4A6,JN-OL4A7,JN-OL4A8,JN-OL4A9
Model differences:	The following models of devices we produce are identical in terms of electrical, mechanical, and physical structure; The only difference lies in the software version, and we ultimately have JN-OL4A as the testing model.
Hardware Version:	N/A
Software Version:	N/A
IEEE 802.11 WLAN Mode Supported	☒ 802.11a ☒ 802.11n(20MHz channel bandwidth) ☒ 802.11n(40MHz channel bandwidth)
Operation Frequency:	5180-5240MHz for 802.11a/n (HT20); 5190-5230MHz for 802.11n(HT40); 5745-5825 MHz for 802.11a/n/(HT20); 5755-5795 MHz for 802.11n(HT40);
Data Rate	☒ 802.11a:54/48/36/24/18/12/9/6Mbps ☒ 802.11n:up to 300 Mbps
Type of Modulation:	☒ OFDM with BPSK/QPSK/16QAM/64QAM for 802.11a/n
Number Of Channel	4 channels for 802.11a/n20 in the 5180-5240MHz band ; 2 channels for 802.11 n40 in the 5190-5230MHz band ; 5 channels for 802.11a/n20 in the 5745-5825MHz band ; 2 channels for 802.11 n40 in the 5755-5795MHz band ;
Transmit Power:	WIFI5.1G:12.95dBm WIFI5.8G:12.62dBm
Antenna installation:	Internal antenna,
Antenna Gain:	1.85dBi
Power supply:	AC 120V/60Hz


4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

Conducted Emission:



Radiated Spurious Emission



4.3 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	Outdoor Wall Lantern Camera	N/A	JN-OL4A	N/A	EUT
E-2	N/A	N/A	N/A	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	N/A	N/A	N/A	N/A

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Channel List

Frequency and Channel list for (5180-5240MHz):

802.11a/n (20MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	44	5220	-	-	-	-
40	5200	48	5240	-	-	-	-

802.11n (40MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	-	-	-	-	-	-
46	5230	-	-	-	-	-	-

Frequency and Channel list for 802.11a/n(20 MHz) (5745-5825MHz):

802.11a/n(20 MHz) Carrier Frequency Channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	153	5765	157	5785	161	5805
165	5825	-	-	-	-	-	-

802.11n(40MHz)Carrier Frequency Channel					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
151	5755	159	5795	-	-

4.5 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	802.11a / n 20 CH36/ CH40 802.11a /n 20 CH149/ CH157
Mode 2	802.11n 40 CH38 802.11n 40 CH 151
Mode 3	Link Mode

4.6 Table Of Parameters Of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters

Test software Version	CMD		
Parameters	DEF	DEF	DEF

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212

ISED Registered No.: 23583

ISED CAB identifier: CN0017

5.2 Test Instrument Used

Conducted Emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	May 16, 2024	May 15, 2025
LISN	R&S	ENV216	101375	May 16, 2024	May 15, 2025
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Pulse limiter	Schwarzbeck	VTSD 9561-F	01323	May 16, 2024	May 15, 2025


RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power meter	Keysight	E4419	\	May 16, 2024	May 15, 2025
Power Sensor (AV)	Keysight	E9300A	\	May 16, 2024	May 15, 2025
Signal Analyzer 20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 16, 2024	May 15, 2025
Spectrum Analyzer 9kHz-40GHz	R&S	FSP40	100363	May 16, 2024	May 15, 2025

Radiated Emissions Test (966 Chamber)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	May 16, 2024	May 15, 2025
Receiver	R&S	ESR3	102075	May 16, 2024	May 15, 2025
Receiver	R&S	ESRP	101154	May 16, 2024	May 15, 2025
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 16, 2024	May 15, 2025
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 21, 2024	May 20, 2025
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 21, 2024	May 20, 2025
Amplifier	SKET	LAPA_01G1 8G-45dB	SK2021040901	May 16, 2024	May 15, 2025
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 21, 2024	May 20, 2025
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35-HG	2034381	May 16, 2024	May 15, 2025
Horn Antenn(18GHz-40GHz)	Schwarzbeck	BBHA9170	00822	May 21, 2024	May 20, 2025
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 16, 2024	May 15, 2025
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

CO. LTD.

6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:

- *Decreasing linearly with logarithm of frequency.
- The lower limit shall apply at the transition frequencies.

6.3 Test Procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.


6.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



6.5 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	L
Test Mode:	Mode 3	Test Voltage :	AC 120V/60Hz




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1500	36.95	10.57	47.52	66.00	-18.48	QP
2	0.1500	13.94	10.57	24.51	56.00	-31.49	AVG
3	0.1815	34.82	10.58	45.40	64.42	-19.02	QP
4	0.1815	19.69	10.58	30.27	54.42	-24.15	AVG
5	0.2355	32.13	10.59	42.72	62.25	-19.53	QP
6	0.2355	15.30	10.59	25.89	52.25	-26.36	AVG
7 *	0.3570	33.11	10.61	43.72	58.80	-15.08	QP
8	0.3570	14.78	10.61	25.39	48.80	-23.41	AVG
9	21.8580	17.27	12.53	29.80	60.00	-30.20	QP
10	21.8580	2.74	12.53	15.27	50.00	-34.73	AVG
11	24.0000	26.05	12.55	38.60	60.00	-21.40	QP
12	24.0000	20.96	12.55	33.51	50.00	-16.49	AVG

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Phase :	N
Test Mode:	Mode 3	Test Voltage :	AC 120V/60Hz


Remark:


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1545	39.30	10.57	49.87	65.75	-15.88	QP
2	0.1545	22.56	10.57	33.13	55.75	-22.62	AVG
3	0.1815	37.27	10.58	47.85	64.42	-16.57	QP
4	0.1815	18.32	10.58	28.90	54.42	-25.52	AVG
5	0.2130	34.45	10.59	45.04	63.09	-18.05	QP
6	0.2130	17.66	10.59	28.25	53.09	-24.84	AVG
7 *	0.3570	32.82	10.61	43.43	58.80	-15.37	QP
8	0.3570	16.59	10.61	27.20	48.80	-21.60	AVG
9	0.4695	22.82	10.63	33.45	56.52	-23.07	QP
10	0.4695	8.23	10.63	18.86	46.52	-27.66	AVG
11	1.0770	18.77	10.60	29.37	56.00	-26.63	QP
12	1.0770	4.78	10.60	15.38	46.00	-30.62	AVG


7. Radiated Emissions

7.1 Block Diagram Of Test Setup


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



7.2 Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Field Strength uV/m	Distance (m)	Field Strength Limit at 3m Distance	
			uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

Limits Of Radiated Emission Measurement (Above 1000MHz)

Frequency (MHz)	Limit (dBuV/m) (at 3M)	
	Peak	Average
Above 1000	74	54

Notes:

- (1)The limit for radiated test was performed according to FCC PART 15C.
- (2)The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

7.3 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205.

It must be performed with the highest gain of each type of antenna proposed for use with the EUT.

Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where $RBWCF [dB] = 10 \cdot \lg(100 [kHz] / \text{narrower RBW} [kHz])$. , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

7.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

7.5 Test Result

Below 30MHz

Temperature:	26°C	Relative Humidity:	24%
Pressure:	101 kPa	Test Voltage:	AC 120V/60Hz
Test Mode:	Mode 3	Polarization:	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance}) (dB)$;

Limit line = specific limits(dBuv) + distance extrapolation factor.

Between 30MHz – 1GHz

Temperature:	24 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage :	AC 120V/60Hz
Test Mode:	Mode 3	Polarization :	Horizontal




Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	216.0240	54.78	-18.42	36.36	46.00	-9.64	QP
2	239.9874	52.88	-18.09	34.79	46.00	-11.21	QP
3 *	336.0352	55.17	-15.57	39.60	46.00	-6.40	QP
4	552.8832	46.94	-9.81	37.13	46.00	-8.87	QP
5	601.4265	47.72	-9.15	38.57	46.00	-7.43	QP
6	672.8444	42.86	-8.39	34.47	46.00	-11.53	QP

Temperature:	24 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage :	AC 120V/60Hz
Test Mode:	Mode 3	Polarization :	Vertical



Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	216.0240	56.05	-18.42	37.63	46.00	-8.37	QP
2	239.9874	54.27	-18.09	36.18	46.00	-9.82	QP
3 !	336.0351	55.93	-15.57	40.36	46.00	-5.64	QP
4	408.9460	53.74	-13.89	39.85	46.00	-6.15	QP
5	552.8832	47.88	-9.81	38.07	46.00	-7.93	QP
6 *	601.4265	52.47	-9.15	43.32	46.00	-2.68	QP

Test Mode :	TX(5.1G) - 802.11a
-------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.197	73.02	-20.73	52.29	68.2	-15.91	Pk
Vertical	4434.197	59.88	-20.73	39.15	54	-14.85	AV
Vertical	10360.088	62.75	-9.36	53.39	68.2	-14.81	Pk
Vertical	10360.088	49.01	-9.36	39.65	54	-14.35	AV
Vertical	15540.003	63.85	-7.84	56.01	74	-17.99	Pk
Vertical	15540.003	49.60	-7.84	41.76	54	-12.24	AV
Horizontal	4434.030	71.64	-20.73	50.91	68.2	-17.29	Pk
Horizontal	4434.030	59.68	-20.73	38.95	54	-15.05	AV
Horizontal	10360.028	61.54	-9.36	52.18	68.2	-16.02	Pk
Horizontal	10360.028	49.05	-9.36	39.69	54	-14.31	AV
Horizontal	15540.069	62.62	-7.84	54.78	74	-19.22	Pk
Horizontal	15540.069	49.55	-7.84	41.71	54	-12.29	AV
middle Channel (5200 MHz)-Above 1G							
Vertical	4592.038	74.46	-20.42	54.05	74	-19.95	Pk
Vertical	4592.038	59.74	-20.42	39.33	54	-14.67	AV
Vertical	10400.162	63.94	-9.30	54.64	68.2	-13.56	Pk
Vertical	10400.162	49.34	-9.30	40.04	54	-13.96	AV
Vertical	15600.028	64.00	-7.82	56.18	74	-17.82	Pk
Vertical	15600.028	49.81	-7.82	41.99	54	-12.01	AV
Horizontal	4592.043	71.12	-20.42	50.70	74	-23.30	Pk
Horizontal	4592.043	59.42	-20.42	39.01	54	-14.99	AV
Horizontal	10400.104	63.16	-9.30	53.86	68.2	-14.34	Pk
Horizontal	10400.104	49.39	-9.30	40.09	54	-13.91	AV
Horizontal	15600.097	63.05	-7.82	55.23	74	-18.77	Pk
Horizontal	15600.097	49.48	-7.82	41.66	54	-12.34	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.037	72.04	-20.12	51.92	74	-22.08	Pk
Vertical	4739.037	59.88	-20.12	39.76	54	-14.24	AV
Vertical	10480.073	61.56	-9.18	52.38	68.2	-15.82	Pk
Vertical	10480.073	49.91	-9.18	40.73	54	-13.27	AV
Vertical	15720.127	64.28	-7.78	56.50	74	-17.50	Pk
Vertical	15720.127	49.77	-7.78	41.99	54	-12.01	AV
Horizontal	4739.002	74.44	-20.12	54.31	74	-19.69	Pk
Horizontal	4739.002	59.64	-20.12	39.52	54	-14.48	AV
Horizontal	10480.006	61.26	-9.18	52.08	68.2	-16.12	Pk
Horizontal	10480.006	49.33	-9.18	40.15	54	-13.85	AV
Horizontal	15720.155	62.39	-7.78	54.61	74	-19.39	Pk
Horizontal	15720.155	49.03	-7.78	41.25	54	-12.75	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX(5.1G) - 802.11n-HT20
-------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5180 MHz)-Above 1G							
Vertical	4434.107	72.56	-20.73	51.83	68.2	-16.37	Pk
Vertical	4434.107	59.38	-20.73	38.65	54	-15.35	AV
Vertical	10360.062	60.33	-9.36	50.97	68.2	-17.23	Pk
Vertical	10360.062	49.69	-9.36	40.33	54	-13.67	AV
Vertical	15540.114	62.42	-7.84	54.58	74	-19.42	Pk
Vertical	15540.114	49.87	-7.84	42.03	54	-11.97	AV
Horizontal	4434.022	71.31	-20.73	50.58	68.2	-17.62	Pk
Horizontal	4434.022	59.97	-20.73	39.24	54	-14.76	AV
Horizontal	10360.058	62.40	-9.36	53.04	68.2	-15.16	Pk
Horizontal	10360.058	49.33	-9.36	39.97	54	-14.03	AV
Horizontal	15540.065	60.18	-7.84	52.34	74	-21.66	Pk
Horizontal	15540.065	49.60	-7.84	41.76	54	-12.24	AV
middle Channel (5200 MHz)-Above 1G							
Vertical	4592.195	74.48	-20.42	54.06	74	-19.94	Pk
Vertical	4592.195	59.62	-20.42	39.21	54	-14.79	AV
Vertical	10400.042	62.17	-9.30	52.87	68.2	-15.33	Pk
Vertical	10400.042	49.88	-9.30	40.58	54	-13.42	AV
Vertical	15600.123	62.35	-7.82	54.53	74	-19.47	Pk
Vertical	15600.123	49.98	-7.82	42.16	54	-11.84	AV
Horizontal	4592.085	72.91	-20.42	52.49	74	-21.51	Pk
Horizontal	4592.085	59.83	-20.42	39.42	54	-14.58	AV
Horizontal	10400.143	62.80	-9.30	53.50	68.2	-14.70	Pk
Horizontal	10400.143	49.98	-9.30	40.68	54	-13.32	AV
Horizontal	15600.071	60.11	-7.82	52.29	74	-21.71	Pk
Horizontal	15600.071	49.05	-7.82	41.23	54	-12.77	AV
High Channel (5240 MHz)-Above 1G							
Vertical	4739.007	73.94	-20.12	53.82	74	-20.18	Pk
Vertical	4739.007	59.94	-20.12	39.82	54	-14.18	AV
Vertical	10480.049	61.73	-9.18	52.55	68.2	-15.65	Pk
Vertical	10480.049	49.38	-9.18	40.20	54	-13.80	AV
Vertical	15720.153	63.52	-7.78	55.74	74	-18.26	Pk
Vertical	15720.153	49.92	-7.78	42.14	54	-11.86	AV
Horizontal	4739.044	71.52	-20.12	51.40	74	-22.60	Pk
Horizontal	4739.044	59.83	-20.12	39.71	54	-14.29	AV
Horizontal	10480.032	63.13	-9.18	53.95	68.2	-14.25	Pk
Horizontal	10480.032	49.53	-9.18	40.35	54	-13.65	AV
Horizontal	15720.016	62.52	-7.78	54.74	74	-19.26	Pk
Horizontal	15720.016	49.04	-7.78	41.26	54	-12.74	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode :	TX(5.1G) - 802.11n-HT40
-------------	-------------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5190 MHz)-Above 1G							
Vertical	4434.125	71.67	-20.73	50.94	68.2	-17.26	Pk
Vertical	4434.125	59.07	-20.73	38.33	54	-15.67	AV
Vertical	10380.177	64.36	-9.33	55.03	68.2	-13.17	Pk
Vertical	10380.177	49.69	-9.33	40.36	54	-13.64	AV
Vertical	15570.080	61.84	-7.83	54.01	74	-19.99	Pk
Vertical	15570.080	49.23	-7.83	41.40	54	-12.60	AV
Horizontal	4434.167	71.05	-20.73	50.32	74	-23.68	Pk
Horizontal	4434.167	59.10	-20.73	38.37	54	-15.63	AV
Horizontal	10380.112	60.01	-9.33	50.68	68.2	-17.52	Pk
Horizontal	10380.112	49.68	-9.33	40.35	54	-13.65	AV
Horizontal	15570.099	62.68	-7.83	54.85	74	-19.15	Pk
Horizontal	15570.099	49.66	-7.83	41.83	54	-12.17	AV
High Channel (5230 MHz)-Above 1G							
Vertical	4739.005	74.92	-20.12	54.79	68.2	-13.41	Pk
Vertical	4739.005	59.77	-20.12	39.65	54	-14.35	AV
Vertical	10460.026	64.43	-9.21	55.22	68.2	-12.98	Pk
Vertical	10460.026	49.81	-9.21	40.60	54	-13.40	AV
Vertical	15690.170	64.90	-7.79	57.11	74	-16.89	Pk
Vertical	15690.170	49.10	-7.79	41.31	54	-12.69	AV
Horizontal	4739.170	70.01	-20.12	49.89	68.2	-18.31	Pk
Horizontal	4739.170	59.43	-20.12	39.31	54	-14.69	AV
Horizontal	10460.091	61.70	-9.21	52.49	68.2	-15.71	Pk
Horizontal	10460.091	49.92	-9.21	40.71	54	-13.29	AV
Horizontal	15690.076	63.17	-7.79	55.38	74	-18.62	Pk
Horizontal	15690.076	49.23	-7.79	41.44	54	-12.56	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

- ☒ Undesirable radiated Undesirable radiated Spurious Emission in Band Edge
- All the modes 802.11a/n has been tested and the worst result 802.11a recorded as below:



Test mode: 802.11a Frequency(MHz): 5180



Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
5136.05	H	47.09	74	38.60	54
5149.10	V	45.95	74	35.90	54

Test mode: 802.11a Frequency(MHz): 5240

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)
5355.45	H	48.58	74	37.60	54
5367.05	V	46.49	74	35.90	54

Note: (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
(2) Emission Level= Reading Level+Correct Factor.
(3) Correct Factor= Ant_F + Cab_L - Preamp





Test Mode:	TX(5.8G) - 802.11a
------------	--------------------

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.049	71.65	-20.24	51.41	74	-22.59	Pk
Vertical	4679.049	59.46	-20.24	39.22	54	-14.78	AV
Vertical	11490.128	63.64	-8.79	54.85	68.2	-13.35	Pk
Vertical	11490.128	49.53	-8.79	40.74	54	-13.26	AV
Vertical	17235.083	57.59	-3.18	54.41	68.2	-13.79	Pk
Vertical	17235.083	44.89	-3.18	41.71	54	-12.29	AV
Horizontal	4679.138	71.29	-20.73	50.56	74	-23.44	Pk
Horizontal	4679.138	59.05	-20.73	38.32	54	-15.68	AV
Horizontal	11490.033	60.17	-8.79	51.38	68.2	-16.82	Pk
Horizontal	11490.033	49.63	-8.79	40.84	54	-13.16	AV
Horizontal	17235.002	57.34	-3.18	54.16	68.2	-14.04	Pk
Horizontal	17235.002	44.60	-3.18	41.42	54	-12.58	AV
middle Channel (5785 MHz)-Above 1G							
Vertical	4592.067	71.04	-20.42	50.62	74	-23.38	Pk
Vertical	4592.067	59.63	-20.42	39.21	54	-14.79	AV
Vertical	11570.035	61.78	-8.86	52.92	68.2	-15.28	Pk
Vertical	11570.035	49.84	-8.86	40.98	54	-13.02	AV
Vertical	17355.126	56.18	-2.52	53.66	68.2	-14.54	Pk
Vertical	17355.126	44.81	-2.52	42.29	54	-11.71	AV
Horizontal	4592.010	70.16	-20.42	49.75	74	-24.25	Pk
Horizontal	4592.010	59.71	-20.42	39.29	54	-14.71	AV
Horizontal	11570.158	62.03	-8.86	53.17	68.2	-15.03	Pk
Horizontal	11570.158	49.67	-8.86	40.81	54	-13.19	AV
Horizontal	17355.040	56.55	-2.52	54.03	68.2	-14.17	Pk
Horizontal	17355.040	44.30	-2.52	41.78	54	-12.22	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.029	74.57	-18.93	55.64	68.2	-12.56	Pk
Vertical	6039.029	59.81	-18.93	40.88	54	-13.12	AV
Vertical	11650.108	64.38	-8.92	55.46	74	-18.54	Pk
Vertical	11650.108	49.35	-8.92	40.43	54	-13.57	AV
Vertical	17475.196	59.73	-1.86	57.87	68.2	-10.33	Pk
Vertical	17475.196	44.02	-1.86	42.16	54	-11.84	AV
Horizontal	6039.199	71.83	-18.93	52.90	68.2	-15.30	Pk
Horizontal	6039.199	59.07	-18.93	40.13	54	-13.87	AV
Horizontal	11650.087	61.83	-8.92	52.91	74	-21.09	Pk
Horizontal	11650.087	50.00	-8.92	41.08	54	-12.92	AV
Horizontal	17475.050	55.04	-1.86	53.18	68.2	-15.02	Pk
Horizontal	17475.050	44.18	-1.86	42.32	54	-11.68	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX(5.8G) - 802.11n-HT20

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5745 MHz)-Above 1G							
Vertical	4679.091	73.53	-20.24	53.29	74	-20.71	Pk
Vertical	4679.091	59.31	-20.24	39.07	54	-14.93	AV
Vertical	11490.183	64.48	-8.79	55.69	68.2	-12.51	Pk
Vertical	11490.183	49.16	-8.79	40.37	54	-13.63	AV
Vertical	17235.063	56.31	-3.18	53.13	68.2	-15.07	Pk
Vertical	17235.063	44.72	-3.18	41.54	54	-12.46	AV
Horizontal	4679.166	73.44	-20.24	53.19	74	-20.81	Pk
Horizontal	4679.166	59.46	-20.24	39.22	54	-14.78	AV
Horizontal	11490.167	60.91	-8.79	52.12	68.2	-16.08	Pk
Horizontal	11490.167	49.55	-8.79	40.76	54	-13.24	AV
Horizontal	17235.065	58.51	-3.18	55.33	68.2	-12.87	Pk
Horizontal	17235.065	44.55	-3.18	41.37	54	-12.63	AV
middle Channel (5785 MHz)-Above 1G							
Vertical	4592.055	71.99	-20.42	51.57	74	-22.43	Pk
Vertical	4592.055	59.93	-20.42	39.51	54	-14.49	AV
Vertical	11570.126	62.44	-8.86	53.58	68.2	-14.62	Pk
Vertical	11570.126	49.37	-8.86	40.51	54	-13.49	AV
Vertical	17355.115	56.88	-2.52	54.36	68.2	-13.84	Pk
Vertical	17355.115	44.92	-2.52	42.40	54	-11.60	AV
Horizontal	4592.037	70.37	-20.42	49.95	74	-24.05	Pk
Horizontal	4592.037	59.86	-20.42	39.45	54	-14.55	AV
Horizontal	11570.172	60.04	-8.86	51.18	68.2	-17.02	Pk
Horizontal	11570.172	49.44	-8.86	40.58	54	-13.42	AV
Horizontal	17355.081	55.71	-2.52	53.19	68.2	-15.01	Pk
Horizontal	17355.081	44.95	-2.52	42.43	54	-11.57	AV
High Channel (5825 MHz)-Above 1G							
Vertical	6039.121	70.59	-18.93	51.66	68.2	-16.54	Pk
Vertical	6039.121	59.32	-18.93	40.38	54	-13.62	AV
Vertical	11650.147	61.80	-8.92	52.88	74	-21.12	Pk
Vertical	11650.147	49.93	-8.92	41.01	54	-12.99	AV
Vertical	17475.079	59.45	-1.86	57.59	68.2	-10.61	Pk
Vertical	17475.079	44.86	-1.86	43.00	54	-11.00	AV
Horizontal	6039.028	70.45	-18.93	51.52	68.2	-16.68	Pk
Horizontal	6039.028	59.88	-18.93	40.95	54	-13.05	AV
Horizontal	11650.057	60.13	-8.92	51.21	74	-22.79	Pk
Horizontal	11650.057	49.05	-8.92	40.13	54	-13.87	AV
Horizontal	17475.193	57.56	-1.86	55.70	68.2	-12.50	Pk
Horizontal	17475.193	44.43	-1.86	42.57	54	-11.43	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Test Mode: TX(5.8G) - 802.11n-HT40

Polar	Frequency	Reading Level	Correct Factor	Measurement	Limits	Over	Detector Type
(H/V)	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel (5755 MHz)-Above 1G							
Vertical	4679.078	72.64	-20.24	52.40	74	-21.60	Pk
Vertical	4679.078	59.45	-20.24	39.21	54	-14.79	AV
Vertical	11510.186	62.83	-8.81	54.02	74	-19.98	Pk
Vertical	11510.186	49.50	-8.81	40.69	54	-13.31	AV
Vertical	17265.064	55.70	-3.01	52.69	68.2	-15.51	Pk
Vertical	17265.064	44.26	-3.01	41.25	54	-12.75	AV
Horizontal	4679.034	70.18	-20.24	49.93	74	-24.07	Pk
Horizontal	4679.034	59.13	-20.24	38.89	54	-15.11	AV
Horizontal	11510.044	63.89	-8.81	55.08	74	-18.92	Pk
Horizontal	11510.044	49.75	-8.81	40.94	54	-13.06	AV
Horizontal	17265.106	59.51	-3.01	56.50	68.2	-11.70	Pk
Horizontal	17265.106	44.86	-3.01	41.85	54	-12.15	AV
middle Channel (5795 MHz)-Above 1G							
Vertical	6039.182	74.12	-18.93	55.19	68.2	-13.01	Pk
Vertical	6039.182	59.32	-18.93	40.38	54	-13.62	AV
Vertical	11590.061	61.26	-8.87	52.39	74	-21.61	Pk
Vertical	11590.061	50.00	-8.87	41.13	54	-12.87	AV
Vertical	17385.156	55.81	-2.35	53.46	68.2	-14.74	Pk
Vertical	17385.156	44.92	-2.35	42.57	54	-11.43	AV
Horizontal	6039.033	71.24	-18.93	52.30	68.2	-15.90	Pk
Horizontal	6039.033	59.31	-18.93	40.38	54	-13.62	AV
Horizontal	11590.081	63.29	-8.87	54.42	74	-19.58	Pk
Horizontal	11590.081	49.36	-8.87	40.49	54	-13.51	AV
Horizontal	17385.046	59.01	-2.35	56.66	68.2	-11.54	Pk
Horizontal	17385.046	44.86	-2.35	42.51	54	-11.49	AV

Note: PK value is lower than the Average value limit, So average didn't record.

The 26.5-40G amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

8. Power Spectral Density Test

8.1 Block Diagram Of Test Setup



8.2 Limit

For the band 5.15-5.25 GHz,

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz

(3) For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

8.3 Test Procedure

For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
- b) Set $VBW \geq 3 RBW$.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.


8.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



8.5 Test Result



Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	(5180-5240MHz)		



Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
NVNT	a	5180	3.23	11	Pass
NVNT	a	5200	2.78	11	Pass
NVNT	a	5240	2.42	11	Pass
NVNT	n20	5180	1.53	11	Pass
NVNT	n20	5200	2.54	11	Pass
NVNT	n20	5240	1.66	11	Pass
NVNT	n40	5190	-2.5	11	Pass
NVNT	n40	5230	-2.58	11	Pass














Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	(5745-5825MHz)		



Condition	Mode	Frequency (MHz)	Conducted PSD (dBm/MHz)	Limit (dBm/MHz)	Verdict
NVNT	a	5745	-1.02	30	Pass
NVNT	a	5785	-1.24	30	Pass
NVNT	a	5825	0.53	30	Pass
NVNT	n20	5745	-2.17	30	Pass
NVNT	n20	5785	-1.69	30	Pass
NVNT	n20	5825	-2.48	30	Pass
NVNT	n40	5755	-5.64	30	Pass
NVNT	n40	5795	-5.58	30	Pass



BCTC
 BCTC
 PPR
 Report












9. 26dB & 6dB & 99% Emission Bandwidth

9.1 Block Diagram Of Test Setup



9.2 Limit

The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

9.3 Test Procedure

- a) Set RBW = approximately 1% of the emission bandwidth.
 - b) Set the VBW > RBW.
 - c) Detector = Peak.
 - d) Trace mode = max hold.
 - e) Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
- The following procedure shall be used for measuring (99 %) power bandwidth:
1. Set center frequency to the nominal EUT channel center frequency.
 2. Set span = 1.5 times to 5.0 times the OBW.
 3. Set RBW = 1 % to 5 % of the OBW
 4. Set VBW $\geq 3 \cdot$ RBW
 5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
 6. Use the 99 % power bandwidth function of the instrument (if available).
 7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.


9.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

9.5 Test Result


Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	(5180-5240MHz)		



Condition	Mode	Frequency (MHz)	-26 dB (MHz)	Verdict
NVNT	a	5180	21.509	Pass
NVNT	a	5200	20.386	Pass
NVNT	a	5240	20.996	Pass
NVNT	n20	5180	21.024	Pass
NVNT	n20	5200	20.908	Pass
NVNT	n20	5240	21.038	Pass
NVNT	n40	5190	40.662	Pass
NVNT	n40	5230	40.506	Pass







Condition	Mode	Frequency (MHz)	99% OBW (MHz)
NVNT	a	5180	16.519
NVNT	a	5200	16.467
NVNT	a	5240	16.472
NVNT	n20	5180	17.563
NVNT	n20	5200	17.582
NVNT	n20	5240	17.567
NVNT	n40	5190	36.022
NVNT	n40	5230	36.015


TEST
TO
OVER
t Sea


























Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	(5745-5825MHz)		



Condition	Mode	Frequency (MHz)	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	a	5745	16.293	0.5	Pass
NVNT	a	5785	16.293	0.5	Pass
NVNT	a	5825	16.294	0.5	Pass
NVNT	n20	5745	16.926	0.5	Pass
NVNT	n20	5785	16.677	0.5	Pass
NVNT	n20	5825	16.353	0.5	Pass
NVNT	n40	5755	35.165	0.5	Pass
NVNT	n40	5795	35.023	0.5	Pass



Condition	Mode	Frequency (MHz)	99% OBW (MHz)
NVNT	a	5745	16.882
NVNT	a	5785	16.611
NVNT	a	5825	16.634
NVNT	n20	5745	17.745
NVNT	n20	5785	17.631
NVNT	n20	5825	17.623
NVNT	n40	5755	36.278
NVNT	n40	5795	36.102


























10. Maximum Conducted Output Power

10.1 Block Diagram Of Test Setup



10.2 Limit

According to FCC §15.407

The maximum conducted output power should not exceed:

Frequency Band(MHz)	Limit
5150~5250	0.25W
5250~5350	0.25W
5725~5850	1W

10.3 Test Procedure

Maximum conducted output power may be measured using a spectrum analyzer/EMI receiver or an RF power meter.

1. Device Configuration

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level (see section II.B.).

a) The intent is to test at 100 percent duty cycle; however a small reduction in duty cycle (to no lower than 98 percent) is permitted if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.

b) If continuous transmission (or at least 98 percent duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level with the transmit duration as long as possible and the duty cycle as high as possible.

2. Measurement using a Spectrum Analyzer or EMI Receiver (SA)

Measurement of maximum conducted output power using a spectrum analyzer requires integrating the spectrum across a frequency span that encompasses, at a minimum, either the EBW or the 99-percent occupied bandwidth of the signal.¹ However, the EBW must be used to determine bandwidth dependent limits on maximum conducted output power in accordance with § 15.407(a).

a) The test method shall be selected as follows: (i) Method SA-1 or SA-1 Alternative (averaging with the EUT transmitting at full power throughout each sweep) shall be applied if either of the following conditions can be satisfied:

- The EUT transmits continuously (or with a duty cycle ≥ 98 percent).
- Sweep triggering or gating can be implemented in a way that the device transmits at the maximum power control level throughout the duration of each of the instrument sweeps to be averaged. This condition can generally be achieved by triggering the instrument's sweep if the duration of the sweep (with the analyzer configured as in Method SA-1, below) is equal to or shorter than the duration T of each transmission from the EUT and if those transmissions exhibit full power throughout their durations.

(ii) Method SA-2 or SA-2 Alternative (averaging across on and off times of the EUT transmissions, followed by duty cycle correction) shall be applied if the conditions of (i) cannot be achieved and the transmissions exhibit a constant duty cycle during the measurement duration. Duty cycle will be considered to be constant if variations are less than ± 2 percent.

(iii) Method SA-3 (RMS detection with max hold) or SA-3 Alternative (reduced VBW with max hold) shall be applied if the conditions of (i) and (ii) cannot be achieved.

b) Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep): (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW ≥ 3 MHz.

(iv) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".

(viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum

10.4 EUT Operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

10.5 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	5180-5240MHz		

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5180	12.58	24	Pass
NVNT	a	5200	12.03	24	Pass
NVNT	a	5240	12.95	24	Pass
NVNT	n20	5180	11.52	24	Pass
NVNT	n20	5200	11.78	24	Pass
NVNT	n20	5240	11.34	24	Pass
NVNT	n40	5190	10.29	24	Pass
NVNT	n40	5230	10.44	24	Pass

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	5745-5825MHz		

Condition	Mode	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	a	5745	12.19	30	Pass
NVNT	a	5785	12.57	30	Pass
NVNT	a	5825	12.62	30	Pass
NVNT	n20	5745	11.63	30	Pass
NVNT	n20	5785	11.71	30	Pass
NVNT	n20	5825	11.25	30	Pass
NVNT	n40	5755	10.37	30	Pass
NVNT	n40	5795	10.6	30	Pass

SHENZHEN

11. Out Of Band Emissions

11.1 Block Diagram Of Test Setup



11.2 Limit

According to FCC §15.407(b)

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

11.3 Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

11.4 EUT Operating Conditions



The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data



11.5 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101kPa	Test Voltage:	AC 120V/60Hz

5180-5240MHz











5745-5825MHz







12. Spurious RF Conducted Emissions

12.1 Block Diagram Of Test Setup



12.2 Limit

Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.725-5.85 GHz band(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge..

12.3 Test Procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



12.4 Test Result



Remark: The measurement frequency range is from 9KHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data.



About: 26.5GHz-40GHz, The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5180-5240MHz
















5745-58250MHz










13. Frequency Stability Measurement

13.1 Block Diagram Of Test Setup



13.2 Limit

Manufactures of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

The transmitter center frequency tolerance shall be ± 20 ppm maximum for the 5 GHz band (IEEE 802.11n specification)..

13.3 Test Procedure

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and he limit is less than ± 20 ppm (IEEE 802.11n specification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature is -20°C ~ 70°C .

13.4 Test Result

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	TX (5.1G) Mode Frequency U-NII-1 (5180-5240MHz)		

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5180.0160	5180	0.0160	3.0920
		V max (V)	132.00	5180.0043	5180	0.0043	0.8286
		V min (V)	108.00	5180.0146	5180	0.0146	2.8152
Limits				5150-5250 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5180MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5180.0045	5180	0.0045	0.8666
		T (°C)	-10	5180.0031	5180	0.0031	0.6066
		T (°C)	0	5180.0129	5180	0.0129	2.4992
		T (°C)	10	5180.0082	5180	0.0082	1.5790
		T (°C)	20	5180.0129	5180	0.0129	2.4890
		T (°C)	30	5180.0068	5180	0.0068	1.3033
		T (°C)	40	5180.0070	5180	0.0070	1.3557
		T (°C)	50	5180.0078	5180	0.0078	1.4988
		T (°C)	60	5180.0059	5180	0.0059	1.1458
		T (°C)	70	5180.0041	5180	0.0041	0.7962
Limits				5150-5250 MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5200.0104	5200	0.0104	2.0087
		V max (V)	132.00	5200.0041	5200	0.0041	0.7826
		V min (V)	108.00	5200.0086	5200	0.0086	1.6460
Limits				5150-5250 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5200MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5200.01317	5200	0.01317	2.5332
		T (°C)	-10	5200.00853	5200	0.00853	1.6395
		T (°C)	0	5200.01144	5200	0.01144	2.2009
		T (°C)	10	5200.00060	5200	0.00060	0.1150
		T (°C)	20	5200.01170	5200	0.01170	2.2506
		T (°C)	30	5200.00021	5200	0.00021	0.0399
		T (°C)	40	5200.00724	5200	0.00724	1.3927
		T (°C)	50	5200.00753	5200	0.00753	1.4490
		T (°C)	60	5200.01084	5200	0.01084	2.0837
		T (°C)	70	5200.00740	5200	0.00740	1.4228
Limits				5150-5250 MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5240.0076	5240	0.0076	1.4499
		V max (V)	132.00	5240.0015	5240	0.0015	0.2802
		V min (V)	108.00	5240.0014	5240	0.0014	0.2611
Limits				5150-5250 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5240MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5240.0088	5240	0.0088	1.6742
		T (°C)	-10	5240.0133	5240	0.0133	2.5418
		T (°C)	0	5240.0092	5240	0.0092	1.7524
		T (°C)	10	5240.0049	5240	0.0049	0.9347
		T (°C)	20	5240.0067	5240	0.0067	1.2858
		T (°C)	30	5240.0035	5240	0.0035	0.6732
		T (°C)	40	5240.0046	5240	0.0046	0.8788
		T (°C)	50	5240.0003	5240	0.0003	0.0566
		T (°C)	60	5240.0073	5240	0.0073	1.3998
		T (°C)	70	5240.0040	5240	0.0040	0.7582
Limits				5150-5250 MHz			
Result				Complies			

Temperature:	26 °C	Relative Humidity:	54%
Pressure:	101KPa	Test Voltage:	AC 120V/60Hz
Test Mode:	TX (5.8G) Mode Frequency U-NII-3 (5745-5825MHz)		

Voltage vs. Frequency Stabilit

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5745.00367	5745	0.00367	0.6381
		V max (V)	132.00	5745.00594	5745	0.00594	1.0341
		V min (V)	108.00	5745.00283	5745	0.00283	0.4921
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5745MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5745.01076	5745	0.01076	1.8736
		T (°C)	-10	5745.00947	5745	0.00947	1.6490
		T (°C)	0	5745.00192	5745	0.00192	0.3349
		T (°C)	10	5745.00653	5745	0.00653	1.1368
		T (°C)	20	5745.01026	5745	0.01026	1.7861
		T (°C)	30	5745.00014	5745	0.00014	0.0245
		T (°C)	40	5745.00783	5745	0.00783	1.3621
		T (°C)	50	5745.00527	5745	0.00527	0.9165
		T (°C)	60	5745.00436	5745	0.00436	0.7583
		T (°C)	70	5745.00303	5745	0.00303	0.5277
Limits				5725-5850 MHz			
Result				Complies			

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5785.00445	5785	0.00445	0.7692
		V max (V)	132.00	5785.00321	5785	0.00321	0.5543
		V min (V)	108.00	5785.01229	5785	0.01229	2.1243
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5785MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5785.00013	5785	0.00013	0.0225
		T (°C)	-10	5785.01023	5785	0.01023	1.7689
		T (°C)	0	5785.00594	5785	0.00594	1.0265
		T (°C)	10	5785.00147	5785	0.00147	0.2535
		T (°C)	20	5785.00479	5785	0.00479	0.8273
		T (°C)	30	5785.00968	5785	0.00968	1.6736
		T (°C)	40	5785.00727	5785	0.00727	1.2573
		T (°C)	50	5785.00723	5785	0.00723	1.2498
		T (°C)	60	5785.01169	5785	0.01169	2.0203
		T (°C)	70	5785.00826	5785	0.00826	1.4275
Limits				5725-5850 MHz			
Result				Complies			

STING
ED

Voltage vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
T nom (°C)	20	V nom (V)	120.00	5825.00299	5825	0.00299	0.5127
		V max (V)	132.00	5825.00812	5825	0.00812	1.3933
		V min (V)	108.00	5825.00920	5825	0.00920	1.5797
Limits				5725-5850 MHz			
Result				Complies			

Temperature vs. Frequency Stability

TEST CONDITIONS				Reference Frequency: 5825MHz			
				f	fc	Max. Deviation (MHz)	Max. Deviation (ppm)
V nom (V)	120	T (°C)	-20	5825.00869	5825	0.00869	1.4927
		T (°C)	-10	5825.00765	5825	0.00765	1.3138
		T (°C)	0	5825.00720	5825	0.00720	1.2356
		T (°C)	10	5825.00669	5825	0.00669	1.1480
		T (°C)	20	5825.01023	5825	0.01023	1.7556
		T (°C)	30	5825.00908	5825	0.00908	1.5595
		T (°C)	40	5825.00383	5825	0.00383	0.6576
		T (°C)	50	5825.00033	5825	0.00033	0.0561
		T (°C)	60	5825.00850	5825	0.00850	1.4600
		T (°C)	70	5825.00753	5825	0.00753	1.2925
Limits				5725-5850 MHz			
Result				Complies			

CO.LTD

14. Duty Cycle Of Test Signal

14.1 Standard Requirement

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle. All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

14.2 Formula

Duty Cycle = $T_{on} / (T_{on} + T_{off})$

14.3 Test Procedure

1. Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak

14.4 Test Result

Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	a	5180	100	0	0
NVNT	a	5200	100	0	0
NVNT	a	5240	100	0	0
NVNT	n20	5180	100	0	0
NVNT	n20	5200	100	0	0
NVNT	n20	5240	100	0	0
NVNT	n40	5190	100	0	0
NVNT	n40	5230	100	0	0


15. Antenna Requirement

15.1 Limit

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.2 Test Result

The EUT antenna is internal antenna, fulfill the requirement of this section.



16. EUT Test Setup Photographs

Conducted emissions



C T
CT
PROV
port S

Radiated Measurement Photos



STATEMENT

1. The equipment lists are traceable to the national reference standards.
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC17025.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END *****

ang
CO., LTD