





## High Channel mode




802.11 g

## Low Channel mode






### Middle Channel mode




### High Channel mode






802.11 n20

Low Channel mode




Middle Channel mode





## High Channel mode





## 8 Band Edge Measurement

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement | : Section 15.247(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Test Method      | : ANSI C63.10:2013                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Test Limit       | : Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |


### 8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto  
Detector function = peak, Trace = max hold



## 8.2 Test Result

802.11b





802.11g





802.11n-H20





## 9 6dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013

Test Limit : Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 9.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

### 9.2 Test Result


| Modulation   | Bandwidth(MHz) |                |              | Limit   |
|--------------|----------------|----------------|--------------|---------|
|              | Low Channel    | Middle Channel | High Channel |         |
| 802.11b      | 7.576          | 7.126          | 7.106        | ≥500kHz |
| 802.11g      | 15.22          | 15.53          | 15.18        | ≥500kHz |
| 802.11n-HT20 | 15.16          | 15.99          | 15.21        | ≥500kHz |



### 802.11b Low Channel




### 802.11b Middle Channel






### 802.11b High Channel




### 802.11g Low Channel






### 802.11g Middle Channel




### 802.11g High Channel







### 802.11n-HT20 Low Channel



### 802.11n-HT20 Middle Channel





Agilent Spectrum Analyzer - Occupied BW

Center Freq 2.462000000 GHz

Center Freq 2.462000000 GHz  
 Trig: Free Run  
 #Atten: 30 dB

Radio Std: None  
 Radio Device: BTS

#IF Gain: 0.0w

Ref 20.00 dBm

Center 2.462 GHz  
 #Res BW 100 kHz

#VBW 300 kHz

Span 30 MHz  
 Sweep 2.933 ms

| Occupied Bandwidth | Total Power |
|--------------------|-------------|
| 17.430 MHz         | 17.4 dBm    |

| Transmit Freq Error | OBW Power |
|---------------------|-----------|
| 14.969 kHz          | 99.00 %   |

| x dB Bandwidth | x dB     |
|----------------|----------|
| 15.21 MHz      | -6.00 dB |



## 10 Maximum Peak Output Power

|                  |   |                                                                                                                                                                                                                                                                                             |
|------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement | : | FCC CFR47 Part 15 Section 15.247                                                                                                                                                                                                                                                            |
| Test Method      | : | ANSI C63.10:2013                                                                                                                                                                                                                                                                            |
| Test Limit       | : | Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. |

### 10.1 Test Procedure

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 D01 15.247 Meas Guidance v05 section 8.3.1.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 10.2 Test Result

| Modulation   | Maximum Peak Output Power (dBm) |                |              | Limit     |
|--------------|---------------------------------|----------------|--------------|-----------|
|              | Low Channel                     | Middle Channel | High Channel |           |
| 802.11b      | 14.23                           | 14.62          | 14.32        | 1W(30dBm) |
| 802.11g      | 13.45                           | 13.48          | 13.54        | 1W(30dBm) |
| 802.11n-HT20 | 13.52                           | 13.44          | 13.55        | 1W(30dBm) |



## 11 Power Spectral density

|                  |                                                                                                                                                                                                                                                                                                                                |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Requirement | : FCC CFR47 Part 15 Section 15.247                                                                                                                                                                                                                                                                                             |
| Test Method      | : ANSI C63.10:2013                                                                                                                                                                                                                                                                                                             |
| Test Limit       | : Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. |

### 11.1 Test Procedure


1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below:  
Center frequency=DTS channel center frequency  
Span = 1.5 times the DTS bandwidth  
RBW = 3KHz, VBW = 10KHz  
Sweep time = auto couple  
Detector = peak  
Trace mode =max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW(no less than 3KHz) and repeat.

### 11.2 Test Result


| Modulation   | Power Spectral density (dBm/3kHz) |                |              | Limit     |
|--------------|-----------------------------------|----------------|--------------|-----------|
|              | Low Channel                       | Middle Channel | High Channel |           |
| 802.11b      | -11.871                           | -12.28         | -11.485      | 8dBm/3kHz |
| 802.11g      | -13.895                           | -13.833        | -11.547      | 8dBm/3kHz |
| 802.11n-HT20 | -13.484                           | -14.451        | -13.255      | 8dBm/3kHz |



### 802.11b Low Channel




### 802.11b Middle Channel






### 802.11b High Channel




### 802.11g Low Channel






### 802.11g Middle Channel




### 802.11g High Channel






### 802.11n-HT20 Low Channel




### 802.11n-HT20 Middle Channel





### 802.11n-HT20 High Channel





## **12 Antenna Application**

### **12.1 Antenna Requirement**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **12.2 Result**


The EUT'S antenna, permanent attached antenna, is FPC antenna. The antenna's gain is 3dBi and meets the requirement.

## 13 Test Setup


Conducted Emissions



Radiated Spurious Emissions  
From 30MHz-1000MHz



Test frequency from Above 1GHz





Report No.: PTC22021800401E-FC01

## 14 EUT PHOTOS

Reference file External Photo and Internal Photo.

\*\*\*\*\*THE END REPORT\*\*\*\*\*