TEST REPORT

Product Name	:	Wireless Headphones
Brand Mark	:	TRUEFREE
Model No.	:	A1
Extension model	:	B1, C1, D1, E1, F1, G1, H1, J1, K1, T1
FCC ID	:	2A5BOHQY001
Report Number	:	BLA-EMC-202203-A0502
Date of Sample Receipt	:	2022/3/3
Date of Test	:	2022/3/3 to 2022/3/25
Date of Issue	:	2022/3/25
Test Standard	:	47 CFR Part 15, Subpart C 15.247
Test Result	:	Pass

Prepared for:

shenzhenshihanqiyuankejiyouxiangongsi
1309, block B, Huihai Plaza, Chuangye Road, Longhua street, Longhua District, Shenzhen, Guangdong, China
shenzhen guangdong China 518109

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: Review by:

Approved by: Date: 2022/3/25

REPORT REVISE RECORD

Version No.	Date	Description
00	2022/3/25	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY....5
2 GENERAL INFORMATION....6
3 GENERAL DESCRIPTION OF E.U.T....6
4 TEST ENVIRONMENT....7
5 TEST MODE....7
6 MEASUREMENT UNCERTAINTY....7
7 DESCRIPTION OF SUPPORT UNIT....8
8 LABORATORY LOCATION....8
9 TEST INSTRUMENTS LIST....9
10 ANTENNA REQUIREMENT....13
10.1 CONCLUSION....13
11 CONDUCTED SPURIOUS EMISSIONS....14
11.1 LIMITS....14
11.2 BLOCK DIAGRAM OF TEST SETUP....14
11.3 TEST DATA....15
12 20DB BANDWIDTH....16
12.1 BLOCK DIAGRAM OF TEST SETUP....16
12.2 TEST DATA....16
13 CONDUCTED PEAK OUTPUT POWER....17
13.1 LIMITS....17
13.2 BLOCK DIAGRAM OF TEST SETUP....17
13.3 TEST DATA....18
14 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)....19
14.1 LIMITS....19
14.2 BLOCK DIAGRAM OF TEST SETUP....19
14.3 PROCEDURE....19
14.4 TEST DATA....21
15 RADIATED SPURIOUS EMISSIONS....23
15.1 LIMITS....23

BlueAsia

15.2 BLOCK DIAGRAM OF TEST SETUP 24
15.3 PROCEDURE 24
15.4 TEST DATA 26

16 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 34

16.1 LIMITS 34
16.2 BLOCK DIAGRAM OF TEST SETUP 35
16.3 PROCEDURE 35
16.4 TEST DATA 37

17 CONDUCTED BAND EDGES MEASUREMENT 41

17.1 LIMITS 41
17.2 BLOCK DIAGRAM OF TEST SETUP 41
17.3 TEST DATA 42

18 DWELL TIME 43

18.1 LIMITS 43
18.2 BLOCK DIAGRAM OF TEST SETUP 43
18.3 TEST DATA 44

19 HOPPING CHANNEL NUMBER 45

19.1 LIMITS 45
19.2 BLOCK DIAGRAM OF TEST SETUP 45
19.3 TEST DATA 45

20 CARRIER FREQUENCIES SEPARATION 46

20.1 LIMITS 46
20.2 BLOCK DIAGRAM OF TEST SETUP 46
20.3 TEST DATA 46

21 APPENDIX 47

APPENDIX A: PHOTOGRAPHS OF TEST SETUP 94

APPENDIX B: PHOTOGRAPHS OF EUT 96

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
20dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.7	47 CFR Part 15, Subpart C 15.247(a)(1)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Dwell Time	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.4	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Hopping Channel Number	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.3	47 CFR Part 15, Subpart C 15.247a(1)(iii)	Pass
Carrier Frequencies Separation	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.2	47 CFR Part 15, Subpart C 15.247a(1)	Pass

BlueAsia

2 GENERAL INFORMATION

Applicant	shenzhenshihanqiyuankejiyouxiangongsi
Address	1309, block B, Huihai Plaza, Chuangye Road, Longhua street, Longhua District, Shenzhen, Guangdong, China shenzhen guangdong China 518109
Manufacturer	shenzhenshihanqiyuankejiyouxiangongsi
Address	1309, block B, Huihai Plaza, Chuangye Road, Longhua street, Longhua District, Shenzhen, Guangdong, China
Factory	Guangzhou U&I Technology Co.,Ltd
Address	Room 08,4th Floor,Building No.15,Vtrek Innovation industrial park,
Product Name	Wireless Headphones
Test Model No.	A1
Extension mode	B1, C1, D1, E1, F1, G1, H1, J1, K1, T1
Note	All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose.

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	N/A
Software Version	N/A

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, π/4 DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Chip Antenna
Antenna Gain:	4dBi(Provided by the applicant)

BlueAsia

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	3.7Vdc

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
Transmitting mode	Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE)
Remark: Full battery is used during all test except ac conducted emission, DH1,DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned only 8DPSK worse case is reported.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

BlueAsia

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

BlueAsia

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of 20dB Bandwidth					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Conducted Peak Output Power					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**

BlueAsia

Shield room	SKET	833	N/A	25/11/2020	24/11/2023
Receiver	R&S	ESPI3	101082	24/9/2021	23/9/2022
LISN	R&S	ENV216	3560.6550.15	24/9/2021	23/9/2022
LISN	AT	AT166-2	AKK1806000003	26/9/2021	25/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A

Test Equipment Of Radiated Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022
Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022

BlueAsia

broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022
Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Conducted Band Edges Measurement

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Dwell Time

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Hopping Channel Number

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022

BlueAsia

Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Carrier Frequencies Separation					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

BlueAsia

10 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

10.1 CONCLUSION

Standard Requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 4dBi.



11 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

11.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

12 20DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.7
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

12.1 BLOCK DIAGRAM OF TEST SETUP



12.2 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

13 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

13.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥50 hopping channels
	0.25 for 25≤ hopping channels <50
	1 for digital modulation
2400-2483.5	1 for ≥75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

13.2 BLOCK DIAGRAM OF TEST SETUP



BlueAsia

13.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

14 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	BT mode
Test Mode (Final Test)	BT mode
Tester	Jozu
Temperature	25℃
Humidity	60%

14.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 PROCEDURE

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

BlueAsia

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

14.4 TEST DATA

[TestMode: BT mode]; [Line: Line] ;[Power:AC120V/60Hz]



Site
Phase: *L1*
Temperature: (C)
Limit: FCC Class B Conduction(QP)
Power:
Humidity: %RH
EUT: Wireless Headphones
M/N: A1
Mode: TX mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.6140	21.01	9.87	30.88	56.00	-25.12	QP	
2	*	0.6140	14.77	9.87	24.64	46.00	-21.36	AVG	
3		2.8300	12.25	9.97	22.22	56.00	-33.78	QP	
4		2.8300	6.96	9.97	16.93	46.00	-29.07	AVG	
5		4.2819	11.24	9.92	21.16	56.00	-34.84	QP	
6		4.2819	6.56	9.92	16.48	46.00	-29.52	AVG	
7		6.5580	9.82	10.08	19.90	60.00	-40.10	QP	
8		6.5580	3.07	10.08	13.15	50.00	-36.85	AVG	
9		9.9940	21.14	0.23	21.37	60.00	-38.63	QP	
10		9.9940	16.96	0.23	17.19	50.00	-32.81	AVG	
11		13.0300	9.80	10.26	20.06	60.00	-39.94	QP	
12		13.0300	10.59	10.26	20.85	50.00	-29.15	AVG	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: BT mode]; [Line: Nutral] ;[Power:AC120V/60Hz]



Site
Phase: N
Temperature: (C)
Limit: FCC Class B Conduction(QP)
Power:
Humidity: %RH
EUT: Wireless Headphones
M/N: A1
Mode: TX mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.6140	19.76	9.80	29.56	56.00	-26.44	QP	
2	*	0.6140	13.50	9.80	23.30	46.00	-22.70	AVG	
3		2.7700	9.22	9.89	19.11	56.00	-36.89	QP	
4		2.7700	4.79	9.89	14.68	46.00	-31.32	AVG	
5		4.1740	7.98	9.92	17.90	56.00	-38.10	QP	
6		4.1740	2.30	9.92	12.22	46.00	-33.78	AVG	
7		5.3540	6.76	9.96	16.72	60.00	-43.28	QP	
8		5.3540	2.10	9.96	12.06	50.00	-37.94	AVG	
9		7.8140	3.84	10.06	13.90	60.00	-46.10	QP	
10		7.8140	-1.22	10.06	8.84	50.00	-41.16	AVG	
11		13.3580	8.07	10.27	18.34	60.00	-41.66	QP	
12		13.3580	4.00	10.27	14.27	50.00	-35.73	AVG	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

15 RADIATED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

15.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

15.2 BLOCK DIAGRAM OF TEST SETUP







15.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.

Remark:
1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

15.4 TEST DATA

[TestMode: TX below 1G]; [Polarity: Horizontal]

Test Lab: BlueAsia EMC Lab（RE #1）	Project: BLA-EMC-202203-A05
EUT: Wireless Headphones	Test Engineer: Charlie
M/N: A1	Temperature:
S/N:	Humidity:
Test Mode: TX mode	Test Voltage:
Note:	Test Data: 2022-03-23 15:42:56



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	39.336MHz	40.0	24.3	-15.7	0.3	24.0	QP	Hor	100.0	281.0
2*	57.888MHz	40.0	23.9	-16.1	0.3	23.6	QP	Hor	100.0	166.0
3*	101.295MHz	43.5	23.1	-20.4	2.3	20.8	QP	Hor	100.0	359.0
4*	133.184MHz	43.5	26.3	-17.2	2.9	23.4	QP	Hor	100.0	111.0
5*	283.655MHz	46.0	27.3	-18.7	3.6	23.7	QP	Hor	100.0	157.0
6*	526.519MHz	46.0	30.6	-15.4	1.4	29.2	QP	Hor	100.0	336.0

Test Result: Pass

[TestMode: TX below 1G]; [Polarity: Vertical]

Test Lab: BlueAsia EMC Lab（RE #1）	Project: BLA-EMC-202203-A05
EUT: Wireless Headphones	Test Engineer: Charlie
M/N: A1	Temperature:
S/N:	Humidity:
Test Mode: TX mode	Test Voltage:
Note:	Test Data: 2022-03-23 15:44:47



No.	Frequency	Limit dBuV/m	Level dBuV/m	Delta dB	Reading dBuV	Factor dB/m	Detector	Polar	Height cm	Angle deg
1*	58.736MHz	40.0	24.8	-15.2	1.3	23.5	QP	Ver	100.0	54.0
2*	145.915MHz	43.5	26.6	-16.9	3.0	23.6	QP	Ver	100.0	166.0
3*	280.260MHz	46.0	26.7	-19.3	3.1	23.6	QP	Ver	100.0	334.0
4*	412.786MHz	46.0	28.2	-17.8	0.8	27.4	QP	Ver	100.0	0.0
5*	493.296MHz	46.0	30.1	-15.9	1.8	28.3	QP	Ver	100.0	219.0
6*	749.376MHz	46.0	35.4	-10.6	2.3	33.1	QP	Ver	100.0	119.0

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Headphones
M/N: A1
Mode: TX-L
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		3820.000	42.72	7.41	50.13	74.00	-23.87	peak	
2		4804.000	40.15	3.71	43.86	74.00	-30.14	peak	
3		7206.000	39.95	5.96	45.91	74.00	-28.09	peak	
4		8285.000	40.92	8.24	49.16	74.00	-24.84	peak	
5		9608.000	38.60	9.29	47.89	74.00	-26.11	peak	
6	*	11387.000	39.13	11.78	50.91	74.00	-23.09	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Headphones
M/N: A1
Mode: TX-L
Note:

Polarization: *Vertical*
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		3679.000	42.28	7.73	50.01	74.00	-23.99	peak	
2		4804.000	40.46	3.71	44.17	74.00	-29.83	peak	
3		7206.000	40.53	5.96	46.49	74.00	-27.51	peak	
4		7791.500	42.49	7.68	50.17	74.00	-23.83	peak	
5		9608.000	39.23	9.29	48.52	74.00	-25.48	peak	
6	*	11340.000	39.52	11.85	51.37	74.00	-22.63	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Headphones
M/N: A1
Mode: TX-M
Note:

Polarization: *Vertical*
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		3702.500	42.39	7.72	50.11	74.00	-23.89	peak	
2		4882.000	40.90	3.36	44.26	74.00	-29.74	peak	
3		7323.000	39.66	6.43	46.09	74.00	-27.91	peak	
4		8308.500	41.26	8.25	49.51	74.00	-24.49	peak	
5		9764.000	39.05	9.63	48.68	74.00	-25.32	peak	
6	*	11340.000	39.78	11.85	51.63	74.00	-22.37	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Headphones
M/N: A1
Mode: TX-M
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		3655.500	42.01	7.76	49.77	74.00	-24.23	peak	
2		4882.000	40.40	3.36	43.76	74.00	-30.24	peak	
3		7323.000	39.13	6.43	45.56	74.00	-28.44	peak	
4		8261.500	41.02	8.23	49.25	74.00	-24.75	peak	
5		9764.000	37.94	9.63	47.57	74.00	-26.43	peak	
6	*	11340.000	39.27	11.85	51.12	74.00	-22.88	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Headphones
M/N: A1
Mode: TX-H
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		3561.500	43.86	6.50	50.36	74.00	-23.64	peak	
2		4960.000	40.20	3.75	43.95	74.00	-30.05	peak	
3		7440.000	39.01	6.86	45.87	74.00	-28.13	peak	
4		8144.000	40.61	8.13	48.74	74.00	-25.26	peak	
5		9920.000	37.52	10.16	47.68	74.00	-26.32	peak	
6	*	11222.500	39.08	12.01	51.09	74.00	-22.91	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Headphones
M/N: A1
Mode: TX-H
Note:

Polarization: *Vertical*
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		3632.000	42.41	7.77	50.18	74.00	-23.82	peak	
2		4960.000	40.13	3.75	43.88	74.00	-30.12	peak	
3		7440.000	39.42	6.86	46.28	74.00	-27.72	peak	
4		8026.500	41.09	7.98	49.07	74.00	-24.93	peak	
5		9920.000	37.06	10.16	47.22	74.00	-26.78	peak	
6	*	11434.000	39.37	11.81	51.18	74.00	-22.82	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

16 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

16.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

16.2 BLOCK DIAGRAM OF TEST SETUP







16.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.
Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

16.4 TEST DATA

[TestMode: TX low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Headphones
M/N: A1
Mode: TX-L
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2310.000	43.87	-3.93	39.94	74.00	-34.06	peak	
2	*	2390.000	43.72	-3.58	40.14	74.00	-33.86	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]



Site
Polarization: *Vertical*
Temperature: (C)
Limit: FCC Part15 (PK)
Power:
Humidity: %RH
EUT: Wireless Headphones
M/N: A1
Mode: TX-L
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2310.000	43.34	-3.93	39.41	74.00	-34.59	peak	
2	*	2390.000	46.90	-3.58	43.32	74.00	-30.68	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Headphones
M/N: A1
Mode: TX-H
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.500	47.66	-3.14	44.52	74.00	-29.48	peak	
2		2500.000	43.36	-3.08	40.28	74.00	-33.72	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: Wireless Headphones
M/N: A1
Mode: TX-H
Note:

Polarization: *Vertical*
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.500	45.60	-3.14	42.46	74.00	-31.54	peak	
2		2500.000	43.86	-3.08	40.78	74.00	-33.22	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

17 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

17.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

18 DWELL TIME

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.4
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

18.1 LIMITS

Frequency(MHz)	Limit
902-928	0.4S within a 20S period(20dB bandwidth<250kHz)
	0.4S within a 10S period(20dB bandwidth≥250kHz)
2400-2483.5	0.4S within a period of 0.4S multiplied by the number of hopping channels
5725-5850	0.4S within a 30S period

18.2 BLOCK DIAGRAM OF TEST SETUP



BlueAsia

18.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

19 HOPPING CHANNEL NUMBER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.3
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

19.1 LIMITS

Frequency range(MHz)	Number of hopping channels (minimum)
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

19.2 BLOCK DIAGRAM OF TEST SETUP



19.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

20 CARRIER FREQUENCIES SEPARATION

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	60%

20.1 LIMITS

Limit:	2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

20.2 BLOCK DIAGRAM OF TEST SETUP



20.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

21 APPENDIX

Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	1-DH1	2402	Ant1	1.726	21	Pass
NVNT	1-DH1	2441	Ant1	1.011	21	Pass
NVNT	1-DH1	2480	Ant1	2.496	21	Pass
NVNT	2-DH1	2402	Ant1	1.63	21	Pass
NVNT	2-DH1	2441	Ant1	0.984	21	Pass
NVNT	2-DH1	2480	Ant1	2.479	21	Pass
NVNT	3-DH1	2402	Ant1	1.734	21	Pass
NVNT	3-DH1	2441	Ant1	1.076	21	Pass
NVNT	3-DH1	2480	Ant1	2.534	21	Pass

Power NVNT 1-DH1 2402MHz Ant1



Power NVNT 1-DH1 2441MHz Ant1



Power NVNT 1-DH1 2480MHz Ant1



Power NVNT 2-DH1 2402MHz Ant1



Power NVNT 2-DH1 2441MHz Ant1



Power NVNT 2-DH1 2480MHz Ant1



Power NVNT 3-DH1 2402MHz Ant1



Power NVNT 3-DH1 2441MHz Ant1



Power NVNT 3-DH1 2480MHz Ant1



-20dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-20 dB Bandwidth (MHz)	Limit -20 dB Bandwidth (MHz)	Verdict
NVNT	1-DH1	2402	Ant1	0.869	0	Pass
NVNT	1-DH1	2441	Ant1	0.934	0	Pass
NVNT	1-DH1	2480	Ant1	0.941	0	Pass
NVNT	2-DH1	2402	Ant1	1.202	0	Pass
NVNT	2-DH1	2441	Ant1	1.16	0	Pass
NVNT	2-DH1	2480	Ant1	1.193	0	Pass
NVNT	3-DH1	2402	Ant1	1.205	0	Pass
NVNT	3-DH1	2441	Ant1	1.207	0	Pass
NVNT	3-DH1	2480	Ant1	1.207	0	Pass

-20dB Bandwidth NVNT 1-DH1 2402MHz Ant1

-20dB Bandwidth NVNT 1-DH1 2441MHz Ant1

-20dB Bandwidth NVNT 1-DH1 2480MHz Ant1

-20dB Bandwidth NVNT 2-DH1 2402MHz Ant1



-20dB Bandwidth NVNT 2-DH1 2441MHz Ant1

-20dB Bandwidth NVNT 2-DH1 2480MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2402MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2441MHz Ant1



-20dB Bandwidth NVNT 3-DH1 2480MHz Ant1



Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	1-DH1	2402	Ant1	0.8325921286
NVNT	1-DH1	2441	Ant1	0.8666440875
NVNT	1-DH1	2480	Ant1	0.8210699855
NVNT	2-DH1	2402	Ant1	1.11806854
NVNT	2-DH1	2441	Ant1	1.116009984
NVNT	2-DH1	2480	Ant1	1.130839561
NVNT	3-DH1	2402	Ant1	1.122847024
NVNT	3-DH1	2441	Ant1	1.110749028
NVNT	3-DH1	2480	Ant1	1.117482374

OBW NVNT 1-DH1 2402MHz Ant1

OBW NVNT 1-DH1 2441MHz Ant1



OBW NVNT 1-DH1 2480MHz Ant1



OBW NVNT 2-DH1 2402MHz Ant1



OBW NVNT 2-DH1 2441MHz Ant1



OBW NVNT 2-DH1 2480MHz Ant1



OBW NVNT 3-DH1 2402MHz Ant1



OBW NVNT 3-DH1 2441MHz Ant1



OBW NVNT 3-DH1 2480MHz Ant1

Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	No-Hopping	-56.69	-20	Pass
NVNT	1-DH1	2480	Ant1	No-Hopping	-57.64	-20	Pass
NVNT	2-DH1	2402	Ant1	No-Hopping	-56.93	-20	Pass
NVNT	2-DH1	2480	Ant1	No-Hopping	-57.39	-20	Pass
NVNT	3-DH1	2402	Ant1	No-Hopping	-57.82	-20	Pass
NVNT	3-DH1	2480	Ant1	No-Hopping	-58.08	-20	Pass

Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Ref

Band Edge NVNT 1-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Ref

Band Edge NVNT 1-DH1 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Ref

Band Edge NVNT 2-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Ref

Band Edge NVNT 2-DH1 2480MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Ref

Band Edge NVNT 3-DH1 2402MHz Ant1 No-Hopping Emission



Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Ref

Band Edge NVNT 3-DH1 2480MHz Ant1 No-Hopping Emission


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.526000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 100/100
10:19:55 AM Mar 23, 2022
Ref Offset 2.08 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.480 2 GHz
2.181 dBm
Start 2.47600 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.57600 GHz
Sweep 9.600 ms (1001 pts)
1 N 1 f 2.480 2 GHz 2.181 dBm
2 N 1 f 2.483 5 GHz -56.040 dBm
3 N 1 f 2.500 0 GHz -58.196 dBm
4 N 1 f 2.483 5 GHz -56.040 dBm

BlueAsia

Band Edge(Hopping)

Condition	Mode	Frequency (MHz)	Antenna	Hopping Mode	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	Hopping	-56.04	-20	Pass
NVNT	1-DH1	2480	Ant1	Hopping	-56.19	-20	Pass
NVNT	2-DH1	2402	Ant1	Hopping	-56.47	-20	Pass
NVNT	2-DH1	2480	Ant1	Hopping	-55.72	-20	Pass
NVNT	3-DH1	2402	Ant1	Hopping	-56.75	-20	Pass
NVNT	3-DH1	2480	Ant1	Hopping	-56.93	-20	Pass

Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 1-DH1 2480MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 2-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 2-DH1 2480MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 3-DH1 2402MHz Ant1 Hopping Emission



Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Ref

Band Edge(Hopping) NVNT 3-DH1 2480MHz Ant1 Hopping Emission


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.526000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 2000/2000
10:27:07 AM Mar 23, 2022
Ref Offset 2.08 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.478 8 GHz
1.482 dBm
-17.87 dBm
Start 2.47600 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.57600 GHz
Sweep 9.600 ms (1001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.478 8 GHz 1.482 dBm
2 N 1 f 2.483 5 GHz -57.480 dBm
3 N 1 f 2.500 0 GHz -55.858 dBm
4 N 1 f 2.494 9 GHz -54.809 dBm
MSG
STATUS

BlueAsia

Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	1-DH1	2402	Ant1	-46.41	-20	Pass
NVNT	1-DH1	2441	Ant1	-46.29	-20	Pass
NVNT	1-DH1	2480	Ant1	-47.27	-20	Pass
NVNT	2-DH1	2402	Ant1	-47.02	-20	Pass
NVNT	2-DH1	2441	Ant1	-46.35	-20	Pass
NVNT	2-DH1	2480	Ant1	-47.65	-20	Pass
NVNT	3-DH1	2402	Ant1	-46.43	-20	Pass
NVNT	3-DH1	2441	Ant1	-46.48	-20	Pass
NVNT	3-DH1	2480	Ant1	-48.05	-20	Pass

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Ref

Tx. Spurious NVNT 1-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Ref

Tx. Spurious NVNT 1-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Ref

Tx. Spurious NVNT 1-DH1 2480MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Ref

Tx. Spurious NVNT 2-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Ref

Tx. Spurious NVNT 2-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Ref

Tx. Spurious NVNT 2-DH1 2480MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Ref

Tx. Spurious NVNT 3-DH1 2402MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Ref

Tx. Spurious NVNT 3-DH1 2441MHz Ant1 Emission



Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Ref

Tx. Spurious NVNT 3-DH1 2480MHz Ant1 Emission


Agilent Spectrum Analyzer - Swept SA
Center Freq 13.265000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 10/10
10:20:33 AM Mar 23, 2022
Ref Offset 2.08 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.480 2 GHz
0.481 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 26.50 GHz
Sweep 2.530 s (30001 pts)
1 N 1 f 2.480 2 GHz 0.481 dBm
2 N 1 f 26.350 0 GHz -45.890 dBm
3 N 1 f 4.959 6 GHz -55.487 dBm
4 N 1 f 7.415 1 GHz -56.158 dBm
5 N 1 f 10.039 2 GHz -55.522 dBm

BlueAsia

Carrier Frequencies Separation

Condition	Mode	Antenna	Hopping Freq1 (MHz)	Hopping Freq2 (MHz)	HFS (MHz)	Limit (MHz)	Verdict
NVNT	1-DH1	Ant1	2440.987	2441.983	0.996	0.934	Pass
NVNT	2-DH1	Ant1	2441.0035	2441.845	0.8415	0.773	Pass
NVNT	3-DH1	Ant1	2440.8355	2441.959	1.1235	0.805	Pass

CFS NVNT 1-DH1 2441MHz Ant1

CFS NVNT 2-DH1 2441MHz Ant1

CFS NVNT 3-DH1 2441MHz Ant1



Number of Hopping Channel

Condition	Mode	Antenna	Hopping Number	Limit	Verdict
NVNT	1-DH1	Ant1	79	15	Pass
NVNT	2-DH1	Ant1	79	15	Pass
NVNT	3-DH1	Ant1	79	15	Pass

Hopping No. NVNT 1-DH1 2441MHz Ant1

Hopping No. NVNT 2-DH1 2441MHz Ant1

Hopping No. NVNT 3-DH1 2441MHz Ant1

Dwell Time

Condition	Mode	Frequency (MHz)	Antenna	Pulse Time (ms)	Total Dwell Time (ms)	Burst Count	Period Time (ms)	Limit (ms)	Verdict
NVNT	1-DH1	2441	Ant1	0.373	118.987	319	31600	400	Pass
NVNT	1-DH3	2441	Ant1	1.62	259.2	160	31600	400	Pass
NVNT	1-DH5	2441	Ant1	2.869	306.983	107	31600	400	Pass

Dwell NVNT 1-DH1 2441MHz Ant1 One Burst



Dwell NVNT 1-DH1 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH3 2441MHz Ant1 One Burst



Dwell NVNT 1-DH3 2441MHz Ant1 Accumulated



Dwell NVNT 1-DH5 2441MHz Ant1 One Burst



Dwell NVNT 1-DH5 2441MHz Ant1 Accumulated


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.441000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
10:29:32 AM Mar 23, 2022
Ref Offset 2.03 dB
10 dB/div
Ref 20.00 dBm
Log
Center 2.441000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 31.60 s (10001 pts)

BlueAsia

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Radiated Spurious Emissions



Conducted Emissions at AC Power Line (150kHz-30MHz)



BlueAsia

APPENDIX B: PHOTOGRAPHS OF EUT

Reference to the test report No. BLA-EMC-202203-A0501

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia