



RF TEST REPORT

Report No.: SHATBL2508013W03

Applicant : SHENZHEN NANXIN TECHNOLOGY CO.,LTD

Product Name : Smart Star Projector with HD Films

Brand Name : N/A

Model Name : SK17

Series model : SK11,SK13,SK15,SK19,SK20,SK21,SK22,SK23,SK25,SK26,
SK27,SK28,SK29,SK30,SK31,SK33,SK35,SK36,SK37,SK39,
SC01,SC03,SC05,SC07,SC09,JS11,JS13,JS15,JS17,JS19,
SF01,SF02,SF03,SF05,SF07,SF09,FS01,FS03,FS05,FS07,
FS09,SP01,SP03,SP05,SP07,SP09,WS31,WS33,WS35,WS37,
WS39,TC01,TC03,TC05,TC7X,TR01,TR03,TR05,TR07,TR0X

Test Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247

FCC ID : 2A5ET-SK17

Date of Sample Arrival : May.22,2025

Date of Test : May.22,2025~Jul.31,2025

Date of Issue : Nov.19,2025

Report Prepared by :

Chris Xu

(Chris Xu)

Report Approved by :

Guozheng Li

(Guozheng Li)

Authorized Signatory :

Terry Yang

(Terry Yang)



"Shanghai ATBL Technology Co., Ltd." hereby certifies that according to actual testing conditions. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards, or regulations, ATBL shall not assume any responsibility. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material. This report will be void without authorized signature or special seal for testing report. Do not copied without authorization.

Tel: +86(0)21-51298625

Web: www.atbl-lab.com

Email: atbl@atbl-lab.com

TABLE OF CONTENTS

REVISION HISTORY	3
DECLARATION OF REPORT	4
SUMMARY OF TEST RESULT	5
1. GENERAL DESCRIPTION	6
1.1. Applicant	6
1.2. Manufacturer	6
1.3. Factory	6
1.4. General Information of EUT	7
1.5. Equipment Specification	8
1.6. Modification of EUT	9
1.7. Laboratory Information	9
1.8. Applicable Standards	9
2. TEST CONFIGURATION OF EUT	10
2.1. Carrier Frequency Channel	10
2.2. Test Modes	10
2.3. Block Diagram of Test System	11
2.4. Description of Support Units	11
2.5. Test Software and Power Level	11
2.6. EUT Operating Conditions	11
2.7. Equipment List	12
2.8. Measurement Uncertainty	14
3. TEST RESULT	15
3.1. Maximum conducted output power	15
3.2. Duty Cycle	16
3.3. 6dB Bandwidth and 99% Bandwidth	17
3.4. Power Spectral Density	19
3.5. Conducted Band Edge	20
3.6. Conducted Spurious Emission	21
3.7. Radiated Spurious Emission and Restricted Band	22
3.8. AC Power-Line Conducted Emission	60
3.9. Antenna Requirement	63
4. Test Setup Photographs	64
5. External And internal Photographs of The EUT	64
Appendix A of data	65
A1.Maximum Peak Conducted output power	65
A2.Duty Cycle	66
A3.6dB Bandwidth	68
A4.Power Spectral Density	70
A5.Conducted Band Edge and Conducted Spurious Emission	73

REVISION HISTORY

Rev.	Issue Date	Revisions	Revised by
00	Nov.19,2025	Initial Release	Ghost Li

DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR 15.247. And it is applicable only to the tested sample identified in the report.
2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.
3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.
4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.
5. In this report, '☐' indicates that EUT does not support content after '☐', and '☑' indicates that it supports content after '☑'

SUMMARY OF TEST RESULT

Report Section	Standard Section	Test Item	Judgment	Remark
3.1	47 CFR 15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	--
3.2	--	Duty Cycle	Report only	--
3.3	47 CFR 15.247(a)(2)	6dB Bandwidth	PASS	--
	--	99% Bandwidth	Report only	--
3.4	47 CFR 15.247(e)	Power Spectral Density	PASS	--
3.5	47 CFR 15.247(d)	Conducted Band Edge	PASS	--
3.6	47 CFR 15.247(d)	Conducted Spurious Emission	PASS	--
3.7	47 CFR 15.247(d)/15.209(a)/15.205(a)	Radiated Spurious Emission and Restricted Band	PASS	--
3.8	47 CFR 15.207(a)	AC Power-Line Conducted Emission	PASS	--
3.9	47 CFR 15.203	Antenna Requirements	PASS	--

1. GENERAL DESCRIPTION

1.1. Applicant

Name : SHENZHEN NANXIN TECHNOLOGY CO.,LTD

Address : 2nd floor, building A, Jiantao Science Park, Longhua District, Shenzhen, China

1.2. Manufacturer

Name : Jiangxi Lepowerlink Technology Co., Ltd

Address : On the north side of the third floor and the entire fourth floor of the Lithium Battery industrial Park factory area, Hengliu Road, Qianping Industrial Zone, Le an Industrial Park, Le an County, Fuzhou City, Jiangxi Province

1.3. Factory

Name : Jiangxi Lepowerlink Technology Co., Ltd

Address : On the north side of the third floor and the entire fourth floor of the Lithium Battery industrial Park factory area, Hengliu Road, Qianping Industrial Zone, Le an Industrial Park, Le an County, Fuzhou City, Jiangxi Province

1.4. General Information of EUT

General Information	
Equipment Name	Smart Star Projector with HD Films
Brand Name	N/A
Model Name	SK17
Series Model	SK11,SK13,SK15,SK19,SK20,SK21,SK22,SK23,SK25,SK26,SK27,SK28,SK29,SK30,SK31,SK33,SK35,SK36,SK37,SK39,SC01,SC03,SC05,SC07,SC09,JS11,JS13,JS15,JS17,JS19,SF01,SF02,SF03,SF05,SF07,SF09,FS01,FS03,FS05,FS07,FS09,SP01,SP03,SP05,SP07,SP09,WS31,WS33,WS35,WS37,WS39,TC01,TC03,TC05,TC7X,TR01,TR03,TR05,TR07,TR0X
Model Difference	The model name and appearance color are different.
Antenna Type	PCB Antenna
Antenna Gain	2.21dBi
Sample No:	2025005210016002
Power supply	Input:DC 5V
Hardware version	SK37 V2.2
Software version	1.0.8
Connecting I/O Port(s)	Refer to the remark below.

Remark:

The above information of EUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.5. Equipment Specification

Equipment Specification			
Frequency Range	2412MHz - 2462MHz		
Maximum Output Power To Antenna	☒ 802.11b:	15.975dBm	
	☒ 802.11g:	13.012dBm	
	☒ 802.11n(HT)20:	12.907dBm	
	☒ 802.11n(HT)40:	12.067dBm	
Type of Modulation	☒ 802.11b: DSSS (DBPSK/DQPSK/CCK)		
	☒ 802.11g/n(HT): OFDM (BPSK/QPSK/16QAM/64QAM)		
	☐ 802.11ax(HE): OFDM (BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM)		
Antenna Information	☒ SISO	Antenna Type:	PCB Antenna
		Antenna 0 Gain:	2.21dBi

1.6. Modification of EUT

No modifications are made to the EUT during all test items.

1.7. Laboratory Information

Company Name	:	Shanghai ATBL Technology Co., Ltd.
Address	:	Building 8, No.160 Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone	:	+86(0)21-51298625
FCC-Registration Number:	:	485917
Designation Number:	:	CN1306
A2LA-Lab Cert. No.:	:	6184.01

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

47 CFR Part 15 Subpart C §15.247

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2020

Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.

2. TEST CONFIGURATION OF EUT

2.1. Carrier Frequency Channel

Frequency Band	Channel	Frequency MHz	Channel	Frequency MHz
2412 - 2462 MHz	01	2412	07	2442
	02	2417	08	2447
	03	2422	09	2452
	04	2427	10	2457
	05	2432	11	2462
	06	2437		

Remark:

1. For 20 MHz Bandwidth: Low Channel: **CH 01_2412 MHz**; Middle Channel: **CH 06_2437 MHz**; High Channel: **CH 11_2462 MHz**. For 40 MHz Bandwidth: Low Channel: **CH 03_2422 MHz**; Middle Channel: **CH 06_2437 MHz**; High Channel: **CH 09_2452 MHz**.

2.2. Test Modes

Final test modes are considering the modulation and worse data rates as below table.


Summary Table of Test Modes			
Test Item	Mode	Data Rate	Channel
For Conducted and Radiated Test	☒ 802.11b:	1 Mbps	Low, Middle, High
	☒ 802.11g:	6 Mbps	Low, Middle, High
	☒ 802.11n(HT)20:	MCS 0	Low, Middle, High
	☒ 802.11n(HT)40:	MCS 0	Low, Middle, High
	☐ 802.11ac(VHT)20:	MCS 0	Low, Middle, High
	☐ 802.11ac(VHT)40:	MCS 0	Low, Middle, High
	☐ 802.11ax(HE)20:	MCS 0	Low, Middle, High
	☐ 802.11ax(HE)40:	MCS 0	Low, Middle, High
For AC Power-line Conducted Emission	802.11b: Low Channel		

Remark:


1.All the test modes of Radiated Spurious Emission (RSE) were tested at the worst data rate; only the worse data shown in report.

2.3. Block Diagram of Test System

2.3.1. For AC Power-Line Conducted Emission



2.3.2. For Radiated Spurious Emission



2.3.3. For Conducted Test



2.4. Description of Support Units

NO.	Unit	Brand	Model	Description
1	USB Line	ZL	24AWG	N/A
2	PC	Redmi G	2021Ryzen	N/A

2.5. Test Software and Power Level

During the test, the channel and power control software provided by the customer is used to control the operation channel and output power level.

2.6. EUT Operating Conditions

For AC power-line conducted emission, the EUT was connected under the large package sizes transmission.

For radiated spurious emission and conducted test, the engineering test program was provided and make the EUT to continuous transmit/receive.

2.7. Equipment List

2.7.1. For AC Power-Line Conducted Emission

Equipment Name	Manufacturer	Model	Serial No.	Equipment No.	Calibration Date	Calibration Until
Test Receiver	R&S	ESPI	101679	SHATBL-E012	2025.05.20	2026.05.19
LISN	R&S	ENV216	100300	SHATBL-E013	2025.05.20	2026.05.19
LISN	R&S	ENV216	100333	SHATBL-E041	2025.05.20	2026.05.19
Thermometer	DeLi	N/A	N/A	SHATBL-E016	2024.09.22	2025.09.21
Test Software	FALA	EZ-EMC	N/A	SHATBL-E046	N/A	N/A

2.7.2. For Radiated Spurious Emission

Equipment Name	Manufacturer	Model	Serial No.	Equipment No.	Calibration Date	Calibration Until
Signal analyzer	Agilent	N9020A	MY5020081 1	SHATBL-E017	2025.05.20	2026.05.19
Amplifier	JPT	JPA0118-55-303A	1910001800 055000	SHATBL-E006	2025.05.20	2026.05.19
Amplifier	JPT	JPA-10M1G3 2	2101010003 5001	SHATBL-E005	2025.05.20	2026.05.19
Antenna/Turn table Controller	Brilliant	N/A	N/A	SHATBL-E007	N/A	N/A
Loop Antenna	Daze	ZN30900C	20077	SHATBL-E042	2025.05.20	2026.05.19
Bilog Antenna	SCHWARZBECK	VULB 9168	01174	SHATBL-E008	2025.05.20	2026.05.19
Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120D	02334	SHATBL-E009	2025.05.20	2026.05.19
Horn Antenna	COM-POWER	AH-1840	10100008	SHATBL-E043	2025.05.20	2026.05.19
Thermometer	DeLi	N/A	N/A	SHATBL-E015	2024.09.22	2025.09.21
Test Software	FALA	EMC-RI	N/A	SHATBL-E046	N/A	N/A

2.7.3. For Conducted Test

Equipment Name	Manufacturer	Model	Serial No.	Equipment No.	Calibration Date	Calibration Until
Power meter	Anritsu	ML2496A	1935001	SHATBL-W030	2024.09.29	2025.09.28
Power sensor	Anritsu	MA2411B	1911006	SHATBL-W031	2024.09.29	2025.09.28
Power sensor	DARE	RPR3006W	16I00054SN016	SHATBL-W008	2024.09.29	2025.09.28
Power sensor	DARE	RPR3006W	RPR6W-2001005	SHATBL-W032	2024.09.29	2025.09.28
Power sensor	Rediteq	RPR3006W	RPR6W-2201002	SHATBL-W033	2024.11.15	2025.11.14
Power sensor	Rediteq	RPR3006W	RPR6W-2201003	SHATBL-W034	2024.11.15	2025.11.14
Power sensor	Keysight	U2021XA	MY59120004	SHATBL-W035	2024.08.14	2025.08.13
Adjustable Attenuator	Agilent	8494B	MY42144015	SHATBL-W009	2024.09.29	2025.09.28
Adjustable Attenuator	Agilent	8496B	MY42143776	SHATBL-W010	2024.09.29	2025.09.28
Environmental Test Chamber	KSON	THS-B6C-150	9159K	SHATBL-W019	2024.09.29	2025.09.28
Signal analyzer	Keysight	N9020A	MY50510136	SHATBL-W003	2024.09.29	2025.09.28
Vector signal generator	Keysight	N5182B	MY57300196	SHATBL-W005	2024.09.29	2025.09.28
Vector signal generator	Agilent	N5182A	MY50143555	SHATBL-W037	2025.07.16	2026.07.15
Analog signal generator	Keysight	N5173B	MY60403026	SHATBL-W038	2025.07.16	2026.07.15
Wideband radio communication tester	R&S	CMW500	101331	SHATBL-W007	2024.09.29	2025.09.28
Spectrum analyzer	R&S	FSV40-N	101761	SHATBL-W036	2024.08.23	2025.08.22
Switch Box	N/A	RFSW3003328	RFSW201019	SHATBL-W029	N/A	N/A
Thermometer	DeLi	N/A	N/A	SHATBL-W012	2024.09.22	2025.09.21
Test Software	FALA	LZ-RF	N/A	SHATBL-W020	N/A	N/A

Remark:

Calibration duration for above equipments is 1 year.

2.8. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	RF output power, conducted	$\pm 0.958\text{dB}$
2	Conducted spurious emissions	$\pm 2.988\text{dB}$
3	All emissions, radiated 9KHz-30MHz	$\pm 0.96\text{dB}$
4	All emissions, radiated 30MHz-1GHz	$\pm 2.50\text{dB}$
5	All emissions, radiated 1GHz-18GHz	$\pm 3.51\text{dB}$
6	Occupied bandwidth	$\pm 23.20\text{Hz}$
7	Power spectral density	$\pm 0.886\text{dB}$

3. TEST RESULT

3.1. Maximum conducted output power

3.1.1. Limit

47 CFR 15.247(b)(3): For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

47 CFR 15.247(b)(4): If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


47 CFR 15.247(c)(1)(i): Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.1.2. Test Procedure

ANSI C63.10-2020 clause 11.9.1.2 Method Peak:

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast responding diode detector.

3.1.3. Test Setup



3.1.4. Test Result of Maximum Conducted Output Power

Please refer to the Appendix A1.

3.2. Duty Cycle

3.2.1. Limit

There is no limit requirement for Duty Cycle.


3.2.2. Test Procedure

ANSI C63.10-2020 clause 11.6: Measurements of duty cycle and transmission duration shall be performed using one of the following techniques:

1. A diode detector and an oscilloscope that together have a sufficiently short response time to permit accurate measurements of the ON and OFF times of the transmitted signal.
2. The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the ON and OFF times of the transmitted signal:

- ① Set the center frequency of the instrument to the center frequency of the transmission.
- ② Set $RBW \geq OBW$ if possible; otherwise, set RBW to the largest available value.
- ③ Set $VBW \geq RBW$. Set detector = peak or average.
- ④ The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$ and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring the duty cycle shall not be used if $T \leq 16.7 \mu s$.)

3.2.3. Test Setup



3.2.4. Test Result of Duty Cycle

Please refer to the Appendix A2.

3.3. 6dB Bandwidth and 99% Bandwidth

3.3.1. Limit

47 CFR 15.247(a)(2): Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

There is no limit requirement for 99% Bandwidth.

3.3.2. Test Procedure

1. The testing of 6dB Bandwidth follows ANSI C63.10-2020 clause 11.8.1: The steps for the first option are as follows:

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

2. The testing of 99% Bandwidth follows ANSI C63.10-2020 clause 6.9.3: The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. The following procedure shall be used for measuring 99% power bandwidth:


- ① The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- ② The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW, unless otherwise specified by the applicable requirement.
- ③ Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level. Specific guidance is given in ANSI C63.10-2020 clause 4.1.5.2.
- ④ Step a) through step c) might require iteration to adjust within the specified range.
- ⑤ Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.

⑥ Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.

⑦ If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.

⑧ The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

3.3.3. Test Setup



3.3.4. Test Result of 6dB Bandwidth and 99% Bandwidth

Please refer to the Appendix A3.

3.4. Power Spectral Density


3.4.1. Limit

47 CFR 15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.4.2. Test Procedure

- 1.Set analyzer center frequency to DTS channel center frequency.
- 2.Set the span to 1.5 times the DTS bandwidth.
- 3.Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- 4.Set the VBW $\geq [3 \times \text{RBW}]$.
- 5.Detector = peak.
- 6.Sweep time = auto couple.
- 7.Trace mode = max hold.
- 8.Allow trace to fully stabilize.
- 9.Use the peak marker function to determine the maximum amplitude level within the RBW.
- 10.If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

3.4.3. Test Setup



3.4.4. Test Result of Power Spectral Density

Please refer to the Appendix A4.

3.5. Conducted Band Edge


3.5.1. Limit

47 CFR 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

3.5.2. Test Procedure

1. The testing follows ANSI C63.10-2020 clause 11.13.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100 kHz, VBW=300 kHz, RMS Detector. Conducted Band Edge measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the 100 kHz bandwidth within the band that contains the highest level of the desired power when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
4. Measure and record the results in the test report.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.5.3. Test Setup



3.5.4. Test Result of Conducted Band Edge

Please refer to the Appendix A5.

3.6. Conducted Spurious Emission


3.6.1. Limit

47 CFR 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

3.6.2. Test Procedure

1. The testing follows ANSI C63.10-2020 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 30 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.6.3. Test Setup



3.6.4. Test Result of Conducted Spurious Emission

Please refer to the Appendix A5.

3.7. Radiated Spurious Emission and Restricted Band

3.7.1. Limit

47 CFR 15.247(d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

47 CFR 15.205(a): Only spurious emissions are permitted in any of the frequency bands listed below:

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)
0.090-0.110	12.29-12.293	149.9-150.05	1660-1710	8.025-8.5
0.495-0.505	12.51975-12.52025	156.52475-156.52525	1718.8-1722.2	9.0-9.2
2.1735-2.1905	12.57675-12.57725	156.7-156.9	2200-2300	9.3-9.5
4.125-4.128	13.36-13.41	162.0125-167.17	2310-2390	10.6-12.7
4.17725-4.17775	16.42-16.423	167.72-173.2	2483.5-2500	13.25-13.4
4.20725-4.20775	16.69475-16.69525	240-285	2690-2900	14.47-14.5
6.215-6.218	16.80425-16.80475	322-335.4	3260-3267	15.35-16.2
6.26775-6.26825	25.5-25.67	399.9-410	3332-3339	17.7-21.4
6.31175-6.31225	37.5-38.25	608-614	3345.8-3358	22.01-23.12
8.291-8.294	73-74.6	960-1240	3600-4400	23.6-24.0
8.362-8.366	74.8-75.2	1300-1427	4500-5150	31.2-31.8
8.37625-8.38675	108-121.94	1435-1626.5	5350-5460	36.43-36.5
8.41425-8.41475	123-138	1645.5-1646.5	7250-7750	Above 38.6

47 CFR 15.209(a): The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

3.7.2. Test Procedure


1. The testing follows ANSI C63.10-2020 clause 11.11 & 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Pre-amp Factor = Level.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - ① Span shall wide enough to fully capture the emission being measured;
 - ② When frequency < 1 GHz:
 - Set RBW=100 kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - ③ When frequency $\geq$ 1 GHz:
 - Set RBW = 1 MHz; VBW = 3 MHz for peak measurement;
 - Set RBW = 1 MHz; VBW = 10 Hz, when duty cycle is no less than 98 percent or VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.7.3. Test Setup


3.7.3.1. For radiated emissions below 30MHz



3.7.3.2. For radiated emissions from 30MHz to 1GHz



3.7.3.3. For radiated emissions above 1GHz



3.7.4. Test Result of Radiated Spurious Emission

For 9 kHz ~ 30 MHz

Note:

1.The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Below 1GHz:

Note:

1.All modes have been tested, only worst case (802.11b-2412MHz) mode was recorded in the test report.

2.Emission Level (dBuV/m) = Reading Value (dBuV) + Correction Factor (dB/m).


3.Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)-Amplifier Gain.

4.The emission levels of other frequencies were less than 20dB margin against the limit.

5.Margin value = Emission level-Limit value.

802.11b_ 2412MHz


Horizontal _ 30MHz-1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	71.8320	58.12	-31.71	26.41	40.00	-13.59	peak	
2	83.8156	60.08	-34.85	25.23	40.00	-14.77	peak	
3	119.8556	70.64	-32.00	38.64	43.50	-4.86	peak	
4	143.8295	64.90	-29.37	35.53	43.50	-7.97	peak	
5	239.9874	63.47	-30.71	32.76	46.00	-13.24	peak	
6	432.5457	54.11	-25.00	29.11	46.00	-16.89	peak	

802.11b_ 2412MHz

Vertical _ 30MHz-1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	37.9450	57.40	-29.52	27.88	40.00	-12.12	peak	
2	72.0843	53.59	-31.77	21.82	40.00	-18.18	peak	
3	107.8877	55.68	-32.48	23.20	43.50	-20.30	peak	
4	119.8556	70.83	-32.00	38.83	43.50	-4.67	peak	
5	239.9874	67.60	-30.71	36.89	46.00	-9.11	peak	
6	360.4476	48.64	-27.29	21.35	46.00	-24.65	peak	

Above 1GHz:

Note:

- 1.The worst test data above 1GHz is the 802.11b/g/n is the Low Channel and High Channel mode test data was recorded in the test report.
- 2.In frequency ranges 18 ~25GHz no any other harmonic emissions detected which are tested to compliance with the limit. No recording in the test report. No any other emissions level which are attenuated less than 20dB below the limit. No recording in the test report.
- 3.We used the filter to test and the main frequency was filtered out.
- 4.Emission Level (dBuV/m) = Reading Value (dBuV) + Correction Factor (dB/m).
5. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)-Amplifier Gain.
6. The emission levels of other frequencies were less than 20dB margin against the limit.
7. Margin value = Emission level-Limit value.

802.11b_ 2412MHz


Horizontal _ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1204.000	71.68	-20.31	51.37	74.00	-22.63	peak	
2	1221.000	49.55	-20.26	29.29	54.00	-24.71	AVG	
3	6797.000	34.90	-0.56	34.34	54.00	-19.66	AVG	
4	7154.000	44.86	-0.26	44.60	74.00	-29.40	peak	
5	12730.000	31.07	9.19	40.26	54.00	-13.74	AVG	
6	12747.000	41.94	9.22	51.16	74.00	-22.84	peak	

802.11b_ 2412MHz


Vertical_ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1374.000	68.05	-19.86	48.19	74.00	-25.81	peak	
2	1510.000	49.15	-19.81	29.34	54.00	-24.66	AVG	
3	2190.000	65.06	-16.43	48.63	74.00	-25.37	peak	
4	2190.000	50.79	-16.43	34.36	54.00	-19.64	AVG	
5	9636.000	45.55	4.44	49.99	74.00	-24.01	peak	
6	9670.000	33.13	4.50	37.63	54.00	-16.37	AVG	

802.11b_2462MHz


Horizontal _ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1187.000	66.71	-20.38	46.33	74.00	-27.67	peak	
2	1408.000	47.44	-19.79	27.65	54.00	-26.35	AVG	
3	4927.000	51.72	-5.46	46.26	74.00	-27.74	peak	
4	4944.000	39.94	-5.39	34.55	54.00	-19.45	AVG	
5	12152.000	44.54	8.41	52.95	74.00	-21.05	peak	
6	12152.000	31.93	8.41	40.34	54.00	-13.66	AVG	

802.11b_ 2462MHz


Vertical_ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2173.000	49.42	-16.51	32.91	54.00	-21.09	AVG	
2	2190.000	62.47	-16.43	46.04	74.00	-27.96	peak	
3	4927.000	53.86	-5.46	48.40	74.00	-25.60	peak	
4	4944.000	41.82	-5.39	36.43	54.00	-17.57	AVG	
5	9840.000	45.26	4.82	50.08	74.00	-23.92	peak	
6	9857.000	33.27	4.84	38.11	54.00	-15.89	AVG	

802.11g_2412MHz


Horizontal _ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1969.000	48.21	-17.58	30.63	54.00	-23.37	AVG	
2	1986.000	59.14	-17.39	41.75	74.00	-32.25	peak	
3	5182.000	50.20	-4.78	45.42	74.00	-28.58	peak	
4	5199.000	37.83	-4.74	33.09	54.00	-20.91	AVG	
5	12135.000	43.31	8.40	51.71	74.00	-22.29	peak	
6	12152.000	31.99	8.41	40.40	54.00	-13.60	AVG	

802.11g_ 2412MHz


Vertical_ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1187.000	70.12	-20.38	49.74	74.00	-24.26	peak	
2	1408.000	47.68	-19.79	27.89	54.00	-26.11	AVG	
3	10231.000	33.03	5.51	38.54	54.00	-15.46	AVG	
4	10299.000	43.76	5.64	49.40	74.00	-24.60	peak	
5	14005.000	41.12	10.60	51.72	74.00	-22.28	peak	
6	14005.000	29.90	10.60	40.50	54.00	-13.50	AVG	

802.11g_2462MHz


Horizontal _ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1408.000	48.08	-19.79	28.29	54.00	-25.71	AVG	
2	1595.000	61.54	-19.82	41.72	74.00	-32.28	peak	
3	6797.000	34.77	-0.56	34.21	54.00	-19.79	AVG	
4	7137.000	45.44	-0.25	45.19	74.00	-28.81	peak	
5	10231.000	33.09	5.51	38.60	54.00	-15.40	AVG	
6	10248.000	43.90	5.55	49.45	74.00	-24.55	peak	

802.11g_ 2462MHz

Vertical_ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2088.000	64.82	-16.86	47.96	74.00	-26.04	peak	
2	2105.000	50.75	-16.79	33.96	54.00	-20.04	AVG	
3	5029.000	37.73	-5.14	32.59	54.00	-21.41	AVG	
4	5182.000	52.35	-4.78	47.57	74.00	-26.43	peak	
5	9636.000	45.82	4.44	50.26	74.00	-23.74	peak	
6	9653.000	33.47	4.47	37.94	54.00	-16.06	AVG	

802.11n20_ 2412MHz


Horizontal _ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1884.000	47.69	-18.51	29.18	54.00	-24.82	AVG	
2	2003.000	59.27	-17.21	42.06	74.00	-31.94	peak	
3	4961.000	47.93	-5.34	42.59	74.00	-31.41	peak	
4	5029.000	37.66	-5.14	32.52	54.00	-21.48	AVG	
5	12152.000	32.20	8.41	40.61	54.00	-13.39	AVG	
6	12169.000	43.91	8.42	52.33	74.00	-21.67	peak	

802.11n20_ 2412MHz


Vertical_ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1833.000	50.21	-19.08	31.13	54.00	-22.87	AVG	
2	2207.000	61.63	-16.37	45.26	74.00	-28.74	peak	
3	2564.000	59.15	-14.76	44.39	74.00	-29.61	peak	
4	2581.000	47.71	-14.65	33.06	54.00	-20.94	AVG	
5	5182.000	53.06	-4.78	48.28	74.00	-25.72	peak	
6	5199.000	38.59	-4.74	33.85	54.00	-20.15	AVG	

802.11n20_2462MHz


Horizontal _ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2003.000	59.41	-17.21	42.20	74.00	-31.80	peak	
2	2224.000	45.80	-16.33	29.47	54.00	-24.53	AVG	
3	4961.000	48.31	-5.34	42.97	74.00	-31.03	peak	
4	5029.000	37.42	-5.14	32.28	54.00	-21.72	AVG	
5	10231.000	44.97	5.51	50.48	74.00	-23.52	peak	
6	10231.000	33.11	5.51	38.62	54.00	-15.38	AVG	

802.11n20_ 2462MHz


Vertical_ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1187.000	66.32	-20.38	45.94	74.00	-28.06	peak	
2	1374.000	48.62	-19.86	28.76	54.00	-25.24	AVG	
3	5063.000	37.51	-5.06	32.45	54.00	-21.55	AVG	
4	5182.000	51.03	-4.78	46.25	74.00	-27.75	peak	
5	8344.000	44.80	2.15	46.95	74.00	-27.05	peak	
6	8752.000	32.39	2.95	35.34	54.00	-18.66	AVG	

802.11n40_2422MHz


Horizontal _ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1357.000	47.93	-19.90	28.03	54.00	-25.97	AVG	
2	1680.000	61.30	-19.68	41.62	74.00	-32.38	peak	
3	6797.000	34.63	-0.56	34.07	54.00	-19.93	AVG	
4	7154.000	45.54	-0.26	45.28	74.00	-28.72	peak	
5	12152.000	31.26	8.41	39.67	54.00	-14.33	AVG	
6	12186.000	43.00	8.43	51.43	74.00	-22.57	peak	

802.11n40_ 2422MHz

Vertical_ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1340.000	62.33	-19.95	42.38	74.00	-31.62	peak	
2	1357.000	48.39	-19.90	28.49	54.00	-25.51	AVG	
3	5012.000	48.90	-5.17	43.73	74.00	-30.27	peak	
4	5029.000	37.68	-5.14	32.54	54.00	-21.46	AVG	
5	12849.000	42.31	9.45	51.76	74.00	-22.24	peak	
6	13223.000	30.37	9.95	40.32	54.00	-13.68	AVG	

802.11n40_2452MHz


Horizontal _ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1357.000	47.62	-19.90	27.72	54.00	-26.28	AVG	
2	1680.000	61.08	-19.68	41.40	74.00	-32.60	peak	
3	9636.000	45.00	4.44	49.44	74.00	-24.56	peak	
4	9806.000	32.52	4.76	37.28	54.00	-16.72	AVG	
5	14005.000	29.47	10.60	40.07	54.00	-13.93	AVG	
6	14090.000	41.30	10.56	51.86	74.00	-22.14	peak	

802.11n40_ 2452MHz


Vertical_ Above 1GHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	1340.000	61.00	-19.95	41.05	74.00	-32.95	peak	
2	1357.000	47.80	-19.90	27.90	54.00	-26.10	AVG	
3	7953.000	32.77	1.59	34.36	54.00	-19.64	AVG	
4	8378.000	43.78	2.17	45.95	74.00	-28.05	peak	
5	12849.000	42.31	9.45	51.76	74.00	-22.24	peak	
6	13240.000	30.23	9.97	40.20	54.00	-13.80	AVG	


Restricted Band:

802.11b_ 2412MHz_Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2389.190	54.33	-15.88	38.45	54.00	-15.55	AVG	
2	2389.540	72.33	-15.88	56.45	74.00	-17.55	peak	
3	2390.000	61.47	-15.88	45.59	74.00	-28.41	peak	
4	2390.000	47.60	-15.88	31.72	54.00	-22.28	AVG	

802.11b_ 2412MHz_Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2385.480	73.10	-15.88	57.22	74.00	-16.78	peak	
2	2387.860	54.38	-15.88	38.50	54.00	-15.50	AVG	
3	2390.000	62.64	-15.88	46.76	74.00	-27.24	peak	
4	2390.000	47.72	-15.88	31.84	54.00	-22.16	AVG	

802.11b_ 2462MHz_Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2483.500	56.82	-15.30	41.52	74.00	-32.48	peak	
2	2483.500	48.73	-15.30	33.43	54.00	-20.57	AVG	
3	2486.000	61.20	-15.29	45.91	74.00	-28.09	peak	
4	2490.300	48.18	-15.25	32.93	54.00	-21.07	AVG	

802.11b_ 2462MHz_Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2483.500	59.88	-15.30	44.58	74.00	-29.42	peak	
2	2483.500	48.00	-15.30	32.70	54.00	-21.30	AVG	
3	2491.700	47.86	-15.23	32.63	54.00	-21.37	AVG	
4	2491.800	61.83	-15.23	46.60	74.00	-27.40	peak	

802.11g_2412MHz_Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2385.200	61.81	-15.89	45.92	74.00	-28.08	peak	
2	2386.180	47.11	-15.88	31.23	54.00	-22.77	AVG	
3	2390.000	60.12	-15.88	44.24	74.00	-29.76	peak	
4	2390.000	45.45	-15.88	29.57	54.00	-24.43	AVG	

802.11g_ 2412MHz_Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2384.080	51.26	-15.90	35.36	54.00	-18.64	AVG	
2	2386.250	68.30	-15.88	52.42	74.00	-21.58	peak	
3	2390.000	71.72	-15.88	55.84	74.00	-18.16	peak	
4	2390.000	51.40	-15.88	35.52	54.00	-18.48	AVG	

802.11g_ 2462MHz_Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2483.500	59.32	-15.30	44.02	74.00	-29.98	peak	
2	2483.500	46.37	-15.30	31.07	54.00	-22.93	AVG	
3	2509.500	45.81	-15.12	30.69	54.00	-23.31	AVG	
4	2511.700	57.28	-15.10	42.18	74.00	-31.82	peak	

802.11g_ 2462MHz_Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2483.500	75.28	-15.30	59.98	74.00	-14.02	peak	
2	2483.500	62.37	-15.30	47.07	54.00	-6.93	AVG	
3	2485.600	56.74	-15.29	41.45	54.00	-12.55	AVG	
4	2486.200	72.85	-15.28	57.57	74.00	-16.43	peak	

802.11n20_ 2412MHz_Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2386.740	54.22	-15.88	38.34	54.00	-15.66	AVG	
2	2387.020	70.83	-15.88	54.95	74.00	-19.05	peak	
3	2390.000	66.52	-15.88	50.64	74.00	-23.36	peak	
4	2390.000	50.00	-15.88	34.12	54.00	-19.88	AVG	

802.11n20_ 2412MHz_Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2386.810	54.96	-15.88	39.08	54.00	-14.92	AVG	
2	2389.820	71.82	-15.88	55.94	74.00	-18.06	peak	
3	2390.000	63.48	-15.88	47.60	74.00	-26.40	peak	
4	2390.000	51.94	-15.88	36.06	54.00	-17.94	AVG	

802.11n20_ 2462MHz_Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2483.500	64.02	-15.30	48.72	74.00	-25.28	peak	
2	2483.500	51.94	-15.30	36.64	54.00	-17.36	AVG	
3	2485.400	51.26	-15.29	35.97	54.00	-18.03	AVG	
4	2488.100	66.73	-15.27	51.46	74.00	-22.54	peak	

802.11n20_ 2462MHz_Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2483.500	61.79	-15.30	46.49	74.00	-27.51	peak	
2	2483.500	49.87	-15.30	34.57	54.00	-19.43	AVG	
3	2486.400	50.37	-15.27	35.10	54.00	-18.90	AVG	
4	2487.500	66.45	-15.27	51.18	74.00	-22.82	peak	

802.11n40_ 2422MHz_Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2390.000	78.74	-15.88	62.86	74.00	-11.14	peak	
2	2390.000	65.70	-15.88	49.82	54.00	-4.18	AVG	

802.11n40_ 2422MHz_Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2390.000	64.20	-15.88	48.32	74.00	-25.68	peak	
2	2422.000	48.22	-15.88	32.34	54.00	-21.66	AVG	

802.11n40_ 2452MHz_Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2483.500	69.72	-15.30	54.42	74.00	-19.58	peak	
2	2483.500	54.95	-15.30	39.65	54.00	-14.35	AVG	

802.11n40_ 2452MHz_Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Remark
1	2483.500	61.70	-15.30	46.40	74.00	-27.60	peak	
2	2483.500	47.02	-15.30	31.72	54.00	-22.28	AVG	

3.8. AC Power-Line Conducted Emission

3.8.1. Limit

47 CFR 15.207(a): For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table:


Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.8.2. Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.8.3. Test Setup




3.8.4. Test Result of AC Power-Line Conducted Emission

Note:

- 1.All modes have been tested, only worst case(802.11b_2412MHz)mode was recorded in the test report.
- 2.Emission Level = Reading Value+ Correction Factor.
- 3.Correction Factor= Insertion loss + Cable loss.
- 4.The emission levels of other frequencies were less than 20dB margin against the limit.
- 5.Margin value = Emission level-Limit value.





3.9. Antenna Requirement

3.9.1. Standard Requirement

According to 47 CFR 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

3.9.2. EUT Antenna

The antenna used for the EUT is PCB Antenna, which meets the antenna requirements.

4. Test Setup Photographs

Please refer to the Appendix F.

5. External And internal Photographs of The EUT

External Please refer to the Appendix G.

Internal Please refer to the Appendix H.

Appendix A of data

A1.Maximum Peak Conducted output power

Test Result


Mode	Channel	Conducted output power (dBm)	Duty Cycle Factor (dB)	Limit (dBm)	Result
IEEE 802.11b	1	15.975	0.0511	≤30	PASS
	6	15.202	0.0511	≤30	PASS
	11	14.54	0.0511	≤30	PASS
IEEE 802.11g	1	13.012	0.0432	≤30	PASS
	6	12.478	0.0463	≤30	PASS
	11	12.064	0.0463	≤30	PASS
IEEE 802.11n_20	1	12.907	0.0485	≤30	PASS
	6	12.444	0.0432	≤30	PASS
	11	12.01	0.0485	≤30	PASS
IEEE 802.11n_40	3	12.067	0.0533	≤30	PASS
	6	11.699	0.0559	≤30	PASS
	9	11.31	0.0533	≤30	PASS


A2.Duty Cycle

Test Result


Mode	Data rates	Channel	Antenna	On Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle (linear)	Duty Cycle Factor (dB)	1/T
IEEE 802.11b	1	1	1	1.683	1.703	98.83	0.9883	0.0511	0.5942
		6		1.683	1.703	98.83	0.9883	0.0511	0.5942
		11		1.683	1.703	98.83	0.9883	0.0511	0.5942
IEEE 802.11g	6	1		1.396	1.410	99.01	0.9901	0.0432	0.7163
		6		1.396	1.411	98.94	0.9894	0.0463	0.7163
		11		1.396	1.411	98.94	0.9894	0.0463	0.7163
IEEE 802.11n_20	MCS 0	1		1.303	1.318	98.89	0.9889	0.0485	0.7675
		6		1.304	1.317	99.01	0.9901	0.0432	0.7669
		11		1.303	1.318	98.89	0.9889	0.0485	0.7675
IEEE 802.11n_40		3		0.650	0.658	98.78	0.9878	0.0533	1.5385
		6		0.650	0.659	98.72	0.9872	0.0559	1.5385
		9		0.650	0.658	98.78	0.9878	0.0533	1.5385

Test Graphs







IEEE 802.11g 20MHz_Channel 6




IEEE 802.11g 20MHz_Channel 11




IEEE 802.11n 20MHz_Channel 1




IEEE 802.11n 20MHz_Channel 6




IEEE 802.11n 20MHz_Channel 11



IEEE 802.11n 40MHz_Channel 3



IEEE 802.11n 40MHz_Channel 6




IEEE 802.11n 40MHz_Channel 9

A3.6dB Bandwidth

6dB Bandwidth

Mode	Channel	Ant.	Center Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)	Result
IEEE 802.11b	1	0	2412	9.970	≥0.5	PASS
	6		2437	11.04		PASS
	11		2462	11.03		PASS
IEEE 802.11g	1		2412	16.32		PASS
	6		2437	16.36		PASS
	11		2462	16.34		PASS
IEEE 802.11n_20	1		2412	15.09		PASS
	6		2437	15.06		PASS
	11		2462	15.13		PASS
IEEE 802.11n_40	3		2422	33.82		PASS
	6		2437	33.81		PASS
	9		2457	35.63		PASS

Test Graphs



IEEE 802.11b_Channel 1_20MHz_Antenna 0




IEEE 802.11b_Channel 6_20MHz_Antenna 0




IEEE 802.11b_Channel 11_20MHz_Antenna 0




IEEE 802.11g_Channel 1_20MHz_Antenna 0




IEEE 802.11g_Channel 6_20MHz_Antenna 0




IEEE 802.11g_Channel 11_20MHz_Antenna 0




IEEE 802.11n_Channel 1_20MHz_Antenna 0




IEEE 802.11n_Channel 6_20MHz_Antenna 0



IEEE 802.11n_Channel 11_20MHz_Antenna 0



IEEE 802.11n_Channel 3_40MHz_Antenna 0



IEEE 802.11n_Channel 6_40MHz_Antenna 0




A4.Power Spectral Density


Test Result

Mode	Channel	PSD (dBm/3kHz) Ant. 0	Limit (dBm/3kHz)	Result
IEEE 802.11b	1	-7.610	≤8	PASS
	6	-9.140		PASS
	11	-9.060		PASS
IEEE 802.11g	1	-11.660		PASS
	6	-12.050		PASS
	11	-12.620		PASS
IEEE 802.11n_20	1	-11.150		PASS
	6	-11.440		PASS
	11	-11.930		PASS
IEEE 802.11n_40	3	-15.160		PASS
	6	-15.590		PASS
	10	-22.87		PASS


Test Graphs




IEEE 802.11b_Channel 1_20MHz_Antenna 0




IEEE 802.11b_Channel 6_20MHz_Antenna 0




IEEE 802.11b_Channel 11_20MHz_Antenna 0




IEEE 802.11g_Channel 1_20MHz_Antenna 0




IEEE 802.11g_Channel 6_20MHz_Antenna 0




IEEE 802.11g_Channel 11_20MHz_Antenna 0




IEEE 802.11n_Channel 1_20MHz_Antenna 0




IEEE 802.11n_Channel 6_20MHz_Antenna 0




IEEE 802.11n_Channel 11_20MHz_Antenna 0



IEEE 802.11n_Channel 3_40MHz_Antenna 0



IEEE 802.11n_Channel 6_40MHz_Antenna 0



IEEE 802.11n_Channel 9_40MHz_Antenna 0

A5.Conducted Band Edge and Conducted Spurious Emission




Test Result


Mode	Channel	Ant.	OOB Emission Frequency (MHz)	OOB Emission Level (dBm)	Limit (dBm)	Over Limit (dB)	Result
IEEE 802.11b	1	0	2396.97	-13.919	-12.62	-1.299	PASS
			2400.00	-14.360	-12.62	-1.740	PASS
			4812.50	-53.569	-12.62	-40.949	PASS
			7244.60	-50.734	-12.62	-38.114	PASS
			9663.00	-49.770	-12.62	-37.150	PASS
			24269.6	-37.129	-12.62	-24.509	PASS
	6		4878.67	-52.414	-14.16	-38.254	PASS
			7317.05	-51.583	-14.16	-37.423	PASS
			9747.94	-50.575	-14.16	-36.415	PASS
			23649.7	-37.114	-14.16	-22.954	PASS
	11		2483.50	-34.550	-14.29	-20.260	PASS
			4923.62	-48.220	-14.29	-33.930	PASS
			7376.98	-51.931	-14.29	-37.641	PASS
			9847.83	-46.446	-14.29	-32.156	PASS
			24298.9	-37.310	-14.29	-23.020	PASS
IEEE 802.11g	1		2400.00	-20.720	-17.23	-3.490	PASS
			4827.48	-53.016	-17.23	-35.786	PASS
			7227.16	-52.292	-17.23	-35.062	PASS
			9641.19	-50.212	-17.23	-32.982	PASS
	6		23704.6	-37.255	-17.23	-20.025	PASS
			4855.57	-53.555	-17.68	-35.875	PASS
			7315.80	-52.896	-17.68	-35.216	PASS
			9733.58	-51.187	-17.68	-33.507	PASS
			23726.5	-37.031	-17.68	-19.351	PASS
	11		2483.50	-28.820	-18.17	-10.650	PASS
			4913.01	-53.171	-18.17	-35.001	PASS
			7374.48	-52.314	-18.17	-34.144	PASS
			9851.57	-50.516	-18.17	-32.346	PASS
			24543.0	-37.017	-18.17	-18.847	PASS
			IEEE 802.11n_20	1	2398.01	-20.624	-15.71
2400.00	-22.890				-15.71	-7.180	PASS
4806.30	-53.043				-15.71	-37.333	PASS
7231.50	-52.341				-15.71	-36.631	PASS
9658.00	-50.990				-15.71	-35.280	PASS
23789.5	-36.907				-15.71	-21.197	PASS
6	4886.16			-52.625	-16.13	-36.495	PASS
	7292.71			-52.513	-16.13	-36.383	PASS
	9731.71			-50.832	-16.13	-34.702	PASS
				24295.2	-37.810	-16.13	-21.680

IEEE 802.11n_40	11	2483.50	-29.340	-17.28	-12.060	PASS
		4908.01	-52.687	-17.28	-35.407	PASS
		7393.21	-52.437	-17.28	-35.157	PASS
		9862.81	-51.428	-17.28	-34.148	PASS
		24137.9	-37.657	-17.28	-20.377	PASS
	3	2394.50	-22.612	-20.43	-2.182	PASS
		2400.00	-25.340	-20.43	-4.910	PASS
		4870.60	-52.914	-20.43	-32.484	PASS
		7256.50	-53.383	-20.43	-32.953	PASS
		9724.20	-50.494	-20.43	-30.064	PASS
	6	24149.8	-37.830	-20.43	-17.400	PASS
		4906.76	-52.811	-20.73	-32.081	PASS
		7335.16	-52.659	-20.73	-31.929	PASS
		9741.08	-50.620	-20.73	-29.890	PASS
		24096.7	-37.618	-20.73	-16.888	PASS
	10	2483.50	-33.080	-27.56	-5.520	PASS
		4910.39	-53.919	-27.56	-26.360	PASS
		7326.23	-51.239	-27.56	-23.679	PASS
		9786.40	-53.246	-27.56	-25.686	PASS
		24910.7	-39.176	-27.56	-11.616	PASS

Test Graphs




30.0 MHz - 25000.0 MHz IEEE 802.11b_Channel 1_20MHz_Antenna 0 	In-Band Reference Level IEEE 802.11b_Channel 6_20MHz_Antenna 0 
30.0 MHz - 25000.0 MHz IEEE 802.11b_Channel 6_20MHz_Antenna 0 	In-Band Reference Level IEEE 802.11b_Channel 11_20MHz_Antenna 0 
Out Of Band Emission IEEE 802.11b_Channel 11_20MHz_Antenna 0 	30.0 MHz - 25000.0 MHz IEEE 802.11b_Channel 11_20MHz_Antenna 0 
In-Band Reference Level IEEE 802.11g_Channel 1_20MHz_Antenna 0	Out Of Band Emission IEEE 802.11g_Channel 1_20MHz_Antenna 0



30.0 MHz - 25000.0 MHz
IEEE 802.11g_Channel 1_20MHz_Antenna 0



In-Band Reference Level
IEEE 802.11g_Channel 6_20MHz_Antenna 0




30.0 MHz - 25000.0 MHz
IEEE 802.11g_Channel 6_20MHz_Antenna 0




In-Band Reference Level
IEEE 802.11g_Channel 11_20MHz_Antenna 0



Out Of Band Emission
IEEE 802.11g_Channel 11_20MHz_Antenna 0




30.0 MHz - 25000.0 MHz
IEEE 802.11g_Channel 11_20MHz_Antenna 0



In-Band Reference Level

IEEE 802.11n_Channel 1_20MHz_Antenna 0




Out Of Band Emission

IEEE 802.11n_Channel 1_20MHz_Antenna 0



30.0 MHz - 25000.0 MHz

IEEE 802.11n_Channel 1_20MHz_Antenna 0



In-Band Reference Level

IEEE 802.11n_Channel 6_20MHz_Antenna 0




30.0 MHz - 25000.0 MHz

IEEE 802.11n_Channel 6_20MHz_Antenna 0



In-Band Reference Level

IEEE 802.11n_Channel 11_20MHz_Antenna 0



Out Of Band Emission

IEEE 802.11n_Channel 11_20MHz_Antenna 0

30.0 MHz - 25000.0 MHz


IEEE 802.11n_Channel 11_20MHz_Antenna 0



In-Band Reference Level
IEEE 802.11n_Channel 3_40MHz_Antenna 0




Out Of Band Emission
IEEE 802.11n_Channel 3_40MHz_Antenna 0



30.0 MHz - 25000.0 MHz
IEEE 802.11n_Channel 3_40MHz_Antenna 0





In-Band Reference Level
IEEE 802.11n_Channel 6_40MHz_Antenna 0



30.0 MHz - 25000.0 MHz
IEEE 802.11n_Channel 6_40MHz_Antenna 0



In-Band Reference Level
IEEE 802.11n_Channel 9_40MHz_Antenna 0



Out Of Band Emission

30.0 MHz - 25000.0 MHz

IEEE 802.11n_Channel 9_40MHz_Antenna 0

IEEE 802.11n_Channel 9_40MHz_Antenna 0

*****END OF THE REPORT*****