

**FCC ID:2A5FW-PX3**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

## 2.4GWIFI:

| Modulation    | Channel Freq. (GHz) | Conduct ed power (dBm) | Conducte d power (mW) | Tune-up power (dBm) | Max tune-up power (dBm) | Max tune-up power (mW) | Distance (mm) | Result calculation | SAR Exclusion threshold | SAR test exclusion |
|---------------|---------------------|------------------------|-----------------------|---------------------|-------------------------|------------------------|---------------|--------------------|-------------------------|--------------------|
| 802.11b       | 2.412               | 8.053                  | 6.39                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.46728            | 3.00                    | YES                |
|               | 2.437               | 8.215                  | 6.63                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.48003            | 3.00                    | YES                |
|               | 2.462               | 8.939                  | 7.83                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.49272            | 3.00                    | YES                |
| 802.11g       | 2.412               | 8.052                  | 6.39                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.46728            | 3.00                    | YES                |
|               | 2.437               | 8.393                  | 6.91                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.48003            | 3.00                    | YES                |
|               | 2.462               | 8.338                  | 6.82                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.49272            | 3.00                    | YES                |
| 802.11n(HT20) | 2.412               | 8.428                  | 6.96                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.46728            | 3.00                    | YES                |
|               | 2.437               | 8.447                  | 6.99                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.48003            | 3.00                    | YES                |
|               | 2.462               | 8.081                  | 6.43                  | 8±1                 | 9.00                    | 7.94                   | <5            | 2.49272            | 3.00                    | YES                |

**Conclusion:**

For the max result :  $2.49272 \leq \text{FCC Limit } 3.0$  for 1g SAR.