



FCC TEST REPORT

FCC ID: 2A5JO-AMA005899

Product	:	Treadmill
Model Name	:	AMA005899
Brand	:	FUNMILY
Report No.	:	PTC22022200605E-FC01
Prepared for		
Shenzhen Mingbofang Clothing Co., Ltd.		
Room 403, Fuji Pavilion, No. 2058, Cuizhu Road, Cuida Community, Cuizhu Street, Luohu District, Shenzhen		
Prepared by		
Precise Testing & Certification Co., Ltd		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China		



1 TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Mingbofang Clothing Co., Ltd.
Address : Room 403, Fuji Pavilion, No. 2058, Cuizhu Road, Cuida Community,
Cuizhu Street, Luohu District, Shenzhen
Manufacture's name : Xiamen Mydo Sports Equipment Co.,Ltd
Address : 30, Bannan Road,Dongfu street,Haicang District,Xiamen,Fujian,China
Product name : Treadmill
Model name : AMA005899
Standards : FCC CFR47 Part 15 Section 15.247
Test procedure : ANSI C63.10:2013
Test Date : Feb. 22 ,2022 to Mar. 20 ,2022
Date of Issue : Mar. 20 ,2022
Test Result : Pass

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink, appearing to read 'Leo Yang'.

Leo Yang / Engineer

Technical Manager:

A handwritten signature in black ink, appearing to read 'Wu Weimin'.

Wu Weimin / Manager



Contents

	Page
1 TEST RESULT CERTIFICATION.....	2
2 TEST SUMMARY.....	5
2.1 TEST SITE.....	6
3 GENERAL INFORMATION.....	7
3.1 GENERAL DESCRIPTION OF E.U.T.....	7
3.2 CHANNEL LIST.....	8
4 EQUIPMENT DURING TEST.....	9
4.1 EQUIPMENTS LIST.....	9
4.2 MEASUREMENT UNCERTAINTY.....	10
4.3 DESCRIPTION OF SUPPORT UNITS.....	11
5 CONDUCTED EMISSION.....	12
5.1 E.U.T. OPERATION.....	12
5.2 EUT SETUP.....	12
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	13
5.4 MEASUREMENT PROCEDURE.....	13
5.5 CONDUCTED EMISSION LIMIT.....	13
5.6 MEASUREMENT DESCRIPTION.....	13
5.7 CONDUCTED EMISSION TEST RESULT.....	13
6 RADIATED SPURIOUS EMISSIONS.....	16
6.1 EUT OPERATION.....	16
6.2 TEST SETUP.....	17
6.3 SPECTRUM ANALYZER SETUP.....	18
6.4 TEST PROCEDURE.....	19
6.5 SUMMARY OF TEST RESULTS.....	21
7 BAND EDGE MEASUREMENT.....	27
7.1 TEST PROCEDURE.....	27
7.2 TEST RESULT.....	28
8 6DB BANDWIDTH MEASUREMENT.....	29
8.1 TEST PROCEDURE.....	29



8.2 TEST RESULT.....	29
9 MAXIMUM PEAK OUTPUT POWER.....	32
9.1 TEST PROCEDURE.....	32
9.2 TEST RESULT.....	32
10 POWER SPECTRAL DENSITY.....	35
10.1 TEST PROCEDURE.....	35
10.2 TEST RESULT.....	35
11 ANTENNA APPLICATION.....	38
11.1 ANTENNA REQUIREMENT.....	38
11.2 RESULT.....	38
12 TEST SET-UP.....	39
13 EUT PHOTOS.....	41



2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	15.207	PASS
Radiated Spurious Emissions	15.205(a) 15.209 15.247(d)	PASS
Conducted Spurious Emission	15.247(d)	PASS
Band edge	15.247(d) 15.205(a)	PASS
6dB Bandwidth	15.247(a)(2)	PASS
Maximum Peak Output Power	15.247(b)(1)	PASS
Power Spectral Density	15.247(e)	PASS
Antenna Requirement	15.203	PASS



Report No.: PTC22022200605E-FC01

2.1 Test Site

Precise Testing & Certification Co., Ltd

Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China

FCC Registration Number: 790290

A2LA Certificate No.: 4408.01

IC Registration Number: 12191A-1



3 General Information

3.1 General Description of E.U.T.

Product Name	:	Treadmill
Model Name	:	AMA005899
Bluetooth Version	:	BT 4.2 EDR+BLE
Operating frequency	:	2402-2480MHz
Number of Channels	:	BLE:40 channels EDR:79 channels
Type of Modulation	:	GFSK, $\pi/4$ -DQPSK
Antenna installation	:	PCB Antenna
Antenna Gain	:	2dBi
Power supply	:	AC 120V/60Hz, 10A
Hardware Version	:	N/A
Software Version	:	N/A



3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.



4 Equipment During Test

4.1 Equipments List

RF Conducted Test

Name of Equipment	Manufacturer	Model	Serial No.	Last calibration	Calibration Due	Calibration period
MXG Signal Analyzer	Agilent	N9020A	MY56070279	Aug. 21, 2021	Aug. 20, 2022	1 year
Spectrum Analyzer	Rohde&Schwarz	FSU26	1166.1660.26	Aug. 21, 2021	Aug. 20, 2022	1 year
Coaxial Cable	CDS	79254	46107086	Aug. 21, 2021	Aug. 20, 2022	1 year
Power Meter	Anritsu	ML2495A	0949003	Aug. 21, 2021	Aug. 20, 2022	1 year
Power Sensor	Anritsu	MA2411B	0917017	Aug. 21, 2021	Aug. 20, 2022	1 year

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

Radiated Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Last calibration	Calibration Due	Calibration period
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	Aug. 21, 2021	Aug. 20, 2022	1 year
Loop Antenna	Schwarzbeck	FMZB 1519	012	Aug. 21, 2021	Aug. 20, 2022	1 year
Bilog Antenna	SCHWARZBECK	VULB9160	9160-3355	Aug. 21, 2021	Aug. 20, 2022	1 year
Preamplifier (low frequency)	SCHWARZBECK	BBV 9475	9745-0013	Aug. 21, 2021	Aug. 20, 2022	1 year
Cable	Schwarzbeck	PLF-100	549489	Aug. 21, 2021	Aug. 20, 2022	1 year
Spectrum Analyzer	Agilent	E4407B	MY45109572	Aug. 21, 2021	Aug. 20, 2022	1 year
Horn Antenna	SCHWARZBECK	9120D	9120D-1246	Aug. 21, 2021	Aug. 20, 2022	1 year
Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	Aug. 21, 2021	Aug. 20, 2022	1 year
Horn Antenna	SCHWARZBECK	BBHA 9170	9170-181	Aug. 21, 2021	Aug. 20, 2022	1 year
Amplifier	SCHWARZBECK	BBV 9721	9721-205	Aug. 21, 2021	Aug. 20, 2022	1 year
Cable	H+S	CBL-26	N/A	Aug. 21, 2021	Aug. 20, 2022	1 year
RF Cable	R&S	R204	R21X	Aug. 21, 2021	Aug. 20, 2022	1 year



Conducted Emissions

Name of Equipment	Manufacturer	Model	Serial No.	Last calibration	Calibration Due	Calibration period
EMI Test Receiver	Rohde&Schwarz	ESCI	101417	Aug. 21, 2021	Aug. 20, 2022	1 year
Artificial Mains Network	Rohde&Schwarz	L2-16B	000WX31025	Aug. 21, 2021	Aug. 20, 2022	1 year
Artificial Mains Network	Rohde&Schwarz	ENV216	101342	Aug. 21, 2021	Aug. 20, 2022	1 year

4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10 ⁻⁶
Bandwidth	± 1.5 x 10 ⁻⁶
Time	±2%
Duty Cycle	±2%
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	



Report No.: PTC22022200605E-FC01

4.3 Description of Support Units

Equipment	Model No.	Series No.
-	-	-

5 Conducted Emission

Test Requirement: : FCC CFR 47 Part 15 Section 15.207

Test Method: : ANSI C63.10: 2013

Test Result: : PASS

Frequency Range: : 150kHz to 30MHz

Class/Severity: : Class B

5.1 E.U.T. Operation

Operating Environment :


Temperature: : 25.5 °C

Humidity: : 51 % RH


Atmospheric Pressure: : 101.2kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.1m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description


The maximised peak emissions from the EUT was scanned with AC 240V 50Hz and AC 120V 60Hz, and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line. The worst case was recorded by (GFSK TX 2402MHz) with AC 120V 60Hz.

5.7 Conducted Emission Test Result

Pass.


All the modulation modes were tested the data of the worst mode (GFSK TX 2402MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Line:



No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dBuV	Emission Level dBuV	Limit dBuV	Over Limit dB	Remark
1.	0.162	0.23	9.59	3.81	13.63	55.34	-41.71	Average
2.	0.162	0.23	9.59	27.14	36.96	65.34	-28.38	QP
3.	0.206	0.29	9.59	5.00	14.88	53.36	-38.48	Average
4.	0.206	0.29	9.59	24.98	34.86	63.36	-28.50	QP
5.	0.555	0.43	9.61	9.48	19.52	46.00	-26.48	Average
6.	0.555	0.43	9.61	23.73	33.77	56.00	-22.23	QP
7.	1.269	0.46	9.61	12.82	22.89	46.00	-23.11	Average
8.	1.269	0.46	9.61	21.18	31.25	56.00	-24.75	QP
9.	1.654	0.47	9.61	10.60	20.68	46.00	-25.32	Average
10.	1.654	0.47	9.61	19.01	29.09	56.00	-26.91	QP
11.	2.110	0.47	9.61	10.69	20.77	46.00	-25.23	Average
12.	2.110	0.47	9.61	20.86	30.94	56.00	-25.06	QP

Neutral



No.	Freq MHz	Cable Loss dB	AMN Factor dB	Receiver Reading dBuV	Emission Level dBuV	Limit dBuV	Over Limit dB	Remark
1.	0.182	0.25	9.61	5.44	15.30	54.42	-39.12	Average
2.	0.182	0.25	9.61	27.36	37.22	64.42	-27.20	QP
3.	0.194	0.27	9.61	5.11	14.99	53.84	-38.85	Average
4.	0.194	0.27	9.61	27.05	36.93	63.84	-26.91	QP
5.	0.549	0.43	9.63	10.14	20.20	46.00	-25.80	Average
6.	0.549	0.43	9.63	22.33	32.39	56.00	-23.61	QP
7.	1.262	0.46	9.64	12.65	22.75	46.00	-23.25	Average
8.	1.262	0.46	9.64	21.48	31.58	56.00	-24.42	QP
9.	1.716	0.47	9.64	8.80	18.91	46.00	-27.09	Average
10.	1.716	0.47	9.64	20.02	30.13	56.00	-25.87	QP
11.	2.190	0.47	9.64	9.63	19.74	46.00	-26.26	Average
12.	2.190	0.47	9.64	22.68	32.79	56.00	-23.21	QP



6 Radiated Spurious Emissions

Test Requirement: : FCC CFR47 Part 15 Section 15.209 & 15.247
 Test Method: : ANSI C63.10:2013
 Test Result: : PASS
 Measurement Distance: : 3m
 Limit: : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

6.1 EUT Operation


Operating Environment :

Temperature : 23.5 °C
 Humidity : 51.1 % RH
 Atmospheric Pressure : 101.2kPa


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

Below 30MHz			
IF Bandwidth	:	10kHz	
Resolution Bandwidth	:	10kHz	
Video Bandwidth	:	10kHz	
30MHz ~ 1GHz			
Detector	:	PK	QP
Resolution Bandwidth	:	100kHz	120kHz
Video Bandwidth	:	300kHz	300kHz
Above 1GHz			
Detector	:	PK	AV
Resolution Bandwidth	:	1MHz	1MHz
Video Bandwidth	:	3MHz	10Hz



6.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.1m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.
8. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.



For Average Measurement:

VBW=10Hz, when duty cycle is no less than 98 percent.

VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(μ s)	1/T(KHz)	Average Correction Factor	VBW Setting
2402-2480	100	-	-	0	10Hz



6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance} / \text{test distance})$ (dB);

Limit line = Specific limits (dBuV) + distance extrapolation factor.


Test Frequency: 30MHz ~ 1GHz

Pass.

Please refer to the following test plots for the worst test mode (GFSK (CH00: 2402MHz)).



Antenna Polarization: Horizontal GFSK(CH00: 2402MHz)




Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor

No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBuV	Preamp Factor dB	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	30.531	1.23	11.76	42.04	29.89	25.14	40.00	-14.86	QP
2.	38.888	1.65	12.12	40.95	29.91	24.81	40.00	-15.19	QP
3.	62.871	2.47	11.29	30.60	29.94	14.42	40.00	-25.58	QP
4.	99.878	3.27	9.59	33.56	29.99	16.43	43.50	-27.07	QP
5.	141.330	3.87	13.36	29.60	30.01	16.82	43.50	-26.68	QP
6.	202.810	4.48	11.09	34.56	30.05	20.08	43.50	-23.42	QP



Antenna Polarization: Vertical GFSK(CH00: 2402MHz)



Remark:Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor

No.	Freq MHz	Cable Loss dB	ANT Factor dB/m	Receiver Reading dBuV	Preamp Factor dB	Emission Level dBuV/m	Limit dBuV/m	Over Limit dB	Remark
1.	30.531	1.23	11.76	48.05	29.89	31.15	40.00	-8.85	QP
2.	39.576	1.68	12.11	44.40	29.91	28.28	40.00	-11.72	QP
3.	62.651	2.47	11.32	32.67	29.94	16.52	40.00	-23.48	QP
4.	99.878	3.27	9.59	39.34	29.99	22.21	43.50	-21.29	QP
5.	145.351	3.91	13.52	31.85	30.02	19.26	43.50	-24.24	QP
6.	203.523	4.49	11.12	38.33	30.05	23.89	43.50	-19.61	QP



Test Frequency 1GHz-25GHz:

Test Mode: Low Channel 2402MHz									
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Detector (PK/AV)
4804	41.23	34.04	6.58	34.09	47.76	74.00	-26.24	V	PK
7206	35.30	37.11	7.73	34.50	45.64	74.00	-28.36	V	PK
9608	34.40	39.31	9.23	34.79	48.15	74.00	-25.85	V	PK
4804	42.30	34.04	6.58	34.09	48.83	74.00	-25.17	H	PK
7206	34.90	37.11	7.73	34.50	45.24	74.00	-28.76	H	PK
9608	33.87	39.31	9.23	34.79	47.62	74.00	-26.38	H	PK
4804	37.68	34.04	6.58	34.09	44.21	54.00	-9.79	4804	AV
7206	31.11	37.11	7.73	34.50	41.45	54.00	-12.55	7206	AV
9608	30.16	39.31	9.23	34.79	43.91	54.00	-10.09	9608	AV
4804	37.60	34.04	6.58	34.09	44.13	54.00	-9.87	4804	AV
7206	29.89	37.11	7.73	34.50	40.23	54.00	-13.77	7206	AV
9608	29.02	39.31	9.23	34.79	42.77	54.00	-11.23	9608	AV

Test Mode: Middle Channel 2440MHz									
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Detector (PK/AV)
4880	45.20	34.38	6.69	34.09	52.18	74.00	-21.82	V	PK
7320	40.30	37.22	7.78	34.53	50.77	74.00	-23.23	V	PK
9760	33.54	39.46	9.35	34.80	47.55	74.00	-26.45	V	PK
4880	40.22	34.38	6.69	34.09	47.20	74.00	-26.80	H	PK
7320	35.20	37.22	7.78	34.53	45.67	74.00	-28.33	H	PK
9760	33.85	39.46	9.35	34.80	47.86	74.00	-26.14	H	PK
4880	42.06	34.38	6.69	34.09	49.04	54.00	-4.96	V	AV
7320	35.94	37.22	7.78	34.53	46.41	54.00	-7.59	V	AV
9760	29.02	39.46	9.35	34.80	43.03	54.00	-10.97	V	AV
4880	35.33	34.38	6.69	34.09	42.31	54.00	-11.69	H	AV
7320	30.07	37.22	7.78	34.53	40.54	54.00	-13.46	H	AV
9760	28.65	39.46	9.35	34.80	42.66	54.00	-11.34	H	AV



Test Mode: High Channel 2480MHz									
Frequency (MHz)	Read Level (dBuV/m)	Antenna Factor (dB)	Cable Loss (dB)	Preamplifier Factor (dB)	Emission Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Pol.	Detector (PK/AV)
4960	45.50	34.72	6.79	34.09	52.92	74.00	-21.08	V	4804
7440	39.63	37.34	7.82	34.57	50.22	74.00	-23.78	V	7206
9920	33.40	39.62	9.46	34.81	47.67	74.00	-26.33	V	9608
4960	40.56	34.72	6.79	34.09	47.98	74.00	-26.02	H	4804
7440	34.80	37.34	7.82	34.57	45.39	74.00	-28.61	H	7206
9920	32.00	39.62	9.46	34.81	46.27	74.00	-27.73	H	9608
4960	41.38	34.04	6.58	34.09	47.91	54.00	-6.09	V	4804
7440	35.08	37.11	7.73	34.50	45.42	54.00	-8.58	V	7206
9920	28.79	39.31	9.23	34.79	42.54	54.00	-11.46	V	9608
4960	35.62	34.04	6.58	34.09	42.15	54.00	-11.85	H	4804
7440	29.46	37.11	7.73	34.50	39.80	54.00	-14.20	H	7206
9920	26.93	39.31	9.23	34.79	40.68	54.00	-13.32	H	9608

Note:

1. The testing has been conformed to 10*2480MHz=24800MHz.
2. All other emissions more than 30dB below the limit.
3. Factor = Antenna Factor + Cable Loss – Preamplifier Factor
Emission Level = Read Level + Factor
Over Limit =Emission Level-Limit



Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Test Mode: Low Channel 2402MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2390	43.25	29.15	3.41	34.01	41.80	74.00	-32.20	H	Peak
2400	55.43	29.16	3.43	34.01	54.01	74.00	-19.99	H	Peak
2390	43.22	29.15	3.41	34.01	41.77	74.00	-32.23	V	Peak
2400	54.73	29.16	3.43	34.01	53.31	74.00	-20.69	V	Peak
2390	35.46	29.15	3.41	34.01	34.01	54.00	-19.99	H	AV
2400	44.10	29.16	3.43	34.01	42.68	54.00	-11.32	H	AV
2390	35.12	29.15	3.41	34.01	33.67	54.00	-20.33	V	AV
2400	45.32	29.16	3.43	34.01	43.90	54.00	-10.10	V	AV

Test Mode: High Channel 2480MHz									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	Polarity H/V	Test Value
2483.5	44.25	29.28	3.53	34.03	43.03	74.00	-30.97	H	Peak
2500	42.31	29.30	3.56	34.03	41.14	74.00	-32.86	H	Peak
2483.5	45.86	29.28	3.53	34.03	44.64	74.00	-29.36	V	Peak
2500	55.43	29.30	3.56	34.03	54.26	74.00	-19.74	V	Peak
2483.5	41.35	29.28	3.53	34.03	40.13	54.00	-13.87	H	AV
2500	34.25	29.30	3.56	34.03	33.08	54.00	-20.92	H	AV
2483.5	41.42	29.28	3.53	34.03	40.20	54.00	-13.80	V	AV
2500	34.73	29.30	3.56	34.03	33.56	54.00	-20.44	V	AV



7 Band Edge Measurement

Test Requirement	: Section 15.247(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247 (d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


7.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold




7.2 Test Result

Low Band Edge Plot on Channel 00



High Band Edge Plot on Channel 39





8 6dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013


Test Limit : Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

8.2 Test Result

Channel number	Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)
00	2402	656.8	>500
19	2440	656.5	>500
39	2480	661.3	>500



2402



2440



2480



9 Maximum Peak Output Power

Test Requirement : FCC CFR47 Part 15 Section 15.247

Test Method : ANSI C63.10:2013

Test Limit : Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

9.1 Test Procedure

1. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Measure the conducted output power and record the results in the test report.

9.2 Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-4.41	≤30	PASS
		2440	-3.18	≤30	PASS
		2480	-2.34	≤30	PASS



BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480



10 Power Spectral density

Test Requirement	: FCC CFR47 Part 15 Section 15.247
Test Method	: ANSI C63.10:2013
Test Limit	: Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.

10.2 Test Result

Channel number	Channel frequency (MHz)	Measurement level (dBm)	Required Limit (dBm/3kHz)	Pass/Fail
		PSD/3kHz		
00	2402	-23.54	8	PASS
19	2440	-22.18	8	PASS
39	2480	-21.39	8	PASS



2402



2440



2480


11 Antenna Application

11.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2 Result

The EUT'S antenna, permanent attached antenna, is PCB antenna. The antenna's gain is 0dBi and meets the requirement.



BLE Module

12 Test set-up


Conducted Emission



Radiated Spurious Emissions From 30MHz-1000MHz




Above 1GHz





13 EUT PHOTOS






























*****THE END REPORT*****