



Appendix A

RF Test Data for BLE (Conducted Measurement)

Product Name: ARKROCKET CURIOSITY TURNTABLE

Test Model: AR108A

Environmental Conditions

Temperature:	23.5° C
Relative Humidity:	52.2%
ATM Pressure:	100.0 kPa
Test Engineer:	Ling Zhu
Supervised by:	Li Huan




A.1 6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	6 dB Bandwidth (MHz)	Limit 6 dB Bandwidth (MHz)	Verdict
NVNT	BLE 1M	2402	Ant1	0.7	0.5	Pass
NVNT	BLE 1M	2440	Ant1	0.734	0.5	Pass
NVNT	BLE 1M	2480	Ant1	0.711	0.5	Pass





Test Graphs

6dB Bandwidth NVNT BLE 1M 2402MHz Ant1



6dB Bandwidth NVNT BLE 1M 2440MHz Ant1








A.2 Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Total Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE 1M	2402	Ant1	-1.01	30	Pass
NVNT	BLE 1M	2440	Ant1	0.41	30	Pass
NVNT	BLE 1M	2480	Ant1	1.01	30	Pass





Test Graphs

Power NVNT BLE 1M 2402MHz Ant1



Power NVNT BLE 1M 2440MHz Ant1








A.3 Maximum Power Spectral Density

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	BLE 1M	2402	Ant1	-16.6	0	-16.6	8	Pass
NVNT	BLE 1M	2440	Ant1	-15.1	0	-15.1	8	Pass
NVNT	BLE 1M	2480	Ant1	-14.42	0	-14.42	8	Pass





Test Graphs

PSD NVNT BLE 1M 2402MHz Ant1



PSD NVNT BLE 1M 2440MHz Ant1








A.4 Band edge measurements

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-52.58	-20	Pass
NVNT	BLE 1M	2480	Ant1	-53.58	-20	Pass




Test Graphs

Band Edge NVNT BLE 1M 2402MHz Ant1 Ref




Band Edge NVNT BLE 1M 2402MHz Ant1 Emission






Band Edge NVNT BLE 1M 2480MHz Ant1 Ref



Band Edge NVNT BLE 1M 2480MHz Ant1 Emission






A.5 Conducted Spurious Emission


Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE 1M	2402	Ant1	-50.04	-20	Pass
NVNT	BLE 1M	2440	Ant1	-56.93	-20	Pass
NVNT	BLE 1M	2480	Ant1	-49.98	-20	Pass

Test Graphs

Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2402MHz Ant1 Emission






Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Ref




Tx. Spurious NVNT BLE 1M 2440MHz Ant1 Emission






Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 1M 2480MHz Ant1 Emission






A.6 Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	BLE 1M	2402	Ant1	85.16	0.7	0.47
NVNT	BLE 1M	2440	Ant1	85.16	0.7	0.47
NVNT	BLE 1M	2480	Ant1	85.16	0.7	0.47

Test Graphs

Duty Cycle NVNT BLE 1M 2402MHz Ant1



Duty Cycle NVNT BLE 1M 2440MHz Ant1






A.7 Emissions in Restricted Bands


Condition	Mode	Frequency (MHz)	Antenna	Spur Freq (MHz)	Power (dBm)	Gain (dBi)	E (dBuV/m)	Detector	Limit (dBuV/m)	Verdict
NVNT	BLE 1M	2402	Ant1	2310	-50.96	2	46.3	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2310	-60.36	2	36.9	Average	54	Pass
NVNT	BLE 1M	2402	Ant1	2355.216	-45.11	2	52.15	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2354.064	-55.13	2	42.13	Average	54	Pass
NVNT	BLE 1M	2402	Ant1	2390	-48.4	2	48.86	Peak	74	Pass
NVNT	BLE 1M	2402	Ant1	2390	-58.1	2	39.16	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2483.5	-47.97	2	49.29	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2483.5	-58.2	2	39.06	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2496.04	-43.75	2	53.51	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2499.616	-55.46	2	41.8	Average	54	Pass
NVNT	BLE 1M	2480	Ant1	2500	-45.5	2	51.76	Peak	74	Pass
NVNT	BLE 1M	2480	Ant1	2500	-55.77	2	41.49	Average	54	Pass


Test Graphs

Restrict Band NVNT BLE 1M 2402MHz Ant1 Peak



Restrict Band NVNT BLE 1M 2402MHz Ant1 Average





Restrict Band NVNT BLE 1M 2480MHz Ant1 Average

