FCC TEST REPORT

FOR

Shenzhen SOYES Premium Technology limited

Mini smartphone

Test Model: XS19Pro

Additional Model No.: Please Refer to Page 7

Prepared for	:	Shenzhen SOYES Premium Technology limited
Address	:	Building 521, 305, Bagualing Industrial Zone, 255Baguagsan Road, Hualin Community, Yuanling, Futian Shenzhen.518000 China
Prepared by	:	Shenzhen LCS Compliance Testing Laboratory Ltd.
Address	:	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample	:	March 21, 2025
Number of tested samples	:	2
Sample No.	:	A250317046-1, A250317046-2
Serial number	:	Prototype
Date of Test	:	March 21, 2025 ~ April 08, 2025
Date of Report	:	April 09, 2025

FCC TEST REPORT
FCC Part 22 /Part 24

Report Reference No. ..... :	**LCSA03205190EE**
FCC ID. ..... :	**2A5MW-SEKO**
Date of Issue. ..... :	**April 09, 2025**
Testing Laboratory Name ..... :	**Shenzhen LCS Compliance Testing Laboratory Ltd.**
Address ..... :	101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
Applicant's name ..... :	**Shenzhen SOYES Premium Technology limited**
Address ..... :	Building 521, 305, Bagualing Industrial Zone, 255Baguagsan Road, Hualin Community, Yuanling, Futian Shenzhen.518000 China
Test specification ..... **:**	
Standard ..... :	**FCC Part 22: Public Mobile Services** **FCC Part 24: Personal Communication Services**
Test Report Form No ..... :	TRF-4-E-151 A/0
TRF Originator ..... :	Shenzhen LCS Compliance Testing Laboratory Ltd.
Master TRF ..... :	Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description ..... :	**Mini smartphone**
Trade Mark ..... :	SOYES
Test Model ..... :	XS19Pro
Ratings ..... :	Input: 5V⎓2A DC 3.85V by Rechargeable Li-ion Battery, 2000mAh
Frequency	GSM 850MHz; PCS 1900MHz
Result ..... :	**PASS**

Compiled by:	**Supervised by:**	**Approved by:**
Joker Hu/Administrator	Jack Liu/ Technique principal	Gavin Liang/ Manager

TEST REPORT

Test Report No. : LCSA03205190EE	April 09, 2025 Date of issue

EUT.....	: Mini smartphone
Test Model.....	: XS19Pro
Applicant.....	**: Shenzhen SOYES Premium Technology limited**
Address.....	: Building 521, 305, Bagualing Industrial Zone, 255Baguagsan Road, Hualin Community, Yuanling, Futian Shenzhen.518000 China
Telephone.....	: /
Fax.....	: /
Manufacturer.....	**: Shenzhen SOYES Premium Technology limited**
Address.....	: Building 521, 305, Bagualing Industrial Zone, 255Baguagsan Road, Hualin Community, Yuanling, Futian Shenzhen.518000 China
Telephone.....	: /
Fax.....	: /
Factory.....	**: Shenzhen SOYES Premium Technology limited**
Address.....	: Building 521, 305, Bagualing Industrial Zone, 255Baguagsan Road, Hualin Community, Yuanling, Futian Shenzhen.518000 China
Telephone.....	: /
Fax.....	: /

Test Result:	**PASS**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revison History

Report Version	Issue Date	Revision Content	Revised By
000	April 09, 2025	Initial Issue	---

Contents

1 TEST STANDARDS 6

2 SUMMARY 7

2.1 Product Description 7
2.2 Equipment under Test 9
2.3 Short description of the Equipment under Test (EUT) 9
2.4 Support equipment List 9
2.5 External I/O Cable 9
2.6 Normal Accessory setting 9
2.7 Test Sample 10
2.8 EUT configuration 10
2.9 Related Submittal(s) / Grant (s) 10
2.10 Modifications 10
2.11 General Test Conditions/Configurations 10

3 TEST ENVIRONMENT 11

3.1 Address of the test laboratory 11
3.2 Test Facility 11
3.3 Environmental conditions 11
3.4 Test Description 12
3.5 Equipments Used during the Test 13
3.6 Measurement uncertainty 14

4 TEST CONDITIONS AND RESULTS 15

4.1 Output Power 15
4.2 Radiated Spurious Emssion 19
4.3 Occupied Bandwidth and Emission Bandwidth 23
4.4 Band Edge Complicance 26
4.5 Spurious Emission on Antenna Port 29
4.6 Frequency Stability Test 39
4.7 Peak-to-Average Ratio (PAR) 42

5 TEST SETUP PHOTOGRAPHS OF EUT 45

6 EXTERIOR PHOTOGRAPHS OF THE EUT 45

7 INTERIOR PHOTOGRAPHS OF THE EUT 45

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Part 22 (10-1-16 Edition): Cellular Radiotelephone Service.
FCC Part 24(10-1-16 Edition): Broadband PCS.
ANSI/TIA-603-E-2016: Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.
47 CFR FCC Part 15 Subpart B: Unintentional Radiators.
FCC Part 2: Frequency Allocations And Radio Treaty Matters: General Rules And Regulations.
ANSI C63.4:2014: Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
ANSI C63.26-2015: Compliance Testing of Transmitters Used in Licensed Radio Services.
FCC KDB971168 D01 Power Meas License Digital Systems v03r01.

2 SUMMARY

2.1 Product Description

The **Shenzhen SOYES Premium Technology limited**'s Model: XS19Pro or the "EUT" as referred to in this report; more general information as follows, for more details, refer to the user's manual of the EUT.

EUT	:	Mini smartphone
Test Model	:	XS19Pro
Additional Model No.	:	XS19,X19Max,N95,N95Pro,N90,XS36,XS36Max,S24,S24+,S24Max,X6Pro,X8Pro,14Pro
Model Declaration	:	PCB board, structure and internal of these model(s) are the same, Only the colors are different, So no additional models were tested
Ratings	:	Input: 5V⎓2A DC 3.85V by Rechargeable Li-ion Battery, 2000mAh
Hardware Version	:	R62_MB_V2.0
Software Version	:	R62K3Q1N_SYE_C11_XS19Pro_SOYES_M02
Bluetooth	:	
Frequency Range	:	2402MHz~2480MHz
Channel Number	:	79 channels for Bluetooth V5.0 (DSS) 40 channels for Bluetooth V5.0 (DTS)
Channel Spacing	:	1MHz for Bluetooth V5.0 (DSS) 2MHz for Bluetooth V5.0 (DTS)
Modulation Type	:	GFSK, π/4-DQPSK, 8-DPSK for Bluetooth V5.0 (DSS) GFSK for Bluetooth V5.0 (DTS)
Bluetooth Version	:	V5.0
Antenna Description	:	PIFA Antenna, 2.41dBi(Max.)
WIFI(2.4G Band)	:	
Frequency Range	:	2412MHz~2462MHz
Channel Spacing	:	5MHz
Channel Number	:	11 Channels for 20MHz bandwidth (2412~2462MHz)
Modulation Type	:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Antenna Description	:	PIFA Antenna, 2.41dBi(Max.)
2G	:	
Support Band	:	☒GSM 850 (U.S.-Band) ☒PCS 1900 (U.S.-Band)
Release Version	:	R9
GPRS Class	:	Class 12
EGPRS Class	:	Class 12
Type Of Modulation	:	GMSK for GSM/GPRS; GMSK/8PSK for EGPRS
Antenna Description	:	PIFA Antenna -1.62dBi (max.) For GSM 850 -1.68dBi (max.) For PCS 1900
3G	:	
Support Band	:	☒WCDMA Band II (U.S.-Band) ☒WCDMA Band IV (U.S.-Band) ☒WCDMA Band V (U.S.-Band)
Release Version	:	R8
Type Of Modulation	:	QPSK, 16QAM
Antenna Description	:	PIFA Antenna

	1.68dBi (max.) For WCDMA Band II -1.63dBi (max.) For WCDMA Band IV -1.62dBi (max.) For WCDMA Band V
LTE	:
Support Band	: ☒E-UTRA Band 2(U.S.-Band) ☒E-UTRA Band 4(U.S.-Band) ☒E-UTRA Band 5(U.S.-Band) ☒E-UTRA Band 7(U.S.-Band) ☒E-UTRA Band 12(U.S.-Band)
LTE Release Version	: R9
Type Of Modulation	: QPSK/16QAM
Antenna Description	: PIFA Antenna -1.68dBi (max.) For E-UTRA Band 2 -1.66dBi (max.) For E-UTRA Band 4 -1.62dBi (max.) For E-UTRA Band 5 -1.35dBi (max.) For E-UTRA Band 7 -1.81dBi (max.) For E-UTRA Band 12
Power Class	: Class 3
GPS function	: Support and only RX
FM function	: Support and only RX
Extreme temp. Tolerance	: -30°C to +50°C
Extreme vol. Limits	: 3.3VDC to 4.4VDC (nominal: 3.85VDC)

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

2.2 Equipment under Test

Power supply system utilised

Power supply voltage	:	●	120V / 60 Hz	○	115V / 60Hz
		○	12 V DC	○	24 V DC
		○	Other (specified in blank below)		

Test frequency list

Test Mode	TX/RX	RF Channel		
		Low(L)	Middle (M)	High (H)
GSM850	TX	Channel 128	Channel 190	Channel 251
		824.2 MHz	836.6 MHz	848.8 MHz
	RX	Channel 128	Channel 190	Channel 251
		869.2 MHz	881.6 MHz	893.8 MHz
Test Mode	TX/RX	RF Channel		
		Low(L)	Middle (M)	High (H)
PCS1900	TX	Channel 512	Channel 661	Channel 810
		1850.2 MHz	1880.0 MHz	1909.8 MHz
	RX	Channel 512	Channel 661	Channel 810
		1930.2 MHz	1960.0 MHz	1989.8 MHz

2.3 Short description of the Equipment under Test (EUT)

2.3.1 General Description

Mini smartphone is subscriber equipment in the BT/BLE/2.4GWIFI/GSM/WCDMA/LTE system. GSM/GPRS/EGPRS frequency band is Band II/V. The HSPA/UMTS frequency band is Band II/IV/V. LTE frequency band is band 2/4/5/7/12. The HSPA/UMTS frequency band II and Band IV and Band V test data included in this report. The Mini smartphone implements such functions as RF signal receiving/transmitting, GSM/GPRS/EGPRS/ HSPA/UMTS/LTE protocol processing, video MMS service and etc. Externally it provides SIM card interface.

2.4 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN TIANYIN ELECTRONICS CO., LTD	Power Adapter	TPA-46050200UU	---	FCC

Note: The adapter is supplied by lab and only use tested.

2.5 External I/O Cable

I/O Port Description	Quantity	Cable
Type-C USB Port	1	N/A

2.6 Normal Accessory setting

Fully charged battery was used during the test.

2.7 Test Sample

The application provides 2 samples to meet requirement;

Sample Number	Description
Sample 1(A250317046-1)	Engineer sample – continuous transmit
Sample 2(A250317046-2)	Normal sample – Intermittent transmit

2.8 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- ● - supplied by the manufacturer
- ○ - supplied by the lab

○	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
○	Multimeter	Manufacturer :	/
		Model No. :	/

2.9 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2A5MW-SEKO** filing to comply with FCC Part 22 and Part 24 Rules.

2.10 Modifications

No modifications were implemented to meet testing criteria.

2.11 General Test Conditions/Configurations

2.11.1 Test Modes

NOTE: The test mode(s) are selected according to relevant radio technology specifications.

Test Mode	Test Modes Description
GSM/TM1	GSM system, GSM, GMSK modulation
GSM/TM2	GSM system, GPRS, GMSK modulation
GSM/TM3	GSM system, EDGE, GMSK, 8PSK modulation

Note:

1. As GSM and GPRS with the same emission designator, test result recorded in this report at the worst case GSM/TM1 only after exploratory scan.

2.11.2 Test Environment

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Temperature	TN	Ambient
Voltage	VL	DC 3.3V
	VN	DC 3.85V
	VH	DC 4.4V

NOTE: VL=lower extreme test voltage VN=nominal voltage
VH=upper extreme test voltage TN=normal temperature

3 TEST ENVIRONMENT

3.1 Address of the test laboratory

Shenzhen LCS Compliance Testing Laboratory Ltd

101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China
The sites are constructed in conformance with the requirements of ANSI C63.4 (2014) and CISPR Publication 22.

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024.

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912

3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4 Test Description

3.4.1 Cellular Band (824-849MHz paired with 869-894MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §22.913	FCC: ERP ≤ 7W.	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §22.917	≤-13dBm/1%*EBW, in 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §22.917	≤ -13dBm/100kHz, from 9kHz to 10th harmonics but outside authorized operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §22.917	≤ -13dBm/100kHz.	Pass
Frequency Stability	§2.1055, §22.355	≤ ±2.5ppm.	Pass
Peak-Average Ratio	§22.913	FCC:Limit≤13dB	N/A
Receiver Spurious Emissions	N/A	--	Pass
NOTE 1: For the verdict, the “N/A” denotes “not applicable”, the “N/T” de notes “not tested”.			

3.4.2 PCS Band (1850-1910MHz paired with 1930-1990MHz)

Test Item	FCC Rule No.	Requirements	Verdict
Effective(Isotropic) Radiated Output Power	§2.1046, §24.232	EIRP ≤ 2W	Pass
Peak-Average Ratio	§2.1046, §24.232	≤13dB	Pass
Modulation Characteristics	§2.1047	Digital modulation	N/A
Bandwidth	§2.1049	OBW: No limit. EBW: No limit.	Pass
Band Edges Compliance	§2.1051, §24.238	≤ -13dBm/1%*EBW, In 1MHz bands immediately outside and adjacent to The frequency block.	Pass
Spurious Emission at Antenna Terminals	§2.1051, §24.238	≤-13dBm/1MHz, from 9kHz to10th harmonics but outside authorized Operating frequency ranges.	Pass
Field Strength of Spurious Radiation	§2.1053, §24.238	≤ -13dBm/1MHz.	Pass
Frequency Stability	§2.1055, §24.235	≤ ±2.5ppm.	Pass
Peak-Average Ratio	§24.232	FCC:Limit≤13dB	Pass
Receiver Spurious Emissions	N/A	--	Pass
NOTE 1: For the verdict, the “N/A” denotes “not applicable”, the “N/T” de notes “not tested”.			

Remark: The measurement uncertainty is not included in the test result.

3.5 Equipments Used during the Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Power Meter	R&S	NRVS	100444	2024-06-06	2025-06-05
2	Power Sensor	R&S	NRV-Z81	100458	2024-06-06	2025-06-05
3	Power Sensor	R&S	NRV-Z32	10057	2024-06-06	2025-06-05
4	LTE Test Software	Tonscend	JS1120-1	N/A	N/A	N/A
5	RF Control Unit	Tonscend	JS0806-1	158060009	2024-11-08	2025-11-07
6	MXA Signal Analyzer	Agilent	N9020A	MY51250905	2024-10-08	2025-10-07
7	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW 500	103818	2024-06-06	2025-06-05
8	DC Power Supply	Agilent	E3642A	N/A	2024-10-08	2025-10-07
9	EMI Test Software	AUDIX	E3	/	N/A	N/A
10	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2024-06-06	2025-06-05
11	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
12	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2024-07-13	2027-07-12
13	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2024-08-03	2027-08-02
14	By-log Antenna	SCHWARZBECK	VULB9163	9163-471	2024-08-03	2027-08-02
15	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2024-07-13	2027-07-12
16	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1926	2024-07-13	2027-07-12
17	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2024-07-13	2027-07-12
18	Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	792	2024-07-13	2027-07-12
19	Broadband Preamplifier	SCHWARZBECK	BBV9719	9719-025	2024-07-30	2025-07-29
20	EMI Test Receiver	R&S	ESR 7	101181	2024-06-06	2025-06-05
21	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2024-06-06	2025-06-05
22	Low-frequency amplifier	SchwarzZBECK	BBV9745	00253	2024-10-08	2025-10-07
23	High-frequency amplifier	JS Denki Pte	PA0118-43	JSPA21009	2024-10-08	2025-10-07
24	6dB Attenuator	/	100W/6dB	1172040	2024-06-06	2025-06-05
25	3dB Attenuator	/	2N-3dB	/	2024-10-08	2025-10-07
26	Temperature & Humidity Chamber	Baro	/	/	2024-06-12	2025-06-11
27	EMI Test Software	Farad	EZ	/	N/A	N/A
28	RADIO COMMUNICATION TESTER	R&S	CMU 200	105988	2024-06-06	2025-06-05
29	Antenna Mast	Max-Full	MFA-515BSN	1308572	N/A	N/A

3.6 Measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to ETSI TR 100 028 " Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics" and is documented in the Shenzhen LCS Compliance Testing Laboratory Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen LCS Compliance Testing Laboratory Ltd. is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	3.10 dB	(1)
Radiated Emission	1~18GHz	3.80 dB	(1)
Radiated Emission	18-40GHz	3.90 dB	(1)
Conducted Disturbance	0.15~30MHz	1.63 dB	(1)
Conducted Power	9KHz~18GHz	0.61 dB	(1)
Spurious RF Conducted Emission	9KHz~40GHz	1.22 dB	(1)
Band Edge Compliance of RF Emission	9KHz~40GHz	1.22 dB	(1)
Occuiped Bandwidth	9KHz~40GHz	-	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4 TEST CONDITIONS AND RESULTS

4.1 Output Power

TEST APPLICABLE

During the process of testing, the EUT was controlled via R&S Digital Radio Communication tester (CMU200) to ensure max power transmission and proper modulation. This result contains output power and EIRP measurements for the EUT. In all cases, output power is within the specified limits.

4.1.1 Conducted Output Power

TEST CONFIGURATION



TEST PROCEDURE

Conducted Power Measurement:

a) Place the EUT on a bench and set it in transmitting mode.
b) Connect a low loss RF cable from the antenna port to a CMU200 by an Att.
c) EUT Communicate with CMU200 then selects a channel for testing.
d) Add a correction factor to the display CMU200, and then test.

TEST RESULTS

GSM 850		Burst Average Conducted power (dBm)		
		Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8
GSM		32.70	32.73	32.66
GPRS (GMSK)	1TX slot	32.55	32.58	32.48
	2TX slot	30.97	31.02	30.97
	3TX slot	29.46	29.49	29.44
	4TX slot	27.97	27.98	27.99
EDGE (8PSK)	1TX slot	25.99	26.03	25.95
	2TX slot	24.47	24.51	24.47
	3TX slot	22.96	23.02	22.95
	4TX slot	21.47	21.50	21.49

PCS 1900		Burst Average Conducted power (dBm)		
		Channel/Frequency(MHz)		
		512/1850.2	661/1880	810/1909.8
GSM		29.67	29.73	29.65
GPRS (GMSK)	1TX slot	29.52	29.54	29.49
	2TX slot	27.99	28.02	27.93
	3TX slot	26.45	26.51	26.44
	4TX slot	24.95	25.01	24.95
EDGE (8PSK)	1TX slot	25.46	25.52	25.42
	2TX slot	23.98	24.02	23.96
	3TX slot	22.48	22.50	22.46
	4TX slot	20.99	21.02	20.97

4.1.2 Radiated Output Power

TEST DESCRIPTION

This is the test for the maximum radiated power from the EUT.
Per rule Part 24.232(c) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(e) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage."
Per rule Part 22.913(a) specifies " The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test.Set Test Receiver or Spectrum RBW=1MHz,VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution

antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}) ,the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
   The measurement results are obtained as described below:
   Power(EIRP)=P_{Mea}+ P_{Ag} - P_{cl} + G_a
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP-2.15dBi.

TEST LIMIT

According to 22.913(a), 24.232(c) , the ERP should be not exceed following table limits:

GSM850(GPRS850,EDGE850)		
Function	Power Step	Burst Peak ERP (dBm)
GSM	5	FCC: ≤38.45dBm (7W)
GPRS	3	FCC: ≤38.45dBm (7W)
EDGE	8	FCC: ≤38.45dBm (7W)

PCS1900(GPRS1900,EDGE1900)		
Function	Power Step	Burst Peak EIRP (dBm)
GSM	0	≤33.01dBm (2W)
GPRS	3	≤33.01dBm (2W)
EDGE	2	≤33.01dBm (2W)

TEST RESULTS

Remark:

1. *We were tested all Configuration refer 3GPP TS151 010.*
2. *EIRP=P_{Mea}(dBm)-P_{cl}(dB)+P_{Ag}(dB)+G_a(dBi)*
3. *ERP = EIRP – 2.15dBi as EIRP by subtracting the gain of the dipole.*
4. *Margin = Emission Level - Limit*
5. *We tested the worst-case records for H and V directions, and only the worst-case records for V direction were recorded in the report.*

GSM/TM1/GSM850

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	Correction (dB)	P_{Ag} (dB)	Burst Average ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.20	-7.06	3.45	8.45	2.15	33.79	**29.58**	38.45	-8.87	V
836.60	-7.02	3.49	8.45	2.15	33.85	**29.64**	38.45	-8.81	V
848.80	-6.95	3.55	8.36	2.15	33.88	**29.59**	38.45	-8.86	V

GSM/TM3/EDGE850

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	Correction (dB)	P_{Ag} (dB)	Burst Average ERP (dBm)	Limit (dBm)	Margin (dB)	Polarization
824.20	-11.95	3.45	8.45	2.15	33.79	**24.69**	38.45	-13.76	V
836.60	-11.93	3.49	8.45	2.15	33.85	**24.73**	38.45	-13.72	V
848.80	-12.05	3.55	8.36	2.15	33.88	**24.49**	38.45	-13.96	V

GSM/TM1/PCS1900

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.20	-12.10	4.03	8.38	35.51	**27.76**	33.01	-5.25	V
1880.00	-11.96	4.08	8.33	35.56	**27.85**	33.01	-5.16	V
1909.80	-11.97	4.14	8.26	35.63	**27.78**	33.01	-5.23	V

GSM/TM3/EDGE1900

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	G_a Antenna Gain(dB)	P_{Ag} (dB)	Burst Average EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.20	-17.09	4.03	8.38	35.51	**22.77**	33.01	-10.24	V
1880.00	-17.04	4.08	8.33	35.56	**22.77**	33.01	-10.24	V
1909.80	-17.01	4.14	8.26	35.63	**22.74**	33.01	-10.27	V

4.2 Radiated Spurious Emssion

TEST APPLICABLE

According to the TIA/EIA 603D:2010 and FCC Part 2.1033 test method, The Receiver or Spectrum was scanned from lowest frequency frequency generated within the equipment to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set as outlined in Part 24.238, Part 22.917, RSS-132 §5.5 and RSS-133 §6.5. The spectrum is scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of PCS1900 and GSM850.

TEST CONFIGURATION



TEST PROCEDURE

1. EUT was placed on a 1.50 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.50 m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
2. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
3. The EUT is then put into continuously transmitting mode at its maximum power level during the test.Set Test Receiver or Spectrum RBW=1MHz,VBW=3MHz, And the maximum value of the receiver should be recorded as (P_r).
4. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

5. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}) ,the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
   The measurement results are obtained as described below:
   Power(EIRP)=P_{Mea}+ P_{Ag} - P_{cl} + G_a
6. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
7. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dBi.
8. In order to make sure test results more clearly,we set frequency range and sweep time for difference frequency range as follows table:

Working Frequency	Subrange (GHz)	RBW	VBW	Sweep time (s)
TM1/GSM 850	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~10	1 MHz	3 MHz	3
TM1/PCS 1900	0.00009~0.15	1KHz	3KHz	30
	0.00015~0.03	10KHz	30KHz	10
	0.03~1	100KHz	300KHz	10
	1~2	1 MHz	3 MHz	2
	2~5	1 MHz	3 MHz	3
	5~8	1 MHz	3 MHz	3
	8~11	1 MHz	3 MHz	3
	11~14	1 MHz	3 MHz	3
	14~18	1 MHz	3 MHz	3
	18~20	1 MHz	3 MHz	2

TEST LIMITS

According to 24.238 and 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Frequency	Channel	Frequency Range	Verdict
TM1/GSM 850	Low	9KHz -10GHz	PASS
	Middle	9KHz -10GHz	PASS
	High	9KHz -10GHz	PASS
TM1/PCS 1900	Low	9KHz -20GHz	PASS
	Middle	9KHz -20GHz	PASS
	High	9KHz -20GHz	PASS

TEST RESULTS

Remark:
1. *We were tested all refer 3GPP TS151 010.*
2. *EIRP=P_{Mea}(dBm)-P_{cl}(dB) +G_a(dBi)*
3. *We were not recorded other points as values lower than limits.*
4. *Margin = EIRP - Limit*

GSM/TM1/GSM850_ Low Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.40	-43.21	3.86	3.00	8.56	-38.51	-13.00	-25.51	H
2472.60	-44.43	4.29	3.00	6.98	-41.74	-13.00	-28.74	H
1648.40	-39.83	3.86	3.00	8.56	-35.13	-13.00	-22.13	V
2472.60	-42.19	4.29	3.00	6.98	-39.50	-13.00	-26.50	V

GSM/TM1/GSM850_ Middle Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.20	-42.06	3.9	3.00	8.58	-37.38	-13.00	-24.38	H
2509.80	-46.54	4.32	3.00	6.8	-44.06	-13.00	-31.06	H
1673.20	-37.35	3.9	3.00	8.58	-32.67	-13.00	-19.67	V
2509.80	-43.33	4.32	3.00	6.8	-40.85	-13.00	-27.85	V

GSM/TM1/GSM850_ High Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.60	-46.48	3.91	3.00	9.06	-41.33	-13.00	-28.33	H
2546.40	-49.34	4.32	3.00	6.65	-47.01	-13.00	-34.01	H
1697.60	-42.97	3.91	3.00	9.06	-37.82	-13.00	-24.82	V
2546.40	-44.67	4.32	3.00	6.65	-42.34	-13.00	-29.34	V

GSM/TM3/EDGE850_ Low Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1648.40	-45.07	3.86	3.00	8.56	-40.37	-13.00	-27.37	H
2472.60	-46.61	4.29	3.00	6.98	-43.92	-13.00	-30.92	H
1648.40	-41.84	3.86	3.00	8.56	-37.14	-13.00	-24.14	V
2472.60	-44.35	4.29	3.00	6.98	-41.66	-13.00	-28.66	V

GSM/TM3/EDGE850_ Middle Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1673.20	-44.01	3.9	3.00	8.58	-39.33	-13.00	-26.33	H
2509.80	-48.79	4.32	3.00	6.8	-46.31	-13.00	-33.31	H
1673.20	-39.65	3.9	3.00	8.58	-34.97	-13.00	-21.97	V
2509.80	-45.33	4.32	3.00	6.8	-42.85	-13.00	-29.85	V

GSM/TM3/EDGE850_ High Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1697.60	-48.69	3.91	3.00	9.06	-43.54	-13.00	-30.54	H
2546.40	-51.38	4.32	3.00	6.65	-49.05	-13.00	-36.05	H
1697.60	-45.40	3.91	3.00	9.06	-40.25	-13.00	-27.25	V
2546.40	-46.97	4.32	3.00	6.65	-44.64	-13.00	-31.64	V

GSM/TM1/PCS1900_ Low Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.40	-45.25	5.26	3.00	9.88	-40.63	-13.00	-27.63	H
5550.60	-46.44	6.11	3.00	11.36	-41.19	-13.00	-28.19	H
3700.40	-41.46	5.26	3.00	9.88	-36.84	-13.00	-23.84	V
5550.60	-43.75	6.11	3.00	11.36	-38.50	-13.00	-25.50	V

GSM/TM1/PCS1900_ Middle Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.00	-44.18	5.32	3.00	10.03	-39.47	-13.00	-26.47	H
5640.00	-48.07	6.19	3.00	11.41	-42.85	-13.00	-29.85	H
3760.00	-39.70	5.32	3.00	10.03	-34.99	-13.00	-21.99	V
5640.00	-44.93	6.19	3.00	11.41	-39.71	-13.00	-26.71	V

GSM/TM1/PCS1900_ High Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.60	-48.93	5.36	3.00	9.62	-44.67	-13.00	-31.67	H
5729.40	-51.73	6.24	3.00	11.46	-46.51	-13.00	-33.51	H
3819.60	-45.26	5.36	3.00	9.62	-41.00	-13.00	-28.00	V
5729.40	-46.77	6.24	3.00	11.46	-41.55	-13.00	-28.55	V

GSM/TM3/EDGE1900_ Low Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3700.40	-46.91	5.26	3.00	9.88	-42.29	-13.00	-29.29	H
5550.60	-48.20	6.11	3.00	11.36	-42.95	-13.00	-29.95	H
3700.40	-43.98	5.26	3.00	9.88	-39.36	-13.00	-26.36	V
5550.60	-46.11	6.11	3.00	11.36	-40.86	-13.00	-27.86	V

GSM/TM3/EDGE1900_ Middle Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3760.00	-45.50	5.32	3.00	10.03	-40.79	-13.00	-27.79	H
5640.00	-50.16	6.19	3.00	11.41	-44.94	-13.00	-31.94	H
3760.00	-41.16	5.32	3.00	10.03	-36.45	-13.00	-23.45	V
5640.00	-46.67	6.19	3.00	11.41	-41.45	-13.00	-28.45	V

GSM/TM3/EDGE1900_ High Channel

Frequency (MHz)	P_{Mea} (dBm)	P_{cl} (dB)	Diatance	G_a Antenna Gain(dB)	Peak EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
3819.60	-50.64	5.36	3.00	9.62	-46.38	-13.00	-33.38	H
5729.40	-53.31	6.24	3.00	11.46	-48.09	-13.00	-35.09	H
3819.60	-47.26	5.36	3.00	9.62	-43.00	-13.00	-30.00	V
5729.40	-49.43	6.24	3.00	11.46	-44.21	-13.00	-31.21	V

4.3 Occupied Bandwidth and Emission Bandwidth

TEST APPLICABLE

Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of PCS1900 band and GSM850 band. The table below lists the measured 99% Bandwidth
and -26dBc Bandwidth.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The Occupied bandwidth and Emission Bandwidth were measured with Spectrum AnalyzerN9020A;
3. Set RBW=5.1KHz,VBW=15KHz,Span=1MHz,SWT=Auto;
4. Set SPA Max hold and View, Set 99% Occupied Bandwidth/ Set -26dBc Occupied Bandwidth
5. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (Low, middle and high of operational frequency range).

TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Occupied Bandwidth (99% BW) (MHz)	Emission Bandwidth (-26 dBc BW) (MHz)	Verdict
GSM/TM1 /GSM850	128	824.2	0.24281	0.3109	PASS
	190	836.6	0.24662	0.3101	PASS
	251	848.8	0.24167	0.3139	PASS
GSM/TM3 /EDGE850	128	824.2	0.24342	0.3076	PASS
	190	836.6	0.23969	0.3110	PASS
	251	848.8	0.23832	0.2986	PASS
GSM/TM1 /PCS1900	512	1850.2	0.24222	0.3115	PASS
	661	1880.0	0.24522	0.3140	PASS
	810	1909.8	0.24358	0.3090	PASS
GSM/TM3 /EDGE1900	512	1850.2	0.23933	0.3007	PASS
	661	1880.0	0.23938	0.3015	PASS
	810	1909.8	0.23857	0.3060	PASS

Remark:
1. *Test results including cable loss;*
2. *Please refer to following plots;*

Occupied Bandwidth and Emission Bandwidth

GSM/TM1/GSM850



GSM/TM3/EDGE850



Channel 128 / 824.2 MHz



Channel 128 / 824.2 MHz



Channel 190 / 836.6 MHz



Channel 251 / 848.8 MHz



Channel 251 / 848.8 MHz

Occupied Bandwidth and Emission Bandwidth	
GSM/TM1/GSM1900	GSM/TM3/ EDGE1900
	
Channel 512 / 1850.2 MHz	Channel 512 / 1850.2 MHz
	
Channel 661 / 1880.0MHz	Channel 661 / 1880.0MHz
	
Channel 810 / 1909.8 MHz	Channel 810 / 1909.8 MHz

4.4 Band Edge Complicance

TEST APPLICABLE

During the process of testing, the EUT was controlled via Digital Radio Communication tester (CMU200) to ensure max power transmission and proper modulation.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Spectrum Analyzer N9020A;
3. Set RBW=5.1KHz,VBW=15KHz,Span=2MHz,SWT=Auto, Dector: RMS;
1. These measurements were done at 2 frequencies, 1850.20 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz and 848.80 MHz for GSM850 band. (bottom and top of operational frequency range).

TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Band Edg Compliance (dBm)	Limits (dBm)	Verdict
GSM/TM1/GSM850	128	824.2	<-13dBm	-13dBm	PASS
	251	848.8	<-13dBm	-13dBm	
GSM/TM3/EDGE850	128	824.2	<-13dBm	-13dBm	PASS
	251	848.8	<-13dBm	-13dBm	
GSM/TM1/PCS1900	512	1850.2	<-13dBm	-13dBm	PASS
	810	1909.8	<-13dBm	-13dBm	
GSM/TM3/EDGE1900	512	1850.2	<-13dBm	-13dBm	PASS
	810	1909.8	<-13dBm	-13dBm	

Remark:
1. *Test results including cable loss;*
2. *Please refer to following plots;*

Band-edge Compliance	
GSM/TM1/GSM850	GSM/TM3/EDGE850
	
Channel 128 / 824.2 MHz	Channel 128 / 824.2 MHz
	
Channel 251 / 848.8 MHz	Channel 251 / 848.8 MHz

Band-edge Compliance	
GSM/TM1/PCS1900	GSM/TM3/EDGE1900
	
Channel 512 / 1850.2 MHz	Channel 512 / 1850.2 MHz
	
Channel 810 / 1909.8 MHz	Channel 810 / 1909.8 MHz

4.5 Spurious Emission on Antenna Port

TEST APPLICABLE

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 and RSS-GEN the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 9 KHz to 20 GHz, data taken from 30 MHz to 20 GHz. For GSM850, this equates to a frequency range of 9 KHz to 9 GHz,data taken from 30 MHz to 9 GHz.
2. The sweep time is set automatically by instrument itself. That should be the optimal sweep time for the span and the RBW. If the sweep time is too short, that is sweep is too fast, the sweep result is not accurate; if the sweep time is too long, that is sweep is too low, some frequency components may be lost. The instrument will give an optimal sweep time according the selected span and RBW.
3. The procedure to get the conducted spurious emission is as follows:
   The trace mode is set to MaxHold to get the highest signal at each frequency;
   Wait 25 seconds;
   Get the result.
4. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was set up for the max output power with pseudo random data modulation;
2. The power was measured with Spectrum Analyzer N9020A;
3. These measurements were done at 3 frequencies, 1850.20 MHz, 1880.00 MHz and 1909.80 MHz for PCS1900 band; 824.20 MHz, 836.60 MHz and 848.80 MHz for GSM850 band. (Low, middle and high of operational frequency range).

TEST LIMIT

Part 24.238, Part 22.917 specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.
The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

TEST RESULTS

Test Mode	Channel	Frequency (MHz)	Spurious RF Conducted Emission (dBm)	Limits (dBm)	Verdict
GSM/TM1/GSM850	128	824.2	<-13dBm	-13dBm	PASS
	190	836.6	<-13dBm	-13dBm	
	251	848.8	<-13dBm	-13dBm	
GSM/TM3/EDGE850	128	824.2	<-13dBm	-13dBm	PASS
	190	836.6	<-13dBm	-13dBm	
	251	848.8	<-13dBm	-13dBm	
GSM/TM1/PCS1900	512	1850.2	<-13dBm	-13dBm	PASS
	661	1880.0	<-13dBm	-13dBm	
	810	1909.8	<-13dBm	-13dBm	
GSM/TM3/EDGE1900	512	1850.2	<-13dBm	-13dBm	PASS
	661	1880.0	<-13dBm	-13dBm	
	810	1909.8	<-13dBm	-13dBm	

Remark:
1. *Test results including cable loss;*
2. *Please refer to following plots;*
3. *Not reorded test plots from 9 KHz to 30 MHz as emission levels 20dB lower than emission limit;*

Spurious Emssion on Antenna Port	
GSM/TM1/GSM850	GSM/TM3/EDGE850
Channel 128 / 824.2 MHz	Channel 128 / 824.2 MHz
	
30 MHz – 1000 MHz	30 MHz – 1000 MHz
	
1 GHz – 10 GHz	1 GHz – 10 GHz
Channel 190 / 836.6 MHz	Channel 190 / 836.6 MHz
	
30 MHz – 1000 MHz	30 MHz – 1000 MHz

Spurious Emssion on Antenna Port	
GSM/TM1/GSM850	GSM/TM3/EDGE850
Channel 190 / 836.6 MHz	Channel 190 / 836.6 MHz
	
1 GHz – 10 GHz	1 GHz – 10 GHz
Channel 251 / 848.8 MHz	Channel 251 / 848.8 MHz
	
30 MHz – 1000 MHz	30 MHz – 1000 MHz
	
1 GHz – 10 GHz	1 GHz – 10 GHz

Spurious Emssion on Antenna Port	
GSM/TM1/PCS1900	
Channel 512 / 1850.2 MHz	
	
30 MHz – 1000 MHz	*1 GHz – 3 GHz*
	
3 GHz – 18 GHz	

Spurious Emssion on Antenna Port	
GSM/TM1/PCS1900	
Channel 661 / 1880 MHz	
	
30 MHz – 1000 MHz	*1 GHz – 3 GHz*
	
3 GHz – 18 GHz	

Spurious Emssion on Antenna Port	
GSM/TM1/PCS1900	
Channel 810 / 1909.8 MHz	
	
30 MHz – 1000 MHz	*1 GHz – 3 GHz*
	
3 GHz – 18 GHz	

Spurious Emssion on Antenna Port	
GSM/TM3/EDGE1900	
Channel 512 / 1850.2 MHz	
	
30 MHz – 1000 MHz	*1 GHz – 3 GHz*
	
3 GHz – 18 GHz	

Spurious Emssion on Antenna Port	
GSM/TM3/EDGE1900	
Channel 661 / 1880 MHz	
	
30 MHz – 1000 MHz	*1 GHz – 3 GHz*
	
3 GHz – 18 GHz	

Spurious Emssion on Antenna Port	
GSM/TM3/EDGE1900	
Channel 810 / 1909.8 MHz	
	
30 MHz – 1000 MHz	*1 GHz – 3 GHz*
	
3 GHz – 18 GHz	

4.6 Frequency Stability Test

TEST APPLICABLE

1. According to FCC Part 2 Section 2.1055 (a)(1), the frequency stability shall be measured with variation of ambient temperature from -30℃ to +50℃ centigrade.
2. According to FCC Part 2 Section 2.1055 (E) (2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacture.
3. Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried voltage equipment and the end voltage point was 3.3V.

TEST PROCEDURE

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a “call mode”. This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature;
2. Subject the EUT to overnight soak at -30℃;
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on middle channel of PCS 1900 and GSM850, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
4. Repeat the above measurements at 10℃ increments from -30℃ to +50℃. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 0.5 hours unpowered, to allow any self-heating to stabilize, before continuing;
6. Subject the EUT to overnight soak at +50℃;
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming;
8. Repeat the above measurements at 10℃ increments from +50℃ to -30℃. Allow at least 0.5 hours at each temperature, unpowered, before making measurements;
9. At all temperature levels hold the temperature to +/- 0.5℃ during the measurement procedure;

TEST CONFIGURATION



TEST LIMITS

For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.3VDC and 4.35VDC, with a nominal voltage of 3.8DC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

TEST RESULTS

GSM/TM1/GSM850					
DC Power	Temperature (℃)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	25	7	0.008	2.50	PASS
VN	25	44	0.053	2.50	PASS
VH	25	28	0.033	2.50	PASS
VN	-30	-12	-0.015	2.50	PASS
VN	-20	26	0.032	2.50	PASS
VN	-10	21	0.025	2.50	PASS
VN	0	15	0.018	2.50	PASS
VN	10	44	0.052	2.50	PASS
VN	20	-4	-0.005	2.50	PASS
VN	30	-31	-0.037	2.50	PASS
VN	40	4	0.005	2.50	PASS
VN	50	10	0.012	2.50	PASS

GSM/TM3/EDGE850					
DC Power	Temperature (℃)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	25	-4	-0.005	2.50	PASS
VN	25	-1	-0.001	2.50	PASS
VH	25	-21	-0.025	2.50	PASS
VN	-30	34	0.041	2.50	PASS
VN	-20	-20	-0.023	2.50	PASS
VN	-10	26	0.031	2.50	PASS
VN	0	16	0.019	2.50	PASS
VN	10	10	0.012	2.50	PASS
VN	20	0	-0.001	2.50	PASS
VN	30	1	0.001	2.50	PASS
VN	40	-46	-0.055	2.50	PASS
VN	50	-19	-0.023	2.50	PASS

GSM/TM1/PCS1900					
DC Power	Temperature (℃)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	25	0	0.000	2.50	PASS
VN	25	23	0.012	2.50	PASS
VH	25	3	0.001	2.50	PASS
VN	-30	-22	-0.012	2.50	PASS
VN	-20	-18	-0.010	2.50	PASS
VN	-10	-47	-0.025	2.50	PASS
VN	0	-50	-0.027	2.50	PASS
VN	10	-24	-0.013	2.50	PASS
VN	20	-39	-0.021	2.50	PASS
VN	30	-40	-0.021	2.50	PASS
VN	40	41	0.022	2.50	PASS
VN	50	-23	-0.012	2.50	PASS

GSM/TM3/EDGE1900					
DC Power	Temperature (℃)	Frequency error(Hz)	Frequency error(ppm)	Limit (ppm)	Verdict
VL	25	13	0.007	2.50	PASS
VN	25	-28	-0.015	2.50	PASS
VH	25	22	0.012	2.50	PASS
VN	-30	-49	-0.026	2.50	PASS
VN	-20	-35	-0.018	2.50	PASS
VN	-10	15	0.008	2.50	PASS
VN	0	-41	-0.022	2.50	PASS
VN	10	-50	-0.026	2.50	PASS
VN	20	-7	-0.004	2.50	PASS
VN	30	-29	-0.015	2.50	PASS
VN	40	-43	-0.023	2.50	PASS
VN	50	4	0.002	2.50	PASS

4.7 Peak-to-Average Ratio (PAR)

LIMIT

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE

Use spectrum to measure the total peak power and record as P_{Pk}. Use spectrum to measure the total average power and record as P_{Avg}. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm).
Determine the PAPR from:
PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).
Record the maximum PAPR level associated with a probability of 0.1%.

TEST RESULTS

Test Mode	Channel	Frequency (MHz)	PAPR Value (dB)	Limits (dB)	Verdict
GSM/TM1/GSM850	128	824.2	9.57	13.0	PASS
	190	836.6	9.66	13.0	
	251	848.8	9.44	13.0	
GSM/TM3/EDGE850	128	824.2	12.96	13.0	PASS
	190	836.6	12.85	13.0	
	251	848.8	12.76	13.0	
GSM/TM1/PCS1900	512	1850.20	9.69	13.0	PASS
	661	1880.00	9.52	13.0	
	810	1909.80	9.47	13.0	
GSM/TM3/EDGE1900	512	1850.20	12.82	13.0	PASS
	661	1880.00	12.84	13.0	
	810	1909.80	12.90	13.0	

Peak-to-Average Ratio (PAR)	
GSM/TM1/GSM850	GSM/TM3/EDGE850
	
Channel 128 / 824.2 MHz	Channel 128 / 824.2 MHz
	
Channel 190 / 836.6 MHz	Channel 190 / 836.6 MHz
	
Channel 251 / 848.8 MHz	Channel 251 / 848.8 MHz

Peak-to-Average Ratio (PAR)	
GSM/TM1/PCS1900	GSM/TM3/EDGE1900
	
Channel 512 / 1850.2 MHz	Channel 512 / 1850.2 MHz
	
Channel 661 / 1880 MHz	Channel 661 / 1880 MHz
	
Channel 810 / 1909.8 MHz	Channel 810 / 1909.8 MHz

5 TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

6 EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

7 INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

----------THE END OF TEST REPORT----------