



SAR Test Report

Report No.: STS2511135H01

Issued for

Shenzhen SOYES Premium Technology limited

Building 521, 305, Bagualing Industrial Zone, 255Baguagsan
Road, Hualin Community, Yuanling, Futian Shenzhen
518000 China

Product Name: Mini smartphone

Brand Name: SOYES

Model Name: XS19Pro

Series Model(s): XS19, XS17mini, 17Pro, XS18Pro Max,
XS17Pro, XS17, XS18mini, XS19mini,
XS19Max, XS20mini, XS14Pro, 14Pro,
14mini, XS14Pro Max

FCC ID: 2A5MW-XS19PRO

Test Standard: ANSI/IEEE Std. C95.1
FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

Max. Report Head: 0.739 W/kg
SAR (1g) Body: 1.395 W/kg

The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Shenzhen STS Test Services Co., Ltd.

**TEST REPORT CERTIFICATION**

Applicant's name : Shenzhen SOYES Premium Technology limited
Building 521, 305, Bagualing Industrial Zone, 255Baguagsan
Address : Road, Hualin Community, Yuanling, Futian Shenzhen 518000
China
Manufacturer's Name : Shenzhen SOYES Premium Technology limited
Building 521, 305, Bagualing Industrial Zone, 255Baguagsan
Address : Road, Hualin Community, Yuanling, Futian Shenzhen 518000
China

Product description

Product name : Mini smartphone
Brand name : SOYES
Model name : XS19Pro
XS19, XS17mini, 17Pro, XS18Pro Max, XS17Pro, XS17,
Series Model..... : XS18mini, XS19mini, XS19Max, XS20mini, XS14Pro, 14Pro,
14mini, XS14Pro Max
ANSI/IEEE Std. C95.1
Standards..... : FCC 47 CFR Part 2 (2.1093)
IEEE Std. 1528-2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664 The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of Test..... :

Date (s) of performance of tests..... : 25 Nov. 2025 ~ 30 Nov. 2025

Date of Issue..... : 10 DEC. 2025

Test Result..... : **Pass**

Testing Engineer :

Xin Liu

(Xin.Liu)

Technical Manager :

Shi fan-long

(Shifan. Long)

Authorized Signatory :

Bovey Yang

(Bovey Yang)





Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System	9
3.1 Definition of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check	12
5. SAR System Validation	16
5.1 Validation System	16
5.2 Validation Result	16
6. SAR Evaluation Procedures	17
7. EUT Antenna Location Sketch	18
7.1 SAR test exclusion consider table	19
8. EUT Test Position	23
8.1 Define Two Imaginary Lines on the Handset	23
9. Uncertainty	25
9.1 Measurement Uncertainty	25
10. Conducted Power Measurement	28
10.1 Test Result	28
11. EUT and Test Setup Photo	47
11.1 EUT Photo	47
11.2 Setup Photo	50
12. SAR Result Summary	56
12.1 Head SAR	56
12.2 Body-worn SAR	59
12.3 Repeated SAR	63
12.4 Repeated SAR measurement	65
12.5 Simultaneous Multi-band Transmission Evaluation	68
13. Equipment List	70
Appendix A. System Validation Plots	71
Appendix B. SAR Test Plots	83
Appendix C. Probe Calibration and Dipole Calibration Report	131

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	10 DEC. 2025	STS2511135H01	ALL	Initial Issue



1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	Mini smartphone
Brand Name	SOYES
Model Name	XS19Pro
Series Model	XS19, XS17mini, 17Pro, XS18Pro Max, XS17Pro, XS17, XS18mini, XS19mini, XS19Max, XS20mini, XS14Pro, 14Pro, 14mini, XS14Pro Max
Model Difference	The model and appearance color are different.
Sample number	251113017-1
Battery	DC 3.85V from battery
Device Category	Portable
Product stage	Production unit
RF Exposure Environment	General Population / Uncontrolled
Hardware Version	HV1.0
Software Version	SV1.0
Frequency Range	GSM 850: 824 MHz ~ 849 MHz PCS1900: 1850 MHz ~ 1910 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 66: 1710 MHz ~ 1780 MHz WLAN802.11b/g/n20: 2412 MHz ~ 2462 MHz WLAN 802.11n40: 2422 MHz ~ 2452 MHz Bluetooth: 2402 MHz to 2480 MHz



Max. Reported SAR(1g): (Limit:1.6W/kg) Test distance: Head:0mm Body:5mm	Band	Mode	Head (W/kg)	Body Worn (W/kg)
	PCE	GSM 850	0.411	1.253
	PCE	GSM 1900	0.262	1.247
	PCE	WCDMA Band II	0.274	0.836
	PCE	WCDMA Band V	0.385	0.892
	PCE	LTE Band 2	0.447	1.102
	PCE	LTE Band 4	0.371	1.288
	PCE	LTE Band 5	0.486	1.186
	PCE	LTE Band 7	0.681	1.179
	PCE	LTE Band 12	0.127	0.478
	PCE	LTE Band 66	0.428	1.075
	DTS	2.4G WLAN	0.058	0.107
	DSS	BT	0.052	0.050
	1-g Sum SAR			0.739
FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter (DSS) Digital Transmission System (DTS) Unlicensed National Information Infrastructure TX(NII)			
Operating Mode:	GSM: GSM Voice; GPRS/EGPRS Class 12 WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM 2.4G WLAN : 802.11b(DSSS):CCK,DQPSK,DBPSK 802.11g(OFDM):BPSK,QPSK,16-QAM,64-QAM 802.11n(OFDM):BPSK,QPSK,16-QAM,64-QAM Bluetooth: GFSK + π /4DQPSK+8DPSK BLE: GFSK			
Antenna Specification:	GSM/WCDMA/LTE: FPC Antenna Bluetooth: FPC Antenna WLAN: FPC Antenna			
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot transmitting at the same time			
Hotspot Mode	Not Support			
DTM Mode	Not Support			
Note: 1. The dual SIM card mobile has 2 SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active) 2. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 card to perform all tests. 3. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power				



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

ShenZhen STS Test Services Co.,Ltd.

A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01



2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	IEEE Std C95.1, 2019	IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz. It specifies the maximum exposure limit of 1.6 W/kg as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D04 v01	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
10	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE

PARTIAL BODY LIMIT

1.6 W/kg



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The Open SAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 08/21 EPGO352 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 150 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Dipole

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm $\pm$ 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.


SN 32/14 SAM115



Figure-SN 21/21 ELLI48



3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine if the dielectric parameters are within the tolerances of the specified target values

The uncertainty due to the liquid conductivity and permittivity arises from two different sources. The first source of error is the deviation of the liquid conductivity from its target value (max _ 5 %) and the second source of error arises from the measurement procedures used to assess conductivity. The uncertainty shall be assessed using a rectangular probability For 1 g averaging, the maximum weighting coefficient for SAR is 0,5.

IEEE SCC-34/SC-2 RECOMMENDED TISSUE DIELECTRIC PARAMETERS

The head and body tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table.

Frequency	ϵ_r	σ 10g S/m
300	45.3	0.87
450	43.5	0.87
750	41.9	0.89
835	41.5	0.90
900	41.5	0.97
1450	40.5	1.20
1800 to 2000	40.0	1.40
2100	39.8	1.49
2450	39.2	1.80
2600	39.0	1.96
3000	38.5	2.40
3500	37.9	2.91
4000	37.4	3.43
4500	36.8	3.94
5000	36.2	4.45
5200	36.0	4.66
5400	35.8	4.86
5600	35.5	5.07
5800	35.3	5.27



The following table gives the recipes for tissue simulating liquid and the theoretical Conductivity/Permittivity.

Head (Reference IEEE1528)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.4	40.0
2450	55.0	0	0	0.1	0	44.9	1.80	39.2
2600	54.9	0	0	0.1	0	45.0	1.96	39.0
Frequency (MHz)	Water (%)	Hexyl Carbitol (%)			Triton X-100 (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	62.52	17.24			17.24		4.66	36.0
5800	62.52	17.24			17.24		5.27	35.3
Body (From instrument manufacturer)								
Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity σ (S/m)	Permittivity ϵ
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0.1	0	31.3	1.95	52.7
2600	68.2	0	0	0.1	0	31.7	2.16	52.5
Frequency(MHz)	Water	DGBE (%)			Salt (%)		Conductivity σ (S/m)	Permittivity ϵ
5200	78.60	21.40			/		5.30	49.00
5800	78.50	21.40			0.1		6.00	48.20

**LIQUID MEASUREMENT RESULTS**

Date	Ambient		Simulating Liquid		Parameters	Target	Measured	Deviation %	Limited %
	Temp. [°C]	Humidity %	Frequency (MHz)	Temp. [°C]					
2025-11-26	22.9	45	704	22.5	Permittivity	42.15	42.63	1.15	±5
					Conductivity	0.89	0.91	2.60	±5
2025-11-26	22.9	45	711	22.5	Permittivity	42.11	41.87	-0.57	±5
					Conductivity	0.89	0.89	0.29	±5
2025-11-26	22.9	45	750	22.5	Permittivity	41.90	41.90	0.00	±5
					Conductivity	0.89	0.89	0.00	±5
2025-11-26	22.9	45	824.2	22.5	Permittivity	41.55	42.32	1.85	±5
					Conductivity	0.90	0.89	-0.97	±5
2025-11-26	22.9	45	829	22.5	Permittivity	41.53	41.42	-0.26	±5
					Conductivity	0.90	0.90	0.08	±5
2025-11-26	22.9	45	835	22.5	Permittivity	41.50	42.49	2.39	±5
					Conductivity	0.90	0.91	1.11	±5
2025-11-26	22.9	45	836.5	22.5	Permittivity	41.49	42.16	1.61	±5
					Conductivity	0.90	0.90	-0.02	±5
2025-11-26	22.9	45	836.6	22.5	Permittivity	41.49	41.14	-0.85	±5
					Conductivity	0.90	0.90	-0.02	±5
2025-11-26	22.9	45	844	22.5	Permittivity	41.46	41.19	-0.65	±5
					Conductivity	0.90	0.91	0.99	±5
2025-11-26	22.9	45	848.8	22.5	Permittivity	41.44	41.96	1.27	±5
					Conductivity	0.90	0.88	-2.40	±5
2025-11-25	21.7	57	1720	21.5	Permittivity	40.11	40.43	0.79	±5
					Conductivity	1.35	1.36	0.42	±5
2025-11-25	21.7	57	1732.5	21.5	Permittivity	40.10	40.71	1.53	±5
					Conductivity	1.36	1.35	-0.84	±5
2025-11-25	21.7	57	1745	21.5	Permittivity	40.08	40.36	0.70	±5
					Conductivity	1.37	1.39	1.57	±5
2025-11-25	21.7	57	1770	21.5	Permittivity	40.04	40.07	0.07	±5
					Conductivity	1.38	1.38	-0.21	±5
2025-11-25	21.7	57	1800	21.5	Permittivity	40.00	40.60	1.50	±5
					Conductivity	1.40	1.38	-1.43	±5
2025-11-30	22.3	50	1850.2	22.0	Permittivity	40.00	40.83	2.08	±5
					Conductivity	1.40	1.40	0.00	±5
2025-11-25	22.3	50	1852.4	22.0	Permittivity	40.00	39.99	-0.02	±5
					Conductivity	1.40	1.37	-2.14	±5
2025-11-30	22.3	50	1860	22.0	Permittivity	40.00	39.93	-0.18	±5
					Conductivity	1.40	1.38	-1.43	±5
	22.3	50	1880	22.0	Permittivity	40.00	40.92	2.30	±5




2025-11-30					Conductivity	1.40	1.42	1.43	±5
2025-11-30	22.3	50	1900	22.0	Permittivity	40.00	40.34	0.85	±5
					Conductivity	1.40	1.41	0.71	±5
2025-11-30	22.3	50	1907.6	22.0	Permittivity	40.00	40.40	1.00	±5
					Conductivity	1.40	1.40	0.00	±5
2025-11-30	22.3	50	1909.8	22.0	Permittivity	40.00	40.50	1.25	±5
					Conductivity	1.40	1.42	1.43	±5
2025-11-29	22.5	49	2450	22.3	Permittivity	39.20	39.18	-0.05	±5
					Conductivity	1.80	1.80	0.00	±5
2025-11-29	22.5	49	2462	22.3	Permittivity	39.18	39.79	1.56	±5
					Conductivity	1.81	1.81	-0.04	±5
2025-11-29	22.5	49	2480	22.3	Permittivity	39.15	39.19	0.11	±5
					Conductivity	1.83	1.83	0.18	±5
2025-11-29	22.5	49	2510	22.3	Permittivity	39.12	39.33	0.54	±5
					Conductivity	1.86	1.86	-0.21	±5
2025-11-29	22.5	49	2535	22.3	Permittivity	39.09	39.55	1.19	±5
					Conductivity	1.89	1.89	-0.04	±5
2025-11-29	22.5	49	2560	22.3	Permittivity	39.05	39.97	2.35	±5
					Conductivity	1.92	1.94	1.18	±5
2025-11-29	22.5	49	2600	22.3	Permittivity	39.00	39.44	1.13	±5
					Conductivity	1.96	1.93	-1.53	±5

5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder. The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.



5.2 Validation Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %.

Date	Frequency (MHz)	Power	SAR _{1g} (W/Kg)	SAR _{10g} (W/Kg)	Drift (%)	1W Target		Difference percentage		Limited %
						SAR _{1g} (W/Kg)	SAR _{10g} (W/Kg)	1g	10g	
2025-05-02	750	100 mW	0.835	0.505	-0.59	8.49	5.53	-1.67%	-8.68%	10
		Normalize to 1 Watt	8.35	5.05						
2025-05-05	835	100 mW	0.947	0.656	1.68	9.63	6.15	-1.65%	6.62%	10
		Normalize to 1 Watt	9.47	6.56						
2025-05-06	1800	100 mW	3.853	1.996	2.36	38.40	20.10	0.33%	-0.69%	10
		Normalize to 1 Watt	38.53	19.96						
2025-05-07	1900	100 mW	3.964	2.049	-2.27	39.84	20.20	-0.51%	1.44%	10
		Normalize to 1 Watt	39.64	20.49						
2025-05-08	2450	100 mW	5.489	2.416	-2.20	54.70	24.11	0.35%	0.23%	10
		Normalize to 1 Watt	54.89	24.16						
2025-05-09	2600	100 mW	5.566	2.441	-1.28	56.19	24.08	-0.94%	1.39%	10
		Normalize to 1 Watt	55.66	24.41						

Note:

(1) We use a CW signal of 20dBm(750,835,1800,1900,2450,2600MHz) for system check, and then all SAR values are normalized to 1W forward power. The result must be within $\pm 10\%$ of target value.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position


- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.

➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below. When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a Smart phone, support GSM/WCDMA/LTE/WLAN/BT mode.



Antenna Separation Distance(cm)						
ANT	Back Side	Front Side	Left Side	Right Side	Top Side	Bottom Side
WLAN/BT	≤0.5	≤0.5	4	≤0.5	≤0.5	9.2
WWAN	≤0.5	≤0.5	2.25	2.25	9.2	≤0.5

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

The WWAN/WLAN/BT SAR evaluation of Maximum power (dBm) summing tolerance.

Exposure Position	Wireless Interface	GSM850	PCS1900	WCDMA II	WCDMA V
	Calculated Frequency(GHz)	0.8488	1.8502	1.9076	0.8366
	Maximum Turn-up power (dBm)	26	28.5	21.5	22
	Maximum rated power(mW)	398.11	707.95	141.25	158.49
Back Side	Separation distance (cm)	0.5	0.5	0.5	0.5
	exclusion threshold(mW)	9.04	3.44	3.35	6.49
	Testing required?	YES	YES	YES	YES
Front Side	Separation distance (cm)	0.5	0.5	0.5	0.5
	exclusion threshold(mW)	9.04	3.44	3.35	6.49
	Testing required?	YES	YES	YES	YES
Left Side	Separation distance (cm)	2.25	2.25	2.25	2.25
	exclusion threshold(mW)	77.02	54.79	54.00	79.85
	Testing required?	YES	YES	YES	YES
Right Side	Separation distance (cm)	2.25	2.25	2.25	2.25
	exclusion threshold(mW)	77.02	54.79	54.00	79.85
	Testing required?	YES	YES	YES	YES
Top Side	Separation distance (cm)	9.2	9.2	9.2	9.2
	exclusion threshold(mW)	572.76	732.48	728.72	837.38
	Testing required?	NO	NO	NO	NO
Bottom Side	Separation distance (cm)	0.5	0.5	0.5	0.5
	exclusion threshold(mW)	9.04	3.44	3.35	6.49
	Testing required?	YES	YES	YES	YES



	Wireless Interface	LTE Band 2	LTE Band 4	LTE Band 5	LTE Band 7	LTE Band 12	LTE Band 66	2.4G WLAN	BT
Exposure Position	Calculated Frequency(GHz)	1.9093	1.7325	0.8247	2.5625	0.7075	1.745	2.462	2.48
	Maximum Turn-up power (dBm)	23	23	23	23	23	23	17	6
	Maximum rated power(mW)	199.53	199.53	199.53	199.53	199.53	199.53	50.12	3.98
Back Side	Separation distance (cm)	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
	exclusion threshold(mW)	3.35	3.62	9.41	2.65	11.67	3.60	2.73	2.72
	Testing required?	YES	YES	YES	YES	YES	YES	YES	YES
Front Side	Separation distance (cm)	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
	exclusion threshold(mW)	3.35	3.62	9.41	2.65	11.67	3.60	2.73	2.72
	Testing required?	YES	YES	YES	YES	YES	YES	YES	YES
Left Side	Separation distance (cm)	2.25	2.25	2.25	2.25	2.25	2.25	4	4
	exclusion threshold(mW)	53.98	56.53	77.97	46.95	83.19	56.34	143.03	142.67
	Testing required?	YES	YES	YES	YES	YES	YES	NO	NO
Right Side	Separation distance (cm)	2.25	2.25	2.25	2.25	2.25	2.25	0.5	0.5
	exclusion threshold(mW)	53.98	56.53	77.97	46.95	83.19	56.34	2.73	2.72
	Testing required?	YES	YES	YES	YES	YES	YES	YES	YES
Top Side	Separation distance (cm)	9.2	9.2	9.2	9.2	9.2	9.2	0.5	0.5
	exclusion threshold(mW)	728.61	740.65	564.66	693.34	523.47	739.75	2.73	2.72
	Testing required?	NO	NO	NO	NO	NO	NO	YES	YES
Bottom Side	Separation distance (cm)	0.5	0.5	0.5	0.5	0.5	0.5	9.2	9.2
	exclusion threshold(mW)	3.35	3.62	9.41	2.65	11.67	3.60	698.04	697.18
	Testing required?	YES	YES	YES	YES	YES	YES	NO	NO

Note:

1. maximum power is the source-based time-average power and represents the maximum RF output power among production units.
2. Per KDB 447498 D04, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
3. Per KDB 447498 D04, if the maximum time-averaged power available does not exceed 1 mW. This stand-alone SAR exemption test.



4. Per KDB 447498 D04, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

5. Per KDB 447498 D04, An alternative to the SAR-based exemption is using below table and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in below table to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency (MHz)	Threshold ERP(watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.




6. Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8. for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode, thus the SAR can be excluded.
7. Per KDB 616217 D04, SAR evaluation for the front surface of tablet display screens are generally not necessary.
8. Per KDB 248227, as maximum rated power for U-NII-2A > U-NII-1, U-NII-2A was chosen for SAR evaluation. Based on the measurements obtained, SAR measurements on U-NII-1 are not required as highest reported SAR from U-NII-2A band is $\leq 1.2\text{W/Kg}$.

8. EUT Test Position

This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Front Face, Rear Face, Left Side, Right Side, Top Side and Bottom Side.


8.1 Define Two Imaginary Lines on the Handset

- (1) The vertical centerline passes through two points on the front side of the handset the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the handset.
- (2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- (3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Cheek Position


- 1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- 2) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost.






Title Position

- (1) To position the device in the “cheek” position described above.
- (2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.



Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D04 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported SAR* for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported SAR* configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

SATIMO Uncertainty- SN 08/21 EPG0352									
Measurement uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+/- %)	10g Ui (+/- %)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.71	0.71	0.07	0.07	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.71	0.71	0.42	0.42	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	1.00	1.00	1.97	1.97	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	1.00	1.00	0.10	0.10	∞
Integration Time	E.2.8	1.43	R	1.73	1.00	1.00	0.83	0.83	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions-reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
Test sample Related									
Test sample positioning	E.4.2	3.10	N	1.00	1.00	1.00	3.10	3.10	∞
Device holder uncertainty	E.4.1	3.80	N	1.00	1.00	1.00	3.80	3.80	∞
Output power variation—SAR drift measurement	E.2.9	4.50	R	1.73	1.00	1.00	2.60	2.60	∞
SAR scaling	E.6.5	1.80	R	1.73	1.00	1.00	1.04	1.04	∞
Phantom and tissue parameters									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	M
Liquid permittivity measurement	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity—temperature uncertainty	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity—temperature uncertainty	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	∞
Combined Standard Uncertainty			RSS				10.08	9.59	
			K=2				19.58	19.18	



Expanded Uncertainty (95% Confidence interval)									
--	--	--	--	--	--	--	--	--	--

SATIMO Uncertainty- SN 08/21 EPGO352									
System Validation uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System									
Probe calibration	E.2.1	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	1.00	1.00	0.10	0.10	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.80	R	1.73	1.00	1.00	0.46	0.46	∞
Linearity	E.2.4	1.25	R	1.73	1.00	1.00	0.72	0.72	∞
System detection limits	E.2.4	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	1.00	1.00	0.26	0.26	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	1.00	1.00	2.03	2.03	∞
RF ambient conditions-reflections	E.6.1	3.15	R	1.73	1.00	1.00	1.82	1.82	∞
Probe positioner mechanical tolerance	E.6.2	1.20	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.40	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	2.10	R	1.73	1.00	1.00	1.21	1.21	∞
System validation source									
Deviation of experimental dipole from numerical dipole	E.6.4	4.80	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.10	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.40	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and set-up									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	3.70	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.90	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	E.3.3	2.40	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid conductivity (measured)	E.3.3	4.10	N	1.00	0.78	0.71	3.20	2.91	M
Liquid permittivity (temperature uncertainty)	E.3.4	2.70	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity (measured)	E.3.4	4.80	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				9.72	9.52	
Expanded Uncertainty (95% Confidence interval)			K=2				19.44	19.03	



SATIMO Uncertainty- SN 08/21 EPG0352									
。 System Check uncertainty for DUT averaged over 1 gram / 10 gram.									
Uncertainty Component	Sec.	Tol	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
		(+-%)							
Measurement System									
Probe calibration drift	E.2.1.3	5.72	N	1.00	1.00	1.00	5.72	5.72	∞
Axial Isotropy	E.2.2	0.18	R	1.73	0.00	0.00	0.00	0.00	∞
Hemispherical Isotropy	E.2.2	1.04	R	1.73	0.00	0.00	0.00	0.00	∞
Boundary effect	E.2.3	0.8	R	1.73	0.00	0.00	0.00	0.00	∞
Linearity	E.2.4	1.25	R	1.73	0.00	0.00	0.00	0.00	∞
System detection limits	E.2.4	1.20	R	1.73	0.00	0.00	0.00	0.00	∞
Modulation response	E.2.5	3.42	R	1.73	0.00	0.00	0.00	0.00	∞
Readout Electronics	E.2.6	0.26	N	1.00	0.00	0.00	0.00	0.00	∞
Response Time	E.2.7	0.17	R	1.73	0.00	0.00	0.00	0.00	∞
Integration Time	E.2.8	1.43	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-Noise	E.6.1	3.51	R	1.73	0.00	0.00	0.00	0.00	∞
RF ambient conditions-reflections	E.6.1	3.15	R	1.73	0.00	0.00	0.00	0.00	∞
Probe positioner mechanical tolerance	E.6.2	1.2	R	1.73	1.00	1.00	0.69	0.69	∞
Probe positioning with respect to phantom shell	E.6.3	1.4	R	1.73	1.00	1.00	0.81	0.81	∞
Extrapolation, interpolation, and integrations algorithms for max. SAR evaluation	E.5	3.9	R	1.73	0.00	0.00	0.00	0.00	∞
System check source (dipole)									
Deviation of experimental dipoles	E.6.4	4.8	N	1.00	1.00	1.00	4.80	4.80	∞
Input power and SAR drift measurement	8,6.6.4	5.1	R	1.73	1.00	1.00	2.94	2.94	∞
Dipole axis to liquid distance	8,E.6.6	2.4	R	1.73	1.00	1.00	1.39	1.39	∞
Phantom and tissue parameters									
Phantom shell uncertainty—shape, thickness, and permittivity	E.3.1	3.7	R	1.73	1.00	1.00	2.14	2.14	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	E.3.2	1.9	N	1.00	1.00	0.84	1.90	1.60	∞
Liquid conductivity measurement	E.3.3	2.4	R	1.73	0.78	0.71	1.08	0.98	∞
Liquid permittivity measurement	E.3.3	4.1	N	1.00	0.78	0.71	3.20	2.91	M
Liquid conductivity—temperature uncertainty	E.3.4	2.7	R	1.73	0.23	0.26	0.36	0.41	∞
Liquid permittivity—temperature uncertainty	E.3.4	4.8	N	1.00	0.23	0.26	1.10	1.25	M
Combined Standard Uncertainty			RSS				5.56	5.20	
Expanded Uncertainty (95% Confidence interval)			K=2				11.12	10.41	



10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	24.12	25.25	25.41	28.21	27.52	27.52
GPRS (GMSK, 1-Slot)	24.73	25.14	25.73	28.13	27.86	27.56
GPRS (GMSK, 2-Slot)	23.84	24.26	24.52	27.34	27.05	26.52
GPRS (GMSK, 3-Slot)	21.14	22.24	22.73	25.21	25.24	24.95
GPRS (GMSK, 4-Slot)	20.36	21.01	21.65	24.36	24.14	23.14
EGPRS(8PSK, 1-Slot)	17.85	18.63	19.44	25.25	24.73	24.76
EGPRS(8PSK, 2-Slot)	16.94	17.45	18.01	24.24	23.84	23.52
EGPRS(8PSK, 3-Slot)	14.21	15.41	16.85	22.28	22.01	21.66
EGPRS(8PSK, 4-Slot)	13.63	13.73	14.76	20.66	20.63	20.14
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Frame- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	15.09	16.22	16.38	19.18	18.49	18.49
GPRS (GMSK, 1-Slot)	15.70	16.11	16.70	19.10	18.83	18.53
GPRS (GMSK, 2-Slot)	17.82	18.24	18.50	21.32	21.03	20.50
GPRS (GMSK, 3-Slot)	16.88	17.98	18.47	20.95	20.98	20.69
GPRS (GMSK, 4-Slot)	17.35	18.00	18.64	21.35	21.13	20.13
EGPRS(8PSK, 1-Slot)	8.82	9.60	10.41	16.22	15.70	15.73
EGPRS(8PSK, 2-Slot)	10.92	11.43	11.99	18.22	17.82	17.50
EGPRS(8PSK, 3-Slot)	9.95	11.15	12.59	18.02	17.75	17.40
EGPRS(8PSK, 4-Slot)	10.62	10.72	11.75	17.65	17.62	17.13
Remark : 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						



WCDMA

Band	WCDMA Band 2			WCDMA Band 5		
Channel	9262	9400	9538	4132	4183	4233
Frequency (MHz)	1852.4	1880	1907.6	826.4	836.6	846.6
RMC 12.2Kbps	21.35	21.21	21.41	21.46	21.52	21.21
HSDPA Subtest-1	20.04	20.36	20.23	20.67	20.73	20.73
HSDPA Subtest-2	19.48	19.85	19.52	20.45	20.52	20.55
HSDPA Subtest-3	18.56	18.44	18.56	19.06	19.34	19.41
HSDPA Subtest-4	18.54	18.81	18.64	19.41	19.21	19.36
HSUPA Subtest-1	18.51	20.03	20.01	19.83	20.53	20.52
HSUPA Subtest-2	20.05	20.85	20.08	20.61	20.85	20.66
HSUPA Subtest-3	18.63	19.12	18.84	18.85	19.44	19.55
HSUPA Subtest-4	20.85	20.28	20.63	20.63	20.72	20.74
HSUPA Subtest-5	18.44	19.65	19.55	19.07	20.26	20.41

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	$MAX(CM-1,0)$
Note: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

**2.4G WLAN**

2.4GWIFI				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
802.11b	1	2412	12.06	16.07
	7	2437	12.66	18.45
	11	2462	16.89	48.87
802.11g	1	2412	12.84	19.23
	7	2437	14.34	27.16
	11	2462	16.20	41.69
802.11 n-HT20	1	2412	13.40	21.88
	7	2437	14.11	25.76
	11	2462	15.02	31.77
802.11 n-HT40	3	2422	11.19	13.15
	6	2437	13.36	21.68
	9	2452	14.40	27.54

Bluetooth

BT				
Mode	Channel Number	Frequency (MHz)	Average Power (dBm)	Output Power (mW)
GFSK(1Mbps)	0	2402	-0.29	0.94
	39	2441	1.92	1.56
	78	2480	3.91	2.46
$\pi/4$ -QPSK(2Mbps)	0	2402	0.88	1.22
	39	2441	2.05	1.60
	78	2480	5.23	3.33
8DPSK(3Mbps)	0	2402	1.18	1.31
	39	2441	2.64	1.84
	78	2480	5.58	3.61

**LTE Conducted Power****General Note:**

1. Anritsu CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.86	22.81	22.90
1.4	1	2		22.09	22.38	22.39
1.4	1	5		22.13	22.46	22.37
1.4	3	0		22.07	22.41	22.37
1.4	3	1		22.08	22.43	22.34
1.4	3	2		22.08	22.46	22.31
1.4	6	0		21.09	21.43	21.43
1.4	1	0	16-QAM	22.18	22.16	22.96
1.4	1	2		22.06	22.53	22.29
1.4	1	5		22.16	22.51	22.75
1.4	3	0		22.19	22.47	22.65
1.4	3	1		22.23	22.49	22.62
1.4	3	2		22.22	22.48	22.57
1.4	6	0		21.28	21.28	21.49
3	1	0	QPSK	22.26	22.41	22.40
3	1	7		22.29	22.60	22.53
3	1	14		22.21	22.53	22.28
3	8	0		22.34	22.52	22.48
3	8	4		22.31	22.57	22.52
3	8	7		22.30	22.59	22.47
3	15	0		21.26	21.53	21.52
3	1	0	16-QAM	22.56	22.44	22.63
3	1	7		22.66	22.62	22.09
3	1	14		22.60	22.57	22.57
3	8	0		22.39	22.62	22.49
3	8	4		22.46	22.68	22.55
3	8	7		22.47	22.62	22.50
3	15	0		22.26	22.41	22.40



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.38	22.37	22.42
5	1	12		22.43	22.61	22.51
5	1	24		22.23	22.66	22.43
5	12	0		22.28	22.37	22.28
5	12	6		22.34	22.54	22.43
5	12	11		22.23	22.50	22.42
5	25	0		21.21	21.44	21.33
5	1	0	16-QAM	22.72	22.60	22.47
5	1	12		22.72	22.73	22.65
5	1	24		22.60	22.11	22.59
5	12	0		22.20	22.58	22.48
5	12	6		22.33	22.16	22.55
5	12	11		22.17	22.70	22.54
5	25	0		21.33	21.51	21.34
10	1	0	QPSK	22.24	22.06	22.74
10	1	24		22.06	22.41	22.20
10	1	49		22.67	22.46	22.29
10	25	0		21.97	22.03	22.66
10	25	12		22.26	22.32	22.11
10	25	24		22.71	22.27	22.08
10	50	0		21.29	21.09	21.90
10	1	0	16-QAM	22.42	22.17	22.05
10	1	24		22.31	22.47	22.52
10	1	49		21.97	22.55	22.56
10	25	0		N/A	N/A	N/A
10	25	12		N/A	N/A	N/A
10	25	24		N/A	N/A	N/A
10	50	0		N/A	N/A	N/A



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.18	22.04	22.12
15	1	37		22.57	22.22	22.15
15	1	74		22.52	22.63	22.41
15	36	0		22.09	22.23	22.20
15	36	18		21.92	22.52	22.53
15	36	39		22.65	22.58	22.21
15	75	0		21.72	21.31	21.15
15	1	0	16-QAM	22.44	22.21	22.24
15	1	38		22.14	22.08	22.26
15	1	75		22.09	22.13	22.62
15	36	0		N/A	N/A	N/A
15	36	18		N/A	N/A	N/A
15	36	39		N/A	N/A	N/A
15	75	0		N/A	N/A	N/A
20	1	0	QPSK	22.23	22.69	22.57
20	1	49		22.63	22.54	22.01
20	1	99		22.53	22.28	22.28
20	50	0		22.62	22.54	22.61
20	50	24		21.80	22.34	22.60
20	50	49		22.39	22.38	22.03
20	100	0		21.73	21.94	21.70
20	1	0	16-QAM	22.24	21.84	22.38
20	1	49		22.66	22.65	22.67
20	1	99		22.62	22.58	22.32
20	50	0		N/A	N/A	N/A
20	50	24		N/A	N/A	N/A
20	50	49		N/A	N/A	N/A
20	100	0		N/A	N/A	N/A



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.93	22.94	22.88
1.4	1	2		22.59	22.44	22.29
1.4	1	5		22.43	22.34	22.22
1.4	3	0		22.52	22.15	22.23
1.4	3	1		22.56	22.09	22.26
1.4	3	2		22.62	22.12	22.21
1.4	6	0		21.79	21.08	21.44
1.4	1	0	16-QAM	22.52	22.18	22.58
1.4	1	2		22.71	22.23	22.01
1.4	1	5		22.62	22.99	22.69
1.4	3	0		22.64	22.29	22.16
1.4	3	1		22.59	22.32	22.30
1.4	3	2		22.51	22.17	22.24
1.4	6	0		21.78	21.20	21.45
3	1	0	QPSK	22.76	22.73	22.07
3	1	7		22.63	22.67	22.47
3	1	14		22.60	22.50	22.51
3	8	0		22.57	22.02	22.15
3	8	4		22.61	22.03	22.18
3	8	7		22.51	22.11	22.26
3	15	0		21.51	21.99	21.26
3	1	0	16-QAM	22.42	22.63	22.04
3	1	7		22.34	22.20	22.34
3	1	14		22.32	22.74	22.17
3	8	0		22.50	22.74	22.55
3	8	4		22.47	22.75	22.39
3	8	7		22.36	22.10	22.07
3	15	0		21.44	21.82	21.24



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.50	22.53	22.06
5	1	12		22.71	22.68	22.03
5	1	24		22.53	22.60	22.08
5	12	0		22.49	22.61	22.12
5	12	6		22.49	22.59	22.18
5	12	11		22.50	22.68	22.24
5	25	0		21.46	21.56	21.14
5	1	0	16-QAM	22.39	22.58	22.54
5	1	12		22.53	22.16	22.11
5	1	24		22.35	22.67	22.10
5	12	0		22.36	22.15	22.96
5	12	6		22.30	22.09	22.04
5	12	11		22.28	22.68	22.09
5	25	0		22.50	22.53	22.16
10	1	0	QPSK	22.61	22.60	22.12
10	1	24		22.59	22.17	22.28
10	1	49		22.53	22.65	22.25
10	25	0		22.35	22.52	22.55
10	25	12		22.51	22.11	22.46
10	25	24		22.55	22.15	22.49
10	50	0		22.37	21.96	22.53
10	1	0	16-QAM	22.39	22.47	22.25
10	1	24		22.32	22.71	22.22
10	1	49		22.37	22.65	22.11
10	25	0		N/A	N/A	N/A
10	25	12		N/A	N/A	N/A
10	25	24		N/A	N/A	N/A
10	50	0		N/A	N/A	N/A



LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.50	22.55	22.43
15	1	37		22.74	22.18	22.43
15	1	74		22.00	22.14	22.42
15	36	0		22.35	22.50	22.40
15	36	18		22.42	22.56	22.35
15	36	39		22.62	22.60	22.27
15	75	0		22.36	22.44	22.37
15	1	0	16-QAM	22.27	22.52	22.23
15	1	38		22.09	22.74	22.03
15	1	75		22.39	22.54	22.44
15	36	0		N/A	N/A	N/A
15	36	18		N/A	N/A	N/A
15	36	39		N/A	N/A	N/A
15	75	0		N/A	N/A	N/A
20	1	0	QPSK	22.12	22.67	22.74
20	1	49		22.21	22.12	22.75
20	1	99		22.65	22.74	22.17
20	50	0		22.12	22.12	22.14
20	50	24		22.08	22.07	22.11
20	50	49		22.51	22.54	22.00
20	100	0		22.46	22.46	22.01
20	1	0	16-QAM	22.50	22.57	22.48
20	1	49		22.08	22.11	22.12
20	1	99		22.16	22.16	22.18
20	50	0		N/A	N/A	N/A
20	50	24		N/A	N/A	N/A
20	50	49		N/A	N/A	N/A
20	100	0		N/A	N/A	N/A



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.88	22.86	22.89
1.4	1	2		22.72	22.04	22.75
1.4	1	5		22.50	22.57	22.62
1.4	3	0		22.54	22.75	22.54
1.4	3	1		22.64	22.30	22.59
1.4	3	2		22.73	22.71	22.66
1.4	6	0		22.21	22.20	22.50
1.4	1	0	16-QAM	22.30	22.50	22.07
1.4	1	2		22.70	22.54	22.42
1.4	1	5		22.56	22.36	22.70
1.4	3	0		22.75	22.58	22.39
1.4	3	1		22.67	22.73	22.66
1.4	3	2		22.68	22.63	22.75
1.4	6	0		22.01	22.57	22.58
3	1	0	QPSK	22.10	22.08	22.24
3	1	7		22.50	22.42	22.24
3	1	14		22.13	22.55	22.48
3	8	0		22.12	22.38	22.00
3	8	4		22.50	22.33	22.51
3	8	7		22.19	22.49	22.46
3	15	0		22.53	22.50	22.83
3	1	0	16-QAM	22.71	22.72	22.26
3	1	7		22.18	22.09	22.34
3	1	14		22.07	22.71	22.81
3	8	0		22.71	22.22	22.70
3	8	4		22.39	22.75	22.50
3	8	7		22.22	22.66	22.67
3	15	0		22.57	22.57	22.43



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.00	22.44	22.49
5	1	12		22.29	22.39	22.12
5	1	24		22.67	22.61	22.75
5	12	0		22.55	22.00	22.35
5	12	6		22.12	22.02	22.22
5	12	11		22.46	22.76	22.48
5	25	0		22.26	22.76	22.09
5	1	0		22.61	22.67	22.17
5	1	12	16-QAM	22.04	22.36	22.39
5	1	24		22.62	22.55	22.13
5	12	0		22.55	22.69	22.18
5	12	6		22.38	22.81	22.32
5	12	11		22.61	22.58	22.08
5	25	0		22.35	22.70	22.22
10	1	0	QPSK	22.19	22.29	22.26
10	1	24		22.30	22.42	22.50
10	1	49		22.10	22.37	22.60
10	25	0		22.29	22.22	22.18
10	25	12		22.46	22.00	22.64
10	25	24		22.59	22.61	22.18
10	50	0		22.13	22.21	22.38
10	1	0		22.02	22.17	22.68
10	1	24	16-QAM	22.70	22.63	22.67
10	1	49		22.12	22.38	22.47
10	25	0		N/A	N/A	N/A
10	25	12		N/A	N/A	N/A
10	25	24		N/A	N/A	N/A
10	50	0		N/A	N/A	N/A



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.43	22.42	22.40
5	1	12		22.78	22.72	22.79
5	1	24		22.40	22.42	22.40
5	12	0		21.44	21.38	21.52
5	12	6		21.55	21.43	21.51
5	12	11		21.46	21.38	21.48
5	25	0		21.49	21.38	21.49
5	1	0	16-QAM	21.50	21.41	21.68
5	1	12		21.81	21.83	21.97
5	1	24		21.47	21.38	21.66
5	12	0		20.53	20.48	20.49
5	12	6		20.64	20.52	20.48
5	12	11		20.59	20.48	20.45
5	25	0		20.47	20.42	20.55
10	1	0	QPSK	22.53	22.55	22.47
10	1	24		22.57	22.55	22.65
10	1	49		22.46	22.38	22.51
10	25	0		21.39	21.51	21.61
10	25	12		21.49	21.43	21.54
10	25	24		21.50	21.45	21.51
10	50	0		21.41	21.44	21.54
10	1	0	16-QAM	21.71	21.51	21.41
10	1	24		21.80	21.63	21.62
10	1	49		21.64	21.51	21.50
10	25	0		N/A	N/A	N/A
10	25	12		N/A	N/A	N/A
10	25	24		N/A	N/A	N/A
10	50	0		N/A	N/A	N/A



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.47	22.46	22.49
15	1	37		22.76	22.74	22.87
15	1	74		22.32	22.28	22.45
15	36	0		21.50	21.74	21.64
15	36	18		21.59	21.61	21.63
15	36	39		21.55	21.54	21.57
15	75	0		21.54	21.63	21.64
15	1	0	16-QAM	21.60	21.29	21.39
15	1	37		21.87	21.61	21.71
15	1	74		21.44	21.25	21.35
15	36	0		N/A	N/A	N/A
15	36	18		N/A	N/A	N/A
15	36	39		N/A	N/A	N/A
15	75	0		N/A	N/A	N/A
20	1	0	QPSK	22.26	22.32	22.20
20	1	49		22.60	22.54	22.60
20	1	99		22.21	22.14	22.27
20	50	0		21.29	21.47	21.56
20	50	24		21.46	21.41	21.52
20	50	49		21.26	21.47	21.36
20	100	0		21.34	21.46	21.49
20	1	0	16-QAM	21.24	21.20	21.35
20	1	49		21.54	21.52	21.66
20	1	99		21.06	21.19	21.34
20	50	0		N/A	N/A	N/A
20	50	24		N/A	N/A	N/A
20	50	49		N/A	N/A	N/A
20	100	0		N/A	N/A	N/A



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.91	22.93	22.87
1.4	1	2		22.07	22.25	22.73
1.4	1	5		22.17	22.03	22.60
1.4	3	0		22.65	22.31	22.48
1.4	3	1		22.66	22.32	22.32
1.4	3	2		22.50	22.28	22.67
1.4	6	0		22.70	22.25	22.39
1.4	1	0	16-QAM	22.31	22.03	22.22
1.4	1	2		22.35	22.49	22.01
1.4	1	5		22.22	22.27	22.53
1.4	3	0		22.48	22.40	22.02
1.4	3	1		22.52	22.34	22.06
1.4	3	2		22.45	22.34	22.69
1.4	6	0		22.74	22.26	22.04
3	1	0	QPSK	22.62	22.05	22.15
3	1	7		22.51	22.14	22.43
3	1	14		22.54	22.33	22.69
3	8	0		22.46	22.13	22.35
3	8	4		22.50	22.12	22.39
3	8	7		22.53	22.22	22.29
3	15	0		22.47	22.06	22.33
3	1	0	16-QAM	22.41	22.26	22.30
3	1	7		22.44	22.19	22.22
3	1	14		22.50	22.69	22.56
3	8	0		22.48	22.06	22.08
3	8	4		22.44	22.04	22.30
3	8	7		22.36	22.38	22.54
3	15	0		22.27	22.37	22.48



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.36	22.39	22.03
5	1	12		22.68	22.35	22.19
5	1	24		22.26	22.48	22.49
5	12	0		22.43	22.09	22.19
5	12	6		22.51	22.22	22.02
5	12	11		22.48	22.01	22.46
5	25	0		22.38	22.02	22.04
5	1	0	16-QAM	22.34	22.30	22.65
5	1	12		22.40	22.38	22.12
5	1	24		22.19	22.40	22.21
5	12	0		22.02	22.06	22.11
5	12	6		22.45	22.12	22.05
5	12	11		22.38	22.28	22.75
5	25	0		22.36	22.07	22.00
10	1	0	QPSK	22.60	22.22	22.14
10	1	24		22.15	22.12	22.66
10	1	49		22.37	22.01	22.27
10	25	0		22.51	22.22	22.07
10	25	12		22.42	22.28	22.12
10	25	24		22.32	22.10	22.02
10	50	0		22.24	22.12	22.12
10	1	0	16-QAM	22.21	22.24	22.40
10	1	24		22.60	22.54	22.52
10	1	49		22.11	22.61	22.08
10	25	0		N/A	N/A	N/A
10	25	12		N/A	N/A	N/A
10	25	24		N/A	N/A	N/A
10	50	0		N/A	N/A	N/A



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.84	22.95	22.91
1.4	1	2		22.39	22.11	22.31
1.4	1	5		22.36	22.00	22.30
1.4	3	0		22.29	22.05	22.34
1.4	3	1		22.30	22.09	22.34
1.4	3	2		22.25	22.03	22.20
1.4	6	0		22.24	22.02	22.08
1.4	1	0	16-QAM	22.24	22.23	22.24
1.4	1	2		22.32	22.28	22.24
1.4	1	5		22.25	22.16	22.14
1.4	3	0		22.39	22.24	22.13
1.4	3	1		22.42	22.28	22.13
1.4	3	2		22.37	22.22	22.06
1.4	6	0		22.46	22.34	22.37
3	1	0	QPSK	22.25	22.04	22.22
3	1	7		22.31	22.07	22.29
3	1	14		22.28	22.32	22.10
3	8	0		22.20	22.06	22.00
3	8	4		22.24	22.05	22.20
3	8	7		22.23	22.39	22.18
3	15	0		22.21	22.23	22.39
3	1	0	16-QAM	22.46	22.21	22.52
3	1	7		22.56	22.28	22.33
3	1	14		22.53	22.12	22.10
3	8	0		22.34	22.23	22.11
3	8	4		22.38	22.25	22.03
3	8	7		22.37	22.39	22.27
3	15	0		22.26	22.16	22.11



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.22	22.01	22.50
5	1	12		22.30	22.01	22.22
5	1	24		22.32	22.36	22.74
5	12	0		22.21	22.06	22.29
5	12	6		22.26	22.04	22.10
5	12	11		22.27	22.24	22.21
5	25	0		22.23	22.28	22.04
5	1	0	16-QAM	22.52	22.23	22.66
5	1	12		22.68	22.31	22.36
5	1	24		22.65	22.10	22.30
5	12	0		22.28	22.02	22.48
5	12	6		22.36	22.61	22.22
5	12	11		22.35	22.62	22.37
5	25	0		22.35	22.74	22.11
10	1	0	QPSK	22.48	22.38	22.16
10	1	24		22.42	22.05	22.63
10	1	49		22.29	22.16	22.13
10	25	0		22.03	22.87	22.46
10	25	12		22.29	22.34	22.28
10	25	24		22.21	22.69	22.29
10	50	0		22.11	22.17	22.22
10	1	0	16-QAM	22.68	22.30	22.39
10	1	24		22.67	22.07	22.28
10	1	49		22.19	22.19	22.39
10	25	0		N/A	N/A	N/A
10	25	12		N/A	N/A	N/A
10	25	24		N/A	N/A	N/A
10	50	0		N/A	N/A	N/A



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.38	22.22	22.27
15	1	37		22.47	22.26	22.59
15	1	74		22.16	22.71	22.33
15	36	0		22.01	22.74	22.54
15	36	18		22.45	22.67	22.15
15	36	39		22.48	22.65	22.06
15	75	0		22.24	22.70	22.16
15	1	0	16-QAM	22.30	22.40	22.39
15	1	38		22.18	22.50	22.22
15	1	75		22.20	22.52	22.32
15	36	0		N/A	N/A	N/A
15	36	18		N/A	N/A	N/A
15	36	39		N/A	N/A	N/A
15	75	0		N/A	N/A	N/A
20	1	0	QPSK	22.27	22.36	22.23
20	1	49		22.08	22.54	22.58
20	1	99		22.11	22.73	22.38
20	50	0		22.22	22.05	22.34
20	50	24		22.36	22.37	22.24
20	50	49		22.52	22.47	22.32
20	100	0		22.37	22.44	22.14
20	1	0	16-QAM	22.28	22.39	22.50
20	1	49		22.08	22.38	22.39
20	1	99		22.39	22.42	22.38
20	50	0		N/A	N/A	N/A
20	50	24		N/A	N/A	N/A
20	50	49		N/A	N/A	N/A
20	100	0		N/A	N/A	N/A


11. EUT and Test Setup Photo

11.1 EUT Photo


Front side




Back side




Top side



Bottom side



Left side




Right side



11.2 Setup Photo


Right Touch



Right Tilt



Left Touch



Left Tilt




Body Front side(separation distance is 5mm)




Body Back side(separation distance is 5mm)



Body Left side(separation distance is 5mm)



Body Right side(separation distance is 5mm)



Body Bottom side(separation distance is 5mm)




Body Top side(separation distance is 5mm)





Liquid depth (15 cm)





12. SAR Result Summary

12.1 Head SAR

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas.No.
GSM850	N/A	GPRS Data-4 Slot	N/A	N/A	Right Cheek	848.8	0.379	0.75	22.00	21.65	1.084	0.411	1
					Right Tilt	848.8	0.197	1.68	22.00	21.65	1.084	0.214	/
					Left Cheek	848.8	0.263	1.14	22.00	21.65	1.084	0.285	/
					Left Tilt	848.8	0.156	2.68	22.00	21.65	1.084	0.169	/
GSM1900	N/A	GPRS Data-4 Slot	N/A	N/A	Right Cheek	1850.2	0.254	-3.90	24.50	24.36	1.033	0.262	3
					Right Tilt	1850.2	0.127	3.49	24.50	24.36	1.033	0.131	/
					Left Cheek	1850.2	0.205	-0.35	24.50	24.36	1.033	0.212	/
					Left Tilt	1850.2	0.099	0.11	24.50	24.36	1.033	0.102	/
WCDMA Band II	N/A	RMC	N/A	N/A	Right Cheek	1907.6	0.268	-0.61	21.50	21.41	1.021	0.274	5
					Right Tilt	1907.6	0.165	-2.70	21.50	21.41	1.021	0.168	/
					Left Cheek	1907.6	0.237	-3.26	21.50	21.41	1.021	0.242	/
					Left Tilt	1907.6	0.102	1.39	21.50	21.41	1.021	0.104	/
WCDMA Band V	N/A	RMC	N/A	N/A	Right Cheek	836.6	0.345	3.12	22.00	21.52	1.117	0.385	7
					Right Tilt	836.6	0.205	-3.16	22.00	21.52	1.117	0.229	/
					Left Cheek	836.6	0.248	3.33	22.00	21.52	1.117	0.277	/
					Left Tilt	836.6	0.116	0.49	22.00	21.52	1.117	0.130	/
2.4G WLAN	N/A	802.11b	N/A	N/A	Right Cheek	2462	0.057	0.25	17.00	16.89	1.026	0.058	21
					Right Tilt	2462	0.021	-3.95	17.00	16.89	1.026	0.022	/
					Left Cheek	2462	0.046	3.04	17.00	16.89	1.026	0.047	/
					Left Tilt	2462	0.015	-2.29	17.00	16.89	1.026	0.015	/
BT	N/A	GFSK	N/A	N/A	Right Cheek	2480	0.047	-3.04	6.00	5.58	1.102	0.052	23
					Right Tilt	2480	0.020	2.55	6.00	5.58	1.102	0.022	/
					Left Cheek	2480	0.029	1.17	6.00	5.58	1.102	0.032	/
					Left Tilt	2480	0.008	-2.44	6.00	5.58	1.102	0.009	/
LTE Band 2	20M	QPSK	1	0	Right Cheek	1880	0.416	0.52	23	22.69	1.074	0.447	9
			50	0	Right Cheek	1860	0.389	3.60	23	22.62	1.091	0.425	/
			1	0	Right Tilt	1880	0.267	-3.25	23	22.69	1.074	0.287	/
			50	0	Right Tilt	1860	0.235	-1.90	23	22.62	1.091	0.256	/
			1	0	Left Cheek	1880	0.331	2.70	23	22.69	1.074	0.355	/
			50	0	Left Cheek	1860	0.309	3.10	23	22.62	1.091	0.337	/
			1	0	Left Tilt	1880	0.195	3.39	23	22.69	1.074	0.209	/
			50	0	Left Tilt	1860	0.163	-1.66	23	22.62	1.091	0.178	/



LTE Band 4	20M	QPSK	1	49	Right Cheek	1745	0.350	1.17	23	22.75	1.059	0.371	11
			50	49	Right Cheek	1732.5	0.313	-2.84	23	22.54	1.112	0.348	/
			1	49	Right Tilt	1745	0.125	2.72	23	22.75	1.059	0.132	/
			50	49	Right Tilt	1732.5	0.117	3.64	23	22.54	1.112	0.130	/
			1	49	Left Cheek	1745	0.251	2.66	23	22.75	1.059	0.266	/
			50	49	Left Cheek	1732.5	0.202	-1.25	23	22.54	1.112	0.225	/
			1	49	Left Tilt	1745	0.106	-0.63	23	22.75	1.059	0.112	/
			50	49	Left Tilt	1732.5	0.085	1.82	23	22.54	1.112	0.094	/
LTE Band 5	10M	QPSK	1	49	Right Cheek	844	0.443	1.29	23	22.6	1.096	0.486	13
			25	12	Right Cheek	844	0.408	0.69	23	22.64	1.086	0.443	/
			1	49	Right Tilt	844	0.300	-1.06	23	22.6	1.096	0.329	/
			25	12	Right Tilt	844	0.261	0.54	23	22.64	1.086	0.284	/
			1	49	Left Cheek	844	0.369	0.91	23	22.6	1.096	0.405	/
			25	12	Left Cheek	844	0.358	3.17	23	22.64	1.086	0.389	/
			1	49	Left Tilt	844	0.232	-3.90	23	22.6	1.096	0.254	/
			25	12	Left Tilt	844	0.217	0.95	23	22.64	1.086	0.236	/
LTE Band 7	20M	QPSK	1	49	Right Cheek	2510	0.621	3.69	23	22.6	1.096	0.681	15
			50	0	Right Cheek	2560	0.605	-1.73	22	21.56	1.107	0.670	/
			1	49	Right Tilt	2510	0.352	3.99	23	22.6	1.096	0.386	/
			50	0	Right Tilt	2560	0.307	1.89	22	21.56	1.107	0.340	/
			1	49	Left Cheek	2510	0.527	-0.86	23	22.6	1.096	0.578	/
			50	0	Left Cheek	2560	0.510	-2.10	22	21.56	1.107	0.564	/
			1	49	Left Tilt	2510	0.263	-0.20	23	22.6	1.096	0.288	/
			50	0	Left Tilt	2560	0.221	-3.55	22	21.56	1.107	0.245	/
LTE Band 12	10M	QPSK	1	24	Right Cheek	711	0.117	-2.69	23	22.66	1.081	0.127	17
			25	0	Right Cheek	704	0.088	0.57	23	22.51	1.119	0.099	/
			1	24	Right Tilt	711	0.031	1.42	23	22.66	1.081	0.034	/
			25	0	Right Tilt	704	0.042	-0.02	23	22.51	1.119	0.047	/
			1	24	Left Cheek	711	0.087	-1.89	23	22.66	1.081	0.094	/
			25	0	Left Cheek	704	0.065	-0.15	23	22.51	1.119	0.073	/
			1	24	Left Tilt	711	0.033	2.34	23	22.66	1.081	0.036	/
			25	0	Left Tilt	704	0.021	2.40	23	22.51	1.119	0.024	/
LTE Band 66	20M	QPSK	1	99	Right Cheek	1745	0.402	-2.89	23	22.73	1.064	0.428	19
			50	49	Right Cheek	1720	0.366	1.59	23	22.52	1.117	0.409	/
			1	99	Right Tilt	1745	0.208	-2.41	23	22.73	1.064	0.221	/
			50	49	Right Tilt	1720	0.156	-1.46	23	22.52	1.117	0.174	/



			1	99	Left Cheek	1745	0.351	-2.57	23	22.73	1.064	0.374	/
			50	49	Left Cheek	1720	0.337	2.64	23	22.52	1.117	0.376	/
			1	99	Left Tilt	1745	0.152	-1.27	23	22.73	1.064	0.162	/
			50	49	Left Tilt	1720	0.130	2.56	23	22.52	1.117	0.145	/

Note:

1. Per KDB 447498 D04, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
2. Per KDB 865664 D01, Repeated measurement is not required when the original highest measured SAR is <0.80 W/kg



12.2 Body-worn SAR

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift (%)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaling Factor	Scaled SAR (W/Kg)	Meas.No.
GSM850	N/A	GPRS Data-4 Slot	N/A	N/A	Front Side	848.8	0.735	3.95	22.00	21.65	1.084	0.797	/
					Back Side	824.2	0.952	-1.46	20.50	20.36	1.033	0.983	/
					Back Side	836.6	0.818	-2.02	21.50	21.01	1.119	0.916	/
					Back Side	848.8	1.156	-3.55	22.00	21.65	1.084	1.253	2
					Left Side	848.8	0.602	3.75	22.00	21.65	1.084	0.653	/
					Right Side	848.8	0.531	-0.87	22.00	21.65	1.084	0.576	/
					Bottom Side	848.8	0.687	1.33	22.00	21.65	1.084	0.745	/
GSM1900	N/A	GPRS Data-4 Slot	N/A	N/A	Front Side	1850.2	0.853	-0.62	24.50	24.36	1.033	0.881	/
					Front Side	1880	0.769	-3.03	24.50	24.14	1.086	0.835	/
					Front Side	1909.8	0.720	-3.02	23.50	23.14	1.086	0.782	/
					Back Side	1850.2	1.207	1.06	24.50	24.36	1.033	1.247	4
					Back Side	1880	1.021	-0.97	24.50	24.14	1.086	1.109	/
					Back Side	1909.8	0.926	-2.20	23.50	23.14	1.086	1.006	/
					Left Side	1850.2	0.578	2.65	24.50	24.36	1.033	0.597	/
					Right Side	1850.2	0.604	-2.93	24.50	24.36	1.033	0.624	/
					Bottom Side	1850.2	0.717	0.27	24.50	24.36	1.033	0.740	/
WCDMA Band II	N/A	RMC	N/A	N/A	Front Side	1907.6	0.705	-2.60	21.50	21.41	1.021	0.720	/
					Back Side	1852.4	0.728	2.23	21.50	21.35	1.035	0.754	/
					Back Side	1880	0.763	2.23	21.50	21.21	1.069	0.816	/
					Back Side	1907.6	0.819	2.23	21.50	21.41	1.021	0.836	6
					Left Side	1907.6	0.359	-3.26	21.50	21.41	1.021	0.367	/
					Right Side	1907.6	0.373	-0.53	21.50	21.41	1.021	0.381	/
					Bottom Side	1907.6	0.612	3.11	21.50	21.41	1.021	0.625	/
WCDMA Band V	N/A	RMC	N/A	N/A	Front Side	836.6	0.671	-1.26	22.00	21.52	1.117	0.749	/
					Back Side	836.6	0.799	-2.78	22.00	21.52	1.117	0.892	8
					Left Side	836.6	0.432	1.44	22.00	21.52	1.117	0.482	/
					Right Side	836.6	0.425	3.88	22.00	21.52	1.117	0.475	/
					Bottom Side	836.6	0.651	-2.91	22.00	21.52	1.117	0.727	/
2.4GHz WLAN	N/A	802.11b	N/A	N/A	Front Side	2462	0.089	-2.15	17.00	16.89	1.026	0.091	/
					Back Side	2462	0.104	-1.07	17.00	16.89	1.026	0.107	22
					Right Side	2462	0.063	-2.03	17.00	16.89	1.026	0.065	/



					Top Side	2462	0.071	1.90	17.00	16.89	1.026	0.073	/
BT	N/A	GFSK	N/A	N/A	Front Side	2480	0.035	-2.86	6.00	5.58	1.102	0.039	/
					Back Side	2480	0.045	-1.78	6.00	5.58	1.102	0.050	24
					Right Side	2480	0.023	0.78	6.00	5.58	1.102	0.025	/
					Top Side	2480	0.035	-2.86	6.00	5.58	1.102	0.039	/
LTE Band 2	20M	QPSK	1	0	Front side	1860	0.867	-3.48	22.5	22.23	1.064	0.923	/
			1	0	Front side	1880	0.802	-0.51	23	22.69	1.074	0.861	/
			1	0	Front side	1900	0.751	-1.74	23	22.57	1.104	0.829	/
			50	0	Front side	1860	0.726	3.85	23	22.62	1.091	0.792	/
			1	0	Back Side	1860	0.937	-3.55	22.5	22.23	1.064	0.997	/
			1	0	Back Side	1880	1.026	-1.03	23	22.69	1.074	1.102	10
			1	0	Back Side	1900	0.952	-3.46	23	22.57	1.104	1.051	/
			50	0	Back Side	1860	0.859	3.01	23	22.62	1.091	0.938	/
			50	0	Back Side	1880	0.837	1.50	23	22.54	1.112	0.931	/
			50	0	Back Side	1900	0.861	-3.78	23	22.61	1.094	0.942	/
			100	0	Back Side	1880	0.753	0.34	22	21.94	1.014	0.763	/
			1	0	Left Side	1880	0.463	1.79	23	22.69	1.074	0.497	/
			50	0	Left Side	1860	0.405	0.72	23	22.62	1.091	0.442	/
			1	0	Right Side	1880	0.439	3.57	23	22.69	1.074	0.471	/
			50	0	Right Side	1860	0.387	-2.41	23	22.62	1.091	0.422	/
			1	0	Bottom Side	1880	0.696	-2.48	23	22.69	1.074	0.747	/
			50	0	Bottom Side	1860	0.653	3.26	23	22.62	1.091	0.713	/
LTE Band 4	20M	QPSK	1	49	Front side	1720	0.873	-3.41	22.5	22.21	1.069	0.933	/
			1	49	Front side	1732.5	0.825	3.59	22.5	22.12	1.091	0.900	/
			1	49	Front side	1745	0.819	-2.64	23	22.75	1.059	0.868	/
			50	49	Front side	1720	0.739	3.37	23	22.51	1.119	0.827	/
			50	49	Front side	1732.5	0.761	-0.41	23	22.54	1.112	0.846	/
			50	49	Front side	1745	0.725	0.26	22.5	22	1.122	0.813	/
			1	49	Back Side	1720	1.102	3.46	22.5	22.21	22.120	1.178	/
			1	49	Back Side	1732.5	1.087	1.12	22.5	22.12	1.091	1.186	/
			1	49	Back Side	1745	1.216	-1.35	23	22.75	1.059	1.288	12
			50	49	Back Side	1720	0.921	-3.30	23	22.51	1.119	1.031	/
			50	49	Back Side	1732.5	1.066	2.97	23	22.54	1.112	1.185	/
			50	49	Back Side	1745	0.856	2.69	22.5	22	1.122	0.960	/



			100	0	Back Side	1745	0.705	-3.38	23	22.46	1.132	0.798	/
			1	49	Left Side	1745	0.483	-0.01	23	22.75	1.059	0.512	/
			50	49	Left Side	1732.5	0.492	-3.24	23	22.54	1.112	0.547	/
			1	49	Right Side	1745	0.479	-0.71	23	22.75	1.059	0.507	/
			50	49	Right Side	1732.5	0.432	-0.80	23	22.54	1.112	0.480	/
			1	49	Bottom Side	1745	0.607	-2.83	23	22.75	1.059	0.643	/
			50	49	Bottom Side	1732.5	0.594	1.64	23	22.54	1.112	0.660	/
LTE Band 5	10M	QPSK	1	49	Front side	829	0.736	-3.23	22.5	22.1	1.096	0.807	/
			1	49	Front side	836.5	0.752	1.87	22.5	22.37	1.030	0.775	/
			1	49	Front side	844	0.816	-2.95	23	22.6	1.096	0.895	/
			25	12	Front side	844	0.729	3.93	23	22.64	1.086	0.792	/
			1	49	Back Side	829	0.975	-1.93	22.5	22.1	1.096	1.069	/
			1	49	Back Side	836.5	0.891	0.62	22.5	22.37	1.030	0.918	/
			1	49	Back Side	844	1.082	1.44	23	22.6	1.096	1.186	14
			25	12	Back Side	844	0.921	2.85	23	22.64	1.086	1.001	/
			1	49	Left Side	844	0.603	0.89	23	22.6	1.096	0.661	/
			25	12	Left Side	844	0.549	-0.78	23	22.64	1.086	0.596	/
			1	49	Right Side	844	0.594	3.39	23	22.6	1.096	0.651	/
			25	12	Right Side	844	0.518	2.79	23	22.64	1.086	0.563	/
			1	49	Bottom Side	844	0.696	-1.19	23	22.6	1.096	0.763	/
			25	12	Bottom Side	844	0.657	-0.74	23	22.64	1.086	0.714	/
LTE Band 7	10M	QPSK	1	49	Front side	2510	0.838	-2.65	23	22.6	1.096	0.919	/
			50	0	Front side	2560	0.718	3.46	22	21.56	1.107	0.795	/
			1	49	Back Side	2510	1.075	-3.87	23	22.6	1.096	1.179	16
			1	49	Back Side	2535	0.852	0.29	23	22.54	1.112	0.947	/
			1	49	Back Side	2560	0.927	-0.29	23	22.6	1.096	1.016	/
			50	0	Back Side	2510	0.776	2.39	21.5	21.46	1.009	0.783	/
			50	0	Back Side	2535	0.769	3.62	21.5	21.41	1.021	0.785	/
			50	0	Back Side	2560	0.783	-1.12	22	21.56	1.107	0.866	/
			100	0	Back Side	2560	0.737	1.44	21.5	21.49	1.002	0.739	/
			1	49	Left Side	2510	0.594	-2.40	23	22.6	1.096	0.651	/
			50	0	Left Side	2560	0.536	-2.81	22	21.56	1.107	0.593	/
			1	49	Right Side	2510	0.565	-0.05	23	22.6	1.096	0.620	/
			50	0	Right Side	2560	0.481	1.82	22	21.56	1.107	0.532	/



			1	49	Bottom Side	2510	0.693	-2.51	23	22.6	1.096	0.760	/
			50	0	Bottom Side	2560	0.627	-3.12	22	21.56	1.107	0.694	/
LTE Band 12	10M	QPSK	1	24	Front side	711	0.359	3.16	23	22.66	1.081	0.388	/
			25	0	Front side	704	0.335	-2.67	23	22.51	1.119	0.375	/
			1	24	Back Side	711	0.442	3.30	23	22.66	1.081	0.478	18
			25	0	Back Side	704	0.421	-1.32	23	22.51	1.119	0.471	/
			1	24	Left Side	711	0.252	2.60	23	22.66	1.081	0.273	/
			25	0	Left Side	704	0.231	2.93	23	22.51	1.119	0.259	/
			1	24	Right Side	711	0.251	1.71	23	22.66	1.081	0.271	/
			25	0	Right Side	704	0.218	0.30	23	22.51	1.119	0.244	/
			1	24	Bottom Side	711	0.332	-3.02	23	22.66	1.081	0.359	/
			25	0	Bottom Side	704	0.317	0.57	23	22.51	1.119	0.355	/
LTE Band 66	20M	QPSK	1	99	Front side	1720	0.808	-3.00	22.5	22.11	1.094	0.884	/
			1	99	Front side	1745	0.786	1.97	23	22.73	1.064	0.836	/
			1	99	Front side	1770	0.791	-1.18	22.5	22.38	1.028	0.813	/
			50	49	Front side	1720	0.705	-3.96	23	22.52	1.117	0.787	/
			1	99	Back Side	1720	0.925	2.53	22.5	22.11	1.094	1.012	/
			1	99	Back Side	1745	1.010	-2.00	23	22.73	1.064	1.075	20
			1	99	Back Side	1770	0.931	3.31	22.5	22.38	1.028	0.957	/
			50	49	Back Side	1720	0.852	0.05	23	22.52	1.117	0.952	/
			50	49	Back Side	1745	0.764	3.23	22.5	22.47	1.007	0.769	/
			50	49	Back Side	1770	0.731	3.01	22.5	22.32	1.042	0.762	/
			1	99	Left Side	1745	0.434	-1.80	23	22.73	1.064	0.462	/
			50	49	Left Side	1720	0.417	2.17	23	22.52	1.117	0.466	/
			1	99	Right Side	1745	0.502	-3.65	23	22.73	1.064	0.534	/
			50	49	Right Side	1720	0.459	3.57	23	22.52	1.117	0.513	/
			1	99	Bottom Side	1745	0.725	-1.52	23	22.73	1.064	0.772	/
			50	49	Bottom Side	1720	0.683	0.90	23	22.52	1.117	0.763	/

Note:

- The test separation of all above table is 5mm.
- Per KDB 447498 D04, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency



RF signal.

12.3 Repeated SAR

Band	Mode	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR(W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Back Side	824.2	0.930	-3.60	20.5	20.36	0.960	-
		Back Side	836.6	0.805	-3.84	21.5	21.01	0.901	-
		Back Side	848.8	1.110	-2.33	22	21.65	1.203	-
GSM1900	GPRS Data-4 Slot	Front Side	1850.2	0.817	3.79	24.5	24.36	0.844	-
		Front Side	1880	0.738	-1.92	24.5	24.14	0.802	-
		Front Side	1909.8	0.703	0.01	23.5	23.14	0.764	-
		Back Side	1850.2	1.202	0.36	24.5	24.36	1.241	-
		Back Side	1880	0.974	-1.13	24.5	24.14	1.058	-
		Back Side	1909.8	0.889	-3.46	23.5	23.14	0.966	-
WCDMA Band V	RMC	Back Side	836.6	0.803	-1.11	21.5	21.41	0.820	-
WCDMA Band V	RMC	Back Side	836.6	0.766	-1.11	22	21.52	0.856	-

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR(W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Front side	1860	0.831	-3.70	22.5	22.23	0.884	-
			1	0	Front side	1880	0.786	-2.45	23	22.69	0.845	-
			1	0	Front side	1900	0.734	3.58	23	22.57	0.810	-
			50	0	Front side	1860	0.699	3.02	23	22.62	0.763	-
			1	0	Back Side	1860	0.934	-0.03	22.5	22.23	0.994	-
			1	0	Back Side	1880	1.019	0.55	23	22.69	1.095	-
			1	0	Back Side	1900	0.908	-0.33	23	22.57	1.003	-
			50	0	Back Side	1860	0.818	3.43	23	22.62	0.893	-
			50	0	Back Side	1880	0.798	-3.37	23	22.54	0.887	-
			50	0	Back Side	1900	0.842	0.93	23	22.61	0.921	-



LTE Band 4	20M	QPSK	1	49	Front side	1720	0.859	3.30	22.5	22.21	0.919	-
			1	49	Front side	1732.5	0.790	-1.04	22.5	22.12	0.863	-
			1	49	Front side	1745	0.793	1.52	23	22.75	0.840	-
			50	49	Front side	1720	0.707	-3.01	23	22.51	0.792	-
			50	49	Front side	1732.5	0.730	3.50	23	22.54	0.812	-
			50	49	Front side	1745	0.721	-0.88	22.5	22.00	0.809	-
			1	49	Back Side	1720	1.077	-3.55	22.5	22.21	1.152	-
			1	49	Back Side	1732.5	1.076	3.76	22.5	22.12	1.174	-
			1	49	Back Side	1745	1.207	2.80	23	22.75	1.278	-
			50	49	Back Side	1720	0.907	-0.36	23	22.51	1.016	-
			50	49	Back Side	1732.5	1.061	3.40	23	22.54	1.180	-
			50	49	Back Side	1745	0.827	-2.21	22.5	22.00	0.927	-
LTE Band 5	10M	QPSK	1	49	Front side	829	0.708	2.60	22.5	22.10	0.776	-
			1	49	Front side	836.5	0.744	-1.33	22.5	22.37	0.766	-
			1	49	Front side	844	0.784	2.83	23	22.60	0.860	-
			25	12	Front side	844	0.727	-2.81	23	22.64	0.790	-
			1	49	Back Side	829	0.933	1.33	22.5	22.10	1.023	-
			1	49	Back Side	836.5	0.857	1.25	22.5	22.37	0.883	-
			1	49	Back Side	844	1.060	1.14	23	22.60	1.162	-
			25	12	Back Side	844	0.881	-0.64	23	22.64	0.957	-
LTE Band 7	10M	QPSK	1	49	Front side	2510	0.837	0.48	23	22.60	0.918	-
			50	0	Front side	2560	0.698	-0.60	22	21.56	0.773	-
			1	49	Back Side	2510	1.022	2.42	23	22.60	1.121	-
			1	49	Back Side	2535	0.812	-1.58	23	22.54	0.903	-
			1	49	Back Side	2560	0.922	-3.87	23	22.60	1.011	-
			50	0	Back Side	2510	0.747	-1.85	21.5	21.46	0.754	-
			50	0	Back Side	2535	0.747	2.27	21.5	21.41	0.763	-
			50	0	Back Side	2560	0.754	2.19	22	21.56	0.834	-



LTE Band 66	20M	QPSK	1	99	Front side	1720	0.804	0.17	22.5	22.11	0.880	-
			1	99	Front side	1745	0.756	1.40	23	22.73	0.805	-
			1	99	Front side	1770	0.762	-3.45	22.5	22.38	0.784	-
			50	49	Front side	1720	0.703	3.61	23	22.52	0.785	-
			1	99	Back Side	1720	0.906	-0.98	22.5	22.11	0.991	-
			1	99	Back Side	1745	0.973	-2.85	23	22.73	1.035	-
			1	99	Back Side	1770	0.926	-2.66	22.5	22.38	0.952	-
			50	49	Back Side	1720	0.847	0.95	23	22.52	0.946	-

12.4 Repeated SAR measurement

Band	Mode	Test Position	Freq.	Original Measured SAR 1g(W/kg)	1 st Repeated SAR 1g	Ratio	Original Measured SAR 1g(W/kg)	2nd Repeated SAR 1g	Ratio
GSM850	GPRS Data-4 Slot	Back Side	824.2	0.952	0.930	1.024	-	-	-
		Back Side	836.6	0.818	0.805	1.016	-	-	-
		Back Side	848.8	1.156	1.110	1.042	-	-	-
GSM1900	GPRS Data-4 Slot	Front Side	1850.2	0.853	0.817	1.044	-	-	-
		Front Side	1880	0.769	0.738	1.042	-	-	-
		Front Side	1909.8	0.72	0.703	1.024	-	-	-
		Back Side	1850.2	1.207	1.202	1.004	-	-	-
		Back Side	1880	1.021	0.974	1.048	-	-	-
		Back Side	1909.8	0.926	0.889	1.042	-	-	-
WCDMA Band II	RMC	Back Side	1907.6	0.819	0.803	1.020	-	-	-
WCDMA Band V	RMC	Back Side	836.6	0.799	0.766	1.043	-	-	-

Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Freq.	Original Measured SAR 1g(W/kg) 1g (W/kg)	1 st Repeated SAR 1g	Ratio	Original Measured	2nd Repeated SAR 1g	Ratio
LTE Band 2	20M	QPSK	1	0	Front side	1860	0.867	0.831	1.043	-	-	-
			1	0	Front side	1880	0.802	0.786	1.020	-	-	-



			1	0	Front side	1900	0.751	0.734	1.023	-	-	-
			50	0	Front side	1860	0.726	0.699	1.038			
			1	0	Back Side	1860	0.937	0.934	1.003	-	-	-
			1	0	Back Side	1880	1.026	1.019	1.006	-	-	-
			1	0	Back Side	1900	0.952	0.908	1.048	-	-	-
			50	0	Back Side	1860	0.859	0.818	1.050	-	-	-
			50	0	Back Side	1880	0.837	0.798	1.049	-	-	-
			50	0	Back Side	1900	0.861	0.842	1.023	-	-	-
LTE Band 4	20M	QPSK	1	49	Front side	1720	0.873	0.859	1.016			
			1	49	Front side	1732.5	0.825	0.790	1.044	-	-	-
			1	49	Front side	1745	0.819	0.793	1.033	-	-	-
			50	49	Front side	1720	0.739	0.707	1.045	-	-	-
			50	49	Front side	1732.5	0.761	0.730	1.043	-	-	-
			50	49	Front side	1745	0.725	0.721	1.005	-	-	-
			1	49	Back Side	1720	1.102	1.077	1.023	-	-	-
			1	49	Back Side	1732.5	1.087	1.076	1.010	-	-	-
			1	49	Back Side	1745	1.216	1.207	1.008	-	-	-
			50	49	Back Side	1720	0.921	0.907	1.015	-	-	-
			50	49	Back Side	1732.5	1.066	1.061	1.005	-	-	-
			50	49	Back Side	1745	0.856	0.827	1.036	-	-	-
LTE Band 5	10M	QPSK	1	49	Front side	829	0.736	0.708	1.040			
			1	49	Front side	836.5	0.752	0.744	1.011	-	-	-
			1	49	Front side	844	0.816	0.784	1.040	-	-	-
			25	12	Front side	844	0.729	0.727	1.002	-	-	-
			1	49	Back Side	829	0.975	0.933	1.045	-	-	-
			1	49	Back Side	836.5	0.891	0.857	1.039	-	-	-
			1	49	Back Side	844	1.082	1.060	1.021	-	-	-
			25	12	Back Side	844	0.921	0.881	1.046	-	-	-