

TEST REPORT

Applicant: Autel New Energy Co., Ltd.
Address: Room 101, Building B2, Zhiyuan, No.1001 Xueyuan Avenue, Changyuan Community, Taoyuan Road, Nanshan District, Shenzhen, 518055, China
Equipment Type: MaxiCharger AC Wallbox Commercial
Model Name: Maxi US AC W12-L-4G (refer section 2.4)
Brand Name: AUTEL
FCC ID: 2A5NP-AUTELNEACL
ISED Number: 28321-AUTELNEACL
Test Standard: 47 CFR Part 15 Subpart C
RSS-210 Issue 10 (2019-12)
RSS-Gen Issue 5 (2021-02)
Test Date: May 31, 2022 ~ Jun. 01, 2022
Date of Issue: Jun. 14, 2022

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Xiong Chong

Checked by: Xia Long

Approved by: Liao Jianming
(Technical Director)

Xiong Chong

Xia Long

Jim Liao

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Jun. 09, 2022</u>	<u>Initial Issue</u>
<u>Rev. 02</u>	<u>Jun. 14, 2022</u>	<u>Updated Section 2.5 Technical Information, 4.1 Test Environments and A.4 Frequency Stability</u>

TABLE OF CONTENTS

1 GENERAL INFORMATION	4
1.1 Identification of the Testing Laboratory	4
1.2 Identification of the Responsible Testing Location	4
2 PRODUCT INFORMATION	5
2.1 Applicant Information	5
2.2 Manufacturer Information	5
2.3 Factory Information	5
2.4 General Description for Equipment under Test (EUT)	6
2.5 Technical Information	7
3 SUMMARY OF TEST RESULTS	8
3.1 Test Standards	8
3.2 Verdict	8
3.3 Test Uncertainty	8
4 GENERAL TEST CONFIGURATIONS	9
4.1 Test Environments	9
4.2 Test Equipment List	9
4.3 Description of Test Setup	10
5 TEST ITEMS	12
5.1 Antenna Requirements	12
5.2 Emission Bandwidth	14
5.3 Field Strength of Fundamental Emissions and Radiated Emissions	16
5.4 Frequency Tolerance	18
5.5 Conducted Emission	19

ANNEX A TEST RESULT	20
A.1 Emission Bandwidth	20
A.2 Field Strength of Fundamental Emissions	21
A.3 Radiated Emissions	22
A.4 Frequency Stability	25
A.5 Conducted Emissions	26
ANNEX B TEST SETUP PHOTOS	28
ANNEX C EUT EXTERNAL PHOTOS	28
ANNEX D EUT INTERNAL PHOTOS	28

1 GENERAL INFORMATION

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, Guangdong Province, China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, Guangdong Province, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A.
Description	All measurement facilities used to collect the measurement data are located at Block B, 1/F, Baisha Science and Technology Park, Shahe West Road, Nanshan District, ShenZhen, Guangdong Province, China

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Autel New Energy Co., Ltd.
Address	Room 101, Building B2, Zhiyuan, No.1001 Xueyuan Avenue, Changyuan Community, Taoyuan Road, Nanshan District, Shenzhen, 518055, China

2.2 Manufacturer Information

Manufacturer	Autel New Energy Co., Ltd.
Address	Room 101, Building B2, Zhiyuan, No.1001 Xueyuan Avenue, Changyuan Community, Taoyuan Road, Nanshan District, Shenzhen, 518055, China

2.3 Factory Information

Factory	Autel Intelligent Technology Co., Ltd. Guangming Brach
Address	6F, West Wing and 7F&6F, East Wing, Building 2, and 6F of Electronical Building, Yanxiang Industrial Zone, Gaoxin Rd, Dongzhou Community of Guangming New District, Shenzhen

2.4 General Description for Equipment under Test (EUT)

EUT Name	MaxiCharger AC Wallbox Commercial
Model Name Under Test	Maxi US AC W12-L-4G
Series Model Name	Maxi US AC W12-4G, Maxi US AC W10-N14-4G Maxi US AC W10-N6-4G, Maxi US AC W7-N14-4G Maxi US AC W7-N6-4G, Maxi US AC W12-4G-H Maxi US AC W10-N14-4G-H, Maxi US AC W10-N6-4G-H Maxi US AC W7-N14-4G-H, Maxi US AC W7-N6-4G-H Maxi US AC W10-N14-L-4G, Maxi US AC W10-N6-L-4G Maxi US AC W7-N14-L-4G, Maxi US AC W7-N6-L-4G Maxi US AC W12-L- 4G-H, Maxi US AC W10-N14-L-4G-H Maxi US AC W10-N6-L-4G-H, Maxi US AC W7-N14-L-4G-H Maxi US AC W7-N6-L-4G-H
Description of Model name differentiation	W12, W10, W7 means maximum rated output power, we tested the max rated output power W12 here, N6, N14 means different power supply plug, it doesn't influent the test result. Charging cable of W7 is different from W12 and W10, we added the test for W7 model. -L means whether the product has LCD display. We tested the product has LCD display. The product name of the model without -L is MaxiCharger AC Wallbox Home. -H means the product whether attached a separate holster, The model we tested has a built-in holster on the charger; The others are the same.
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Technical Information

Network and Wireless connectivity	3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network LTE FDD Band 2/4/5/12/13/14/66 LTE TDD Band 71 Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20/40), NFC
-----------------------------------	--

The requirement for the following technical information of the EUT was tested in this report:

Modulation Type	ASK
Product Type	☐ Mobile ☐ Portable ☒ Fix Location
Frequency Range	13.56 MHz
Receiver Categorization	3
Number of channel	1
Tested Channel	1
Antenna Type	Internal Antenna

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Miscellaneous Wireless Communications Services
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3	RSS-Gen (Issue 5, Feb. 2021)	General Requirements for Compliance of Radio Apparatus
4	RSS-210 (Issue 10, Dec. 2019)	Licence-Exempt Radio Apparatus: Category I Equipment

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Result
1	Antenna Requirement	15.203	RSS-Gen 6.8	--
2	Emissions Bandwidth	15.215	RSS-Gen 6.7	ANNEX A.1
3	Field Strength of Fundamental Emissions	15.225(a)	RSS-210 B.6	ANNEX A.2
4	Radiated Emissions	15.225(d) 15.209	RSS-210 B.6	ANNEX A.3
5	Frequency Stability	15.225(e)	RSS-210 B.6	ANNEX A.4
6	Conducted Emission	15.207	RSS-Gen 8.8	ANNEX A.5
Note: The EUT has a permanently and irrelaceable attached antenna, which complies with the requirement FCC 15.203 & RSS-Gen 8.3.				

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	4.28 dB
Radiated emissions (9 kHz-30 MHz)	3.22 dB
Radiated emissions (30 MHz-1 GHz)-10m	4.80 dB
Radiated emissions (30 MHz-1 GHz)-3m	4.76 dB
Radiated emissions (1 GHz-18 GHz)-3m	4.88 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:


Relative Humidity	30% to 60%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	240 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2021.10.10	2022.10.09
LISN	SCHWARZBECK	NSLK 8127	8127-687	2021.06.08	2022.06.07
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2021.06.04	2022.06.03
Temperature Chamber	AHK	SP20	1412	2021.11.30	2022.11.29
Test Antenna- Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2021.04.16	2024.04.15
Test Antenna- Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2021.08.20	2024.08.19
Anechoic Chamber	EMC TECHNOLOGY LTD	20.1m*11.6 m*7.35m	N/A	2021.08.15	2024.08.14
Anechoic Chamber	CHANGNING	9m*6m*6m	N/A	2020.03.16	2023.03.15
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m* 2.8m	N/A	2022.02.19	2025.02.18
Test Software	BALUN	BL410_E	V19.918	--	--


4.3 Description of Test Setup

4.3.1 For Radiated Test (Below 30 MHz)




(Diagram 1)

4.3.2 For Radiated Test (30 MHz-1 GHz)



(Diagram 2)

4.3.3 For AC Power Supply Port Test



(Diagram 3)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer EUT internal photos.

5.2 Emission Bandwidth

5.2.1 Definition

15.215(c);

Intentional radiators operating under the alternative provisions to the general emission limits must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

RSS-Gen 6.7

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

5.2.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The 20dB bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 2 to 5 times the OBW

RBW = 1% to 5% the OBW

VBW $\geq$ 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

The 99% emission bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 1.5 to 5 times the OBW

RBW = 1% to 5% OBW

VBW $\geq$ 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.2.4 Test Result

Please refer to ANNEX A.1

5.3 Field Strength of Fundamental Emissions and Radiated Emissions

5.3.1 Limit

FCC §15.225(a), (b), (c); RSS-210 B.6

According to FCC section 15.225, for <30 MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 10 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 KHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT)

There was no detected Restricted bands and Radiated suprious emission below 30MHz. The 30m limit was converted to 3m Limit using square factor(x) as it was found by measurements as follows; 3 m Limit(dBuV/m) = 20log(X)+40log(30/3)= 20log(15848)+40log(30/3) = 124dBuV

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency range (MHz)	Field Strength@30m		Field Strength@10m	Field Strength@3m
	μV/m	dBμV/m	dBμV/m	dBμV/m
Below 13.110	30	29.5	48.58	69.5
13.110 ~ 13.410	106	40.5	59.58	80.5
13.410 ~ 13.553	334	50.5	69.58	90.5
13.553 ~13.567	15848	84	103.08	124
13.567 ~ 13.710	334	50.5	69.58	90.5
13.710 ~14.010	106	40.5	59.58	80.5
Above 14.010	30	29.5	48.58	69.5

NOTE:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.

FCC §15.225(d)

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measure-ment dis-tance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.3.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.3.4 Test Result

Please refer to ANNEX A.2

NOTE:

1. Results (dBuV/m) = Reading (dBuV/m) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Over limit = Results – Limit.

5.4 Frequency Tolerance

5.4.1 Limit

FCC §15.225(e)

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

RSS-210 B.6

(a) at the temperatures of -30°C (-22°F), $+20^{\circ}\text{C}$ ($+68^{\circ}\text{F}$) and $+50^{\circ}\text{C}$ ($+122^{\circ}\text{F}$), and at the manufacturer's rated supply voltage; and

(b) at the temperature of $+20^{\circ}\text{C}$ ($+68^{\circ}\text{F}$) and at $\pm 15\%$ of the manufacturer's rated supply voltage.

If the frequency stability limits are only met within a temperature range that is smaller than the -30°C to $+50^{\circ}\text{C}$ range specified in (a), the frequency stability requirement will be deemed to be met if the transmitter is automatically prevented from operating outside this smaller temperature range and if the published operating characteristics for the equipment are revised to reflect this restricted temperature range.

5.4.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

1. The test is performed in a Temperature Chamber.
2. The EUT is configured as MS + DC Power Supply.

5.4.4 Test Result

Please refer to ANNEX A.4.

5.5 Conducted Emission

5.5.1 Limit

FCC §15.207; RSS-Gen

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.5.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.5.4 Test Result

Please refer to ANNEX A.5.

NOTE:

1. Results (dBuV) = Reading (dBuV) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Over limit = Results – Limit.

ANNEX A TEST RESULT

A.1 Emission Bandwidth


Test Data

Frequency (MHz)	Emission Bandwidth(20dB down) (kHz)	Occupied Bandwidth(99%) (kHz)
13.56	25.914	23.574

Note: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.


Test plots

Emission Bandwidth



Date: 1.JUN.2022 10:23:27

99% Occupied Bandwidth



Date: 1.JUN.2022 10:22:33

A.2 Field Strength of Fundamental Emissions


Note: Field Strength of Fundamental Emissions tests were performed in X, Y, Z axis direction of EUT. And only the worst axis test condition was recorded in this test report.

Test Data

Field Strength of Fundamental Emissions Value					
Frequency (MHz)	Detector	Field Strength (dBuV/m)	Limit @3m (dBuV/m)	EUT	Margin (dB)
13.560	PEAK	59.12	124.0	Y	-64.88

Test Plot

Test Antenna-LOOP, ANT Vertical



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	13.560	59.12	20.86	124.0	-64.88	Peak	4.00	100	Vertical	Pass


A.3 Radiated Emissions

Note 1: This frequency which near 13.560 MHz with circle should be ignored because they are NFC carrier frequency.

Note 2: All Radiated Emissions tests were performed in X, Y, Z axis direction of EUT. And only the worst axis test condition was recorded in this test report.

The Data and Plots (9 kHz ~ 30 MHz)(at 10m chamber)


Below 30 MHz, ANT Vertical



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	0.013	51.09	20.11	125.1	-74.01	Peak	15.00	100	Vertical	Pass
2	0.070	42.62	20.17	110.7	-68.08	Peak	10.00	100	Vertical	Pass
3	0.172	45.50	20.10	102.9	-57.40	Peak	15.00	100	Vertical	Pass
4	0.419	40.66	20.20	95.2	-54.54	Peak	15.00	100	Vertical	Pass
5	4.023	33.72	20.68	69.5	-35.78	Peak	14.00	100	Vertical	Pass
6	13.560	59.09	20.86	69.5	-10.41	Peak	2.00	100	Vertical	N/A


Test Data and Plots (30 MHz ~ 10th Harmonic)

30 MHz to 1 GHz, ANT Vertical



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	84.087	26.22	-31.40	30.0	-3.78	Peak	201.00	200	Horizontal	N/A
1*	84.087	22.06	-31.40	30.0	-7.94	QP	201.00	200	Horizontal	Pass
2	241.892	32.07	-26.56	36.0	-3.93	Peak	287.00	200	Horizontal	Pass
3	382.264	30.98	-22.99	36.0	-5.02	Peak	75.00	200	Horizontal	Pass
4	417.127	36.65	-21.93	36.0	0.65	Peak	287.00	200	Horizontal	N/A
4*	417.127	26.91	-21.93	36.0	-9.09	QP	287.00	200	Horizontal	Pass
5	446.034	35.31	-21.61	36.0	-0.69	Peak	140.00	178	Horizontal	N/A
5*	446.034	23.78	-21.61	36.0	-12.22	QP	140.00	178	Horizontal	Pass
6	950.017	35.14	-12.02	36.0	-0.86	Peak	114.00	104	Horizontal	N/A
6*	950.017	33.69	-12.02	36.0	-2.31	QP	114.00	104	Horizontal	Pass

30 MHz to 1 GHz, ANT Horizontal



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	87.292	29.68	-30.46	30.0	-0.32	Peak	83.00	155	Vertical	N/A
1*	87.292	25.55	-30.46	30.0	-4.45	QP	83.00	155	Vertical	Pass
2	93.866	29.67	-28.90	33.5	-3.83	Peak	360.00	124	Vertical	N/A
2*	93.866	26.08	-28.90	33.5	-7.42	QP	360.00	124	Vertical	Pass
3	115.581	24.04	-28.93	33.5	-9.46	Peak	360.00	100	Vertical	Pass
4	241.650	24.86	-26.57	36.0	-11.14	Peak	156.00	100	Vertical	Pass
5	394.871	30.78	-22.66	36.0	-5.22	Peak	70.00	100	Vertical	Pass
6	949.815	30.71	-12.02	36.0	-5.29	Peak	144.00	200	Vertical	Pass

A.4 Frequency Stability

Note 1: Because the 85%(204V) and 115% (276V)of the rated supply voltage value exceeds the cut-off voltage upper(250V) and lower(230V) limit of the manufacturer, the cut-off voltage of EUT is test here.

Note 2: The operating temperature range of the EUT is -40°C to 55°C.


OPERATING FREQUENCY:	13560000 Hz
REFERENCE VOLTAGE:	240 V
DEVIATION LIMIT:	±0.01%

VOLTAGE (%)	Test Conditions		Frequency(Hz)	Deviation(%)	Verdict
	Power (VAC)	Temperature (°C)			
100	240	-30	13560638	0.004705	
100		-20	13560878	0.006475	
100		-10	13560758	0.005590	
100		0	13560778	0.005737	
100		+10	13560538	0.003968	
100		+20	13560798	0.005885	
100		+25	13560678	0.005000	
100		+30	13560858	0.006327	
100		+40	13560658	0.004853	
100		+50	13560858	0.006327	
MAX(Cut-off Point, 115)	230	+20	13560138	0.001018	
MIN(Cut-off Point, 115)	250	+20	13560138	0.001018	

A.5 Conducted Emissions


Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.154	53.89	10.99	65.78	-11.89	Peak	L	Pass
1**	0.154	33.90	10.99	55.78	-21.88	AV	L	Pass
2	0.242	51.87	10.92	62.03	-10.16	Peak	L	Pass
2**	0.242	31.84	10.92	52.03	-20.19	AV	L	Pass
3	0.332	48.37	10.89	59.40	-11.03	Peak	L	Pass
3**	0.332	30.15	10.89	49.40	-19.25	AV	L	Pass
4	1.052	46.34	10.70	56.00	-9.66	Peak	L	Pass
4**	1.052	27.82	10.70	46.00	-18.18	AV	L	Pass
5	9.602	47.82	10.65	60.00	-12.18	Peak	L	Pass
5**	9.602	33.93	10.65	50.00	-16.07	AV	L	Pass
6	17.670	47.58	10.68	60.00	-12.42	Peak	L	Pass
6**	17.670	34.51	10.68	50.00	-15.49	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.200	54.25	10.96	63.61	-9.36	Peak	N	Pass
1**	0.200	33.23	10.96	53.61	-20.38	AV	N	Pass
2	0.258	52.89	10.91	61.50	-8.61	Peak	N	Pass
2**	0.258	33.97	10.91	51.50	-17.53	AV	N	Pass
3	0.386	49.20	10.90	58.15	-8.95	Peak	N	Pass
3**	0.386	31.57	10.90	48.15	-16.58	AV	N	Pass
4	0.592	48.53	10.88	56.00	-7.47	Peak	N	Pass
4**	0.592	31.40	10.88	46.00	-14.60	AV	N	Pass
5	9.740	49.78	10.66	60.00	-10.22	Peak	N	Pass
5**	9.740	26.72	10.66	50.00	-23.28	AV	N	Pass
6	17.060	46.81	10.67	60.00	-13.19	Peak	N	Pass
6**	17.060	32.64	10.67	50.00	-17.36	AV	N	Pass

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2250922-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2250922-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2250922-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--