

TEST REPORT

Applicant: Shantou Yile Technology Co., Ltd.
Address of Applicant: No.5YongxiangRoad,LingtingVillage,
ChenghaiDistrict,ShantouCity,Guangdong Province,
China
Manufacturer/Factory: Shantou Yile Technology Co., Ltd.
**Address of
Manufacturer/Factory:** No.5YongxiangRoad,LingtingVillage,
ChenghaiDistrict,ShantouCity,Guangdong Province,
China
Equipment Under Test (EUT)
Product Name: R/C CAR
Model No.: C6, C7, C8, C9, C10, C11, C12, C15, C16, C17, C18,
C19, C20, C21, C25, C26, C27, C29, C31, C35, C37,
C39, C50, C51, C52, C54, C55, C56, C57, C58, C59,
C60, C61, C63, C65, C66, C67, C68, C69, C71, C73,
C75
FCC ID: 2A5OM-C6
Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249
Date of sample receipt: January 21, 2026
Date of Test: January 21, 2026-March 13, 2026
Date of report issued: March 13, 2026
Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	March 13, 2026	Original

Tested By:




Date:

March 13, 2026

Test Engineer

Prepared By:




Date:

March 13, 2026

Project Engineer

Check By:



Date:

March 13, 2026

Reviewer

3 Contents

Page

1	COVER PAGE.....	1
2	VERSION.....	2
3	CONTENTS	3
4	TEST SUMMARY	4
4.1	MEASUREMENT UNCERTAINTY	4
5	GENERAL INFORMATION.....	5
5.1	GENERAL DESCRIPTION OF EUT	5
5.2	TEST MODE.....	7
5.3	DESCRIPTION OF SUPPORT UNITS.....	7
5.4	DEVIATION FROM STANDARDS.....	7
5.5	ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6	TEST FACILITY	7
5.7	TEST LOCATION	7
5.8	ADDITIONAL INSTRUCTIONS.....	7
6	TEST INSTRUMENTS LIST	8
7	TEST RESULTS AND MEASUREMENT DATA.....	10
7.1	ANTENNA REQUIREMENT	10
7.2	RADIATED EMISSION METHOD.....	11
7.2.1	Field Strength of The Fundamental Signal.....	13
7.2.2	Spurious emissions.....	14
7.2.3	Bandedge emissions.....	22
7.3	20dB OCCUPY BANDWIDTH.....	26
8	TEST SETUP PHOTO	28
9	EUT CONSTRUCTIONAL DETAILS.....	28

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Pass
AC Power Line Conducted Emission	15.207	N/A
Field strength of the fundamental signal	15.249 (a)	Pass
Spurious emissions	15.249 (a) (d)/15.209	Pass
Band edge	15.249 (d)/15.205	Pass
20dB Occupied Bandwidth	15.215 (c)	Pass

Remarks:

1. Test according to ANSI C63.10:2020.
2. Pass: The EUT complies with the essential requirements in the standard.
3. N/A: not applicable

4.1 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	RF conducted power	$\pm 0.75\text{dB}$
5	RF power density	$\pm 3\text{dB}$
6	Conducted Spurious emissions	$\pm 2.58\text{dB}$
7	AC Power Line Conducted Emission	$\pm 3.44\text{dB}$ (0.15MHz ~ 30MHz)
8	Radiated Spurious emission test	$\pm 3.1\text{dB}$ (9kHz-30MHz)
		$\pm 3.8039\text{dB}$ (30MHz-200MHz)
		$\pm 3.9679\text{dB}$ (200MHz-1GHz)
		$\pm 4.29\text{dB}$ (1GHz-18GHz)
		$\pm 3.30\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Time	$\pm 3\%$

5 General Information

5.1 General Description of EUT

Product Name:	R/C CAR
Model No.:	C6, C7, C8, C9, C10, C11, C12, C15, C16, C17, C18, C19, C20, C21, C25, C26, C27, C29, C31, C35, C37, C39, C50, C51, C52, C54, C55, C56, C57, C58, C59, C60, C61, C63, C65, C66, C67, C68, C69, C71, C73, C75
Test Model No.:	C6
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The difference is model name for commercial purpose.	
Test sample(s) ID:	GTS2026010283-1
Sample(s) Status	Engineered sample
Operation Frequency:	2444MHz~2462MHz
Channel Numbers:	19
Modulation Type:	GFSK
Antenna Type:	PCB Antenna
Antenna gain:	0dbi(declare by applicant)
Power supply:	DC 3.7V, 500mAh, 1.85Wh Li-ion battery

Disclaimer statement:

1. Antenna gain information provided by the customer, and the laboratory is not responsible for its authenticity.
2. The information in this section is provided by the applicant or manufacturer, GTS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

Operation Frequency each of channel							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2444	6	2449	11	2454	16	2459
2	2445	7	2450	12	2455	17	2460
3	2446	8	2451	13	2456	18	2461
4	2447	9	2452	14	2457	19	2462
5	2448	10	2453	15	2458		

The test frequencies are below:

Channel	Frequency
The lowest channel	2444MHz
The middle channel	2453MHz
The Highest channel	2462MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
-------------------	---

Per-test mode.

We have verified the construction and function in typical operation, The EUT was placed on three different polar directions; i.e. X axis, Y axis, Z axis. which was shown in this test report (Only show the worst case:Y axis) and defined as follows:

Axis	X	Y	Z
Field Strength(dBuV/m)	88.98	89.85	89.52

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC—Registration No.: 381383**

Designation Number: CN5029

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files.

- **ISED—Registration No.: 9079A**

CAB identifier: CN0091

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing

- **NVLAP (LAB CODE:600179-0)**

Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd.
Address: No. 123- 128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

5.8 Additional Instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Apr. 11, 2025	Apr. 10, 2026
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Apr. 12, 2025	Apr. 11, 2026
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	Apr. 12, 2025	Apr. 11, 2026
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	Jul. 11, 2025	Jul 10, 2026
7	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov.22, 2025	Nov.21, 2026
8	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	Apr. 11, 2025	Apr. 10, 2026
9	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	Apr. 11, 2025	Apr. 10, 2026
10	Horn Antenna (18GH-40GHz)	Schwarzbeck	BBHA 9170	GTS691	Apr. 11, 2025	Apr. 10, 2026
11	FSV-Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	Mar. 11, 2025	Mar. 10, 2026
12	Amplifier	/	LNA-1000-30S	GTS650	Apr. 11, 2025	Apr. 10, 2026
13	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 24, 2025	Nov. 23, 2026
14	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	Apr. 11, 2025	Apr. 10, 2026
15	Thermo meter	JINCHUANG	GSP-8A	GTS643	Apr. 15, 2025	Apr. 14, 2026
16	RE cable 1	GTS	N/A	GTS675	Jul. 11, 2025	Jul. 10, 2026
17	RE cable 2	GTS	N/A	GTS676	Jul. 11, 2025	Jul. 10, 2026
18	RE cable 3	GTS	N/A	GTS677	Jul. 11, 2025	Jul. 10, 2026
19	RE cable 4	GTS	N/A	GTS678	Jul. 11, 2025	Jul. 10, 2026
20	RE cable 5	GTS	N/A	GTS679	Jul. 11, 2025	Jul. 10, 2026
21	RE cable 6	GTS	N/A	GTS680	Jul. 11, 2025	Jul. 10, 2026
22	RE cable 7	GTS	N/A	GTS681	Jul. 11, 2025	Jul. 10, 2026
23	RE cable 8	GTS	N/A	GTS682	Jul. 11, 2025	Jul. 10, 2026
24	EMI Test Software	AUDIX	E3-6.100614a	GTS725	N/A	N/A

RF Conducted Test:						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	Apr. 11, 2025	Apr. 10, 2026
2	EMI Test Receiver	R&S	ESCI 7	GTS552	Apr. 12, 2025	Apr. 11, 2026
3	PSA Series Spectrum Analyzer	Agilent	E4440A	GTS536	Apr. 11, 2025	Apr. 10, 2026
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	Apr. 11, 2025	Apr. 10, 2026
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	Apr. 11, 2025	Apr. 10, 2026
6	Wideband Power Meter	Keysight	N1924A	GTS673	Apr. 11, 2025	Apr. 10, 2026
7	USB RF Power Sensor	DARE	RPR3006W	GTS569	Apr. 11, 2025	Apr. 10, 2026
8	RF Switch Box	Shongyi	RFSW3003328	GTS571	Apr. 11, 2025	Apr. 10, 2026
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	Apr. 11, 2025	Apr. 10, 2026
10	Thermo meter	JINCHUANG	GSP-8A	GTS641	Apr. 15, 2025	Apr. 14, 2026
11	EXA Signal Analyzer	Keysight	N9010B	MY60241168	Nov. 01, 2025	Oct. 31, 2026


General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	Jul. 16, 2025	Jul. 15, 2026


7 Test results and Measurement Data

7.1 Antenna requirement


Standard requirement:	FCC Part15 C Section 15.203
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
EUT Antenna:	
The antenna is wire antenna, reference to the appendix II for details.	

7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2020				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	300Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	10kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Peak		1MHz	10Hz	Average Value	
Limit: (Field strength of the fundamental signal)	Frequency	Limit (dBuV/m @3m)			Remark
	2400MHz-2483.5MHz	94.00			Average Value
		114.00			Peak Value
Limit: (Spurious Emissions)	Frequency	Limit (uV/m)			Remark
	0.009MHz-0.490MHz	2400/F(kHz) @300m			Quasi-peak Value
	0.490MHz-1.705MHz	24000/F(kHz) @30m			Quasi-peak Value
	1.705MHz-30.0MHz	30 @30m			Quasi-peak Value
	30MHz-88MHz	100 @3m			Quasi-peak Value
	88MHz-216MHz	150 @3m			Quasi-peak Value
	216MHz-960MHz	200 @3m			Quasi-peak Value
	960MHz-1GHz	500 @3m			Quasi-peak Value
	Above 1GHz	500 @3m			Average Value
5000 @3m			Peak Value		
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.				
Test setup:	For radiated emissions from 9kHz to 30MHz  For radiated emissions from 30MHz to 1GHz				



For radiated emissions above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test Instruments: Refer to section 6.0 for details

Test mode: Refer to section 5.2 for details

Test environment: Temp.: 25 °C Humid.: 52% Press.: 1012mbar

Test voltage: DC 3V

Test results: Pass

Measurement data:**7.2.1 Field Strength of The Fundamental Signal****Peak value:**

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Final Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2444.00	95.53	27.14	4.16	39.40	87.43	114.00	-26.57	Vertical
2444.00	97.85	27.14	4.16	39.40	89.75	114.00	-24.25	Horizontal
2453.00	96.20	27.18	4.13	39.46	88.05	114.00	-25.95	Vertical
2453.00	98.00	27.18	4.13	39.46	89.85	114.00	-24.15	Horizontal
2462.00	96.16	27.22	4.11	39.51	87.98	114.00	-26.02	Vertical
2462.00	97.53	27.22	4.11	39.51	89.35	114.00	-24.65	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Final Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
2444.00	85.00	27.14	4.16	39.40	76.90	94.00	-17.10	Vertical
2444.00	87.32	27.14	4.16	39.40	79.22	94.00	-14.78	Horizontal
2453.00	85.67	27.18	4.13	39.46	77.52	94.00	-16.48	Vertical
2453.00	87.47	27.18	4.13	39.46	79.32	94.00	-14.68	Horizontal
2462.00	85.63	27.22	4.11	39.51	77.45	94.00	-16.55	Vertical
2462.00	87.00	27.22	4.11	39.51	78.82	94.00	-15.18	Horizontal

Note:

1. For fundamental frequency , $RBW \geq 20$ bandwidth., $VBW \geq 3 \times RBW$, PK detector for PK value, RMS detector for AV value
2. Final Level(dBuV/m)=Read level(dBuV)+Antenna Factor(dB/m)+Cable Loss(dB)–Preamplifier Factor(dB)


7.2.2 Spurious emissions

■ Below 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.

■ Below 1GHz

Pre-scan all test modes, found worst case at 2444MHz, and so only show the test result of it
Horizontal




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
39.576	25.11	14.32	1.29	33.55	7.17	40.00	-32.83	QP
69.357	30.05	10.96	1.72	33.55	9.18	40.00	-30.82	QP
141.826	30.25	13.98	2.38	33.50	13.11	43.50	-30.39	QP
294.114	26.12	12.16	3.51	33.21	8.58	46.00	-37.42	QP
468.876	26.27	16.28	4.45	32.94	14.06	46.00	-31.94	QP
863.056	25.19	22.80	6.16	31.83	22.32	46.00	-23.68	QP

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Vertical




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
59.649	37.65	12.23	1.61	33.53	17.96	40.00	-22.04	QP
68.631	38.44	11.04	1.72	33.55	17.65	40.00	-22.35	QP
167.824	31.02	13.72	2.58	33.45	13.87	43.50	-29.63	QP
408.946	25.86	14.98	4.18	33.02	12.00	46.00	-34.00	QP
645.120	25.56	19.90	5.29	32.52	18.23	46.00	-27.77	QP
982.620	25.47	23.90	6.61	31.19	24.79	54.00	-29.21	QP

Remarks:

$$\text{Final level (dBuV/m)} = \text{Reading level (dBuV)} + \text{Antenna factor (dB/m)} + \text{Cable loss (dB)} - \text{Preamp Factor (dB)}$$

■ Above 1GHz

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4888.000	48.10	32.58	5.67	37.97	48.38	74.00	-25.62	Peak
7332.000	37.52	36.66	7.27	38.07	43.38	74.00	-30.62	Peak
9776.000	40.25	38.30	9.18	39.23	48.50	74.00	-25.50	Peak

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4888.000	49.80	32.58	5.67	37.97	50.08	74.00	-23.92	Peak
7332.000	37.11	36.66	7.27	38.07	42.97	74.00	-31.03	Peak
9776.000	38.95	38.30	9.18	39.23	47.20	74.00	-26.80	Peak

Remarks:

$$\text{Final level(dBuV/m)} = \text{Reading level(dBuV)} + \text{Antenna factor(dB/m)} + \text{Cable loss(dB)} - \text{Preamp Factor(dB)}$$

Test channel:	Middle	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4906.000	48.15	32.61	5.70	37.96	48.50	74.00	-25.50	Peak
7359.000	37.50	36.68	7.30	38.09	43.39	74.00	-30.61	Peak
9812.000	37.83	38.32	9.20	39.24	46.11	74.00	-27.89	Peak

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Middle	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4906.000	49.74	32.61	5.70	37.96	50.09	74.00	-23.91	Peak
7359.000	39.42	36.68	7.30	38.09	45.31	74.00	-28.69	Peak
9812.000	38.06	38.32	9.20	39.24	46.34	74.00	-27.66	Peak

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4924.000	50.21	32.65	5.72	37.95	50.63	74.00	-23.37	Peak
7386.000	37.91	36.63	7.32	38.11	43.75	74.00	-30.25	Peak
9848.000	40.27	38.40	9.22	39.25	48.64	74.00	-25.36	Peak

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4924.000	47.56	32.65	5.72	37.95	47.98	74.00	-26.02	Peak
7386.000	39.57	36.63	7.32	38.11	45.41	74.00	-28.59	Peak
9848.000	40.12	38.40	9.22	39.25	48.49	74.00	-25.51	Peak

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)


Remarks:

1. The emission levels of other frequencies are very lower than the limit and not show in test report.
2. For above 18GHz, no emission found.
3. If the average limit is met when using a Peak detector, the EUT shall be deemed to meet both peak and average limits. And measurement with the average detector is unnecessary.

7.2.3 Bandedge emissions

All of the restriction bands were tested, and only the data of worst case was exhibited.

Test channel:	Lowest	Polarization:	Horizontal
---------------	--------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	34.28	26.66	4.09	38.86	26.17	54.00	-27.83	Average
2310.000	46.18	26.66	4.09	38.86	38.07	74.00	-35.93	Peak
2390.000	35.63	26.62	4.11	38.88	27.48	54.00	-26.52	Average
2390.000	47.43	26.62	4.11	38.88	39.28	74.00	-34.72	Peak
2400.000	38.55	26.43	4.11	38.88	30.21	54.00	-23.79	Average
2400.000	50.63	26.43	4.11	38.88	42.29	74.00	-31.71	Peak

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Lowest	Polarization:	Vertical
---------------	--------	---------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	45.75	28.05	4.09	38.86	39.03	74.00	-34.97	Peak
2389.968	46.58	27.03	4.11	38.88	38.84	74.00	-35.16	Peak
2400.032	48.38	26.94	4.11	38.88	40.55	74.00	-33.45	Peak

Remarks:

Final level (dBuV/m) = Reading level (dBuV) + Antenna factor (dB/m) + Cable loss (dB) - Preamp Factor (dB)

Test channel:	Highest	Polarization:	Horizontal
---------------	---------	---------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	41.29	26.78	4.13	38.90	33.30	54.00	-20.70	Average
2483.500	55.22	26.78	4.13	38.90	47.23	74.00	-26.77	Peak
2500.000	36.18	26.48	4.14	38.90	27.90	54.00	-26.10	Average
2500.000	49.01	26.48	4.14	38.90	40.73	74.00	-33.27	Peak

Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Test channel:	Highest	Polarization:	Vertical
---------------	---------	---------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	Final level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2483.500	38.53	28.22	4.13	38.90	31.98	54.00	-22.02	Average
2483.500	52.70	28.22	4.13	38.90	46.15	74.00	-27.85	Peak
2500.000	31.07	28.63	4.14	38.90	24.94	54.00	-29.06	Average
2500.000	46.11	28.63	4.14	38.90	39.98	74.00	-34.02	Peak


Remarks:

Final level(dBuV/m) = Reading level(dBuV) + Antenna factor(dB/m) + Cable loss(dB) - Preamp Factor(dB)

Remark:

1. For above 18GHz, no emission found


7.3 20dB Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.10:2020
Limit:	Operation Frequency range 2400MHz~2483.5MHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test channel	20dB bandwidth(MHz)	Result
Lowest	1.477	Pass
Middle	1.870	Pass
Highest	1.480	Pass

Test plot as follows:



Lowest channel



Middle channel



Highest channel

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----